

 Status Configure Cloud Statistics Delete CloudBuild Executor Status

Cloud Docker Configuration

Name

Docker

Docker Cloud details ^

 Edited

Docker Host URI

unix:///var/run/docker.sock

Server credentials

- none -

+ Add

Advanced v

Test Connection

Enabled

Error Duration

Default = 300



Expose DOCKER_HOST

Container Cap

Docker Agent templates ^

 Edited

Docker Agent templates

List of Images to be launched as agents

Docker Agent templates

Labels

Enabled

Name

Docker Image

Registry Authentication ^

Container settings ^

 Edited

Docker Command

Hostname

User

Extra Groups

▼

DNS

DNS Search

Network

Mounts

type=bind,source=/var/run/docker.sock,target=/var/run/docker.sock

▼

Volumes From

▼

Devices

▼

Environment

▼

Port bindings

☐ Bind all declared ports

Memory Limit in MB

Swap Memory Limit in MB

CGroup Parent

CPU resources

CPU Period in us

Not a positive integer

CPU Quota in us

Not a positive integer

CPU Shares

Shared Memory Size in MB

☐ Run container privileged at your own risk

Security Options

Capabilities to add

Capabilities to drop

☐ Allocate a pseudo-TTY

MAC address

Extra Hosts



Extra Docker Labels



Instance Capacity

Remote File System Root

Usage

Idle timeout

Connect method

Prerequisites:

- Docker image must have [Java](#) installed.
- Docker image CMD must either be empty or simply sit and wait forever, e.g. `/bin/bash`.

The Jenkins remote agent code will be copied into the container and then run using the Java that's installed in the container.

See docker container [jenkins/agent](#) and/or source [jenkinsci/docker-agent](#) as an example.

User

Java Executable

JVM Arguments



EntryPoint Cmd



Stop timeout

☐

Remove volumes

Pull strategy

Pull timeout

Node Properties

[+ Add Node Property](#)[+ Add Docker Template](#)[Save](#)[Apply](#)