![gsmgateway.in logo]

VS-GW2120 V2 WCDMA Wireless Gateway

VS-GW2120 V2 Wireless Gateway, an perfect product of the VS- GW2120 Series, is now the popular open-source Asterisk-based VoIP Gateway solution for SMBs and SOHOs. similar agreeable GUI and matchless modular plan, it can first hot-swap for both SIM cards and GSM/WCDMA/LTE wireless gateway modules. client can easy to add or remove the modules for hardware expansion or exchange.

Features	
♦ Simple and convenient configuration via Web GUI ♦ Support http / https / SSH ♦ Basic security strategy(white/black list, security rules) ♦ Optional GSM Voice Codec ♦ SIP(RFC3261) compliance ♦ Support diverse SIP, IAX2 protocols ♦ Multiple SIP/IAX2 Registration models: None, server, client DTMF Signaling support: RFC2833, In band, SIPINFO ♦ Real Open API Protocol(based on Asterisk) ♦ Support static IP and DHCP ♦ Call Duration Limit ♦ Independent System for Each Module ♦ Hot-swap Design for both Sim cards and Modules	♦ CLIR(Call Line Identification Restriction) ♦ Call Waiting ♦ Call Forwarding (unconditional, no reply, busy, not reachable) ♦ SMSC/SMS/USSD ♦ SMS bulk transceiver, SMS automatically resend, Sent to Email ♦ Support HTTP SMS interface ♦ SMS Forwarding ♦ USSD transceiver ♦ SMS remotely controlling gateway ♦ IMEI number automatically modify ♦ PIN identification ♦ Mobile number portability (MNP) ♦ Flexible routing settings & unlimited routing rules ♦ Affordable Price with Superior Performance ♦ Available for OEM

Compatible with sip server, such as: Asterisk, Elastix, 3CX, Free SWITCH, etc. ♦ One Year Warranty ♦	♦ 3-Month "No Questions Asked" Return Policy

VS-GW2120 V2 WCDMA Wireless Gateway Frequency Range			
Module Type	GSM	WCDMA	LTE
Band	850/900/1800/1900MHz@GSM	900/2100MHz @UMTS 900/1800MHz @GSM	LTE FDD: B1/B3/B5/B8 LTE TDD: B38/B38/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA: BC0 GSM: 900/1800MHz