






OpenVox VS-GWM401G

The VS-GWM401 series wireless gateway modules can bring you excellent HD voice service with multiple codecs, including G.711U, G.711A, GSM, G.722, G.726, G.729, and also flexible SMS service with multiple SMS API. The GWM401 SeriesWireless Gateway Module is 100% compatible with Asterisk, 3CX, Free PBX, Free SWITCH and VOS VoIP system platform, providing users with more diverse telecommunications access methods and helping users reduce communication costs.



Features

 Frequency range: GSM 850/900/1800/1900MHz

♦ Storage temperature range: -40~125°C

♦ Operation temperature range: 0~50°C

♦ Operation humidity range: 10%~90%

non-condensing

♦ Max Power Consumption: 28W

♦ Dimension: 12.4cm × 18.5cm × 2.1cm

♦ Weight: 164g

♦ Warranty: One Year





OpenVox VS-GWM401G Wireless Gateway Frequency Range				
Module Type	GSM	WCDMA	LTE	
Band	850/900/1800/1900M Hz@GSM	900/2100MHz @UMTS 900/1800MHz @GSM	LTE FDD: B1/B3/B5/B8 LTE TDD: B38/B38/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA: BC0 GSM: 900/1800MHz	

Office Address	Contact Us Via Mobile	Contact Us Via Mail
Asfera Technologies Private Limited , Saroj Tower,Office	+91-9066677770	info@asfera.in
No:- 15 First Floor, 59/1, above Bank of Baroda, Kalkaji Extension, New Delhi, 110019.	+91-1146579777	sales@asfera.in