



# **COM106: Introduction to Databases**

**SQL – Multiple Table  
Queries**

# SQL – Multiple Table Queries

So far, we've looked at queries where the information required can be found in a **single table**  
- often, the information required is spread across **two or more tables**.

For example - **Get the *names of employees* and the *roles* they have performed for employees on the 1st floor.**

*ename and floor are in  
the **EMPLOYEE** table*

*role is in the  
**WORKS\_ON** table*

Retrieving data from two or more tables requires **JOINS** (normally **across PK/FK matches**)

There are **TWO** SQL approaches

**Original (Mark 1):** specify join clause as an extra **WHERE/AND** clause

**New (Mark 2):** specify join clause in a subsidiary **ON** clause after FROM clause

For standard SQL, **JOINS** using a query block require that:

1. all attributes occurring in two tables are referred to as <relation>.<attribute>  
e.g. EMPLOYEE.enum
2. all relations (tables) participating in the join are listed in the FROM clause
3. join clauses must be inserted as **WHERE/AND** clause(s)  
e.g. WHERE EMPLOYEE.enum = WORKS\_ON.enum

# SQL – Multiple Table Queries

In the examples that follow the **EMPLOYEE**, **PROJECT**, **WORKS\_ON** database is used -

with relational schema

and sample data as shown

**EMPLOYEE** (enum , ename, salary, floor)

**PROJECT** (pnum , pname, leader)

**WORKS\_ON** (enum\* , pnum\* , role)

EMPLOYEE

enum	ename	salary	floor
852341	Smith	15000	1
852358	Jones	19000	3
852407	Brown	16000	3
852455	White	25100	2
852491	Adams	30500	1
852514	Doyle	11650	2
852530	Evans	26980	4

PROJECT

pnum	pname	leader
121	IT	Gates
135	Design	Sinclair
147	Analysis	Einstein
216	Publicity	Saatchi
227	Theatre	Dench
251	Sport	Shearer

WORKS\_ON

enum	pnum	role
852341	121	Manager
852341	135	Designer
852358	147	Consultant
852358	135	Consultant
852407	216	Assistant
852455	121	Assistant
852455	227	Manager
852491	135	Designer
852491	216	Manager
852514	121	Assistant
852514	216	Consultant
852514	251	Manager
852530	147	Manager

# SQL – Multiple Table Queries

**Natural Language Query:** *Get the names of employees and the roles they have performed for employees on the 1st floor.*

```
SELECT ename, role
FROM EMPLOYEE, WORKS_ON
WHERE EMPLOYEE.enum = WORKS_ON.enum
AND floor = 1;
```

← Mark 1 Join

Join on PK/FK match – **EMPLOYEE.enum (PK)** and **WORKS\_ON.enum (FK)**

EMPLOYEE

enum	ename	salary	floor
<b>852341</b>	<b>Smith</b>	15000	<b>1</b>
852358	Jones	19000	3
852407	Brown	16000	3
852455	White	25100	2
<b>852491</b>	<b>Adams</b>	30500	<b>1</b>
852514	Doyle	11650	2
852530	Evans	26980	4

Result Table

ename	role
Smith	Manager
Smith	Designer
Adams	Designer
Adams	Manager

WORKS\_ON

enum	pnum	role
<b>852341</b>	121	<b>Manager</b>
<b>852341</b>	135	<b>Designer</b>
852358	147	Consultant
852358	135	Consultant
852407	216	Assistant
852455	121	Assistant
852455	227	Manager
<b>852491</b>	135	<b>Designer</b>
<b>852491</b>	216	<b>Manager</b>
852514	121	Assistant
852514	216	Consultant
852514	251	Manager
852530	147	Manager

# SQL – Multiple Table Queries

Natural Language Query: *Get the **names** and **salaries** of employees who work on projects led by 'Gates'*

```
SELECT ename, salary
FROM EMPLOYEE, WORKS_ON, PROJECT
WHERE EMPLOYEE.enum = WORKS_ON.enum
AND WORKS_ON.pnum = PROJECT.pnum
AND leader = 'Gates';
```

Requires attributes from  
all **three** tables

Mark 1 Join on  
**PK/FK match**

EMPLOYEE			
enum	ename	salary	floor
<b>852341</b>	<b>Smith</b>	<b>15000</b>	1
852358	Jones	19000	3
852407	Brown	16000	3
<b>852455</b>	<b>White</b>	<b>25100</b>	2
852491	Adams	30500	1
<b>852514</b>	<b>Doyle</b>	<b>11650</b>	2
852530	Evans	26980	4

PROJECT		
pnum	pname	leader
<b>121</b>	IT	<b>Gates</b>
135	Design	Sinclair
147	Analysis	Einstein
216	Publicity	Saatchi
227	Theatre	Dench
251	Sport	Shearer

Result Table

ename	salary
Smith	15000
White	25100
Doyle	11650

WORKS_ON		
enum	pnum	role
<b>852341</b>	<b>121</b>	Manager
852341	135	Designer
852358	147	Consultant
852358	135	Consultant
852407	216	Assistant
<b>852455</b>	<b>121</b>	Assistant
852455	227	Manager
852491	135	Designer
852491	216	Manager
<b>852514</b>	<b>121</b>	Assistant
852514	216	Consultant
852514	251	Manager
852530	147	Manager

WORKS\_ON.**pnum** = PROJECT.**pnum**

# SQL – Multiple Table Queries

## Mark 2 Joins - Alternative method for SQL joins

1. all relations participating in the join are listed in the FROM clause
2. Use of **INNER JOIN** as the join operator
3. join clauses must be specified in a subsidiary **ON** clause

*There are a number of different **JOIN** operators – see later*

e.g. ***Get the names of employees and the roles they have performed for employees on the 1st floor.***

### Mark 1

```
SELECT ename, role
FROM EMPLOYEE, WORKS_ON
WHERE EMPLOYEE.enum = WORKS_ON.enum
AND floor = 1;
```

### Mark 2

```
SELECT ename, role
FROM EMPLOYEE INNER JOIN WORKS_ON
ON EMPLOYEE.enum = WORKS_ON.enum
WHERE floor = 1;
```

e.g. ***Get the names and salaries of employees who work on projects led by 'Gates'***

### Mark 1

```
SELECT ename, salary
FROM EMPLOYEE, WORKS_ON, PROJECT
WHERE EMPLOYEE.enum = WORKS_ON.enum
AND WORKS_ON.pnum = PROJECT.pnum
AND leader = 'Gates';
```

### Mark 2

```
SELECT ename, salary
FROM EMPLOYEE INNER JOIN WORKS_ON
ON EMPLOYEE.enum = WORKS_ON.enum
INNER JOIN PROJECT
ON WORKS_ON.pnum = PROJECT.pnum
WHERE leader = 'Gates';
```

# SQL – Multiple Table Queries

## Nested Queries

Join queries can be formulated as a set of nested queries whenever:

- the **SELECT** clause contains attributes from only **one** relation
- extra information is required **for comparison** in the **WHERE** clause  
e.g. an aggregate function, or a list of attributes from another table

Links between the query blocks can be achieved:

- using the **IN predicate** if multiple values may be returned from the lower clause
- using **>, >=, <, <=, =, <>** whenever only one value will be returned from the lower clause

e.g. *Get the names of employees who have worked in the role of 'Consultant'.*

### As Mark 1 Join:

```
SELECT ename
FROM EMPLOYEE, WORKS_ON
WHERE EMPLOYEE.enum = WORKS_ON.enum
AND role = 'Consultant';
```

Result Table

ename
Jones
Jones
Doyle

*The nested **SELECT** clause  
returns a **list of enum** of staff  
who are consultants*

### As a Nested Query:

```
SELECT ename
FROM EMPLOYEE
WHERE enum IN
(SELECT enum
FROM WORKS_ON
WHERE role = 'Consultant');
```

So, WHERE clause is equivalent to:

**WHERE enum IN (852358, 852514);**

# SQL – Multiple Table Queries

e.g. *Get the employee names for employees earning salaries above the average salary for all employees*

```
SELECT ename  
FROM EMPLOYEE  
WHERE salary >
```

```
(SELECT AVG (salary)  
FROM EMPLOYEE);
```



The nested **SELECT** clause  
returns a **single value** –  
average salary

**RECALL:** Aggregate functions can only  
appear in **SELECT** or **HAVING** clauses

Result Table

ename
White
Adams
Evans

e.g. *How many projects have less than 2 people working on them?*

```
SELECT COUNT (pnum) AS Num_Projects  
FROM PROJECT  
WHERE pnum IN  
(SELECT pnum  
FROM WORKS_ON  
GROUP BY pnum  
HAVING COUNT(enum) < 2);
```



The subclause **AS <columnname>**, where  
columnname contains **NO** spaces, is used  
to give the result table a meaningful name

Result Table

Num_Projects
2

The query is evaluated **backwards** as:

**subquery:** get the **pnums** of those projects having less than 2 employees  
and pass them upwards into the top query

**top query:** get the number of projects (pnums) passed into the **IN** list



# SQL – Multiple Table Queries

## Self Joins

In some cases a table needs to be **joined to itself**, particularly if extra information is stored in the table but not explicitly available by a normal query.

e.g. *Find all pairs of employees who work on the same floor as each other.*

```
SELECT EMPLOYEE.ename, TEMP.ename  
FROM EMPLOYEE, EMPLOYEE AS TEMP  
WHERE EMPLOYEE.floor = TEMP.floor  
AND EMPLOYEE.enum < TEMP.enum ;
```

This is an example of a **SELF JOIN** whereby a table is joined to itself.

Result Table

ename	ename
Smith	Adams
Jones	Brown
White	Doyle

To do this one copy of the table is given the **alias TEMP** (signified as **TABLENAME AS ALIAS**)

Joins are performed where the floor numbers are the same:

EMPLOYEE.floor = TEMP.floor

the clause:

EMPLOYEE.enum < TEMP.enum

eliminates an employee being shown as on the **same floor as himself** and **duplicate pairs** (e.g. either Adams, Smith OR Smith, Adams) are eliminated

EMPLOYEE			TEMP		
enum	ename	floor	floor	enum	ename
852341	Smith	1	1	852341	Smith
852358	Jones	3	3	852358	Jones
852407	Brown	3	3	852407	Brown
852455	White	2	2	852455	White
852491	Adams	1	1	852491	Adams
852514	Doyle	2	2	852514	Doyle
852530	Evans	4	4	852530	Evans

# SQL – Multiple Table Queries

## Nested Queries with Negation

e.g. *Get all details of employees who do not work on project 121.*

```
SELECT *  
FROM EMPLOYEE  
WHERE enum NOT IN  
      (SELECT enum  
       FROM WORKS_ON  
       WHERE pnum = 121);
```

The query is evaluated **backwards** as:

**subquery:** pass the **enums** of those employees working on project 121 to top query

**top query:** get the details of the employees **NOT IN** that list of **enums**

e.g. *Get the names of employees working on projects that have no consultants working on them*      **OR**      *Get the names of employees **NOT** working on projects that have a consultant on them*

Sometimes, it is helpful to **reframe** the query.

It can also be useful to build the query from the **bottom up**.

**lowest subquery:** Get the projects which have consultants working on them

**middle subquery:** Get the employee numbers for projects not in this list

**top query:** Get the employee names of employees from this employee list

# SQL – Multiple Table Queries

*Get the names of employees **NOT** working on projects that have a consultant on them*

**lowest subquery:** Get the projects which have consultants working on them

```
SELECT pnum
FROM WORKS_ON
WHERE role = 'Consultant'
```

**middle subquery:** Get the employee numbers for projects not in this list

```
SELECT enum
FROM WORKS_ON
WHERE pnum NOT IN
  (SELECT pnum
   FROM WORKS_ON
   WHERE role = 'Consultant')
```

**top query:** Get the employee names of employees from this employee list

```
SELECT DISTINCT ename
FROM EMPLOYEE
WHERE enum IN
  (SELECT enum
   FROM WORKS_ON
   WHERE pnum NOT IN
     (SELECT pnum
      FROM WORKS_ON
      WHERE role = 'Consultant')) ;
```



Result Table

ename
Smith
White
Doyle

# SQL – Multiple Table Queries

## Views

A view is a **virtual table** defined as a subset of one or more tables and stored in the data dictionary

It is only materialized (actually created as a table) at run time from the base table(s)

Views can be manipulated mostly as though it were a base table (from user perspective)

SQL View Syntax:

```
CREATE VIEW viewname (<new attribute list>
AS SELECT <attribute list>
FROM <table list>
[ other clauses];
```



*Can give the attributes  
new names*

e.g. CREATE VIEW **FLOOR\_1\_EMP** (**employee\_no**, **name**)  
AS SELECT enum, ename  
FROM EMPLOYEE  
WHERE floor = 1;

Views can be used in queries,  
just like any other table

EMPLOYEE			
enum	ename	salary	floor
<b>852341</b>	<b>Smith</b>	15000	1
852358	Jones	19000	3
852407	Brown	16000	3
852455	White	25100	2
<b>852491</b>	<b>Adams</b>	30500	1
852514	Doyle	11650	2
852530	Evans	26980	4



FLOOR_1_EMP	
employee_no	name
852341	Smith
852491	Adams