

```
21 |   res.send("this is a random page");
22 | });
23 |
24 | app.get("/err", (req, res) => {
25 |   abcd = abcd;
26 | });
27 |
28 | app.use((err, req, res, next) => {
29 |   console.log("----- ERROR -----");
30 | });
31 |
32 | app.use((req, res) => {
33 |   res.status(404).send("Page not found!");
34 | });
35 |
36 | app.listen(8080, () => {
37 |   console.log("server listening to port 8080");
38 | }).
```

PROBLEMS    OUTPUT    TERMINAL    DEBUG CONSOLE

```
○ shradhakhapra@Shradhas-MacBook-Air Middlewares % nodemon app.js
[nodemon] 3.0.1
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node app.js`
server listening to port 8080
```

----- ERROR -----

```
app.get("/err", (req, res) => {  
  abcd = abcd;  
});
```

```
app.use((err, req, res, next) => {  
  console.log("----- ERROR -----");  
  next();  
});
```



localhost:8080/err

Cannot GET /err

```
19
20 app.get("/random", (req, res) => {
21   res.send("this is a random page");
22 });
23
24 app.get("/err", (req, res) => {
25   abcd = abcd;
26 });
27
28 app.use((err, req, res, next) => {
29   console.log("----- ERROR -----");
30   next(err);
31 });
```

ReferenceError: abcd is not defined

```
at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/app.js:25:3
at Layer.handle [as handle_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/layer.js:95:5)
at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/route.js:144:13)
at Route.dispatch (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/route.js:114:3)
at Layer.handle [as handle_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/layer.js:95:5)
at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:284:15
at Function.process_params (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:346:12)
at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:280:10)
at expressInit (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/middleware/init.js:40:5)
at Layer.handle [as handle_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/layer.js:95:5)
```

```
27
28 app.use((err, req, res, next) => {
29   console.log("----- ERROR -----");
30   next(err);
31 });
32
33 app.use((err, req, res, next) => {
34   console.log("----- ERROR2 Middleware -----");
35   next(err);
36 });
37
```

```
ReferenceError: abcd is not defined
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/app.js:25:3
    at Layer.handle [as handle_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/layer.js:95:5)
    at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/route.js:144:13)
    at Route.dispatch (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/route.js:114:3)
    at Layer.handle [as handle_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/layer.js:95:5)
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:284:15
    at Function.process_params (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:346:12)
    at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:280:10)
    at expressInit (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/middleware/init.js:40:5)
    at Layer.handle [as handle_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/layer.js:95:5)
```

server listening to port 8080

----- ERROR -----

----- ERROR2 Middleware -----

ReferenceError: abcd is not defined

at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/app.js:25:3

at Layer.handle [as handle\_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/layer.js:95:5)

at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/index.js:144:13)

at Route.dispatch (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/index.js:114:3)

at Layer.handle [as handle\_request] (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/layer.js:95:5)

at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/index.js:15

at Function.process\_params (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/index.js:346:12)

at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/router/index.js:280:10)

at expressInit (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node\_modules/express/lib/express.js:41:5)



# Error Handlers

## Custom

### Error handling Middleware

nehagupta7385@gmail.com

```
app.use((err, req, res, next) => {  
  console.log("----- ERROR -----");  
  next(err);  
});
```

# Error Handlers

## Custom

### Error handling Middleware

```
app.use((err, req, res, next) => {  
  console.log("com -- ERROR -----");  
  next(err);  
});
```

next()

next(err)

shehagupta7255@gmail.com

EXPLORER

...

JS app.js

JS ExpressError.js X

▼ MIDDLEWARES

> node\_modules

JS app.js

JS ExpressError.js

{ } package-lock.json

{ } package.json

JS ExpressError.js > [0] <unknown>

```
1  class ExpressError extends Error {
2    constructor(status, message) {
3      super();
4      this.status = status;
5      this.message = message;
6    }
7  }
8
9  module.exports = ExpressError;
10
```

## EXPLORER

...

JS app.js

X

JS ExpressError.js

snehagupta7385@gmail.

## MIDDLEWARES

&gt; node\_modules

JS app.js


JS ExpressError.js

{ } package-lock.json

{ } package.json

JS app.js &gt; [e] checkToken

```
1  const express = require("express");
2  const app = express();
3  const ExpressError = require("../ExpressError");
4
5  const checkToken = (req, res, next) => {
6    let { token } = req.query;
7    if (token === "giveaccess") {
8      next();
9    }
10   throw new ExpressError(401, "ACCESS DENIED!");
11 };
12
13 app.get("/api", checkToken, (req, res) => {
14   res.send("data");
15 });
16
```



EXPLORER

...

JS app.js

×

JS ExpressError.js

✓ MIDDLEWARES

> node\_modules

JS app.js

JS ExpressError.js

{ } package-lock.json

{ } package.json

JS app.js > ...

```
21 app.get("/random", (req, res) => {
22   | res.send("this is a random page");
23   });
24
25 app.get("/err", (req, res) => {
26   | abcd = abcd;
27   });
28
29 app.use((err, req, res, next) => {
30   | console.log("----- ERROR -----");
31   | res.send(err);
32   });
33
```

ex Express error handling



localhost:8080/api?token=give



localhost:8080/api?token=giveaccessnot

```
{ "status": 401, "message": "ACCESS DENIED!" }
```

# Error Class

## Custom

```
app.use((err, req, res, next) => {  
  let { status = 500, message = "SOME ERROR" } = err;  
  res.status(status).send(message);  
});
```



## EXPLORER

...

JS app.js

✕

JS ExpressError.js

## ▼ MIDDLEWARES

&gt; node\_modules

JS app.js


JS ExpressError.js

{ } package-lock.json

{ } package.json

JS app.js >  app.use() callback

```
21 app.get("/random", (req, res) => {
22   res.send("this is a random page");
23 });
24
25 app.get("/err", (req, res) => {
26   abcd = abcd;
27 });
28
29 app.use((err, req, res, next) => {
30   let { status, message } = err;
31   res.status(status).send(message);
```



localhost:8080/err

```
RangeError [ERR_HTTP_INVALID_STATUS_CODE]: Invalid status code: undefined
    at new NodeError (node:internal/errors:371:5)
    at ServerResponse.writeHead (node:_http_server:274:11)
    at ServerResponse._implicitHeader (node:_http_server:265:8)
    at write_ (node:_http_outgoing:756:9)
    at ServerResponse.end (node:_http_outgoing:855:5)
    at ServerResponse.send (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/response.js:199:12)
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/app.js:31:22
    at Layer.handle_error (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/middleware.js:1:1)
    at trim_prefix (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/next.js:41:1)
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/route.js:139:13
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/route.js:118:17
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:144:15
    at Function.process_params (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:41:12)
    at next (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:144:15)
    at /Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:159:15
    at Function.handle (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/router/index.js:1:1)
    at Function.handle (/Users/shradhakhapra/WebClassroom/Backend/Middlewares/node_modules/express/lib/application.js:174:10)
```

Elements Console Sources >> 1

top Filter Default

No Issues

✖ GET <http://localhost:8080/err> 500 (Internal Server Error)

>

express como ✓

# Error Class

## Custom

```
app.use((err, req, res, next) => {  
  let { status = 500, message = "SOME ERROR" } = err;  
  res.status(status).send(message);  
});
```

Error object → valid status code

EXPLORER

...

JS app.js

×

JS ExpressError.js

▼ MIDDLEWARES



> node\_modules

JS app.js


JS ExpressError.js

{ } package-lock.json

{ } package.json

JS app.js >  app.use() callback >  status

```
20
21 app.get("/random", (req, res) => {
22   res.send("this is a random page");
23 });
24
25 app.get("/err", (req, res) => {
26   abcd = abcd;
27 });
28
29 app.use((err, req, res, next) => {
30   let { status = 500, message } = err;
31   res.status(status).send(message);
32 });
33
34 // app.use((req, res) => {
35 //   res.status(404).send("Page not found!");
36 // });
37
```



## EXPLORER

...

JS app.js

X

JS ExpressError.js

## MIDDLEWARES

&gt; node\_modules

JS app.js

JS ExpressError.js

{ } package-lock.json

{ } package.json

JS app.js &gt; app.use() callback &gt; message

```
20
21 app.get("/random", (req, res) => {
22   | res.send("this is a random page");
23   | });
24
25 app.get("/err", (req, res) => {
26   | abcd = abcd;
27   | });
28
29 app.use((err, req, res, next) => {
30   | let status = 500, message = "Some Error Occurred" = err;
31   | res.status(status).send(message);
32   | });
33
```

## Error Class

Create an admin route & send an error with a 403 status code.



## EXPLORER

...

JS app.js

X

JS ExpressError.js

## MIDDLEWARES

&gt; node\_modules

JS app.js

JS ExpressError.js

{ } package-lock.json

{ } package.json

JS app.js &gt; app.get("/admin") callback

```
20
21 app.get("/random", (req, res) => {
22   res.send("this is a random page");
23 });
24
25 app.get("/err", (req, res) => {
26   abcd = abcd;
27 });
28
29 app.get("/admin", (req, res) => {
30   throw new ExpressError(403, "Access to admin is Forbidden");
31 });
32
33 app.use((err, req, res, next) => {
34   let { status = 500, message = "Some Error Occurred" } = err;
35   res.status(status).send(message);
36 });
```

Express error handling



localhost:8080/admin



← → ↻ ⓘ localhost:8080/admin

Access to admin is Forbidden