# SomaticSeq Documentation

# Li Tai Fang / li\_tai.fang@roche.com April 17, 2019

# Contents

1	Intr		1
	1.1	Dependencies	1
	1.2	Docker images	1
2	Dov	vnload SomaticSeq	2
3	Hov	v to run SomaticSeq	2
	3.1	SomaticSeq Training Mode	3
	3.2	SomaticSeq Prediction Mode	3
	3.3	Consensus Mode	4
4	Use	SomaticSeq as a Python library	4
	4.1	somaticseq.somaticseq modules	4
		4.1.1 Module: run_somaticseq	4
		4.1.2 Module: somatic_vcf2tsv and single_sample_vcf2tsv	5
		4.1.3 Module: SSeq_tsv2vcf	6
	4.2	somaticseq.utilities modules	6
		1 0	6
		4.2.2 Module: lociCounterWithLabels	7
5	The	e step-by-step SomaticSeq Workflow	7
	5.1		7
	5.2	Combine the call sets	7
	5.3		8
	5.4	Model Training or Mutation Prediction	8
6	То		9
	6.1	Location	9
	6.2		9
	6.3	r r	9
			10
		6.3.2 SomaticSeq Training	10
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	10
			11
		8	12
		6.3.6 What does the multi-threaded command do	12

7		e BAMSurgeon to create training data	13
	7.1	Requirements	13
	7.2	Three scenario to simulate somatic mutations	13
		7.2.1 When you have sequencing replicates of normal samples	14
		7.2.2 This example mimicks DREAM Challenge	14
		7.2.3 Merge and then split the input tumor and normal BAM files	15
	7.3	Parameters and Options	16
		7.3.1 -merge-bam / -split-bam / -indel-realign	16
	7.4	To create SomaticSeq classifiers	17
8	Rel	ease Notes	17
9	Con	ntact Us	22

## 1 Introduction

SomaticSeq is a flexible post-somatic-mutation-calling algorithm for improved accuracy. It is compatible with 10+ somatic mutation caller(s). Any combination of them can be used to obtain a combined call set with sequencing features extracted into TSV and VCF files. In addition, SomaticSeq uses machine learning (adaptive boosting) to distinguish true mutations from false positives from that call set. The mutation callers we have incorporated are MuTect/Indelocator/MuTect2, VarScan2, JointSNVMix, SomaticSniper, VarDict, MuSE, LoFreq, Scalpel, Strelka, and TNscope. You may incorporate some or all of those callers into your own pipeline with SomaticSeq.

The manuscript, An ensemble approach to accurately detect somatic mutations using SomaticSeq, was published in Genome Biology 2015, 16:197. The SomaticSeq project is located at <a href="https://github.com/bioinform/somaticseq">https://github.com/bioinform/somaticseq</a>. There have been some major improvements in SomaticSeq since that Genome Biology publication in 2015.

The wrapper script somaticseq/run\_somaticseq.py and its parallelized cousin somaticseq\_parallel.py can 1) train the call set into a classifier, 2) predict high-confidence somatic mutations from the call set based on a pre-defined classifier, or 3) default to consensus mode, i.e., extract sequencing features and output the TSV and VCF files, and then label the calls (i.e., PASS, LowQual, or REJECT) based on majority vote of the tools.

## 1.1 Dependencies

- Python 3, plus pysam (v0.14.1), numpy (v1.14.3), and scipy (v1.1.0). The versions in parentheses are in our docker images and validated to work, though other versions should work, too.
- R, plus the ada package in R.
- BEDTools (if inclusion and/or an exclusion region files are supplied, and/or running somatic-seq\_parallel.py instead of somaticseq/run\_somaticseq.py)
- Optional: dbSNP in VCF format (if you want to use dbSNP membership as a part of the training).
- At least one of MuTect/Indelocator/MuTect2, VarScan2, JointSNVMix2, SomaticSniper, VarDict, MuSE, LoFreq, Scalpel, Strelka2, TNscope, and/or Platypus. Those are the tools we have incorporated in SomaticSeq. If there are other somatic tools that may be good addition to our list, please make the suggestion to us.

## 1.2 Docker images

SomaticSeq and the somatic mutation callers that we routinely use were dockerized.

• SomaticSeq: https://hub.docker.com/r/lethalfang/somaticseq

- MuTect2: https://hub.docker.com/r/broadinstitute/gatk
- VarScan2: https://hub.docker.com/r/djordjeklisic/sbg-varscan2
- JointSNVMix2: https://hub.docker.com/r/lethalfang/jointsnvmix2
- SomaticSniper: https://hub.docker.com/r/lethalfang/somaticsniper
- VarDict: https://hub.docker.com/r/lethalfang/vardictjava
- MuSE: https://hub.docker.com/r/marghoob/muse
- LoFreq: https://hub.docker.com/r/marghoob/lofreq
- Scalpel: https://hub.docker.com/r/lethalfang/scalpel
- Strelka2: https://hub.docker.com/r/lethalfang/strelka

# 2 Download SomaticSeq

Source code of SomaticSeq is available via Github repository in BSD open-source license: https://github.com/bioinform/somaticseq. The latest source code can be cloned by the git command

```
git clone https://github.com/bioinform/somaticseq.git
```

Installation is not required to run SomaticSeq, but the simplest way to place SomaticSeq in your path is to run the setup.py install command in the somaticseq repo, i.e.,

```
./setup.py install
```

# 3 How to run SomaticSeq

The somaticseq/run\_somaticseq.py calls a series of programs and procedures after you have run your individual somatic mutation callers, and somaticseq\_parallel.py is a wrapper script that allows parallel processing. Section 6 will teach you how to run those mutation callers that we have been dockerized. It also includes ways to create semi-simulated training data that can be used to create SomaticSeq classifiers. In the next section, we will describe the workflow in this wrapper script in detail.

Both paired and single modes are supported, although single mode is not as well validated scientifically as the paired mode. To see the required and optional input files and parameters to *somaticseq-parallel.py*:

```
# See the global input parameters
somaticseq_parallel.py — help

# Input parameters for paired—sample mode (i.e., tumor—normal)
somaticseq_parallel.py paired — help

# Input parameters for single—sample mode
somaticseq_parallel.py single — help
```

## 3.1 SomaticSeq Training Mode

To create SomaticSeq classifiers, you need a VCF file containing true SNVs and a VCF file containing true INDELs. There is also an option to include a list of regions to include and/or exclude from this exercise. The exclusion or inclusion regions can be VCF or BED files. An inclusion region may be subset of the call sets where you have validated their true/false mutation status, so that only those regions will be used for training. An exclusion region can be regions where the "truth" is ambigious. All the variants in the truth VCF files are assumed to be true positives. Every mutation call not in the truth VCF files is assumed to be false positives (as long as the genomic coordinate is in inclusion region and not in exclusion region if those regions are provided).

All the output VCF files from individual callers are optional. Those VCF files can be bgzipped if they have .vcf.gz extensions. It is imperative that you will use the same parameter for prediction as you do for training.

```
# An example command for SomaticSeq Training.
somaticseq_parallel.py
 -somaticseq-train
                    $OUTPUT_DIR \
 -output-directory
 -genome-reference
                    GRCh38.fa \
 -truth-snv
                     truePositives.snv.vcf \
-truth-indel
                    truePositives.indel.vcf \
 -inclusion-region
                    genome.bed \
 -exclusion-region
                    blacklist.bed \
 -threads
                    12 \
paired
 -tumor-bam-file
                    tumor.bam \
 -normal-bam-file
                    matched\_normal.bam
                    MuTect2/variants.vcf \
 -mutect2-vcf
 -varscan-snv
                    VarScan2/variants.snp.vcf \
                    VarScan2/variants.indel.vcf
 -varscan-indel
--jsm-vcf
                    JointSNVMix2/variants.snp.vcf
 -somaticsniper-vcf SomaticSniper/variants.snp.vcf
 -vardict-vcf
                     VarDict/variants.vcf \
--muse-vcf
                    MuSE/variants.snp.vcf
                    LoFreq/variants.snp.vcf
 -lofreq-snv
 -lofreq-indel
                    LoFreq/variants.indel.vcf
                     Scalpel/variants.indel.vcf
 -scalpel-vcf
 -strelka-snv
                     Strelka/variants.snv.vcf
  strelka-indel
                    Strelka/variants.indel.vcf
```

For the command's argument placement, caller output and bam files are input "after" paired or single option. Everything else goes before, e.g., reference, ground truths, resources such as dbSNP and COSMIC, etc.

Parallel processing is achieved by splitting the inclusion BED file into a number of sub-BED files of equal region sizes, named 1.th.input.bed, 2.th.input.bed, ..., n.th.input.bed. Then each process will be run using each sub-BED file as the inclusion BED file. If there is no inclusion BED file in the command argument, it will split the reference.fa.fai file instead.

SomaticSeq supports any combination of the somatic mutation callers we have incorporated into the workflow. SomaticSeq will run based on the output VCFs you have provided. It will train for SNV and/or INDEL if you provide the truePositives.snv.vcf and/or truePositives.indel.vcf file(s) and invoke the *--somaticseq-train* option. Otherwise, it will fall back to the simple caller consensus mode.

## 3.2 SomaticSeq Prediction Mode

Make sure the classifiers (.RData files) are supplied, Without either of them, or it will fall back to the simple caller consensus mode.

```
# The *.RData files are trained classifier from the training mode.
somaticseq_parallel.py \
--classifier-snv Ensemble.sSNV.tsv.ntChange.Classifier.RData \
```

```
-classifier -indel
                    Ensemble.sINDEL.tsv.ntChange.Classifier.RData \
 -output-directory
                    $OUTPUT_DIR \
                    GRCh38.fa \
 -genome-reference
 -inclusion-region
                    genome.bed
                    blacklist.bed \
--exclusion-region
 -threads
                    12 \
paired
 -tumor-bam-file
                    tumor.bam \
---normal--bam--file
                    matched_normal.bam
                    MuTect2/variants.vcf \
--mutect2-vcf
 -varscan-snv
                     VarScan2/variants.snp.vcf
-varscan-indel
                    VarScan2/variants.indel.vcf
                    JointSNVMix2/variants.snp.vcf \
--jsm-vcf
 -somaticsniper-vcf SomaticSniper/variants.snp.vcf \
                    VarDict/variants.vcf \
-vardict-vcf
                    MuSE/variants.snp.vcf
 -muse-vcf
                    LoFreq/variants.snp.vcf
 -lofreq-snv
--lofreq-indel
                    LoFreq/variants.indel.vcf
--scalpel-vcf
                     Scalpel/variants.indel.vcf
---strelka-snv
                     Strelka/variants.snv.vcf
 -strelka-indel
                     Strelka/variants.indel.vcf
```

## 3.3 Consensus Mode

Same as the commands previously, but without including classifiers or invoking *-somaticseq-train*. Without those information, SomaticSeq will forgo machine learning, and fall back into a simple majority vote.

## 4 Use SomaticSeq as a Python library

Section 3 described how to use SomaticSeq as a standalone software, but SomaticSeq can also be treated as a python library for your own software.

## 4.1 somaticseq.somaticseq modules

The directory *somaticseq/somaticseq* contain some of the critical modules of SomaticSeq, and many can be used as a function of a library.

### 4.1.1 Module: run\_somaticseq

The script somaticseq/somaticseq/run\_somaticseq.py contains the module to convert individual VCF files (each from a popular somatic mutation caller) to SomaticSeq TSV and VCF files.

The code to produce the .TSV and .VCF files described in Section 3, for example, would be something like this:

```
# Module is located somaticseq/somaticseq/run_somaticseq.py import somaticseq.somaticseq.run_somaticseq as run_somaticseq

run_somaticseq.runPaired(outdir='/PATH/TO/SomaticSeq', ref='/PATH/TO/GRCh38.fa', tbam='/PATH/TO/tumor.bwa.bam', nbam='/PATH/TO/normal.bwa.bam', tumor_name='TUMOR', normal_name='NORMAL', truth_snv=None, truth_indel=None, classifier_snv=None, classifier_indel=None, pass_threshold=0.5, lowqual_threshold=0.1, hom_threshold=0.85, het_threshold=0.01, dbsnp='/PATH/TO/dbSNP_138.hg38.vcf.vcf', cosmic='/PATH/TO/COSMIC.v85.vcf', inclusion='/PATH/TO/Exon_Capture.bed', exclusion='/PATH/TO/ignore.bed', mutect=None, indelocator=None, mutect2='/PATH/TO/MuTect2.vcf', varscan_snv=None, varscan_indel=None, jsm=None, sniper=None, varict='/PATH/TO/VarDict.vcf', muse='/PATH/TO/MuSe.vcf', lofreq_snv='/PATH/TO/LoFreq.snv.vcf.gz', lofreq_indel='/PATH/TO/LoFreq.indel.vcf.gz', scalpel=None, strelka_snv='/PATH/TO/Strelka/results/variants/somatic_ssnv.vcf.gz', strelka_indel='/PATH/TO/Strelka/results/variants/somatic_sindel.vcf.gz', tnscope=None, platypus=None, min_mq=1, min_bq=5, min_caller=0.5, somaticseq_train=False, ensembleOutPrefix='Ensemble
```

```
.', consensusOutPrefix='Consensus.', classifiedOutPrefix='SSeq.Classified.', keep_intermediates=False)
```

The parameters of ensembleOutPrefix, consensusOutPrefix, and classifiedOutPrefix will dictate the output file names under outdir.

Likewise, the single sample mode to convert various individual VCF outputs would be something like this:

```
import somaticseq.somaticseq.run_somaticseq as run_somaticseq

run_somaticseq.runSingle(outdir='/PATH/TO/SomaticSeq', ref='/PATH/TO/GRCh38.fa', bam='/
PATH/TO/tumor.bwa.bam', tumor_name='TUMOR', truth_snv=None, truth_indel=None,
classifier_snv=None, classifier_indel=None, pass_threshold=0.5, lowqual_threshold=0.1,
hom_threshold=0.85, het_threshold=0.01, dbsnp='/PATH/TO/dbSNP_138.hg38.vcf.vcf', cosmic
='/PATH/TO/COSMIC.v85.vcf', inclusion='/PATH/TO/Exon_Capture.bed', exclusion='/PATH/TO/
ignore.bed', mutect=None, mutect2='/PATH/TO/MuTect2.vcf', varscan=None, vardict='/PATH/
TO/VarDict.vcf', lofreq='/PATH/TO/LoFreq.vcf', scalpel=None, strelka='/PATH/TO/Strelka.
vcf', min_mq=1, min_bq=5, min_caller=0.5, somaticseq_train=False, ensembleOutPrefix='
Ensemble.', consensusOutPrefix='Consensus.', classifiedOutPrefix='SSeq.Classified.',
keep_intermediates=False)
```

### Parameters:

- truth\_snv/truth\_indel: if present, then the variants in these VCF files will be considered true positives, and *everything else* will be considered false positive. If None, then nothing with regard to true positive or false positive will be annotated.
- classifier\_snv/classifier\_indel: if present, then SomaticSeq prediction will be invoked to create machine learning classified VCF files. if None, only majority-vote consensus VCF files will be created.
- inclusion: bed file so only variants in it will be considered (requires BEDTools on execution path)
- exclusion: bed file so variants in it will be tossed out (requires BEDTools on the execution path)
- mutect/mutect2/varscan/jsm/vardict/muse/lofreq/strelka/scalpel/tnscope: output VCF files from the callers. If None, then it assumes that tool was not used.
- min\_caller: only output variants if at least N number of callers have called it. Since some LowQual calls are considered 0.5, an input of 0.5 tells the function to also return variants even if it's only been called as a "LowQual" by a tool. However, it will still filter out variants that's only been "RE-JECTED" by a caller.

somaticseq\_train: if True, and also if truth\_snv or truth\_indel are present, then it will create Somatic-Seq classifiers. If False, then will not invoke training mode.

## 4.1.2 Module: somatic\_vcf2tsv and single\_sample\_vcf2tsv

Another useful module is the command to extract SomaticSeq features for variants in any VCF file, and output the results to a TSV file. The following function requires both tumor and normal BAM files, and the reference genome. COSMIC, dbSNP, etc. are optional. None for any null inputs.  $min_mq = 0$  for this purpose. This is a filter to only output variants that has been called by a minimum number of tools (which you may specify as VCF inputs such as mutect, varscan, etc.)

```
import somaticseq.somaticseq.somatic_vcf2tsv as somatic_vcf2tsv

somatic_vcf2tsv.vcf2tsv(is_vcf='/PATH/TO/variants.vcf', is_bed=None, is_pos=None, nbam_fn = '/PATH/TO/normal.bam', tbam_fn='/PATH/TO/tumor.bam', truth=None, cosmic='/PATH/TO/COSMIC.v85.vcf', dbsnp='/PATH/TO/dbSNP_138.hg38.vcf.vcf', mutect=None, varscan=None, jsm =None, sniper=None, vardict=None, muse=None, lofreq=None, scalpel=None, strelka=None, tnscope=None, platypus=None, dedup=True, min_mq=1, min_bq=5, min_caller=0, ref_fa='/PATH/TO/GRCh38.fa', p_scale=None, outfile='/PATH/TO/SomaticSeq.FeaturesExtracted.tsv')
```

You may also extract sequencing info for any VCF file if you just have one bam file

```
import somaticseq.somaticseq.single_sample_vcf2tsv as single_sample_vcf2tsv single_sample_vcf2tsv.vcf2tsv(is_vcf='/PATH/TO/variants.vcf', is_bed=None, is_pos=None, bam_fn='/PATH/TO/tumor.bam', truth=None, cosmic='/PATH/TO/COSMIC.v85.vcf', dbsnp='/PATH/TO/dbSNP_138.hg38.vcf.vcf', mutect=None, varscan=None, vardict=None, muse=None, lofreq= None, scalpel=None, strelka=None, dedup=True, min_mq=1, min_bq=5, min_caller=0, ref_fa = '/PATH/TO/GRCh38.fa', p_scale=None, outfile='/PATH/TO/SomaticSeq.FeaturesExtracted.tsv')
```

Both somaticseq/somaticseq/somatic\_vcf2tsv.py and somaticseq/somaticseq/single\_sample\_vcf2tsv.py may also be run as standalone scripts. Invoke the script with -h to learn their usages. Parameters:

- is\_vcf: the VCF file serves as the input file, from which every variant will have its sequencing feature extracted from the BAM file(s).
- mutect/varscan/jsm/sniper/vardict/muse/lofreq/scalpel/strelka/tnscope: VCF files from these tools. If present, the function will extract information from these files such as if a variant is called by the tool. If None, everything associated with that tool will be "nan" in the TSV file.

## 4.1.3 Module: SSeq\_tsv2vcf

This module converts SomaticSeq's TSV file (described in Sec. 4.1.2) to SomaticSeq VCF files.

```
import somaticseq.somaticseq.SSeq_tsv2vcf as SSeq_tsv2vcf

SSeq_tsv2vcf.tsv2vcf(tsv_fn='/PATH/TO/SomaticSeq.tsv', vcf_fn='/PATH/TO/SomaticSeq.vcf',
    tools=['MuTect2', 'SomaticSniper', 'Strelka'], pass_score=0.5, lowqual_score=0.1,
    hom_threshold=0.85, het_threshold=0.01, single_mode=False, paired_mode=True,
    normal_sample_name='NORMAL', tumor_sample_name='TUMOR', print_reject=True, phred_scaled=
    True)
```

#### Parameters:

- tools: A list of tools that were run, can only be selected from MuTect2, MuTect, VarScan2, JointSNVMix2, SomaticSniper, VarDict, MuSE, LoFreq, Scalpel, Strelka, TNscope, and/or Platypus.
- print\_reject: if False, will only print PASS and LowQual variants into VCF. If True, will print everything from TSV to VCF.
- phred\_scaled: if True, will print Phred-scaled score in QUAL column (if the TSV was produced with SomaticSeq prediction). If False, will print the 0-1 scale. If no SomaticSeq prediction was done, will print 0.

## 4.2 somaticseq.utilities modules

## 4.2.1 Module: split\_Bed\_into\_equal\_regions

Given a .bed or a .fa.fai file, it will split the input region into N number of bed files, such that each bed file has equal-sized regions in them.

## 4.2.2 Module: lociCounterWithLabels

Given a list of .bed files and a .fa.fai file, it will return a .bed file detailing which regions were contained from which .bed inputs.

```
somaticseq/utilities/lociCounterWithLabels.py -fai GRCh38.fa.fai -beds 1.bed 2.bed 3.bed - labels 01 02 03 -out overlapping.bed
```

#### Parameters:

• labels: A list of labels to be written in 4th column of the output bed file. If absent, the 4th column will be populated by the input bed file names.

# 5 The step-by-step SomaticSeq Workflow

We'll describe the workflow here.

## 5.1 Apply inclusion and exclusion regions

This step may be needed for model training. BEDTools is invoked by SomaticSeq. An inclusion region means we will only use calls inside these regions. An exclusion region means we do not care about calls inside this region. DREAM Challenge had exclusion regions, e.g., blacklisted regions, etc. It is also a routine used to parallelize the process by splitting large regions into equal-sized (in terms of number of pairs) regions, so that they can be processed in parallel.

## 5.2 Combine the call sets

We use *vcfModifier/getUniqueVcfPositions.py* and *bedtools sort* to combine the VCF files from different callers. For each caller output, intermediate VCF file(s) may be created to separate the SNVs and INDELs calls, and also remove some REJECT calls to reduce file sizes.

The following scripts are used to modify original VCF outputs.

```
vcfModifier/modify_JointSNVMix2.py
vcfModifier/modify_MuTect2.py
vcfModifier/modify_MuTect.py
vcfModifier/modify_SomaticSniper.py
vcfModifier/modify_ssMuTect2.py
vcfModifier/modify_ssStrelka.py
vcfModifier/modify_Strelka.py
vcfModifier/modify_VarDict.py
vcfModifier/modify_VarDict.py
vcfModifier/modify_VarScan2.py
```

modify\_ssTOOL.py denotes it's for single-sample mode. JointSNVMix2 does not output VCF files. In our own workflow, we convert its output into a basic VCF file with an 2 awk one-liners, which you may see at utilities/dock-ered\_pipelines/mutation\_callers/submit\_JointSNVMix2.sh.

```
# To avoid text files on the order of terabytes, this awk one-liner keeps entries where the
    reference is not "N", and the somatic probabilities are at least 0.95.
awk -F "\t" 'NR!=1 && $4!="N" && $10+$11>=0.95'

# This awk one-liner converts the text file into a basic VCF file
awk -F "\t" '{print $1 "\t" $2 "\t.\t" $3 "\t" $4 "\t.\t.\tAAAB=" $10 ";AABB=" $11 "\tRD:AD\
    t" $5 ":" $6 "\t" $7 ":" $8}'

## The actual commands we've used in our workflow:
echo -e '##fileformat=VCFv4.1' > unsorted.vcf
```

```
echo -e '##NFO=<ID=AAAB, Number=1, Type=Float, Description="Probability of Joint Genotype AA
    in Normal and AB in Tumor">' >> unsorted.vcf
echo -e '##NFO=<ID=AABB, Number=1, Type=Float, Description="Probability of Joint Genotype AA
    in Normal and BB in Tumor">' >> unsorted.vcf
echo -e '##FORMAT=<ID=RD, Number=1, Type=Integer, Description="Depth of reference-supporting
    bases (reads1)">' >> unsorted.vcf
echo -e '##FORMAT=<ID=AD, Number=1, Type=Integer, Description="Depth of variant-supporting
    bases (reads2)">' >> unsorted.vcf
echo -e '#CHROM\tPOS\tID\tREF\tALT\tQUAL\tFILTER\tINFO\tFORMAT\tNORMAL\tTUMOR' >> unsorted.
    vcf

python $PATH/TO/jsm.py classify joint_snv_mix_two genome.GRCh37.fa normal.bam tumor.bam
    trained.parameter.cfg /dev/stdout |\
awk -F "\t" 'NR!=1 && $4!="N" && $10+$11>=0.95' |\
awk -F "\t" 'RP!=1 && $4!="N" && $10+$11>=0.95' |\
awk -F "\t" 'Frint $1 "\t" $2 "\t.\t" $3 "\t" $4 "\t.\t.\tAAAB=" $10 ";AABB=" $11 "\tRD:AD\
    t" $5 ":" $6 "\t" $7 ":" $8}' >> unsorted.vcf
```

## 5.3 Convert the VCF file into TSV file

This script somaticseq/somatic\_vcf2tsv.py works for all VCF files (requires input for two BAM files). It extracts information from the BAM files, as well as some individual callers' output VCF files. If the ground truth VCF file is included, a called variant will be annotated as a true positive, and everything will be annotated as a false positive. somaticseq/single\_sample\_vcf2tsv.py is used for single-sample mode.

At the end of this, Ensemble.sSNV.tsv and Ensemble.sINDEL.tsv are created.

All the options for somaticseq/somatic\_vcf2tsv.py or somaticseq/single\_sample\_vcf2tsv.py can be found by running.

```
somaticseq/somatic_vcf2tsv.py -h
somaticseq/single_sample_vcf2tsv.py -h
```

Note: Do not worry if Python throws a warning like this.

```
RuntimeWarning: invalid value encountered in double_scalars z = (s - expected) / np.sqrt(n1*n2*(n1+n2+1)/12.0)
```

This is to tell you that scipy was attempting some statistical test with empty data. That's usually due to the fact that normal BAM file has no variant reads at that given position. That is why lots of values are NaN for the normal.

## 5.4 Model Training or Mutation Prediction

You can use Ensemble.sSNV.tsv and Ensemble.sINDEL.tsv files either for model training (provided that their mutation status is annotated with 0 or 1) or mutation prediction. This is done with stochastic boosting algorithm we have implemented in R.

Model training:

```
# Training:
r_scripts/ada_model_builder_ntChange.R Ensemble.sSNV.tsv Consistent_Mates
Inconsistent_Mates
r_scripts/ada_model_builder_ntChange.R Ensemble.sINDEL.tsv Strelka_QSS Strelka_TQSS
Consistent_Mates Inconsistent_Mates
```

Ensemble.sSNV.tsv.ntChange.Classifier.RData and Ensemble.sINDEL.tsv.ntChange.Classifier.RData will be created from model training. The arguments after Ensemble.sSNV.tsv and Ensemble.sINDEL.tsv tells

the builder script to ignore those features in training. These features do not improve accuracy in our data sets (mostly WGS data, but they may help other data sets)

Mutation prediction:

```
# Mutation prediction:
r_script/ada_model_predictor.R Ensemble.sSNV.tsv.Classifier.RData Ensemble.sSNV.tsv
Trained.sSNV.tsv
r_script/ada_model_predictor.R Ensemble.sINDEL.tsv.Classifier.RData Ensemble.sINDEL.tsv
Trained.sINDEL.tsv
```

After mutation prediction, if you feel like it, you may convert Trained.sSNV.tsv and Trained.sINDEL.tsv into VCF files. Use -tools to list ONLY the individual tools used to have appropriately annotated VCF files. Accepted tools are MuTect2/MuTect/Indelocator, VarScan2, JointSNVMix2, SomaticSniper, VarDict, MuSE, LoFreq, Scalpel, Strelka, and/or TNscope. To list a tool without having run it, the VCF will be annotated as if the tool was run but did not identify that position as a somatic variant, which is probably undesireable.

```
# Probability above 0.7 labeled PASS (-pass 0.7), and between 0.1 and 0.7 labeled LowQual (-low 0.1):
# Use -all to include REJECT calls in the VCF file
# Use -phred to convert probability values (between 0 to 1) into Phred scale in the QUAL column in the VCF file

somaticseq/SSeq_tsv2vcf.py -tsv Trained.sSNV.tsv -vcf Trained.sSNV.vcf -pass 0.7 -low 0.1 -tools MuTect2 VarScan2 JointSNVMix2 SomaticSniper VarDict MuSE LoFreq Strelka -all -phred

somaticseq/SSeq_tsv2vcf.py -tsv Trained.sINDEL.tsv -vcf Trained.sINDEL.vcf -pass 0.7 -low 0.1 -tools MuTect2 VarScan2 VarDict LoFreq Scalpel Strelka -all -phred
```

## 6 To run the dockerized somatic mutation callers

For your convenience, we have created a couple of scripts that can generate run script for the dockerized somatic mutation callers.

## 6.1 Location

• somaticseq/utilities/dockered\_pipelines/

## 6.2 Requirements

- Have internet connection, and able to pull and run docker images from docker.io
- Have cluster management system such as Sun Grid Engine, so that the "qsub" command is valid

## 6.3 Example commands

You may run the following command to see all the available options for this command, in either paired (tumor-normal) or single (tumor-only) mode.

```
makeSomaticScripts.py [paired|single] -h
```

### 6.3.1 Tumor-Normal Mode

The command shown above will create scripts for MuTect2, SomaticSniper, VarDict, MuSE, LoFreq, Scalpel, and Strelka. Then, it will create the SomaticSeq script that merges those 7 callers. This command defaults to majority-vote consensus.

Since it's --aciton echo, it will echo the mutation caller scripts locations, but these scripts will not be run. If you do --action qsub instead, then those mutation caller scripts will be qsub'ed. You'll still need to mantually run/submit the SomaticSeq script after all the caller jobs are done.

The --threads 12 will create 12 equal-size regions in 12 bed files, and parallelize the jobs into 12 regions. However, you'll need to combine those 12 separate results together.

## 6.3.2 SomaticSeq Training

As things are currently set up, training mode is best run seperately **after** you've run the workflows above, because we don't have a workflow engine to manage and then merge the result of each thread. You may invoke "-train-somaticseq" here, but SomaticSeq will train on each thread. Now if you use just a single thread (e.g., "-threads 1" is the default), you may train it just fine. In this case, two classifiers will be created (\*.RData files), one for SNV and one for INDEL.

```
$PATH/TO/somaticseq/utilities/dockered_pipelines/makeSomaticScripts.py_paired \
 -normal-bam
                   /ABSOLUTE/PATH/TO/normal_sample.bam \
                   /ABSOLUTE/PATH/TO/tumor_sample.bam \
--tumor-bam
 -genome-reference /ABSOLUTE/PATH/TO/GRCh38.fa
                   /ABSOLUTE/PATH/TO/RESULTS
 -output-directory
                   /ABSOLUTE/PATH/TO/dbSNP.GRCh38.vcf \
-dbsnp-vcf
-truth-snv
                   /ABSOLUTE/PATH/TO/truth.snv.vcf \
                   /ABSOLUTE/PATH/TO/truth.indel.vcf \
-truth-indel
 -action
                   echo \
 -run-mutect2 --run-somaticsniper --run-vardict --run-muse --run-lofreq --run-scalpel --run-
    strelka2 --run-somaticseq --train-somaticseq
```

Notice the command includes -truth-snv and -truth-indel, and invokes somaticseq-train. For multi-threaded job, you should not invoke somaticseq-train. Instead, you should combine all the Ensemble.sSNV.tsv and Ensemble.sINDEL.tsv files (separately), and then train on the combined files.

## 6.3.3 SomaticSeq Prediction

```
$PATH/TO/somaticseq/utilities/dockered_pipelines/makeSomaticScripts.py paired \
---normal-bam /ABSOLUTE/PATH/TO/normal_sample.bam \
---tumor-bam /ABSOLUTE/PATH/TO/tumor_sample.bam \
---genome-reference /ABSOLUTE/PATH/TO/GRCh3s.fa \
---output-directory /ABSOLUTE/PATH/TO/RESULTS \
---dbsnp-vcf /ABSOLUTE/PATH/TO/dbSNP.GRCh3s.vcf \
---snv-classifier /ABSOLUTE/PATH/TO/Snv_Classifier.RData \
---indel-classifier /ABSOLUTE/PATH/TO/Indel_Classifier.RData \
---action echo \
```

```
--threads 12 \
--run-mutect2 --run-somaticsniper --run-vardict --run-muse --run-lofreq --run-scalpel --run-
strelka2 --run-somaticseq
```

Notice the command includes –classifier-snv and –classifier-indel.

#### 6.3.4 Parameters

```
paired
                               Invokes tumor-normal modes. Placed immediately after
    makeSomaticScripts.py.
single
                               Invokes tumor-only modes. Placed immediately after
    makeSomaticScripts.py
 -normal-bam
                              /ABSOLUTE/PATH/TO/normal_sample.bam (Required for paired)
                               /ABSOLUTE/PATH/TO/tumor_sample.bam (Required for paired)
--tumor-bam
--bam
                               /ABSOLUTE/PATH/TO/tumor_sample.bam (Required for single)
                               /ABSOLUTE/PATH/TO/human_reference.fa (Required)
 -genome-reference
                              /ABSOLUTE/PATH/TO/dbsnp.vcf (Required: for MuSE and LoFreq)
 -dbsnp-vcf
--cosmic-vcf
                              /ABSOLUTE/PATH/TO/cosmic.vcf (Optional)
                              /ABSOLUTE/PATH/TO/Capture_region.bed (Optional. Will assume
--inclusion-region
    whole genome from the .fai file without it.)
                               /ABSOLUTE/PATH/TO/Blacklist_region.bed (Optional)
 -exclusion-region
                               (Optional. The minimum VAF cutoff for VarDict and VarScan2.
 -minimum-VAF
    Defaults are 0.10 for VarScan2 and 0.05 for VarDict).
 -action
                              qsub (Optional: the command preceding the .cmd scripts.
    Default is echo)
 -threads
                              36 (Optional for multiThreads and invalid for singleThread:
   evenly split the genome into 36 BED files. Default = 1).
 -run-mutect2
                               (Optional flag to invoke MuTect2)
--run-varscan2
                               (Optional flag to invoke VarScan2)
 -run-jointsnymix2
                               (Optional flag to invoke JointSNVMix2. Not for single.)
--run-somaticsniper
                               (Optional flag to invoke SomaticSniper. Not for single.)
--run-vardict
                               (Optional flag to invoke VarDict)
---run-muse
                               (Optional flag to invoke MuSE. Not for single.)
---run-lofreq
                               (Optional flag to invoke LoFreq)
                               (Optional flag to invoke Scalpel)
--run-scalpel
                               (Optional flag to invoke Strelka)
--run-strelka
                               (Optional flag to invoke SomaticSeq. This script always be
 -run-somaticseq
    echo'ed, as it should not be submitted until all the callers above complete).
                               /ABSOLUTE/PATH/TO/OUTPUT.DIRECTORY (Required)
-output-directory
---somaticseq-directory
                               SomaticSeq_Output_Directory (Optional. The directory name of
    the SomaticSeq output. Default = SomaticSeq).
 -train-somaticseq
                              (Optional flag to invoke SomaticSeq to produce classifiers if
    ground truth VCF files are provided. Only recommended in singleThread mode, because
    otherwise it's better to combine the output TSV files first, and then train classifiers
                              (Optional. What to do with the somaticseq.cmd. Default is echo
 -somaticseq-action
    . Only do "qsub" if you have already completed all the mutation callers, but want to run
     SomaticSeq at a different setting.)
 -snv-classifier
                               Trained_sSNV_Classifier.RData (Optional if there is a
    classifer you want to use)
 -indel-classifier
                               Trained_sINDEL_Classifier.RData (Optional if there is a
    classifer you want to use)
 -truth-snv
                              sSNV_ground_truth.vcf (Optional if there is a ground truth,
   and everything else will be labeled false positive)
                              sINDEL_ground_truth.vcf (Optional if there is a ground truth,
 -truth-indel
   and everything else will be labeled false positive)
                               (Optional flag for Strelka)
--exome
---scalpel-two-pass
                               (Optional parameter for Scalpel. Default = false.)
 -mutect2-arguments
                               (Extra parameters to pass onto Mutect2, e.g., --mutect2-
    arguments '--initial_tumor_lod 3.0 --log_somatic_prior -5.0 --min_base_quality_score
--mutect2-filter-arguments
                               (Extra parameters to pass onto FilterMutectCalls)
--varscan-arguments
                               (Extra parameters to pass onto VarScan2)
--varscan-pileup-arguments
                               (Extra parameters to pass onto samtools mpileup that creates
   pileup files for VarScan)
```

```
-ism-train-arguments
                             (Extra parameters to pass onto JointSNVMix2's train command)
-jsm-classify-arguments
                             (Extra parameters to pass onto JointSNVMix2's classify command
somaticsniper-arguments
                             (Extra parameters to pass onto SomaticSniper)
-vardict-arguments
                              (Extra parameters to pass onto VarDict)
-muse-arguments
                              (Extra parameters to pass onto MuSE)
-lofreq-arguments
                              (Extra parameters to pass onto LoFreq)
-scalpel-discovery-arguments
                             (Extra parameters to pass onto Scalpel's discovery command)
                              (Extra parameters to pass onto Scalpel's export command)
-scalpel-export-arguments
-strelka-config-arguments
                              (Extra parameters to pass onto Strelka's config command)
-strelka-run-arguments
                              (Extra parameters to pass onto Strekla's run command)
-somaticseq-arguments
                              (Extra parameters to pass onto SomaticSeq.Wrapper.sh)
```

## 6.3.5 What does the single-threaded command do

- For each flag such as --mutect2, --jointsnvmix2, ...., --strelka, a run script ending with .cmd will be created in /ABSOLUTE/PATH/TO/RESULTS/logs. By default, these .cmd scripts will only be created, and their file path will be printed on screen. However, if you do "--action qsub", then these scripts will be submitted via the qsub command. The default action is "echo."
  - Each of these .cmd script correspond to a mutation caller you specified. They all use docker images.
  - We may improve their functionalities in the future to allow more tunable parameters. For the initial releases, POC and reproducibility take precedence.
- If you do "--somaticseq," the somaticseq script will be created in /ABSOLUTE/PATH/TO/RE-SULTS/SomaticSeq/logs. However, it will not be submitted until you manually do so after each of these mutation callers is finished running.
  - In the future, we may create more sophisticated solution that will automatically solves these
    dependencies. For the initial release, we'll focus on stability and reproducibility.
- Due to the way those run scripts are written, the Sun Grid Engine's standard error log will record the time the task completes (i.e., Done at 2017/10/30 29:03:02), and it will only do so when the task is completed with an exit code of 0. It can be a quick way to check if a task is done, by looking at the final line of the standard error log file.

#### 6.3.6 What does the multi-threaded command do

It's very similar to the single-threaded WES solution, except the job will be split evenly based on genomic lengths.

- If you specified "--threads 36," then 36 BED files will be created. Each BED file represents 1/36 of the total base pairs in the human genome (obtained from the .fa.fai file, but only including 1, 2, 3, ..., MT, or chr1, chr2, ..., chrM contigs). They are named 1.bed, 2.bed, ..., 36.bed, and will be created into /ABSOLUTE/PATH/TO/RESULTS/1, /ABSOLUTE/PATH/TO/RESULTS/2, ..., /ABSOLUTE/PATH/TO/RESULTS/36. You may, of course, specify any number. The default is 12.
- For each mutation callers you specify (with the exception of SomaticSniper), a script will be created into /ABSOLUTE/PATH/TO/RESULTS/1/logs, /ABSOLUTE/PATH/TO/RESULTS/2/logs, etc., with partial BAM input. Again, they will be automatically submitted if you do "--action qsub."
- Because SomaticSniper does not support partial BAM input (one would have to manually split the BAMs in order to parallelize SomaticSniper this way), the above mentioned procedure is not applied to SomaticSniper. Instead, a single-threaded script will be created (and potentially qsub'ed) into /ABSOLUTE/PATH/TO/RESULTS/logs.

- However, because SomaticSniper is by far the fastest tool there, single-thread is doable even for WGS. Even single-threaded SomaticSniper will likely finish before parallelized Scalpel. When I benchmarked the DREAM Challenge Stage 3 by splitting it into 120 regions, Scalpel took 10 hours and 10 minutes to complete 1/120 of the data. SomaticSniper took a little under 5 hours for the whole thing.
- After SomaticSniper finishes, the result VCF files will be split into each of the /ABSOLUTE/-PATH/TO/RESULTS/1, /ABSOLUTE/PATH/TO/RESULTS/2, etc.
- JointSNVMix2 also does not support partial BAM input. Unlike SomaticSniper, it's slow and takes massive amount of memory. It's not a good idea to run JointSNVMix2 on a WGS data. The only way to do so is to manually split the BAM files and run each separately. We may do so in the future, but JointSNVMix2 is a 5-year old that's no longer being supported, so we probably won't bother.
- Like the single-threaded case, a SomaticSeq run script will also be created for each partition like /ABSOLUTE/PATH/TO/RESULTS/1/SomaticSeq/logs, but will not be submitted until you do so manually.
  - For simplicity, you may wait until all the mutation calling is done, then run a command like

```
find /ABSOLUTE/PATH/TO/RESULTS -name 'somaticseq*.cmd' -exec qsub {} \;
```

## 7 Use BAMSurgeon to create training data

For your convenience, we have created a couple of wrapper scripts that can generate the run script to create training data using BAMSurgon at somaticseq/utilities/dockered\_pipelines/bamSimulator. Descriptions and example commands can be found in the README there.

This pipeline is used to spike in in silico somatic mutations into existing BAM files in order to create a training set for somatic mutations.

After the in silico data are generated, you can use the somatic mutation pipeline on the training data to generate the SomaticSeq classifiers.

Classifiers built on training data work if the training data is similar to the data you want to predict. Ideally, the training data are sequenced on the same platform, same sample prep, and similar depth of coverage as the data of interest.

This method is based on BAMSurgeon, slightly modified into our own fork for some speedups.

The proper citation for BAMSurgeon is Ewing AD, Houlahan KE, Hu Y, et al. Combining tumor genome simulation with crowdsourcing to benchmark somatic single-nucleotide-variant detection. Nat Methods. 2015;12(7):623-30.

## 7.1 Requirements

- Have internet connection, and able to pull and run docker images from docker.io
- Have cluster management system such as Sun Grid Engine, so that the "qsub" command is valid

### 7.2 Three scenario to simulate somatic mutations

Which scenario to use depend on the data sets available to you.

## 7.2.1 When you have sequencing replicates of normal samples

This is our approach to define high-confidence somatic mutations in SEQC2 consortium's cancer reference samples, presented here.


In this case, in silico mutations will be spiked into Replicate\_002.bam. Since Replicate\_002.bam and Replicate\_001.bam are otherwise the same sample, any mutations detected that you did not spike in are false positives. The following command is a single-thread example.

```
$PATH/TO/somaticseq/utilities/dockered_pipelines/bamSimulator/BamSimulator_singleThread.sh \
 -genome-reference
                     /ABSOLUTE/PATH/TO/GRCh38.fa
                     /ABSOLUTE/PATH/TO/Replicate_001.bam \
 -tumor-bam-in
 -normal-bam-in
                     /ABSOLUTE/PATH/TO/Replicate_002.bam \
                     syntheticTumor.bam \
 -tumor-bam-out
 -normal-bam-out
                     syntheticNormal.bam \
 -split-proportion
                     0.5
                     20000 \
--num-snvs
                     8000 \
 -num-indels
                     0.0
 -min-vaf
 -max-vaf
                     1.0
 -left -beta
                     2
 -right-beta
                     5
                     2
 -min-variant-reads
  output-dir
                     /ABSOLUTE/PATH/TO/trainingSet \
  -action
                     qsub
```

BamSimulator\_\*.sh creates semi-simulated tumor-normal pairs out of your input tumor-normal pairs. The "ground truth" of the somatic mutations will be synthetic\_snvs.vcf, synthetic\_indels.vcf in the output directory.

For multi-thread job (WGS), use BamSimulator\_multiThreads.sh instead. See below for additional options and parameters.

A schematic of the BAMSurgeon simulation procedure




## 7.2.2 This example mimicks DREAM Challenge

DREAM Somatic Mutation Calling Challenge was an international competition to find algorithms that gave the most accurate performances.

In that case, a high-coverage BAM file is randomly split into two. One of which is designated normal, and the other one is designated tumor where mutations will be spiked in. Like the previous example, any mutations found between the designated tumor and designated normal are false positive, since not only are they from the same sample, but also from the same sequencing run. This example will not capture false positives as a result of run-to-run biases if they exist in your sequencing data. It will, however, still capture artefacts related to sequencing errors, sampling errors, mapping errors, etc.


```
$PATH/TO/somaticseq/utilities/dockered_pipelines/bamSimulator/BamSimulator_multiThreads.sh \
--genome-reference/ABSOLUTE/PATH/TO/GRCh38.fa --tumor-bam-in/ABSOLUTE/PATH/TO/
highCoverageGenome.bam --tumor-bam-out syntheticTumor.bam --normal-bam-out
syntheticNormal.bam --split-proportion 0.5 --num-snvs 10000 --num-indels 8000 --num-svs
1500 --min-vaf 0.0 --max-vaf 1.0 --left-beta 2 --right-beta 5 --min-variant-reads 2 --
```

The –split-bem will randomly split the high coverage BAM file into two BAM files, one of which is designated normal and the other one designated tumor for mutation spike in. The –indel-realign is an option that will perform GATK Joint Indel Realignment on the two BAM files. You may or may not invoke it depending on your real data sets. The –merge-output-bams creates another script that will merge the BAM and VCF files region-by-region. It will need to be run manually after all the spike in is done. A schematic of the DREAM Challenge simulation procedure



## 7.2.3 Merge and then split the input tumor and normal BAM files

The --merge-bam will merge the normal and tumor BAM files into a single BAM file. Then, --split-bem will randomly split the merged BAM file into two BAM files. One of which is designated normal, and one of which is designated tumor. Synthetic mutations will then be spiked into the designated tumor to create "real" mutations. This is the approach described in our 2017 AACR Abstract. A schematic of the simulation procedure



## 7.3 Parameters and Options

```
-genome-reference
                                     /ABSOLUTE/PATH/TO/human_reference.fa (Required)
                                     /ABSOLUTE/PATH/TO/capture_region.bed (BED file to limit where mutation
   selector
       spike in will be attempted)
   -tumor-bam-in
                                     Input BAM file (Required)
  -normal-bam-in
                                     Input BAM file (Optional, but required if you want to merge it with the
       tumor input)
  -tumor-bam-out
                                     Output BAM file for the designated tumor after BAMSurgeon mutation spike
        in
   -normal-bam-out
                                     Output BAM file for the designated normal if --split-bam is chosen
                                     The faction of total reads desginated to the normal. (Defaut = 0.5)
  -split-proportion
--num-snvs
                                     Number of SNVs to spike into the designated tumor
--num-indels
                                     Number of INDELs to spike into the designated tumor
  -num-svs
                                     Number of SVs to spike into the designated tumor (Default = 0)
                                     Minimum depth where spike in can take place
  -min-depth
  -max-depth
                                     Maximum depth where spike in can take place
--min-vaf
                                     Minimum VAF to simulate
                                     Maximum VAF to simulate
--max-vaf
  -left -beta
                                     Left beta of beta distribution for VAF
--right-beta
                                     Right beta of beta distribution for VAF
  -min-variant-reads Minimum number of variant-supporting reads for a successful spike in
--output-dir
                                     Output directory
--merge-bam
                                     Flag to merge the tumor and normal bam file input
---split-bam
                                     Flag to split BAM file for tumor and normal
                                     Flag to go through the BAM file and remove reads where more than 2
--clean-bam
       identical read names are present, or reads where its read length and CIGAR string do not
        match. This was necessary for some BAM files downloaded from TCGA. However, a proper
       pair-end BAM file should not have the same read name appearing more than twice. Use this
         only when necessary as it first sorts BAM file by qname, goes through the cleaning
       procedure, then re-sort by coordinates.
   indel-realign
                                     Conduct GATK Joint Indel Realignment on the two output BAM files.
       Instead of syntheticNormal.bam and syntheticTumor.bam, the final BAM files will be
       syntheticNormal.JointRealigned.bam and syntheticTumor.JointRealigned.bam.
   -seed
                                     Random seed. Pick any integer for reproducibility purposes.
   -threads
                                     Split the BAM files evenly in N regions, then process each (pair) of sub
       -BAM files in parallel.
                                     The command preceding the run script created into /ABSOLUTE/PATH/TO/
  -action
       BamSurgeoned\_SAMPLES/logs.~"qsub"~is~to~submit~the~script~in~SGE~system.~Default = \frac{echo}{control of the control of the con
```

## 7.3.1 -merge-bam / -split-bam / -indel-realign

If you have sequenced replicate normal, that's the best data set for training. You can use one of the normal as normal, and designate the other normal (of the same sample) as tumor. Use *--indel-realign* to invoke GATK IndelRealign.

When you have a normal that's roughly 2X the coverage as your data of choice, you can split that into two halves. One designated as normal, and the other one designated as tumor. That DREAM Challenge's approach. Use --split-bam --indel-realign options.

Another approach is to merge the tumor and normal data, and then randomly split them as described above. When you merge the tumor and normal, the real tumor mutations are relegated as germline or noise, so they are considered false positives, because they are supposed to be evenly split into the designated normal. To take this approach, use --merge-bam --split-bam --indel-realign options.

Don't use --indel-realign if you do not use indel realignment in your alignment pipeline.

In some BAM files, there are reads where read lengths and CIGAR strings don't match. Spike in will fail in these cases, and you'll need to invoke --clean-bam to get rid of these problematic reads.

You can control and visualize the shape of target VAF distribution with python command:

```
import scipy.stats as stats
import numpy as np
import matplotlib.pyplot as plt
```

```
\begin{array}{l} {\rm leftBeta}\;,\;\; {\rm rigthBeta}\;=\;2\;,5\\ {\rm minAF}\;,\;\; {\rm maxAF}\;=\;0\;,1\\ {\rm x}\;=\;{\rm np.linspace}\,(0\;,1\;,10\;1)\\ {\rm y}\;=\;{\rm stats.beta.pdf}({\rm x}\;,\;\; {\rm leftBeta}\;,\;\; {\rm rigthBeta}\;,\;\; {\rm loc}\;=\;{\rm minAF}\;,\;\; {\rm scale}\;=\;{\rm minAF}\;+\;{\rm maxAF})\\ {\rm -}\;=\;{\rm plt.plot}\,({\rm x}\;,\;\;{\rm y}) \end{array}
```

## 7.4 To create SomaticSeq classifiers

After the mutation simulation jobs are completed, you may create classifiers with the training data with the following command:

See our somatic mutation pipeline for more details.

```
$PATH/TO/somaticseq/utilities/dockered_pipelines/submit_callers_multiThreads.sh \
 -output-dir
                  /ABSOLUTE/PATH/TO/trainingSet/somaticMutationPipeline \
 -normal-bam
                  /ABSOLUTE/PATH/TO/trainingSet/syntheticNormal.bam \
                  /ABSOLUTE/PATH/TO/trainingSet/syntheticTumor.bam \
 -tumor-bam
 -human-reference /ABSOLUTE/PATH/TO/GRCh38.fa
                  /ABSOLUTE/PATH/TO/dbSNP.GRCh38.vcf \
-dbsnp
 -thread
                  /ABSOLUTE/PATH/TO/trainingSet/synthetic_snvs.vcf \
 -truth-snv
 -truth-indel
                  /ABSOLUTE/PATH/TO/trainingSet/synthetic_indels.leftAlign.vcf \
 -action
 -mutect2 --somaticsniper --vardict --muse --lofreq --strelka --somaticseq
```

## 8 Release Notes

Make sure training and prediction use the same SomaticSeq version, or at least make sure the different minor version changes do not change the results significantly.

#### 1. Version 1.0

Version used to generate data in the manuscript and Stage 5 of the ICGC-TCGA DREAM Somatic Mutation Challenge, where SomaticSeq's results were #1 for INDEL and #2 for SNV.

In the original manuscript, VarDict's var2vcf\_somatic.pl script was used to generate VarDict VCFs, and subsequently "-filter somatic" was used for SSeq\_merged.vcf2tsv.py. Since then (including DREAM Challenge Stage 5), VarDict recommends var2vcf\_paired.pl over var2vcf\_somatic.pl, and subsequently "-filter paired" was used for SSeq\_merged.vcf2tsv.py. The difference in SomaticSeq results, however, is pretty much negligible.

#### 2. Version 1.1

Automated the SomaticSeq.Wrapper.sh script for both training and prediction mode. No change to any algorithm.

## 3. Version 1.2

Have implemented the following improvement, mostly for indels:

- SSeq\_merged.vcf2tsv.py can now accept pileup files to extract read depth and DP4 (reference forward, reference reverse, alternate forward, and alternate reverse) information (mainly for indels). Previously, that information can only be extracted from SAMtools VCF. Since the SAMtools or HaplotypeCaller generated VCFs hardly contain any indel information, this option improves the indel model. The SomaticSeq.Wrapper.sh script is modified accordingly.
- Extract mapping quality (MQ) from VarDict output if this information cannot be found in SAMtools VCF (also mostly benefits the indel model).

• Indel length now positive for insertions and negative for deletions, instead of using the absolute value previously.

#### 4. Version 2.0

- Removed dependencies for SAMtools and HaplotypeCaller during feature extraction. SSeq\_merged.vcf2tsv.py extracts those information (plus more) directly from BAM files.
- Allow not only VCF file, but also BED file or a list of chromosome coordinate as input format for SSeq\_merged.vcf2tsv.py, i.e., use -mybed or -mypos instead of -myvcf.
- Instead of a separate step to annotate ground truth, that can be done directly by SSeq\_merged.vcf2tsv.py by supplying the ground truth VCF via -truth.
- SSeq\_merged.vcf2tsv.py can annotate dbSNP and COSMIC information directly if BED file or a list of chromosome coordinates are used as input in lieu of an annotated VCF file.
- Consolidated feature sets, e.g., removed some redundant features
- Fixed a bug: if JointSNVMix2 is not included, the values should be "NaN" instead of 0's. This is to keep consistency with how we handle all other caller decision.

## 5. Version 2.0.2

- Incorporated LoFreq.
- Used getopt to replace getopts in the SomaticSeq.Wrapper.sh script to allow long options.

#### 6. Version 2.1.2

- Properly handle cases when multiple ALT's are calls in the same position. The VCF files can either contain multiple calls in the ALT column (i.e., A,G), or have multiple lines corresponding to the same position (one line for each variant call). Some functions were significantly rewritten to allow this.
- Incorporated Scalpel.
- Deprecated HaplotypeCaller and SAMTools dependencies completely as far as feature generation is concerned.
- The Wrapper script removed SnpSift/SnpEff dependencies. Those information can be directly obtained during the SSeq\_merged.vcf2tsv.py step. Also removed some additional legacy steps that has become useless since v2 (i.e., score\_Somatic.Variants.py). Added a step to check the correctness of the input. The v2.1 and 2.1.1 had some typos in the wrapper script, so only describing v2.1.2 here.

## 7. Version 2.2

• Added MuTect2 support.

### 8. Version 2.2.1

- InDel\_3bp now stands for indel counts within 3 bps of the variant site, instead of exactly 3 bps from the variant site as it was previously (likewise for InDel\_2bp).
- Collapse MQ0 (mapping quality of 0) reads supporting reference/variant reads into a single metric of MQ0 reads (i.e., tBAM\_MQ0 and nBAM\_MQ0). From experience, the number of MQ0 reads is at least equally predictive of false positive calls, rather than distinguishing if those MQ0 reads support reference or variant.
- Obtain SOR (Somatic Odds Ratio) from BAM files instead of VarDict's VCF file.
- Fixed a typo in the SomaticSeq.Wrapper.sh script that did not handle inclusion region correctly.

### 9. Version 2.2.2

- Got around an occasional unexplained issue in then ada package were the SOR is sometimes categorized as type, by forcing it to be numeric.
- Defaults PASS score from 0.7 to 0.5, and make them tunable in the SomaticSeq.Wrapper.sh script (--pass-threshold and --lowqual-threshold).

#### 10. Version 2.2.3

- Incorporated Strelka2 since it's now GPLv3.
- Added another R script (ada\_model\_builder\_ntChange.R) that uses nucleotide substitution pattern as a feature. Limited experiences have shown us that it improves the accuracy, but it's not heavily tested yet.
- If a COSMIC site is labeled SNP in the COSMIC VCF file, if\_cosmic and CNT will be labeled as 0. The COSMIC ID will still appear in the ID column. This will not change any results because both of those features are turned off in the training R script.
- Fixed a bug: if JointSNVMix2 is not included, the values should be "NaN" instead of 0's. This is to keep consistency with how we handle all other callers.

## 11. Version 2.2.4

- Resolved a bug in v2.2.3 where the VCF files of Strelka INDEL and Scalpel clash on GATK CombineVariants, by outputting a temporary VCF file for Strelka INDEL without the sample columns.
- Caller classification: consider if\_Scalpel = 1 only if there is a SOMATIC flag in its INFO.

### 12. Version 2.2.5

- Added a dockerfile. Docker repo at https://hub.docker.com/r/lethalfang/somaticseq/.
- Ability to use vcfsort.pl instead of GATK CombineVariants to merge VCF files.

## 13. Version 2.3.0

- Moved some scripts to the utilities directory to clean up the clutter.
- Added the split\_Bed\_into\_equal\_regions.py to utilities, which will split a input BED file into multiple BED files of equal size. This is to be used to parallelize large WGS jobs.
- Made compatible with MuTect2 from GATK4.
- Removed long options for the SomaticSeq.Wrapper.sh script because it's more readable this way.
- Added a script to add "GT" field to Strelka's VCF output before merging it with other VCF files. That was what caused GATK CombineVariants errors mentioned in v2.2.4's release notes.
- Added a bunch of scripts at utilities/dockered\_pipelines that can be used to submit (requiring Sun Grid Engine or equivalent) dockerized pipeline to a computing cluster.

## 14. Version 2.3.1

- Improve the automated run script generator at utilities/dockered\_pipelines.
- No change to SomaticSeq algorithm

## 15. Version 2.3.2

Added run script generators for dockerized BAMSurgeon pipelines at utilities/dockered\_pipelines/bamSurgeon

• Added an error message to r\_scripts/ada\_model\_builder\_ntChange.R when TrueVariants\_or\_False don't have both 0's and 1's. Other than this warning message change, no other change to SomaticSeq algorithm.

#### 16. Version 2.4.0

- Restructured the utilities scripts.
- Added the utilities/filter\_SomaticSeq\_VCF.py script that "demotes" PASS calls to LowQual based on a set of tunable hard filters.
- BamSurgeon scripts invokes modified BamSurgeon script that splits a BAM file without the need to sort by read name. This works if the BAM files have proper read names, i.e., 2 and only 2 identical read names for each paired-end reads.
- No change to SomaticSeq algorithm

## 17. Version 2.4.1

- Updated some docker job scripts.
- Added a script that converts some items in the VCF's INFO field into the sample field, to precipitate the need to merge multiple VCF files into a single multi-sample VCF, i.e., utilities/reformat\_VCF2SEQC2.py.
- No change to SomaticSeq algorithm

### 18. Version 2.5.0

- In modify\_VJSD.py, get rid of VarDict's END tag (in single sample mode) because it causes problem with GATK CombineVariants.
- Added limited single-sample support, i.e., ssSomaticSeq.Wrapper.sh is the wrapper script. singleSample\_callers\_singleThread.sh is the wrapper script to submit single-sample mutation caller scripts.
- Added run scripts for read alignments and post-alignment processing, i.e,. FASTQ  $\rightarrow$  BAM, at utilities/dockered\_pipelines/alignments.
- Fixed a bug where the last two CD4 numbers were both alternate concordant reads in the output VCF file, when the last number should've been alternate discordant reads.
- Changed the output file names from Trained.s(SNV|INDEL).vcf and Untrained.s(SNV|INDEL).vcf to SSeq.Classified.s(SNV|INDE).vcf and Consensus.s(SNV|INDEL).vcf. No change to the actual tumor-normal SomaticSeq algorithm.
- Added utilities/modify\_VarDict.py to VarDict's "complex" variant calls (e.g., GCA¿TAC) into SNVs when possible.
- Modified r\_scripts/ada\_model\_builder\_ntChange.R to allow you to ignore certain features, e.g., r\_scripts/ada\_model\_builder\_ntChange.R Training\_Data.tsv nBAM\_REF\_BQ tBAM\_REF\_BQ SiteHomopolymer\_Length ...

Everything after the input file are features to be ignored during training. Also added r\_scripts/ada\_cross\_validation.R.

## 19. Version 2.5.1

- Additional passable parameters options to pass extra parameters to somatic mutation callers. Fixed a bug where the "two-pass" parameter is not passed onto Scalpel in multiThreads scripts.
- Ignore Strelka\_QSS and Strelka\_TQSS for indel training in the SomaticSeq.Wrapper.sh script.

## 20. Version 2.5.2

• Ported some pipeline scripts to singularities at utilities/singularities.

### 21. Version 2.6.0

- VarScan2\_Score is no longer extracted from VarScan's output. Rather, it's now calculated directly using Fisher's Exact Test, which reproduces VarScan's output, but will have a real value when VarScan2 does not output a particular variant.
- Incorporate TNscope's output VCF into SomaticSeq, but did not incorporate TNscope caller into the dockerized workflow because we don't have distribution license.

### 22. Version 2.6.1

- Optimized memory for singularity scripts.
- Updated utilities/bamQC.py and added utilities/trimSoftClippedReads.py (removed soft-clipped bases on soft-clipped reads)
- Added some docker scripts at utilities/dockered\_pipelines/QC

## 23. Version 2.7.0

- Added another feature: consistent/inconsistent calls for paired reads if the position is covered by both forward and reverse reads. However, they're excluded as training features in Somatic-Seq.Wrapper.sh script for the time being.
- Change non-GCTA characters to N in VarDict.vcf file to make it conform to VCF file specifications

#### 24. Version 2.7.1

- Without –gatk \$PATH/TO/GenomeAnalysisTK.jar in the SomaticSeq.Wrapper.sh script, it will use utilities/getUniqueVcfPositions.py and utilities/vcfsorter.pl to (in lieu of GATK3 CombineVariants) to combine all the VCF files.
- Fixed bugs in the docker/singularities scripts where extra arguments for the callers are not correctly passed onto the callers.

## 25. Version 2.7.2

- Make compatible with .cram format
- Fixed a bug where Strelka-only calls are not considered by SomaticSeq.

### 26. Version 2.8.0

• The program is now designed to crash if the VCF file(s) are not sorted according to the .fasta reference file.

## 27. Version 2.8.1

• Fixed a bug in the ssSomaticSeq.Wrapper.sh script (single-sample mode), where the SNV algorithm weren't looking for SNV VCF files during merging when using utilities/getUniqueVcfPositions.py, causing empty SNV files. For previous commands (invoking –gatk for CombineVariants), the results have never changed.

## 28. Version 3.0.0

Refactored the codes.

• The wrapper scripts written in bash script (i.e., SomaticSeq.Wrapper.sh and ssSomaticSeq.Wrapper.sh) are replaced by somaticseq/run\_somaticseq.py, though they're still kept for backward-compatibility.

• Allow parallel processing using somaticseq\_parallel.py

### 29. Version 3.0.1

• Fixed a bug that didn't handle Strelka/LoFreq indel calls correctly in somaticseq/combine\_callers.py module.

## 30. Version 3.1.0

- When splitting MuTect2 files into SNV and INDEL, make sure either the ref base or the alt base (but not both) consists of a single base, i.e., discarding stuff like GCAA>GCT.
- Fixed a bug introduced in v3.0.1 that caused the program to handle .vcf.gz files incorrectly.
- Incorporated Platypus into paired mode.

## 31. Version 3.1.1

- Fixed some bash scripts involved with single-sample multi-thread callers.
- vcfModifier/splitVcf.py to handle multi-allelic calls better for indels.

## 32. Version 3.2.0

- Re-wrote in Python some somatic caller run script generators that were once written in bash, at utilities/dockered\_pipelines/makeSomaticScripts.py. See Section 6 for details.
- Fixed setup.py, even though running ./setup.py install is optional. You can still (always) run scripts from where you downloaded SomaticSeq.

### 33. Version 3.2.1

• Fixed the TA2CG feature in ada\_model\_builder\_ntChange.R

## 9 Contact Us

For suggestions, bug reports, or technical support, please post in https://github.com/bioinform/somaticseq/issues. The developers are alerted when issues are created there. Alternatively, you may also email li\_tai.fang@roche.com.