

```
#include <iostream>
using namespace std;
int main(){
    cout << code ;
}
```

A. CODE

B. ERROR

```
#include <iostream>
using namespace std;
int main(){
    cout << "career" << "labs";
}
```

A. career labs

B. careerlabs

Which of the following data type stores longest decimal number ?

- A. Float
- B. Int
- C. Long Double
- D. Double

Compiler assigns a garbage value to an uninitialised local variable in C++ Programming ?

- A. true
- B. false

```
bool a = true;  
cout << a;
```

- A. true
- B. false
- C. 1
- D. 0

What is the output of the following code if the input is :
5 15?

```
#include <iostream>  
using namespace std;  
int main() {  
    int a, b;  
    cin >> a;  
    cin >> b;  
    cout << (a+b);  
}
```

```
cout << ('a' + 1);
```

(ASCII Value of 'a' is 97)

- A. 97
- B. 98
- C. 'a' + 1
- D. 'b'

What will be the output of following statement ?

```
int i = 'c';  
cout << i;
```

- A. 'C'
- B. 99
- C. 'c'
- D. 67

```
#include <iostream>
using namespace std;
int main()
{
    int var1 = 5;
    int var2 = 6;
    cout << (var1 > var2);
}
```

- A. 0
- B. 1
- C. True
- D. False

```
#include <iostream>
using namespace std;
int main()
{
    double a = 6 / 4;
    int b = 6 / 4;
    double c = a + b;
    cout << c;
}
```

- A. 3
- B. 1.5
- C. 2
- D. 2.5