Machine-Level Programming I: Basics

Computer Systems, DIKU
Sep. 16, 2019

Michael Kirkedal Thomsen

Based on slides by Randal E. Bryant and David R. O'Hallaron

Today: Machine Programming I: Basics

- **History of Intel processors and architectures**
- **C, assembly, machine code**
- **Assembly Basics: Registers, operands, move**
- **Arithmetic & logical operations**

Intel x86 Processors

- **Dominate laptop/desktop/server market**

- **Evolutionary design**
  - Backwards compatible up until 8086, introduced in 1978
  - Added more features as time goes on

- **Complex instruction set computer (CISC)**
  - Many different instructions with many different formats
    - But, only small subset encountered with Linux programs
  - Hard to match performance of Reduced Instruction Set Computers (RISC)
  - But, Intel has done just that!
    - In terms of speed. Less so for low power.
    - Done by steering the hole market to their architecture

Intel x86 Evolution: Milestones

Name	*Date*	*Transistors*	*MHz*
8086	**1978**	**29K**	**5-10**
386	**1985**	**275K**	**16-33**
Pentium 4E	**2004**	**125M**	**2800-3800**
Core 2	**2006**	**291M**	**1060-3500**
Core i7	**2008**	**731M**	**1700-3900**

- First 16-bit Intel processor. Basis for IBM PC & DOS
- 1MB address space
- First 32 bit Intel processor , referred to as IA32
- Added “flat addressing”, capable of running Unix
- First 64-bit Intel x86 processor, referred to as x86-64
- First multi-core Intel processor
- Four cores

Intel x86 Processors, cont.

- **Machine Evolution**

386	1985	0.3M
Pentium	1993	3.1M
Pentium/MMX	1997	4.5M
PentiumPro	1995	6.5M
Pentium III	1999	8.2M
Pentium 4	2001	42M
Core 2 Duo	2006	291M
Core i7 (quad)	2008	731M
Core i7 Haswell (8)	2014	2,600M
Ci7 Broadwell (10)	2016	3,200M



- **Added Features**
  - Instructions to support multimedia operations
  - Instructions to enable more efficient conditional operations
  - Transition from 32 bits to 64 bits
  - More cores

2015 "State of the Art"

- Core i7 Broadwell 2015

Desktop Model

- 4 cores
- Integrated graphics
- 3.3-3.8 GHz
- 65W

Server Model

- 8 cores
- Integrated I/O
- 2-2.6 GHz
- 45W



Moore's Law

- An observation that the transistors density roughly doubles every 18 to 24 months



Data source: Wikipedia (https://en.wikipedia.org/wiki/Transistor_count)
The data visualization is available at OurWorldinData.org. There you find more visualizations and research on this topic.

- Will slow down. Expected 2020 - 2025

x86 Clones: Advanced Micro Devices (AMD)

- **Historically**
  - AMD has followed just behind Intel, a little bit slower, a lot cheaper
- **Then**
  - Recruited top circuit designers from Digital Equipment Corp. and other downward trending companies
  - Built Opteron: tough competitor to Pentium 4
  - Developed x86-64, their own extension to 64 bits
- **2010's**
  - Intel got its act together, leads the world in semiconductor technology
  - AMD has fallen behind, relies on external semiconductor manufacturer
- **Today**
  - Very close
  - AMD tries with better on-chip GPU support (Nvidia)

Intel's 64-Bit History

- **2001: Intel Attempts Radical Shift from IA32 to IA64**
  - Totally different architecture (Itanium)
  - Executes IA32 code only as legacy
  - Performance disappointing
- **2003: AMD Steps in with Evolutionary Solution**
  - x86-64 (now called "AMD64")
- **Intel Felt Obligated to Focus on IA64**
  - Hard to admit mistake or that AMD is better
- **2004: Intel Announces EM64T extension to IA32**
  - Extended Memory 64-bit Technology
  - Almost identical to x86-64!
- **All but low-end x86 processors support x86-64**
  - But, lots of code still runs in 32-bit mode

Our Coverage

- **IA32**
  - The traditional x86
  - For 15/18-213: RIP, Summer 2015

- **x86-64**
  - The standard
  - `shark> gcc hello.c`
  - `shark> gcc -m64 hello.c`

- **Presentation**
  - Book covers x86-64
  - Web aside on IA32
  - We will only cover x86-64

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- **C, assembly, machine code**
- Assembly Basics: Registers, operands, move
- Arithmetic & logical operations

Definitions

- **Architecture: (also ISA: instruction set architecture) The parts of a processor design that one needs to understand or write assembly/machine code.**
  - Examples: instruction set specification, registers.
- **Microarchitecture: Implementation of the architecture.**
  - Examples: cache sizes and core frequency.
- **Code Forms:**
  - Machine Code: The byte-level programs that a processor executes
  - Assembly Code: A text representation of machine code
- **Example ISAs:**
  - Intel: x86, IA32, Itanium, x86-64
  - ARM: Used in almost all mobile phones
  - MIPS, Alpha, RISC5
  - x86prime

x86prime

- **Simple instruction set we are using on the course**
  - Syntax following x86_64
  - Data control closer to RISC5
- **All programming in this course will be in x86prime**
  - After 2. year many of you will not see assembly code, no need to make it too advanced
- **You still need to understand x86_64**
  - Useful skill to be read x86_64
  - Important in IT security

Simplified Computer System (hardware)



Assembly/Machine Code View



Programmer-Visible State

- **PC: Program counter**
  - Address of next instruction
  - Called "RIP" (x86-64)
- **Register file**
  - Heavily used program data
- **Condition codes**
  - Store status information about most recent arithmetic or logical operation
  - Used for conditional branching

- **Memory**
  - Byte addressable array
  - Code and user data
  - Stack to support procedures

Turning C into Object Code

- Code in files `p1.c p2.c`
- Compile with command: `gcc –Og p1.c p2.c -o p`
  - Use basic optimizations (`–Og`) [New to recent versions of GCC]
  - Put resulting binary in file `p`



Turning C into x86prime

- Code in files `p1.c p2.c`
- Compile C with command: `gcc –Og –S –o p.s p.c`
- Transform assembly code: `Primify p.s`



Compiling Into Assembly

C Code (sum.c)

```
long plus(long x, long y);

void sumstore(long x, long y,
              long *dest)
{
    long t = plus(x, y);
    *dest = t;
}
```

Generated x86-64 Assembly

```
sumstore:
   pushq   %rbx
   movq    %rdx, %rbx
   call    plus
   movq    %rax, (%rbx)
   popq    %rbx
   ret
```

Obtain with command

```
gcc –Og –S sum.c
```

Produces file `sum.s`

***Warning*: Will get very different results on different machines (Linux, Mac OS-X, Windows...) due to different versions of gcc and different compiler settings.**

Assembly Characteristics: Data Types

- **"Integer" data of 1, 2, 4, or 8 bytes**
  - Data values
  - Addresses (untyped pointers)
- **Floating point data of 4, 8, or 10 bytes**
- **Code: Byte sequences encoding series of instructions**
- **No aggregate types such as arrays or structures**
  - Just contiguously allocated bytes in memory

Assembly Characteristics: Operations

- **Perform arithmetic function on register or memory data**
- **Transfer data between memory and register**
  - Load data from memory into register
  - Store register data into memory
- **Transfer control**
  - Unconditional jumps to/from procedures
  - Conditional branches

Object Code

Code for `sumstore`

```
0x0400595:
    0x53
    0x48
    0x89
    0xd3
    0xe8
    0xf2
    0xff
    0xff
    0xff
    0x48
    0x89
    0x03
    0x5b
    0xc3
```

- **Total of 14 bytes**
- **Each instruction 1, 3, or 5 bytes**
- **Starts at address `0x0400595`**

- **Assembler**
  - Translates `.s` into `.o`
  - Binary encoding of each instruction
  - Nearly-complete image of executable code
  - Missing linkages between code in different files
- **Linker**
  - Resolves references between files
  - Combines with static run-time libraries
    - E.g., code for **`printf, sscan`**
  - Some libraries are *dynamically linked*
    - Linking occurs when program begins execution

Machine Instruction Example

```
*dest = t;
```

```
movq %rax, (%rbx)
```

```
0x40059e:  48 89 03
```

- **C Code**
  - Store value **t** where designated by **dest**
- **Assembly**
  - Move 8-byte value to memory
    - Quad words in x86-64 parlance
  - Operands:
    - **t:** Register **%rax**
    - **dest:** Register **%rbx**
    - ***dest:** Memory **M[%rbx]**
- **Object Code**
  - 3-byte instruction
  - Stored at address **0x40059e**

Disassembling Object Code

Disassembled

```
0000000000400595 <sumstore>:
  400595:  53                   push   %rbx
  400596:  48 89 d3             mov    %rdx,%rbx
  400599:  e8 f2 ff ff ff       callq  400590 <plus>
  40059e:  48 89 03             mov    %rax,(%rbx)
  4005a1:  5b                   pop    %rbx
  4005a2:  c3                   retq
```

- **Disassembler**

  `objdump -d sum`

  - Useful tool for examining object code
  - Analyzes bit pattern of series of instructions
  - Produces approximate rendition of assembly code
  - Can be run on either `a.out` (complete executable) or `.o` file

Alternate Disassembly

Object

```
0x0400595:
    0x53
    0x48
    0x89
    0xd3
    0xe8
    0xf2
    0xff
    0xff
    0xff
    0x48
    0x89
    0x03
    0x5b
    0xc3
```

Disassembled

```
Dump of assembler code for function sumstore:
 0x0000000000400595 <+0>: push   %rbx
 0x0000000000400596 <+1>: mov    %rdx,%rbx
 0x0000000000400599 <+4>: callq  0x400590 <plus>
 0x000000000040059e <+9>: mov    %rax,(%rbx)
 0x00000000004005a1 <+12>:pop    %rbx
 0x00000000004005a2 <+13>:retq
```

- **Within gdb Debugger**

  `gdb sum`

  `disassemble sumstore`

  - Disassemble procedure

  `x/14xb sumstore`

  - Examine the 14 bytes starting at `sumstore`

What Can be Disassembled?

```
% objdump -d WINWORD.EXE

WINWORD.EXE:   file format pei-i386

No symbols in "WINWORD.EXE".
Disassembly of section .text:

30001000 <.text>:
30001000:
30001001:
30001003:
30001005:
3000100a:
```

Reverse engineering forbidden by Microsoft End User License Agreement

- Anything that can be interpreted as executable code
- Disassembler examines bytes and reconstructs assembly source

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- C, assembly, machine code
- **Assembly Basics: Registers, operands, move**
- Arithmetic & logical operations

x86-64 Integer Registers

%rax	%eax	%r8	%r8d
%rbx	%ebx	%r9	%r9d
%rcx	%ecx	%r10	%r10d
%rdx	%edx	%r11	%r11d
%rsi	%esi	%r12	%r12d
%rdi	%edi	%r13	%r13d
%rsp	%esp	%r14	%r14d
%rbp	%ebp	%r15	%r15d

- Can reference low-order 4 bytes (also low-order 1 & 2 bytes)

Some History: IA32 Registers



Moving Data

- **Moving Data**

  `movq` *Source*, *Dest*:

- **Operand Types**
  - ***Immediate:*** Constant integer data
    - Example: **`$0x400`, `$-533`**
    - Like C constant, but prefixed with **`'$'`**
    - Encoded with 1, 2, or 4 bytes
  - ***Register:*** One of 16 integer registers
    - Example: **`%rax`, `%r13`**
    - But **`%rsp`** reserved for special use
    - Others have special uses for particular instructions
  - ***Memory:*** 8 consecutive bytes of memory at address given by register
    - Simplest example: **`(%rax)`**
    - Various other "address modes"



movq Operand Combinations

	Source	Dest	Src,Dest	C Analog
movq	*Imm*	*Reg*	`movq $0x4,%rax`	`temp = 0x4;`
		Mem	`movq $-147,(%rax)`	`*p = -147;`
	Reg	*Reg*	`movq %rax,%rdx`	`temp2 = temp1;`
		Mem	`movq %rax,(%rdx)`	`*p = temp;`
	Mem	*Reg*	`movq (%rax),%rdx`	`temp = *p;`

Cannot do memory-memory transfer with a single instruction

Simple Memory Addressing Modes

- **Normal (R) Mem[Reg[R]]**
  - Register R specifies memory address
  - Aha! Pointer dereferencing in C

```
movq (%rcx),%rax
```

- **Displacement D(R) Mem[Reg[R]+D]**
  - Register R specifies start of memory region
  - Constant displacement D specifies offset

```
movq 8(%rbp),%rdx
```

Example of Simple Addressing Modes

```
void swap
    (long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
    movq    (%rdi), %rax
    movq    (%rsi), %rdx
    movq    %rdx, (%rdi)
    movq    %rax, (%rsi)
    ret
```

Understanding Swap()

```
void swap
    (long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```



Register	Value
%rdi	xp
%rsi	yp
%rax	t0
%rdx	t1

```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()




```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()




```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()




```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()




```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Understanding Swap()




```
swap:
    movq    (%rdi), %rax  # t0 = *xp
    movq    (%rsi), %rdx  # t1 = *yp
    movq    %rdx, (%rdi)  # *xp = t1
    movq    %rax, (%rsi)  # *yp = t0
    ret
```

Simple Memory Addressing Modes

- **Normal (R) Mem[Reg[R]]**
  - Register R specifies memory address
  - Aha! Pointer dereferencing in C

```
movq (%rcx),%rax
```

- **Displacement D(R) Mem[Reg[R]+D]**
  - Register R specifies start of memory region
  - Constant displacement D specifies offset

```
movq 8(%rbp),%rdx
```

Complete Memory Addressing Modes

- **Most General Form**

  D(Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]+ D]**

  - D: Constant "displacement" 1, 2, or 4 bytes
  - Rb: Base register: Any of 16 integer registers
  - Ri: Index register: Any, except for `%rsp`
  - S: Scale: 1, 2, 4, or 8 (*why these numbers?*)

- **Special Cases**

  (Rb,Ri) **Mem[Reg[Rb]+Reg[Ri]]**

  D(Rb,Ri) **Mem[Reg[Rb]+Reg[Ri]+D]**

  (Rb,Ri,S) **Mem[Reg[Rb]+S*Reg[Ri]]**

Address Computation Examples

%rdx	0xf000
%rcx	0x0100

Expression	Address Computation	Address
0x8(%rdx)	0xf000 + 0x8	0xf008
(%rdx,%rcx)	0xf000 + 0x100	0xf100
(%rdx,%rcx,4)	0xf000 + 4*0x100	0xf400
0x80(,%rdx,2)	2*0xf000 + 0x80	0x1e080

Today: Machine Programming I: Basics

- History of Intel processors and architectures
- C, assembly, machine code
- Assembly Basics: Registers, operands, move
- **Arithmetic & logical operations**

Address Computation Instruction

- **`leaq` Src, Dst**
  - Src is address mode expression
  - Set Dst to address denoted by expression

- **Uses**
  - Computing addresses without a memory reference
    - E.g., translation of `p = &x[i];`
  - Computing arithmetic expressions of the form x + k*y
    - k = 1, 2, 4, or 8

- **Example**

```
long m12(long x)
{
  return x*12;
}
```

Converted to ASM by compiler:

```
leaq (%rdi,%rdi,2), %rax # t <- x+x*2
salq $2, %rax            # return t<<2
```

Some Arithmetic Operations

- **Two Operand Instructions:**

Format	Computation		
`addq`	Src,Dest	Dest = Dest + Src	
`subq`	Src,Dest	Dest = Dest - Src	
`imulq`	Src,Dest	Dest = Dest * Src	
`salq`	Src,Dest	Dest = Dest << Src	Also called shlq
`sarq`	Src,Dest	Dest = Dest >> Src	Arithmetic
`shrq`	Src,Dest	Dest = Dest >> Src	Logical
`xorq`	Src,Dest	Dest = Dest ^ Src	
`andq`	Src,Dest	Dest = Dest & Src	
`orq`	Src,Dest	Dest = Dest | Src	

- **Watch out for argument order!**
- **No distinction between signed and unsigned int (why?)**

Some Arithmetic Operations

- **One Operand Instructions**

`incq`	Dest	Dest = Dest + 1
`decq`	Dest	Dest = Dest - 1
`negq`	Dest	Dest = - Dest
`notq`	Dest	Dest = ~Dest

- **See book for more instructions**

Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
   leaq    (%rdi,%rsi), %rax
   addq    %rdx, %rax
   leaq    (%rsi,%rsi,2), %rdx
   salq    $4, %rdx
   leaq    4(%rdi,%rdx), %rcx
   imulq   %rcx, %rax
   ret
```

Interesting Instructions

- **`leaq`**: address computation
- **`salq`**: shift
- **`imulq`**: multiplication
  - But, only used once

Understanding Arithmetic Expression Example

```
long arith
(long x, long y, long z)
{
  long t1 = x+y;
  long t2 = z+t1;
  long t3 = x+4;
  long t4 = y * 48;
  long t5 = t3 + t4;
  long rval = t2 * t5;
  return rval;
}
```

```
arith:
   leaq    (%rdi,%rsi), %rax    # t1
   addq    %rdx, %rax           # t2
   leaq    (%rsi,%rsi,2), %rdx
   salq    $4, %rdx             # t4
   leaq    4(%rdi,%rdx), %rcx   # t5
   imulq   %rcx, %rax           # rval
   ret
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	t1, t2, rval
%rdx	t4
%rcx	t5

Machine Programming I: Summary

- **History of Intel processors and architectures**
  - Evolutionary design leads to many quirks and artifacts
- **C, assembly, machine code**
  - New forms of visible state: program counter, registers, ...
  - Compiler must transform statements, expressions, procedures into low-level instruction sequences
- **Assembly Basics: Registers, operands, move**
  - The x86-64 move instructions cover wide range of data movement forms
- **Arithmetic**
  - C compiler will figure out different instruction combinations to carry out computation