

Enumerated Types & Typedefs


CS1A

© Michele Rousseau

Enums & Typedefs

1

C++ Data Types



© Michele Rousseau

Enums & Typedefs

2

C++ Simple Data Types

Type	Size	Values
bool	1 byte	true (1) or false (0)
char	1 byte	'a' to 'z', 'A' to 'Z', '0' to '9', space, tab, and so on
int	4 bytes	-2,147,483,648 to 2,147,483,647
short	2 bytes	-32,768 to 32,767
long	4 bytes	-2,147,483,648 to 2,147,483,647
float	4 bytes	$\pm(1.2 \times 10^{-38}$ to $3.4 \times 10^{38})$
double	8 bytes	$\pm(2.3 \times 10^{-308}$ to $-1.7 \times 10^{308})$

© Michele Rousseau

Enums & Typedefs

3

Data types

- So far the simple data types we've worked with have been
 - int to store integers
 - float to store floating point numbers
 - char to store a character (or a c-string)
 - bool to store T or F (1 or 0)
- We can use these to solve many problems but...

What if we need to create a different data type specifically for our program

© Michele Rousseau

Enums & Typedefs

4

Enumeration Type

Let's say we want a program that works with the days of the week ← there is no days data type

Enumeration Types allow us to create our own data type

Syntax

```
enum TypeName {value1, value2, value3, ...};
```

To Define an enumeration type we need

- a name for the data type
- a set of values for the data type
- a set of operations on the values
- Using enumerated types are self-documenting
 - they make your code more understandable

© Michele Rousseau

Enums & Typedefs

5

Defining a Enumeration Type

Let's say we want to define the days of the week

```
enum Days
```

```
{
```

```
SUNDAY,  
MONDAY,  
TUESDAY,  
WEDNESDAY,  
THURSDAY,  
FRIDAY,  
SATURDAY
```

```
};
```

This is our new type
Capitalize the first
letter

These are the values that Days can take

What we have done is defined *Days* now as a datatype that can only take the *values* we have *specified*.

© Michele Rousseau

Enums & Typedefs

6

```
#include <iostream>
int main()
{
    enum Days
    {
        SUNDAY,
        MONDAY,
        TUESDAY,
        WEDNESDAY,
        THURSDAY,
        FRIDAY,
        SATURDAY
    };

    // this will declare a
    // variable today
    // of type Days
    Days today;

    // now we can assign any of the
    // values we specified to
    // our variable today
    today = MONDAY;

    if (today == SUNDAY || today == SATURDAY)
    {
        cout << "\nGotta love the weekends!\n";
    }
    else
    {
        cout << "\nBack to work.\n";
    }
    return 0;
}
```

© Michele Rousseau Enums & Typedefs 7

How does it work?

- Enumerated type *Days* is defined with 7 values
- Each evaluates to an integer (0-6)
 - We could instead have declared each day as a constant


```
const int SUNDAY = 0;
const int MONDAY = 1;
...
```

© Michele Rousseau Enums & Typedefs 8

Enum Values

- Enumeration values must be legal identifiers
 - These are illegal
 - enum Grades {'A', 'B', 'C', 'D', 'F'};
 - enum Places {1st, 2nd, 3rd, 4th, 5th};
 - These are legal
 - enum Grades {A,B,C,D,F};
 - enum Places {FIRST, SECOND, THIRD, FOURTH, FIFTH}
- CAN'T assign the same value to 2 enum types
 - enum MathStudent {JOHN, BILL, LISA};
 - enum CompStudent {SUSAN, LISA, JOE};

© Michele Rousseau Enums & Typedefs 9

Because they evaluate to numbers

- You **CAN** compare the values

- today < eventDay

... and you **CAN** assign them to each other

- today = eventDay

- But you **CAN'T** do arithmetic and assign it back into your enum type

- today = eventDay - 3

- today++

...although you **CAN** type cast them

- today = Days(today + 1);

... or assign the result into an in

- intVar = today - eventday;

© Michele Rousseau

Enums & Typedefs

10

Example on Enums (1)

```
Days today;
```

```
Days eventDay;
```

```
today = MONDAY;
```

```
eventDay = FRIDAY;
```

```
if (today < eventDay )
```

```
{
```

```
    cout << "You're event is in " << eventDay - today << " days";
```

```
}
```

```
else if (today == eventDay)
```

```
{
```

```
    cout << "Today is the day!";
```

```
}
```

```
else
```

```
{
```

```
    cout << "You missed it!";
```

```
}
```

© Michele Rousseau

Enums & Typedefs

11

Example on Enums (2)

```
Days today;
```

```
Days eventDay;
```

```
int daysToEvent;
```

```
today = MONDAY;
```

```
eventDay = FRIDAY;
```

```
if (today < eventDay )
```

```
{
```

```
    daysToEvent = eventDay - today;
```

```
    cout << "You're event is in " << daysToEvent << " days";
```

```
}
```

```
else if (today == eventDay)
```

```
{
```

```
    cout << "Today is the day!";
```

```
}
```

```
else
```

```
{
```

```
    cout << "You missed it!";
```

```
}
```

© Michele Rousseau

Enums & Typedefs

12

Example on Enums (3)

```
Days today;
Days eventDay;
Days daysToEvent;
today = MONDAY;
eventDay = FRIDAY;
if (today < eventDay )
{
    daysToEvent = Days(eventDay - today);
    cout << "You're event is in " << daysToEvent << " days";
}
else if (today == eventDay)
{
    cout << "Today is the day!";
}
else
{
    cout << "You missed it!";
}
```

© Michele Rousseau

Enums & Typedefs

13

Input / Output of Enum Types

- Enum types **CAN'T** be input or output directly

```
string inputDay;
```

```
Days today;
cout << "What day is it?";
getline(cin, inputDay);
```

```
switch (toupper(inputDay[0])
```

```
{
    case 'S': if (toupper(inputDay[1])=='A')
        today = SATURDAY;
        else
            today = SUNDAY;
            break;
    case 'M': today = MONDAY;
            break;
    case 'W': today = WEDNESDAY;
```

Now you write
the code to output
the day for the
variable today

© Michele Rousseau

Enums & Typedefs

14

Output an Enum Type

```
Days today;
string dayStr;
switch (today)
{
    case SATURDAY : dayStr = "Saturday";
                    break;
    case SUNDAY : dayStr = "Sunday";
                 break;
    case MONDAY : dayStr = "Monday";
                 break;
    case TUESDAY : dayStr = "Tuesday";
                 break;
    case WEDNESDAY: dayStr = "Wednesday";
                 break;
    case THURSDAY : dayStr = "Thursday";
                 break;
    case FRIDAY : dayStr = "Friday";
                 break;
}
cout << dayStr;
```

© Michele Rousseau

Enums & Typedefs

15

typedef

CS1A

© Michele Rousseau

Enums & Typedefs

16

typedef

- typedef creates an additional name for an already existing data type

Syntax

```
typedef existingTypeName NewTypeName;
```

Examples:

```
typedef int    Integer;  
typedef float  Real;  
typedef double BigReal;
```

© Michele Rousseau

Enums & Typedefs

17

Example: typedef

- before the bool type became a part of ISO-ANSI C++ you could simulate a Boolean type using typedef

```
typedef int Boolean;  
const Boolean TRUE  = 1;  
const Boolean FALSE = 0;  
...  
Boolean dataOK;  
...  
dataOK = TRUE;
```

© Michele Rousseau

Enums & Typedefs

18

Example #2: typedef

```
typedef float FloatArrayType[100];
```

- anything of type FloatArrayType is defined as a 100 element array of float values

```
FloatArrayType myArray;
```

- MyArray is a variable representing a 100 element array of float values

- If you make your typedefs global you can use them as parameters

```
void LoadArray(FloatArrayType anArray)
```

© Michele Rousseau

Enums & Typedefs

19

Don't forget where they go in Header Files

```
#ifndef MYHEADER_H_
#define MYHEADER_H_

// preprocessor directives go here
#include <iostream>
#include <iomanip>
#include <string>
using namespace std;

// typedefs and enums go here
enum Color
{
    RED,
    BLUE,
    GREEN
};
typedef float SalesArrayType[7];

// Prototypes go here
void LoadSales(SalesArrayType sales);

#endif /* MYHEADER_H_ */
```

© Michele Rousseau

Enums & Typedefs

20
