



# Overview

Package aes implements AES encryption (formerly Rijndael), as defined in U.S. Federal Information Processing Standards Publication 197.

The AES operations in this package are not implemented using constant-time algorithms. An exception is when running on systems with enabled hardware support for AES that makes these operations constant-time. Examples include amd64 systems using AES-NI extensions and s390x systems using Message-Security-Assist extensions. On such systems, when the result of NewCipher is passed to cipher.NewGCM, the GHASH operation used by GCM is also constant-time.

#### Index

Constants
func NewCipher(key []byte) (cipher.Block, error)
type KeySizeError
func (k KeySizeError) Error() string

#### **Constants**

const BlockSize = 16

The AES block size in bytes.

#### **Variables**

This section is empty.

### **Functions**

### func NewCipher

```
func NewCipher(key []byte) (cipher.Block, error)
```

NewCipher creates and returns a new cipher.Block. The key argument should be the AES key, either 16, 24, or 32 bytes to select AES-128, AES-192, or AES-256.

## **Types**

## type KeySizeError

type KeySizeError int

## func (KeySizeError) Error

func (k KeySizeError) Error() string

# **Source Files**

View all <

☑

aes\_gcm.go block.go cipher.go cipher\_asm.go

const.go modes.go

Why Go	Get Started	Packages	About
Use Cases	Playground	Standard Library	Download
Case Studies	Tour	About Go Packages	Blog
	Stack Overflow		Issue Tracker
	Help		Release Notes
			Brand Guidelines
			Code of Conduct

#### Connect

Twitter

GitHub
Slack
r/golang
Meetup
Golang Weekly

Copyright

Terms of Service

Privacy Policy

Report an Issue





Google

