



Package rand implements a cryptographically secure random number generator.

Index

Overview

Variables

func Int(rand io.Reader, max *big.Int) (n *big.Int, err error)

func Prime(rand io.Reader, bits int) (*big.Int, error)

func Read(b []byte) (n int, err error)

Examples

Read

Constants

This section is empty.

Variables

View Source
var Reader io.Reader

Reader is a global, shared instance of a cryptographically secure random number generator.

On Linux, FreeBSD, Dragonfly and Solaris, Reader uses getrandom(2) if available, /dev/urandom otherwise. On OpenBSD and macOS, Reader uses getentropy(2). On other Unix-like systems, Reader reads from /dev/urandom. On Windows systems, Reader uses the RtlGenRandom API. On Wasm, Reader uses the Web Crypto API.

Functions

func Int

```
func Int(rand io.Reader, max *big.Int) (n *big.Int, err error)
```

Int returns a uniform random value in [0, max). It panics if max <= 0.

func Prime

```
func Prime(rand io.Reader, bits int) (*big.Int, error)
```

Prime returns a number of the given bit length that is prime with high probability. Prime will return error for any error returned by rand.Read or if bits < 2.

func Read

```
func Read(b []byte) (n int, err error)
```

Read is a helper function that calls Reader.Read using io.ReadFull. On return, n == len(b) if and only if err == nil.

Example

Types

This section is empty.

Source Files

View all ☑

rand.go rand_unix.go rand_getrandom.go util.go

Why Go Get Started Packages About

Use Cases Playground Standard Library Download

Case Studies	Tour	About Go Packages	Blog
	Stack Overflow		Issue Tracker
	Help		Release Notes
			Brand Guidelines
			Code of Conduct
Connect			
Twitter			
GitHub			
Slack			
r/golang			
Meetup			
Golang Weekly			
	Сору	right	
	Terms of	Service	
	Privacy	Policy	
	Report an Issue		Google
	•		Coogie