



# Ocumentation

## **Overview**

Package adler32 implements the Adler-32 checksum.

It is defined in RFC 1950:

Adler-32 is composed of two sums accumulated per byte: s1 is the sum of all bytes, s2 is the sum of all s1 values. Both sums are done modulo 65521. s1 is initialized to 1, s2 to zero. The Adler-32 checksum is stored as s2\*65536 + s1 in most-significant-byte first (network) order.

### Index

Constants

func Checksum(data []byte) uint32

func New() hash.Hash32

### **Constants**

Const Size = 4

The size of an Adler-32 checksum in bytes.

### **Variables**

This section is empty.

# **Functions**

## func Checksum

func Checksum(data []byte) uint32

Checksum returns the Adler-32 checksum of data.

## func New

func New() hash.Hash32

New returns a new hash. Hash32 computing the Adler-32 checksum. Its Sum method will lay the value out in big-endian byte order. The returned Hash32 also implements encoding. Binary Marshaler and encoding. Binary Unmarshaler to marshal and unmarshal the internal state of the hash.

# **Types**

This section is empty.

# Source Files

View all ☑

adler32.go

Why Go	Get Started	Packages	About
Use Cases	Playground	Standard Library	Download
Case Studies	Tour	About Go Packages	Blog
	Stack Overflow		Issue Tracker
	Help		Release Notes
			Brand Guidelines
			Code of Conduct

### Connect

Twitter

GitHub

Slack

r/golang

Meetup

Golang Weekly

Copyright

Terms of Service

Privacy Policy

Report an Issue







