

[Discover Packages](#) > [Standard library](#) > [math](#) > [rand](#) 

rand


package

standard library

Version: [go1.20.1](#) **Latest** | Published: Feb 14, 2023 | License: [BSD-3-Clause](#) | Imports: 4 |

Imported by: 162,091

Details

 Valid [go.mod](#) file  Redistributable license  Tagged version  Stable version [Learn more](#)

Repository

cs.opensource.google/go/go

Links

 [Report a Vulnerability](#) Documentation 

<> Documentation

Overview

Package rand implements pseudo-random number generators unsuitable for security-sensitive work.

Random numbers are generated by a [Source](#), usually wrapped in a [Rand](#). Both types should be used by a single goroutine at a time: sharing among multiple goroutines requires some kind of synchronization.

Top-level functions, such as [Float64](#) and [Int](#), are safe for concurrent use by multiple goroutines.

This package's outputs might be easily predictable regardless of how it's seeded. For random numbers suitable for security-sensitive work, see the [crypto/rand](#) package.

[► Example](#)[► Example \(Rand\)](#)

Index

[func ExpFloat64\(\) float64](#)[func Float32\(\) float32](#)[func Float64\(\) float64](#)[func Int\(\) int](#)[func Int31\(\) int32](#)[func Int31n\(n int32\) int32](#)

```
func Int63() int64
func Int63n(n int64) int64
func Intn(n int) int
func NormFloat64() float64
func Perm(n int) []int
func Read(p []byte) (n int, err error) DEPRECATED
func Seed(seed int64) DEPRECATED
func Shuffle(n int, swap func(i, j int))
func Uint32() uint32
func Uint64() uint64
type Rand
    func New(src Source) *Rand
    func (r *Rand) ExpFloat64() float64
    func (r *Rand) Float32() float32
    func (r *Rand) Float64() float64
    func (r *Rand) Int() int
    func (r *Rand) Int31() int32
    func (r *Rand) Int31n(n int32) int32
    func (r *Rand) Int63() int64
    func (r *Rand) Int63n(n int64) int64
    func (r *Rand) Intn(n int) int
    func (r *Rand) NormFloat64() float64
    func (r *Rand) Perm(n int) []int
    func (r *Rand) Read(p []byte) (n int, err error)
    func (r *Rand) Seed(seed int64)
    func (r *Rand) Shuffle(n int, swap func(i, j int))
    func (r *Rand) Uint32() uint32
    func (r *Rand) Uint64() uint64
type Source
    func NewSource(seed int64) Source
type Source64
type Zipf
    func NewZipf(r *Rand, s float64, v float64, imax uint64) *Zipf
    func (z *Zipf) Uint64() uint64
```

Examples

Package

Package (Rand)

Intn

Perm

Shuffle

Shuffle (SlicesInUnison)

Constants

This section is empty.

Variables

This section is empty.

Functions

func ExpFloat64

```
func ExpFloat64() float64
```

ExpFloat64 returns an exponentially distributed float64 in the range (0, +math.MaxFloat64] with an exponential distribution whose rate parameter (lambda) is 1 and whose mean is 1/lambda (1) from the default Source. To produce a distribution with a different rate parameter, callers can adjust the output using:

```
sample = ExpFloat64() / desiredRateParameter
```

func Float32

```
func Float32() float32
```

Float32 returns, as a float32, a pseudo-random number in the half-open interval [0.0,1.0) from the default Source.

func Float64

```
func Float64() float64
```

Float64 returns, as a float64, a pseudo-random number in the half-open interval [0.0,1.0) from the default Source.

func Int

```
func Int() int
```

Int returns a non-negative pseudo-random int from the default Source.

func Int31

```
func Int31() int32
```

Int31 returns a non-negative pseudo-random 31-bit integer as an int32 from the default Source.

func Int31n

```
func Int31n(n int32) int32
```

Int31n returns, as an int32, a non-negative pseudo-random number in the half-open interval [0,n) from the default Source. It panics if n <= 0.

func Int63

```
func Int63() int64
```

Int63 returns a non-negative pseudo-random 63-bit integer as an int64 from the default Source.

func Int63n

```
func Int63n(n int64) int64
```

Int63n returns, as an int64, a non-negative pseudo-random number in the half-open interval [0,n) from the default Source. It panics if n <= 0.

func Intn

```
func Intn(n int) int
```

Intn returns, as an int, a non-negative pseudo-random number in the half-open interval [0,n) from the default Source. It panics if n <= 0.

► [Example](#)

func NormFloat64

```
func NormFloat64() float64
```

NormFloat64 returns a normally distributed float64 in the range [-math.MaxFloat64, +math.MaxFloat64] with standard normal distribution (mean = 0, stddev = 1) from the default Source. To produce a different normal distribution, callers can adjust the output using:

```
sample = NormFloat64() * desiredStdDev + desiredMean
```

func Perm

```
func Perm(n int) []int
```

Perm returns, as a slice of n ints, a pseudo-random permutation of the integers in the half-open interval [0,n) from the default Source.

► [Example](#)

func Seed DEPRECATED [Show](#)

func Shuffle

added in go1.10

```
func Shuffle(n int, swap func(i, j int))
```

Shuffle pseudo-randomizes the order of elements using the default Source. n is the number of elements. Shuffle panics if $n < 0$. swap swaps the elements with indexes i and j.

► [Example](#)

► [Example \(SlicesInUnison\)](#)

func Uint32

```
func Uint32() uint32
```

Uint32 returns a pseudo-random 32-bit value as a uint32 from the default Source.

func Uint64

added in go1.8

```
func Uint64() uint64
```

Uint64 returns a pseudo-random 64-bit value as a uint64 from the default Source.

Types

type Rand

```
type Rand struct {  
    // contains filtered or unexported fields  
}
```

A Rand is a source of random numbers.

func New

```
func New(src Source) *Rand
```

New returns a new Rand that uses random values from src to generate other random values.

func (*Rand) ExpFloat64

```
func (r *Rand) ExpFloat64() float64
```

ExpFloat64 returns an exponentially distributed float64 in the range (0, +math.MaxFloat64] with an exponential distribution whose rate parameter (lambda) is 1 and whose mean is 1/lambda (1). To produce a distribution with a different rate parameter, callers can adjust the output using:

```
sample = ExpFloat64() / desiredRateParameter
```

func (*Rand) Float32

```
func (r *Rand) Float32() float32
```

Float32 returns, as a float32, a pseudo-random number in the half-open interval [0.0,1.0).

func (*Rand) Float64

```
func (r *Rand) Float64() float64
```

Float64 returns, as a float64, a pseudo-random number in the half-open interval [0.0,1.0).

func (*Rand) Int

```
func (r *Rand) Int() int
```

Int returns a non-negative pseudo-random int.

func (*Rand) Int31

```
func (r *Rand) Int31() int32
```

Int31 returns a non-negative pseudo-random 31-bit integer as an int32.

func (*Rand) Int31n

```
func (r *Rand) Int31n(n int32) int32
```

Int31n returns, as an int32, a non-negative pseudo-random number in the half-open interval [0,n). It panics if n <= 0.

func (*Rand) Int63

```
func (r *Rand) Int63() int64
```

Int63 returns a non-negative pseudo-random 63-bit integer as an int64.

func (*Rand) Int63n

```
func (r *Rand) Int63n(n int64) int64
```

Int63n returns, as an int64, a non-negative pseudo-random number in the half-open interval [0,n). It panics if n <= 0.

func (*Rand) Intn

```
func (r *Rand) Intn(n int) int
```

Intn returns, as an int, a non-negative pseudo-random number in the half-open interval [0,n). It panics if n <= 0.

func (*Rand) NormFloat64

```
func (r *Rand) NormFloat64() float64
```

NormFloat64 returns a normally distributed float64 in the range -math.MaxFloat64 through +math.MaxFloat64 inclusive, with standard normal distribution (mean = 0, stddev = 1). To produce a different normal distribution, callers can adjust the output using:

```
sample = NormFloat64() * desiredStdDev + desiredMean
```

func (*Rand) Perm

```
func (r *Rand) Perm(n int) []int
```

Perm returns, as a slice of n ints, a pseudo-random permutation of the integers in the half-open interval [0,n).

func (*Rand) Read

added in go1.6

```
func (r *Rand) Read(p []byte) (n int, err error)
```

Read generates len(p) random bytes and writes them into p. It always returns len(p) and a nil error. Read should not be called concurrently with any other Rand method.

func (*Rand) Seed

```
func (r *Rand) Seed(seed int64)
```

Seed uses the provided seed value to initialize the generator to a deterministic state. Seed should not be called concurrently with any other Rand method.

func (*Rand) Shuffle

added in go1.10

```
func (r *Rand) Shuffle(n int, swap func(i, j int))
```

Shuffle pseudo-randomizes the order of elements. n is the number of elements. Shuffle panics if n < 0. swap swaps the elements with indexes i and j.

func (*Rand) Uint32

```
func (r *Rand) Uint32() uint32
```

Uint32 returns a pseudo-random 32-bit value as a uint32.

func (*Rand) Uint64

added in go1.8

```
func (r *Rand) Uint64() uint64
```

Uint64 returns a pseudo-random 64-bit value as a uint64.

type Source

```
type Source interface {  
    Int63() int64  
    Seed(seed int64)  
}
```

A Source represents a source of uniformly-distributed pseudo-random int64 values in the range [0, 1<<63).

A Source is not safe for concurrent use by multiple goroutines.

func NewSource

```
func NewSource(seed int64) Source
```

NewSource returns a new pseudo-random Source seeded with the given value. Unlike the default Source used by top-level functions, this source is not safe for concurrent use by multiple goroutines. The returned Source implements Source64.

type Source64

added in go1.8

```
type Source64 interface {  
    Source  
    Uint64() uint64  
}
```

A Source64 is a Source that can also generate uniformly-distributed pseudo-random uint64 values in the range [0, 1<<64) directly. If a Rand r's underlying Source s implements Source64, then r.Uint64 returns the result of one call to s.Uint64 instead of making two calls to s.Int63.

type Zipf

```
type Zipf struct {  
    // contains filtered or unexported fields  
}
```


A Zipf generates Zipf distributed variates.

func NewZipf

```
func NewZipf(r *Rand, s float64, v float64, imax uint64) *Zipf
```

NewZipf returns a Zipf variate generator. The generator generates values $k \in [0, \text{imax}]$ such that $P(k)$ is proportional to $(v + k)^{-s}$. Requirements: $s > 1$ and $v \geq 1$.

func (*Zipf) Uint64

```
func (z *Zipf) Uint64() uint64
```

Uint64 returns a value drawn from the Zipf distribution described by the Zipf object.



Source Files

[View all](#)

[exp.go](#)
[normal.go](#)

[rand.go](#)
[rng.go](#)

[zipf.go](#)

Why Go

[Use Cases](#)

[Case Studies](#)

Get Started

[Playground](#)

[Tour](#)

[Stack Overflow](#)

[Help](#)

Packages

[Standard Library](#)

[About Go Packages](#)

About

[Download](#)

[Blog](#)

[Issue Tracker](#)

[Release Notes](#)

[Brand Guidelines](#)

[Code of Conduct](#)

Connect

[Twitter](#)

[GitHub](#)

[Slack](#)

[r/golang](#)

[Meetup](#)

[Golang Weekly](#)

Copyright

[Terms of Service](#)

[Privacy Policy](#)



Report an Issue



Google