

Dimensionality reduction techniques

Sanzhar Askaruly (San)

Ulsan National Institute of Science and Technology
Ph.D. Candidate in Biomedical Engineering

CodeSeoul MLA
December 10, 2022

Overview


What we'll cover today:

- 1 Motivation
- 2 Background mathematics
 - Sample mean
 - Standard deviation
 - Variance
- 3 Examples
 - Iris dataset
- 4 Experiments
- 5 Summary
 - Conclusion
 - Practicum

Motivation

- Relationships between data

Population vs sample



Population vs sample

Population mean

$$\mu = \frac{\sum_{i=1}^N x_i}{N} \quad (1)$$

N is number of items in the population


Sample mean

$$\bar{X} = \frac{\sum_{i=1}^n x_i}{n} \quad (2)$$

n is number of items in the sample

Standard deviation

Let's take a look on two samples:



Here, $\bar{A} = \bar{B} = 35$. Unfortunately, mean doesn't tell us a lot except for a middle point.

Standard deviation

For our two sets, $A = [10\ 20\ 40\ 70]$ and $B = [30\ 33\ 37\ 40]$, we would be more interested in the *spread* of the data. So, how do we calculate it?


Standard deviation

$$s = \sqrt{\frac{\sum_{i=1}^n (X_i - \bar{X})^2}{(n - 1)}} \quad (3)$$

In plain English, it is the "average distance from the mean of the data set to a point."

Standard deviation

Set 1: $A = [10\ 20\ 40\ 70]$, and $\bar{A} = 35$




Let's calculate standard deviation:

A	$(A - \bar{A})$	$(A - \bar{A})^2$
10	-25	625
20	-15	225
40	5	25
70	35	1,225
Total		2,100
Divided by (n-1)		700
Square root		26.4575

Standard deviation

Set 2: $B = [30\ 33\ 37\ 40]$, and $\bar{B} = 35$



Let's calculate standard deviation:

B	$(B - \bar{B})$	$(B - \bar{B})^2$
30	-5	25
33	-2	4
37	2	4
40	5	25
Total		58
Divided by (n-1)		19.333
Square root		4.397

Variance

Similar to standard deviation So, how do we calculate it?

Standard deviation

$$s = \sqrt{\frac{\sum_{i=1}^n (X_i - \bar{X})^2}{(n - 1)}} \quad (4)$$

In plain English, it is the "average distance from the mean of the data set to a point."

Iris flower dataset

iris setosa



petal

sepal

iris versicolor



petal

sepal



iris virginica




petal

sepal

Iris flower dataset



Iris flower dataset



Adagrad

Experiment

Experiment

Experiment

Experiment

Conclusion

Thank you for your attention!

- Workshop contents:

<https://github.com/CodeSeoul/machine-learning/tree/master/221210-pca>

- Follow-up QA?

<http://discord.com/users/tuttelikz>

References



Ning Qian. “On the momentum term in gradient descent learning algorithms”. In: *Neural networks* 12.1 (1999), pp. 145–151.



John Duchi, Elad Hazan, and Yoram Singer. “Adaptive subgradient methods for online learning and stochastic optimization.”. In: *Journal of machine learning research* 12.7 (2011).



Sebastian Ruder. “An overview of gradient descent optimization algorithms”. In: *arXiv preprint arXiv:1609.04747* (2016).



Mykola Novik. *torch-optimizer – collection of optimization algorithms for PyTorch*. Version 1.0.1. Jan. 2020.