

# Index

- $S^n$ , [24](#)
- $\mathbb{R}^n$ , [24](#)
- acceleration ellipsoid, [280](#)
- Ackermann steering, [524](#)
- actuator, [11](#), [303](#)
- Ad, [100](#)
- adjoint map, [100](#)
- admittance, [442](#)
- ambiguity, [495](#)
- angular velocity, [76](#)
  - body, [78](#)
  - spatial, [77](#)
- apparent inertia, [310](#)
- associativity, [70](#)
- atan2, [219](#)
- atlas, [27](#)
- axis-angle representation, [79](#)
- back-emf, [308](#)
- backlash, [2](#), [446](#)
- bang-bang trajectory, [340](#)
- Barrett Technology’s WAM, [150](#)
- bifurcation point, [257](#)
- body frame, [61](#)
- C-space, [12](#)
  - free, [353](#)
  - obstacle, [358](#)
  - representation, [25](#)
  - topologically equivalent, [24](#)
  - topology, [23](#)
- Cartesian product, [25](#)
- Cartesian robot, [431](#)
- Cayley–Rodrigues parameters, [68](#), [582](#)
- center of mass, [283](#)
- center of rotation (CoR), [473](#)
- centripetal force, [276](#)
- Chasles–Mozzi theorem, [105](#)
- chassis, [513](#)
- Christoffel symbols of the first kind, [278](#)
- closed-chain mechanism, [18](#), [245](#)
- collision–detection routine, [362](#)
  - sphere approximation, [363](#)
- commutation, [306](#)
- commutativity, [71](#)
- condition number, [199](#)
- configuration, [12](#)
- configuration space, *see* C-space
- connected component, [358](#)
- connectivity, [368](#)
- constrained dynamics, [301](#)
- constraint
  - active, [466](#)
  - artificial, [439](#)
  - holonomic, [30](#)
  - homogeneous, [469](#)
  - impenetrability, [465](#)
  - integrable, [31](#)
  - natural, [438](#)
  - nonholonomic, [32](#)
  - Pfaffian, [31](#), [439](#)

- rolling, 466
- contact
  - frictionless point, 472
  - kinematics, 463
  - point with friction, 472
  - roll–slide, 465, 466
  - rolling, 466
  - sliding, 466
  - soft, 472
- contact label, 466
- contact mode, 469
- contact normal, 464
- control
  - proportional (P), 414
  - adaptive, 448
  - admittance-controlled robot, 443
  - centralized, 432
  - compliance, 442
  - computed torque, 429
  - decentralized, 431
  - feedback, 414
  - feedforward, 414
  - feedforward–feedback, 418
  - force, 403, 434
  - gain, 414
  - hybrid motion–force, 403, 437
  - impedance, 403, 441
  - impedance-controlled robot, 443
  - inverse dynamics, 429
  - iterative learning, 448
  - linear, 414
  - motion, 403
  - motion, with torque or force inputs, 420
  - motion, with velocity inputs, 413
  - open-loop, 414
  - proportional-derivative (PD), 423
  - proportional-integral (PI), 415
  - proportional-integral-derivative (PID), 422
  - robust, 448
  - setpoint, 414
  - stiffness, 442
  - task-space motion control, 433
- control vector field, 522
- control-affine system, 531
- controllable robot, 529
- coordinate chart, 27
- coordinate free, 60
- Coriolis force, 276
- Coriolis matrix, 279
- D–H parameters, 140, 585
- D–H parameters and product of exponentials
  - comparison, 595
- da Vinci S Surgical System, 238
- damped natural frequency, 411
- damping
  - critical, 411
  - overdamped solution, 411
  - underdamped solution, 411
- damping ratio, 410
- DC motor, 305
  - brushed, 306
  - brushless, 306
- degrees of freedom (dof), 12
- Delta robot, 22, 245
- Denavit–Hartenberg parameters, *see* D–H parameters
- diff-drive robot, 523
- differential equation
  - homogeneous, 407
  - nonhomogeneous, 407
- direct-drive robot, 313
- distance-measurement algorithm, 362
- dof, 12
- Dubins car, 537
- dynamic grasp, 496
- dynamics of a rigid body, 283

- classical formulation, 283
  - twist–wrench formulation, 288
- dynamics of open chains, 271
  - Lagrangian formulation, 272
  - Newton–Euler recursive formulation, 291
  - Newton–Euler recursive formulation with gearing, 312
- Eclipse mechanism, 267
- elbow-down (righty) solution, 219
- elbow-up (lefty) solution, 219
- electrical constant, 308
- end-effector, 11
- equations of motion, 271
- error dynamics, 406
- error response, 406
- Euclidean space, 24
- Euler angles, 68, 575
- Euler’s equation for a rotating body, 284
- Euler–Lagrange equations, 273
- exceptional objects, 479
- exponential coordinates
  - for rigid-body motion, 104
  - for rotation, 79, 82
- five-bar linkage, 20
- fixed frame, 61
- force closure, 489
- force ellipsoid, 176, 199
- form closure, 469, 478
- forward dynamics, 271
- forward kinematics, 137
  - parallel mechanisms, 247
- four-bar linkage, 18
- free vector, 60
- friction, 484
  - Coulomb, 484
  - static, 314
  - viscous, 314
- friction angle, 484
- friction coefficient, 484
- friction cone, 484
- gantry robot, 431
- gearing, 310
  - harmonic drive, 314
- generalized coordinates, 272
- generalized forces, 272
- GJK algorithm, 362
- Grübler’s formula, 17
- graph, 364
  - directed, 364
  - undirected, 364
  - unweighted, 364
  - visibility, 368
  - weighted, 364
- graph edge, 364
- graph node, 364
- grasp metric, 482
- group closure, 70
- homogeneous coordinates, 90
- homogeneous transformation matrix, 89
- homotopic path, 398
- impedance, 441
- inadmissible state, 339
- inconsistent problem, 495
- inertia matching, 323
- inertia matrix
  - rotational, 284
  - spatial, 288
- inertial measurement unit (IMU), 560
- integrator anti-windup, 425
- inverse dynamics, 271
- inverse kinematics, 219
  - analytic, 221
  - numerical, 226
  - parallel mechanisms, 247
- inverse velocity kinematics, 232

- isotropic manipulability ellipsoid, 198
- Jacobi identity, 322
- Jacobian, 171
  - analytic, 188
  - body, 178, 185
  - constraint, 252
  - geometric, 188
  - space, 178, 180
- jamming, 500
- joint, 11
  - cylindrical, 16
  - helical, 16
  - prismatic, 16
  - revolute, 16
  - screw, 16
  - spherical, 16
  - universal, 16
- Kalman rank condition, 528
- kinetic energy, 272
- Krasovskii–LaSalle invariance principle, 458
- Lagrange multiplier, 234, 302, 440, 598
- Lagrangian function, 272
- law of cosines, 220
- lefty solution, 219
- Lie algebra, 77, 98
  - of vector fields, 534
- Lie bracket
  - of twists, 289
  - of vector fields, 532
- Lie product, 533
- linear program, 480
- linear system, 406
- linearly controllable, 528
- link, 11
- loop-closure equation, 28, 29
- Manhattan distance, 370
- manipulability ellipsoid, 173, 197
- mass ellipsoid, 280
- mass matrix, 271, 275, 277, 279
- matrix
  - rotation, 28
- matrix exponential, 80
  - for rigid-body motion, 105
  - for rotations, 84
- matrix Lie group, 70
- matrix logarithm
  - for rigid-body motion, 106
  - for rotation, 85
- mecanum wheel, 514
- meter-stick trick, 498
- mobile manipulation, 548
- moment, 108
  - pure, 109
- moment labeling, 488
- motion planning, 353
  - anytime, 356
  - approximate, 355
  - complete, 356
  - complete planners, 368
  - computational complexity, 356
  - exact, 355
  - grid methods, 369
  - multiple query, 356
  - nonlinear optimization, 392
  - offline, 355
  - online, 355
  - optimal, 355
  - path planning, 355
  - piano mover’s problem, 355
  - PRM algorithm, 384
  - probabilistically complete, 356
  - RDT algorithm, 380
  - resolution complete, 356
  - RRT algorithm, 379
    - bidirectional, 382
  - RRT\* algorithm, 383

- sampling methods, 378
- satisficing, 355
- single query, 356
- smoothing, 394
- virtual potential fields, 386
- wavefront planner, 370
- wheeled mobile robot, 374
- MoveIt, 353
- multi-resolution grid, 372
- natural frequency, 410
- navigation function, 389
- neighborhood, 529
- neighbors
  - 4-connected, 369
  - 8-connected, 369
- Newton–Raphson root finding, 227
- no-load speed, 308
- octree, 373
- odometry, 546
- omniwheel, 514
- Open Motion Planning Library, 398
- open-chain mechanism, 18
- overshoot, 406
- parallel mechanisms, 245
- parallel-axis theorem, 287
- parametrization
  - explicit, 27
- passivity property, 279
- path, 325
- peg insertion, 500
- phase plane, 339
- polyhedral convex cone, 469
- polyhedral convex set, 469
- polytope, 469
- potential energy, 272
- principal axes of inertia, 285
- principal moments of inertia, 285
- product of exponentials, 140
  - body form, 149
  - space form, 142
- product of exponentials and D–H parameters
  - comparison, 595
- pseudoinverse, 229
  - left, 229
  - right, 229
- PUMA-type arm, 221
- quadtree, 373
- quasistatic, 496
- quaternion, unit, 581
- reachability, 368
- reachable set, 529
- reciprocal wrench and twist, 466
- redundant actuation, 246
- redundant constraint, 14
- redundant robot, 190, 234
- Reeds–Shepp car, 538
- reflected inertia, 310
- repelling wrench and twist, 466
- representation
  - implicit, 28
- right-handed reference frame, 62
- righty solution, 219
- rigid body
  - planar, 15
  - spatial, 15
- rigid-body motion, 89
- roadmap, 368
- Robot Operating System (ROS), 152, 354
- Rodrigues’ formula, 84
- roll–pitch–yaw angles, 68, 580
- root locus, 416
- rotation, 68
- rotation matrix, 68
- rotor, 305
- rviz, 354

- SCARA, 34
- screw axis, 102
  - body-frame, 149
  - space-frame, 142
- screw pitch, 103
- $SE(3)$ , 89
- $se(3)$ , 98
- search
  - $A^*$ , 365
  - breadth-first, 367
  - Dijkstra's algorithm, 367
  - suboptimal  $A^*$ , 367
- serial mechanism, 18
- series elastic actuator, 446, 459
- settling time, 406
- shortest paths, car with reverse gear, 538
- shortest paths, forward-only car, 537
- singularity, 21, 27, 172
  - actuator, 256
  - actuator, degenerate, 259
  - actuator, nondegenerate, 259
  - C-space, 256, 258
  - end-effector, 256, 261
  - kinematic, 191
- skew-symmetric matrix, 77
- slider-crank mechanism, 18
- small-time locally accessible (STLA), 529
- small-time locally controllable (STLC), 529
- $so(3)$ , 77
- $SO(2)$ , 70
- $SO(3)$ , 70
- space frame, 61
- span
  - conical, 462
  - convex, 462
  - linear, 462
  - positive, 462
- spatial force, 109
- spatial momentum, 289
- spatial velocity
  - in body frame, 97
  - in space frame, 99
- special Euclidean group ( $SE(3)$ ), 89
- special orthogonal group ( $SO(3)$ ), 70
- speed-torque curve, 308
- stability of an assembly, 499
- stable dynamics, 408
- stall torque, 308
- standard second-order form, 410
- Stanford-type arm, 225
- state, 354
- stator, 305
- steady-state error, 406
- steady-state response, 406
- Steiner's theorem, 287
- Stephenson six-bar linkage, 20
- Stewart-Gough platform, 22, 245
- strain gauge, 405, 435, 446
- Stribeck effect, 314
- Swedish wheel, 514
- $T^n$ , 25
- tangent vector, 522
- tangent vector field, 522
- task space, 32
- task-space dynamics, 300
- Taylor expansion, 227, 531
- time constant, 409
- time scaling, 326
  - cubic, 329
  - quintic, 330
  - S-curve, 333
  - time-optimal, 336
  - trapezoidal, 330
- time-optimal trajectories, diff-drive, 540
- torque, 108
- torque constant, 306

- trajectory, 326
  - point-to-point, 326
  - through via points, 334
- trajectory tracking, nonholonomic mobile robot, 543
- transformation matrix, 89
- transient response, 406
- tree, 364
  - child node, 364
  - leaf node, 364
  - parent node, 364
  - root node, 364
- twist, 97
  - body, 98
  - spatial, 99
- unit quaternions, 68
- Universal Robot Description Format (URDF), 152, 303
- Universal Robots' UR5, 147
- unstable dynamics, 408
- variable-impedance actuator, 449
- variable-stiffness actuator, 449
- vector field, 522
- velocity limit curve, 339
- Watt six-bar linkage, 20
- wedging, 501
- wheeled mobile robot, 513
  - canonical, 526
  - car-like, 524
  - diff-drive, 523
  - nonholonomic, 514
  - omnidirectional, 514
  - unicycle, 521
- workspace, 33
- wrench, 108
  - body, 110
  - spatial, 110
- zero-inertia point, 338, 344