

[Read More](#)

Products

Resources

[Pricing](#)

[We're hiring!](#)

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

MANAGE CHOICES

AGREE & PROCEED

- [Tutorials](#)
- [Announcements](#)
- [Stable Diffusion](#)
- [YOLO](#)
- [NLP](#)
- [Get paid to write](#)
- [We're hiring!](#)
- 

[Series: Ensemble Methods](#)

## Introduction to Bagging and Ensemble Methods

Learn how bagging and ensemble methods decrease variance and prevent overfitting in this 2020 guide to bagging, including an implementation in Python.

4 years ago • 9 min read



By [Vihar Kurama](#)

The bias-variance trade-off is a challenge we all face while training machine learning algorithms. Bagging is a powerful ensemble method which helps to reduce variance, and by extension, prevent overfitting. Ensemble methods improve model precision by using a group (or "ensemble") of models which, when combined, outperform individual models when used separately.

In this article we'll take a look at the inner-workings of bagging, its applications, and implement the bagging algorithm using the scikit-learn library.

In particular, we'll cover:

- An Overview of Ensemble Learning
  - Why Use Ensemble Learning?
  - Advantages of Ensemble Learning
- What Is Bagging?
  - Bootstrapping
  - Basic Concepts
- Applications of Bagging
- The Bagging Algorithm
- Advantages and Disadvantages
- Decoding the Hyperparameters
- Implementing the Algorithm
- Summary and Conclusion

Let's get started.

Bring this project to life

[Run on gradient](#)

## An Overview of Ensemble Learning

As the name suggests, ensemble methods refer to a group of models working together to solve a common problem. Rather than depending on a single model for the best solution, ensemble learning utilizes the advantages of several different methods to counteract each model's individual weaknesses. The resulting collection should be less error-prone than any model alone.

### Why Use Ensemble Learning?

Combining several weak models can result in what we call a *strong learner*.

We can use ensemble methods to combine different models in two ways: either using a single base learning algorithm that remains the same across all models (a *homogeneous ensemble model*), or using multiple base learning algorithms that differ for each model (a *heterogeneous ensemble model*).

Generally speaking, ensemble learning is used with decision trees, since they're a reliable way of achieving regularization. Usually, as the number of levels increases in a decision tree, the model becomes vulnerable to high-variance and might overfit (resulting in high error on test data). We use ensemble techniques with general rules (vs. highly specific rules) in order to implement regularization and prevent overfitting.

### Advantages of Ensemble Learning

Let's understand the advantages of ensemble learning using a real-life scenario. Consider a case where you want to predict if an incoming email is genuine or spam. You want to predict the class (genuine/spam) by looking at several attributes **individually**: whether or not the sender is in your contact list, if the content of the message is linked to money extortion, if the language used is neat and understandable, etc. Also, on the other hand, you would like to predict the class of the email using all of these attributes **collectively**. As a no-brainer, the latter option works well because we consider all the attributes collectively whereas in the former one, we consider each

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

To avail of these benefits, Ensemble Learning is often the most preferred option in a majority of use cases. In the next section, let's understand a popular Ensemble Learning technique, **Bagging**.

## What Is Bagging?

Bagging, also known as **bootstrap aggregating**, is the aggregation of multiple versions of a predicted model. Each model is trained individually, and combined using an averaging process. The primary focus of bagging is to achieve less variance than any model has individually. To understand bagging, let's first understand the term **bootstrapping**.

### Bootstrapping

Bootstrapping is the process of generating bootstrapped samples from the given dataset. The samples are formulated by randomly drawing the data points with replacement.



Bootstrapping (Source: <https://towardsdatascience.com/ensemble-methods-bagging-boosting-and-stacking-c9214a10a205>)

The resampled data contains different characteristics that are as a whole in the original data. It draws the distribution present in the data points, and also tend to remain different from each other, i.e. the data distribution has to remain intact whilst maintaining the dissimilarity among the bootstrapped samples. This, in turn, helps in developing robust models.

Bootstrapping also helps to avoid the problem of overfitting. When different sets of training data are used in the model, the model becomes resilient to generating errors, and therefore, performs well with the test data, and thus reduces the variance by maintaining its strong foothold in the test data. Testing with different variations doesn't bias the model towards an incorrect solution.

Now, when we try to build fully independent models, it requires huge amounts of data. Thus, Bootstrapping is the option that we opt for by utilizing the approximate properties of the dataset under consideration.

### Basic Concepts Behind Bagging

It all started in the year 1994, when Leo Breiman proposed this algorithm, then known as "**Bagging Predictors**". In Bagging, the bootstrapped samples are first created. Then, either a regression or classification algorithm is applied to each sample. Finally, in the case of regression, an average is taken over all the outputs predicted by the individual learners. For classification either the most voted class is accepted (**hard-voting**), or the highest average of all the class probabilities is taken as the output (**soft-voting**). This is where **aggregation** comes into the picture.


Mathematically, Bagging is represented by the following formula,

$$\widehat{f}_{bag} = \widehat{f}_1(X) + \widehat{f}_2(X) + \dots + \widehat{f}_b(X)$$

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Bagging works especially well when the learners are unstable and tend to overfit, i.e. small changes in the training data lead to major changes in the predicted output. It effectively reduces the variance by aggregating the individual learners composed of different statistical properties, such as different standard deviations, means, etc. It works well for high variance models such as Decision Trees. When used with low variance models such as linear regression, it doesn't really affect the learning process. The number of base learners (trees) to be chosen depends on the characteristics of the dataset. Using too many trees doesn't lead to overfitting, but can consume a lot of computational power.

Bagging can be done in parallel to keep a check on excessive computational resources. This is a one good advantages that comes with it, and often is a booster to increase the usage of the algorithm in a variety of areas.



Bagging (Source: <https://towardsdatascience.com/ensemble-methods-bagging-boosting-and-stacking-c9214a10a205>)

## Applications of Bagging

Bagging technique is used in a variety of applications. One main advantage is that it reduces the variance in prediction by generating additional data whilst applying different combinations and repetitions (replacements in the bootstrapped samples) in the training data. Below are some applications where the bagging algorithm is widely used:

- Banking Sector
- Medical Data Predictions
- High-dimensional data
- Land cover mapping
- Fraud detection
- Network Intrusion Detection Systems
- Medical fields like neuroscience, prosthetics, etc.

## The Bagging Algorithm

Let's look at the step-by-step procedure that goes into implementing the Bagging algorithm.

- Bootstrapping comprises the first step in Bagging process flow wherein the data is divided into randomized samples.
- Then fit another algorithm (e.g. Decision Trees) to each of these samples. Training happens in parallel.
- Take an average of all the outputs, or in general, compute the aggregated output.

It's that simple! Now let's talk about the pros and cons of Bagging.

## Advantages and Disadvantages

Let's discuss the advantages first. Bagging is a completely data-specific algorithm. The bagging technique reduces model over-fitting. It also performs well on high-dimensional data. Moreover, the missing values in the dataset do not affect the performance of the algorithm.

That being said, one limitation that it has is giving its final prediction based on the mean predictions from the subset trees, rather than outputting the precise values for the classification or regression model.

## Decoding the Hyperparameters

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

**n\_estimators:** The number of base estimators in the ensemble. Default value is 10.

**random\_state:** The seed used by the random state generator. Default value is None.

**n\_jobs:** The number of jobs to run in parallel for both the `fit` and `predict` methods. Default value is None.

In the code below, we also use **K-Folds** cross-validation. It outputs the train/test indices to generate train and test data. The **n\_splits** parameter determines the number of folds (default value is 3).

To estimate the accuracy, instead of splitting the data into training and test sets, we use K-Folds along with the **cross\_val\_score**. This method evaluates the score by cross-validation. Here's a peek into the parameters defined in `cross_val_score`:

**estimator:** The model to fit the data.

**X:** The input data to fit.

**y:** The target values against which the accuracy is predicted.

**cv:** Determines the cross-validation splitting strategy. Default value is 3.

## Implementing the Bagging Algorithm

### Step 1: Import Modules

Of course, we begin by importing the necessary packages which are required to build our bagging model. We use the [Pandas](#) data analysis library to load our dataset. The dataset to be used is known as the [Pima Indians Diabetes Database](#), used for predicting the onset of diabetes based on various diagnostic measures.

Next, let's import the `BaggingClassifier` from the `sklearn.ensemble` package, and the `DecisionTreeClassifier` from the `sklearn.tree` package.

```
import pandas
from sklearn import model_selection
from sklearn.ensemble import BaggingClassifier
from sklearn.tree import DecisionTreeClassifier
```

[COPY](#)

### Step 2: Loading the Dataset

We'll download the dataset from the GitHub link provided below. Then we store the link in a variable called `url`. We name all the classes of the dataset in a list called `names`. We use the `read_csv` method from `Pandas` to load the dataset, and then set the class names using the parameter "names" to our variable, also called `names`. Next, we load the features and target variables using the slicing operation and assign them to variables **X** and **Y** respectively.

```
url="https://raw.githubusercontent.com/jbrownlee/Datasets/master/pima-indians-diabetes.data.csv"

names = ['preg', 'plas', 'pres', 'skin', 'test', 'mass', 'pedi', 'age', 'class']
dataframe = pandas.read_csv(url, names=names)
array = dataframe.values
X = array[:,0:8]
Y = array[:,8]
```

[COPY](#)

### Step 3: Loading the Classifier

In this step, we set the seed value for all the random states, so that the generated random values shall remain the same until the seed value is exhausted. We now declare the **KFold** model wherein we set the **n\_splits** parameter to 10, and the **random\_state** parameter to the seed value. Here, we shall build the bagging algorithm with the **Classification and Regression Trees algorithm**. To do so, we import the **DecisionTreeClassifier**, store it in the **cart** variable, and initiate the number of trees variable, **num\_trees** to 100.

```
seed = 7
kfold = model_selection.KFold(n_splits=10, random_state=seed)
cart = DecisionTreeClassifier()
num_trees = 100
```

[COPY](#)

### Step 4: Training and Results

In the last step, we train the model using the **BaggingClassifier** by declaring the parameters to the values defined in the previous step. We then check the performance of the model by using the parameters, **Bagging model**, **X**, **Y**, and the **kfold** model. The output printed will be the accuracy of the model. In this particular case, it's around 77%.

```
model = BaggingClassifier(base_estimator=cart, n_estimators=num_trees, random_state=seed)

results = model_selection.cross_val_score(model, X, Y, cv=kfold)
print(results.mean())
```

[COPY](#)

Output:

```
0.770745044429255
```

When using a Decision Tree classifier alone, the accuracy noted is around 66%. Thus, Bagging is a definite improvement over the Decision Tree algorithm.

Get the full code here

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

Here's a brief summary mentioning the notable points that we've learned about. We started off by understanding what ensemble learning is, followed by an introduction about bagging, moving on to its applications, working procedure, pros and cons, hyperparameters, and finally concluded by coding it in Python. Indeed, a good way to progress your Machine Learning skill!

## References

<https://towardsdatascience.com/ensemble-methods-bagging-boosting-and-stacking-c9214a10a205>

<https://bradleyboehmke.github.io/HOML/bagging.html#bagging-vip>

[https://en.wikipedia.org/wiki/Bootstrap\\_aggregating](https://en.wikipedia.org/wiki/Bootstrap_aggregating)

<https://scikit-learn.org/stable/modules/generated/sklearn.ensemble.BaggingClassifier.html>

[https://scikit-learn.org/stable/modules/generated/sklearn.model\\_selection.cross\\_val\\_score.html](https://scikit-learn.org/stable/modules/generated/sklearn.model_selection.cross_val_score.html)

Add speed and simplicity to your Machine Learning workflow today

Get started

Contact Sales

- Tags:
- [Series: Ensemble Methods](#)
- [Data Science](#)
- [Machine Learning](#)

## Spread the word

- [Share](#)
- [Tweet](#)
- [Share](#)
- 
- [Email](#)

[https://blog.paperspace.c](https://blog.paperspace.com/bagging-ensemble-methods/)

[public](#)

[Next article](#)

## [A 2020 Guide to Synthetic Media](#)

[public](#)

[Previous article](#)

## [Introducing The AI Wiki](#)

## Keep reading

public

### [Gradient Boosting In Classification: Not a Black Box Anymore!](#)

4 years ago • 18 min read

public

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.

## [A Guide To Random Forests: Consolidating Decision Trees](#)

4 years ago • 12 min read

### Subscribe to our newsletter

Stay updated with Paperspace Blog by signing up for our newsletter.

Your email address  [JOIN NOW](#)

🎉 Awesome! Now check your inbox and click the link to confirm your subscription.

Please enter a valid email address

Oops! There was an error sending the email, please try later

Paperspace

### Solutions

[Machine Learning](#) [GPU Infrastructure](#) [Cloud Desktops \(VDI\)](#) [3D Workstations](#) [Visual Computing](#) [Gaming](#)

### Product

[Docs](#) [Changelog](#) [Status Page](#) [Referral Program](#) [Download App](#) [Customers](#) [Media Kit](#)

### Resources

[Support](#) [Talk to an expert](#) [Forum](#) [Business](#) [Security](#) [Cloud GPU Comparison](#) [NVIDIA Cloud Partner](#) [Graphcore IPUs](#) [Media Kit](#)

### Company

[About](#) [Blog](#) [Careers](#) [Shop](#) [Get Paid to Write ATG \(Research\)](#)

Part of the

 [Combinator](#)

family

© Copyright by [Paperspace](#) • All rights reserved

[Terms of Service](#)

•

[Privacy Policy](#)

This site uses cookies and related technologies, as described in our [privacy policy](#), for purposes that may include site operation, analytics, enhanced user experience, or advertising. You may choose to consent to our use of these technologies, or manage your own preferences.