INTELLIGENT WASTE MANAGEMENT AND BIN FILL-LEVEL PREDICTION

REPORT

Submitted by

S Ramya - 2362202

Ronna Elizabeth Rajesh – 2362199

Aditya Kumar - 2362201

BACHELOR OF TECHNOLOGY

IN

COMPUTER SCIENCE AND ENGINEERING

(Artificial Intelligence and Machine Learning)

Department of AI,ML AND DATA SCIENCE

School of Engineering and Technology

CHRIST (Deemed to be University)

Kumbalagodu, 560 074

Mar 2026

1. Introduction

In modern urban environments, solid waste management is a critical challenge. Traditional waste collection systems rely on manual reporting or fixed-schedule pick-ups, which are highly inefficient. Often, collection trucks visit empty bins, wasting fuel and labor, while overflowing bins in high-traffic areas are neglected, leading to environmental pollution and health hazards.
With the rapid development of the Internet of Things (IoT), smart systems can be designed to monitor bin levels continuously. An IoT-based Intelligent Waste Management System enables real-time detection of fill levels using ultrasonic sensors and automatically communicates this data to a centralized cloud platform. This project focuses on designing and implementing a cost-effective IoT system that provides timely alerts, predicts when bins will reach capacity, and optimizes collection routes, demonstrating the practical application of IoT in urban infrastructure.

2. Purpose of the Research Paper

The purpose of this case study is to analyze and implement an IoT-based waste monitoring system. The study aims to understand the working principles of distance-sensing technology and wireless data transmission to evaluate their effectiveness in real-world waste management scenarios.
This study focuses on redesigning conventional waste bins into "Smart Bins" that are capable of self-reporting their statu.s. By implementing the system using a microcontroller (ESP32) and cloud analytics, the study demonstrates the feasibility of moving from static collection models to dynamic, data-driven logistics.

3. Objective of the Research Paper

The primary objective is to develop an automated monitoring system that detects bin fill-levels and notifies waste management authorities before an overflow occurs.

- To design an IoT-based system for real-time fill-level detection.
- To minimize operational costs (fuel and labor) by optimizing collection routes.
- To continuously monitor waste levels using ultrasonic sensors.
- To apply predictive analytics to estimate the "Time to Capacity" (TTC) for each bin.
- To automatically generate alerts when bins exceed a 90% threshold.
- To demonstrate the practical application of IoT in environmental sustainability.

4. Methodology Adopted in the Paper

The methodology is based on real-time distance measurement using ultrasonic waves. The system uses an **HC-SR04 Ultrasonic Sensor** placed on the bin lid. The sensor emits a sound pulse and measures the time it takes for the echo to return from the waste surface.

The **ESP32 Microcontroller** processes this signal, converts it into a fill percentage, and compares it with predefined thresholds. To ensure data accuracy, the system takes multiple readings and filters out noise (e.g., occasional small objects tossed into the bin). Once the level is calculated, data is transmitted via the integrated WiFi module to an IoT Cloud Platform (such as ThingSpeak or Firebase). The cloud module then applies a linear regression-based prediction to estimate future fill rates based on historical data.

5. Outcomes of the Research Paper

The system successfully demonstrates the ability to monitor multiple waste nodes from a centralized dashboard.

- **Early Detection:** Authorities are notified of near-full bins, preventing overflow.
- **Cost Efficiency:** Comparative analysis shows a potential 40-50% reduction in truck mileage by skipping empty bins.
- **Data Visualization:** Real-time graphs on the cloud platform allow for long-term waste generation analysis.
- **Automation:** The use of buzzers and LED indicators at the bin site provides immediate local status feedback.

6. Result













7. Implementation of the System.

The system is implemented using a prototype bin and tested in a controlled environment. The ESP32 is programmed using the Arduino IDE.

- Station Setup: A 50cm tall waste bin is used as the test subject.
- Simulation: Using a cloud dashboard, we simulate a week of waste generation to test the "Time to Capacity" prediction algorithm.
- Monitoring: The "Head Station" (a web browser dashboard) displays the status of multiple simulated bins, highlighting those that require immediate collection.

8. Scope of the Study

1. Real-time Monitoring: Continuous tracking of bin levels via IoT.
2. Predictive Alerts: Forecasting when a bin will overflow to allow for proactive scheduling.
3. Logistics Optimization: Providing data for route planning to reduce fuel consumption.
4. Public Health: Improving urban hygiene by eliminating overflowing waste.

9. Limitations of the Study

1. **Interference:** Ultrasonic sensors may provide false readings if waste is piled unevenly.
2. **Connectivity:** Reliance on WiFi networks which may be unstable in certain outdoor locations.
3. **Environmental Factors:** Sensors may require weatherproof casing to withstand rain and extreme heat.

10. References

1. S. S. Navghane et al., "IoT Based Smart Garbage Monitoring System," *International Journal of Advanced Research in Computer and Communication Engineering*.
2. M. Al-Maaded et al., "Solid Waste Management in Smart Cities," *Research Gate*.
3. T. Malche, "Internet of Things for Building Smart Home Systems," *I-SMAC Conference*.