

Module 35 - Spread Operator & Rest Parameter

1. What is Spread Operator?

The Spread Operator (...) is a JavaScript operator used to expand or copy the elements of an array or the properties of an object into another array or object.

Example Code:

I. Spread Operator (Array)

```
let hobbies = ["Cricket", "FootBall", "BasketBall"];
let hobbies1 = ["Reader", "Writer"];
// Combines both arrays into a new array.
let newArray = [...hobbies, ...hobbies1];
// Adds new elements to the copied array.
let newArray1 = [...newArray, "VideoCreator", "Content Writer"];
console.log(newArray);
console.log(newArray1);
```

II. Spread Operator (Object)

```
let empDetail = {
  empId: "IQ123",
  empName: "Kesavan",
  empRole: "React Developer"
};
// Copies all properties and updates/adds new properties.
let team2 = {
  ...empDetail,
  empId: "IQ456",
  empSalary: 100000,
  team2Desig: "Full Stack Developer"
};
console.log(empDetail);
console.log(team2);
```

2. What is Rest Parameter?

The Rest Parameter (...) is a JavaScript feature used in function parameters to collect multiple arguments into a single array. It must always be the last parameter.

Example Code:

```
// '...arr' collects all remaining arguments into an array.  
function restParams(a, b, ...arr) {  
    console.log(a, b, arr);  
}  
restParams(1, 2, 3, 4, 5);
```