

Module 5 - Keywords and Identifiers

1. What are Keywords?

- Keywords are reserved words with a predefined meaning that cannot be used as identifiers.
- Example:** `var, let, const, if, else, for, while, function, return, class`

2. What are Identifiers?

- Identifiers are names given to variables, functions, objects, and other program elements to identify them uniquely.
- Example:** `uName, lName, LName, $lName, _lName`

3. What are the rules for naming identifiers?

- Identifiers must have unique names.
- Names must begin with a letter.
- Names cannot begin with a number.
- Names can also begin with \$ or _.
- Names are case-sensitive.
- Reserved words cannot be used as identifiers.

Example Code:

```
// Keywords and Identifiers

let uName = "ECMAScript";

console.log(uName);

let lName = "JavaScript";

let LName = "Dynamically Typed";

console.log(lName, LName);

let $lName = "Single Page Application";

let _lName = "SPA";

// let 0lName = "SPA"; // Variable names cannot start with a number

console.log($lName, _lName);
```

4. What are the Identifier Naming Conventions?

Identifier Naming Conventions are rules and guidelines used to name variables, functions, and other identifiers clearly and consistently.

I. Camel Case

- Starts with lowercase and capitalizes each following word.
- Commonly used for variable names and function identifiers.

II. Pascal Case

- Starts with uppercase and capitalizes each following word.
- Commonly used for objects and constructors.

III. Underscore Case or Snake Case

- Separates words using underscores (_).
- Commonly used for variable names, function identifiers, and database fields.

Example Code:

```
// Identifier Naming Conventions
let newemployeeid = 10; // Not Recommended

// 1. Camel Case
let newEmployeeId = 10;

// 2. Pascal Case
let NewEmployeeId = 10;

// 3. Underscore Case or Snake Case
let New_Employee_Id = 10;
let new_Employee_Id = 10;
```