

Deploying PhoneBook App to Internet

phonebook (frontend) - react in part2/phonebook running on PORT : 5173

phonebook (backend) - index.js in part3/phonebook-backend running on PORT : 3001

- By above references this is not the case of **SOP(same-origin-policy)** , this is the pure **CORS(cross-origin-resource-sharing)**.
- so we have solution for this.
 - Connect React Frontend to Express Backend :-

- Backend :-

1. In your part3 phonebook-backend project : **npm install cors**
2. In index.js, add cors near the top:

```
const express = require('express');
const cors = require('cors');
const morgan = require('morgan');

const app = express();

<!-- Middleware -->
app.use(cors()) ==> Instantly attaches the Access-Control-Allow-Origin
app.use(express.json());
app.use(
  morgan(':method :url :status :res[content-length] - :response-time ms :body')
);
```

3. Start your backend on port 3001: **npm run dev**

- Frontend :-

1. In your part2/phonebook React project:
 - Open src/services/persons.js.
 - Update your baseUrl to point to your live Express backend

```
const baseUrl = 'http://localhost:3001/api/persons'; <== this
```

```
new backend server url
```

2. Start React on port 5173 : **npm run dev**

◦ Full-Stack Production Build :-

- Now we are going to compile your React app into a static dist folder and serve it directly from Express on Port 3001!

- frontend :-

1. In your React Frontend (part2/phonebook):

- Open src/services/persons.js and change baseUrl to a Relative URL:

```
const baseUrl = '/api/persons'; // 👉 Relative URL!
```

2. Generate the Production Build:

- *In your React terminal (inside part2/phonebook) run: **npm run build*** , Vite will compile your entire **React app into** a brand-new **folder called dist!**
-

- Backend :-

1. Copy dist into your Backend:

- Copy that entire dist folder from part2/phonebook and paste it directly into your phonebook-backend folder (*right next to index.js and package.json*).

2. Tell Express to Serve the dist folder:

- Open phonebook-backend/index.js and add this 1 line right under your middleware:

```
app.use(express.static('dist'));
```

◦ The 4-Step Deployment Checklist:

- Step 1: Pre-Flight Safety Checks (in phonebook-backend/index.js)

1. Static Middleware is active:

```
app.use(express.static('dist'));
```

2. Dynamic Cloud Port is set:

```
const PORT = process.env.PORT || 3001; // 👉 Must use  
process.env.PORT!
```

-
- Step 2: Make sure dist is in your Backend Folder
 - Verify that the compiled dist folder from React is sitting inside your phonebook-backend folder (right next to index.js).
 - ⚠️ Make sure dist is NOT in your backend .gitignore so Git uploads it!
-

- Step 3: Push phonebook-backend to GitHub
 - In your phonebook-backend terminal:

```
git add .  
git commit -m "Deploy full-stack phonebook"  
git push
```

-
- Step 4: Deploy on Render.com
 1. Sign in to <https://render.com> with GitHub.
 2. Click "New +" -> "Web Service" -> select your repository.
 3. Set "Root Directory" to: [part3/phonebook-backend](#)
 4. Set Build Command: `npm install`
 5. Set Start Command: `npm start`
 6. Select Free Tier (\$0) and click "Deploy Web Service"!
-