

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

✓ 恭喜！您通过了！[下一项](#)

1 / 1 分

1。

Recall that with symmetric ciphers it is possible to encrypt a 32-bit message and obtain a 32-bit ciphertext (e.g. with the one time pad or with a nonce-based system). Can the same be done with a public-key system?



Yes, the RSA-OAEP system can produce 32-bit ciphertexts.



No, public-key systems with short ciphertexts can never be secure.

**正确**

An attacker can use the public key to build a

dictionary of all 2^{32} ciphertexts of length 32 bits along with

their decryption and use the dictionary to decrypt any captured ciphertext.



Yes, when encrypting a short plaintext the output

of the public-key encryption algorithm can be truncated to the length

of the plaintext.



It is not possible with the ElGamal system, but may be possible with other systems.



1 / 1 分

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

Let (Gen, E, D) be a semantically secure public-key encryption system. Can algorithm E be deterministic?



No, but chosen-ciphertext secure encryption can be deterministic.



No, semantically secure public-key encryption must be randomized.

**正确**

That's correct since otherwise an attacker can easily break semantic security.



Yes, some public-key encryption schemes are deterministic.



Yes, RSA encryption is deterministic.



0 / 1 分

3.

Let (Gen, E, D) be a chosen ciphertext secure public-key encryption system with message space $\{0, 1\}^{128}$. Which of the following is also chosen ciphertext secure?



(Gen, E', D') where

$$E'(\text{pk}, m) = [c \leftarrow E(\text{pk}, m), \text{ output } (c, c)]$$

$$\text{and } D'(\text{sk}, (c_1, c_2)) = \begin{cases} D(\text{sk}, c_1) & \text{if } c_1 = c_2 \\ \perp & \text{otherwise} \end{cases}.$$

**这应该被选择**

(Gen, E', D') where

$$E'(\text{pk}, m) = (E(\text{pk}, m), E(\text{pk}, m))$$

Week 6 - Problem Set

10/11 分 (90%)

测验, 11 个问题

$$D'(\text{sk}, (c_1, c_2)) = \begin{cases} D(\text{sk}, c_1) & \text{if } D(\text{sk}, c_1) = D(\text{sk}, c_2) \\ \perp & \text{otherwise} \end{cases}.$$

这个选项的答案不正确

This construction is not chosen-ciphertext secure.

An attacker can output two messages $m_0 = 0^{128}$ and $m_1 = 1^{128}$ and be given back a challenge ciphertext (c_1, c_2) . He would then, on his own, create a new random encryption of m_0 , call it c_3 , and ask for the decryption of (c_1, c_3) , which is a valid decryption query since it is different from the challenge ciphertext with high probability. The response is either m_0 or \perp depending on the contents of the challenge ciphertext and this lets the attacker win the game.

☐ (Gen, E', D') where

$$E'(\text{pk}, m) = (E(\text{pk}, m), 0^{128})$$

$$\text{and } D'(\text{sk}, (c_1, c_2)) = \begin{cases} D(\text{sk}, c_1) & \text{if } c_2 = 0^{128} \\ \perp & \text{otherwise} \end{cases}.$$

正确

This construction is chosen-ciphertext secure.

An attack on (Gen, E', D) gives an attack on (Gen, E, D) .

☐ (Gen, E', D') where

$$E'(\text{pk}, m) = (E(\text{pk}, m), E(\text{pk}, 0^{128}))$$

$$\text{and } D'(\text{sk}, (c_1, c_2)) = D(\text{sk}, c_1).$$

未选择的是正确的



1 / 1 分

4.

Recall that an RSA public key consists of an RSA modulus N

Week 6 – Problem Set

测验, 11 个问题

10/11 分 (90%)

and an exponent e . One might be tempted to use the same

RSA modulus in different public keys. For example, Alice might

use $(N, 3)$ as her public key while Bob may use $(N, 5)$ as his

public key. Alice's secret key is $d_a = 3^{-1} \bmod \varphi(N)$

and Bob's secret key is $d_b = 5^{-1} \bmod \varphi(N)$.

In this question and the next we will show that it is insecure

for Alice and Bob to use the same modulus N . In particular,

we show that either user can use their secret key to factor N .

Alice can use the factorization to compute $\varphi(N)$ and then

compute Bob's secret key.

As a first step, show that Alice can use her public key $(N, 3)$

and private key d_a to construct an integer multiple of $\varphi(N)$.

Which of the following is an integer multiple of $\varphi(N)$?

☐ $3d_a + 1$

☐ $5d_a - 1$

☐ $d_a + 1$

☒ $3d_a - 1$

正确

Since $d_a = 3^{-1} \bmod \varphi(N)$ we know that

$3d_a = 1 \bmod \varphi(N)$ and therefore $3d_a - 1$ is

divisibly by $\varphi(N)$.



1 / 1 分

5.

Now that Alice has a multiple of $\varphi(N)$ let's see how she can

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

Let x be the given multiple of $\varphi(N)$.

Then for any g in \mathbb{Z}_N^* we have $g^x = 1$

in \mathbb{Z}_N . Alice chooses a random g

in \mathbb{Z}_N^* and computes the sequence

$$g^x, g^{x/2}, g^{x/4}, g^{x/8} \dots \text{ in } \mathbb{Z}_N$$

and stops as soon as she reaches the first element $y = g^{x/2^i}$ such

that $y \neq 1$ (if she gets stuck because the exponent becomes odd, she

picks a new random g and tries again). It can be shown that with

probability $1/2$ this y satisfies

$$\begin{cases} y = 1 \pmod{p}, \text{ and} \\ y = -1 \pmod{q} \end{cases} \quad \text{or} \quad \begin{cases} y = -1 \pmod{p}, \text{ and} \\ y = 1 \pmod{q} \end{cases}$$

How can Alice use this y to factor N ?

☐ compute $\gcd(N+1, y)$



未选择的是正确的

☐ compute $\gcd(N, y-1)$



正确

We know that $y-1$ is divisible by p or q , but not divisible

by the other. Therefore, $\gcd(N, y-1)$ will output a non-trivial

factor of N .

☐ compute $\gcd(N, 2y-1)$



未选择的是正确的

☐ compute $\gcd(N, y)$



未选择的是正确的

compute $\gcd(N, y^2 - 1)$

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

未选择的是正确的



1 / 1 分

6.

In standard RSA the modulus N is a product of two distinct primes.

Suppose we choose the modulus so that it is a product of three distinct primes,

namely $N = pqr$. Given an exponent e relatively primeto $\varphi(N)$ we can derive the secret keyas $d = e^{-1} \bmod \varphi(N)$. The public key (N, e) andsecret key (N, d) work as before. What is $\varphi(N)$ when N is a product of three distinct primes?

☐ $\varphi(N) = (p+1)(q+1)(r+1)$

☐ $\varphi(N) = (p-1)(q-1)$

☐ $\varphi(N) = (p-1)(q-1)(r+1)$

☒ $\varphi(N) = (p-1)(q-1)(r-1)$

正确

When N is a product of distinct primes then $|\mathbb{Z}_N^*|$ satisfies $|\mathbb{Z}_N^*| = |\mathbb{Z}_p^*| \cdot |\mathbb{Z}_q^*| \cdot |\mathbb{Z}_r^*| = (p-1)(q-1)(r-1)$.

1 / 1 分

7.

An administrator comes up with the following key management scheme:

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

The administrator generates an RSA modulus N and an element s

in \mathbb{Z}_N^* . He then gives user number i the secret

key $s_i = s^{r_i}$ in \mathbb{Z}_N where r_i is the i 'th

prime (i.e. 2 is the first prime, 3 is the second, and so on).

Now, the administrator encrypts a file that is accessible to

users i, j and t with the key $k = s^{r_i r_j r_t}$ in \mathbb{Z}_N .

It is easy to see that each of the three users can compute k . For

example, user i computes k as $k = (s_i)^{r_j r_t}$. The

administrator hopes that other than users i, j and t , no other user

can compute k and access the file.

Unfortunately, this system is terribly insecure. Any two colluding

users can combine their secret keys to recover the master secret s

and then access all files on the system. Let's see how. Suppose

users 1 and 2 collude. Because r_1 and r_2 are distinct

primes there are integers a and b such that $ar_1 + br_2 = 1$.

Now, users 1 and 2 can compute s from the secret keys s_1

and s_2 as follows:

☒ $s = s_1^a \cdot s_2^b$ in \mathbb{Z}_N .

正确

$$s = s_1^a \cdot s_2^b = s^{r_1 a} \cdot s^{r_2 b} = s^{r_1 a + r_2 b} = s \text{ in } \mathbb{Z}_N.$$

☐ $s = s_1^b + s_2^a$ in \mathbb{Z}_N .

☐ $s = s_1^b / s_2^a$ in \mathbb{Z}_N .

☐ $s = s_1^a / s_2^b$ in \mathbb{Z}_N .



1 / 1 分

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

Let G be a finite cyclic group of order n and consider

the following variant of ElGamal encryption in G :

- Gen: choose a random generator g in G and a random x in \mathbb{Z}_n . Output $\text{pk} = (g, h = g^x)$ and $\text{sk} = (g, x)$.
- $E(\text{pk}, m \in G)$: choose a random r in \mathbb{Z}_n and output $(g^r, m \cdot h^r)$.
- $D(\text{sk}, (c_0, c_1))$: output c_1/c_0^x .

This variant, called plain ElGamal, can be shown to be semantically secure

under an appropriate

assumption about G . It is however not chosen-ciphertext secure

because it is easy to compute on ciphertexts. That is,

let (c_0, c_1) be the output of $E(\text{pk}, m_0)$ and let

(c_2, c_3) be the output of $E(\text{pk}, m_1)$. Then just given

these two ciphertexts it is easy to construct the

encryption of $m_0 \cdot m_1$ as follows:

- ☐ $(c_0/c_3, c_1/c_2)$ is an encryption of $m_0 \cdot m_1$.
- ☐ $(c_0/c_2, c_1/c_3)$ is an encryption of $m_0 \cdot m_1$.
- ☒ $(c_0 c_2, c_1 c_3)$ is an encryption of $m_0 \cdot m_1$.

正确

Indeed, $(c_0 c_2, c_1 c_3) = (g^{r_0+r_1}, m_0 m_1 h^{r_0+r_1})$,

which is a valid encryption of $m_0 m_1$.

- ☐ $(c_0 c_3, c_1 c_2)$ is an encryption of $m_0 \cdot m_1$.



1 / 1 分

9.

Let G be a finite cyclic group of order n and let $\text{pk} = (g, h = g^a)$ and $\text{sk} = (g, a)$ be an ElGamal public/secret

Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题

key pair in G as described in [Segment 12.1](#). Suppose we want to distribute the secret key to two parties so that both parties are needed to decrypt. Moreover, during decryption the secret key is never re-constructed in a single location. A simple way to do so it to choose random numbers a_1, a_2 in \mathbb{Z}_n such that $a_1 + a_2 = a$. One party is given a_1 and the other party is given a_2 . Now, to decrypt an ElGamal ciphertext (u, c) we send u to both parties. What do the two parties return and how do we use these values to decrypt?

- ☒ party 1 returns $u_1 \leftarrow u^{a_1}$, party 2 returns $u_2 \leftarrow u^{a_2}$ and the results are combined by computing $v \leftarrow u_1 \cdot u_2$.

正确

Indeed, $v = u_1 \cdot u_2 = g^{a_1+a_2} = g^a$ as needed

for decryption. Note that the secret key was never re-constructed for this distributed decryption to work.

- ☐ party 1 returns $u_1 \leftarrow u^{(a_1^2)}$, party 2 returns $u_2 \leftarrow u^{(a_2^2)}$ and the results are combined by computing $v \leftarrow u_1 \cdot u_2$.
- ☐ party 1 returns $u_1 \leftarrow u^{a_1}$, party 2 returns $u_2 \leftarrow u^{a_2}$ and the results are combined by computing $v \leftarrow u_1 + u_2$.
- ☐ party 1 returns $u_1 \leftarrow u^{a_1}$, party 2 returns $u_2 \leftarrow u^{a_2}$ and the results are combined by computing $v \leftarrow u_1 / u_2$.



1 / 1 分

10.

Suppose Alice and Bob live in a country with 50 states. Alice is

Week 6 – Problem Set

测验, 11 个问题

10/11 分 (90%)

currently in state $a \in \{1, \dots, 50\}$ and Bob is currently in

state $b \in \{1, \dots, 50\}$. They can communicate with one

another and Alice wants to test if she is currently in the same state

as Bob. If they are in the same state, Alice should learn that fact

and otherwise she should learn nothing else about Bob's location. Bob

should learn nothing about Alice's location.

They agree on the following scheme:

- They fix a group G of prime order p and generator g of G
- Alice chooses random x and y in \mathbb{Z}_p and sends to Bob $(A_0, A_1, A_2) = (g^x, g^y, g^{xy+a})$
- Bob choose random r and s in \mathbb{Z}_p and sends back to Alice $(B_1, B_2) = (A_1^r g^s, (A_2/g^b)^r A_0^s)$

What should Alice do now to test if they are in the same state (i.e. to test if $a = b$)?

Note that Bob learns nothing from this protocol because he simply

recieved a plain ElGamal encryption of g^a under the public key g^x . One can show that

if $a \neq b$ then Alice learns nothing else from this protocol because

she recieves the encryption of a random value.



Alice tests if $a = b$ by checking if $B_2/B_1^x = 1$.

正确

The pair (B_1, B_2) from Bob satisfies $B_1 = g^{yr+s}$ and $B_2 = (g^x)^{yr+s} g^{r(a-b)}$. Therefore, it is a

plain ElGamal encryption of the plaintext $g^{r(a-b)}$ under the

public key (g, g^x) . This plaintext happens to be 1 when $a = b$.

The term B_2/B_1^x computes the ElGamal plaintext and compares it to 1.

Note that when $a \neq b$ the $r(a-b)$ term ensures that Alice learns

nothing about b other than the fact that $a \neq b$.

Week 6 – Problem Set

测验, 11 个问题

indeed, when $a \neq b$ then $r(a - b)$ is a uniform non-zero element of

$$\mathbb{Z}_p.$$

10/11 分 (90%)

- ☐ Alice tests if $a = b$ by checking if $B_2 B_1^x = 1$.
- ☐ Alice tests if $a = b$ by checking if $B_1 / B_2^x = 1$.
- ☐ Alice tests if $a = b$ by checking if $B_2^x B_1 = 1$.



1 / 1 分

11.

What is the bound on d for Wiener's attack when N is a product of **three** equal size distinct primes?

- ☐ $d < N^{2/3}/c$ for some constant c .
- ☐ $d < N^{1/2}/c$ for some constant c .
- ☒ $d < N^{1/6}/c$ for some constant c .

正确

The only change to the analysis is that $N - \varphi(N)$ is now

on the order of $N^{2/3}$. Everything else stays the same. Plugging

in this bound gives the answer. Note that the bound is weaker in this case compared to when N is a product of two primes making the attack less effective.

- ☐ $d < N^{1/5}/c$ for some constant c .



Week 6 – Problem Set

10/11 分 (90%)

测验, 11 个问题