

Baking Instruction — Country Sourdough

Production · 2025-06 · Revision B

1. Scope

This instruction covers the making of the Country Sourdough, product code SD-13, from mixed dough to the point of final inspection. It applies at every site that bakes the product.

Field	Entry
Instruction	BI-SD13
Revision	Revision B
Issued	2025-06
Applies to	Country Sourdough (SD-13)

Bakers shall work to the current revision only.

2. Equipment

Item	Specification	Check
Rack oven	Rotating rack, with steam	Daily
Loaf tins	900 g, lidded	Each use
Probe thermometer	Reads to one degree	Weekly against reference

Loaf tins shall be greased lightly before each use. Tins that are dented or have a damaged coating shall be taken out of use.

3. Shaping and proving

Dough arrives divided and rested. Each piece is shaped into a log and placed seam side down in a greased tin.

Prove until the dough reaches the rim of the tin. A loaf that rises above the rim before baking has proved too far.

4. Baking

The loaves are baked in the rack oven, in their tins, on the rotating rack. Confirm before starting that the rack turns freely and that every shelf is seated.

Load the tins with a gap between them so that air can move around each one.

Bake with steam for the first 5 minutes. Set it to 210 °C. Check the core temperature after 45 minutes.

Turn the loaves out of their tins as soon as they leave the oven. A loaf left in its tin sweats and the crust softens.

5. Inspection

Final inspection is carried out when the loaves have cooled on the rack for one hour. Loaves that fail inspection are recorded on the waste sheet and are not sold.