

Name: Nguyen Duc Tri

Proof of Work

Introduction

This section explores Proof of Work (PoW), a foundational element of this report and a critical turning point in the evolution of Ethereum, led by Vitalik Buterin—a writer and technologist who holds Canadian, Saint Kitts and Nevis, and Montenegrin citizenships. As an early Bitcoin enthusiast, Buterin co-founded *Bitcoin Magazine* in 2011 to popularize blockchain technology before publishing the landmark Ethereum Whitepaper in late 2013. While Proof of Work was originally engineered by Satoshi Nakamoto in 2008, Buterin's genius lay in adopting this robust consensus mechanism to secure a radical new vision: a decentralized, Turing-complete global platform capable of executing smart contracts. This synthesis positioned him as a pioneer of decentralized infrastructure, ushering in an era of borderless governance and shifting the definition of authority from centralized institutions to code-based legislation. Rather than merely launching a technology, Buterin aimed to build a transparent, consensus-driven value system. This article examines Proof of Work through the lens of a researcher deeply inspired by Buterin's lifelong dedication to decentralized ideals.

Table of Contents


- I. Definition of Proof of Work – The foundation of decentralized finances.**
- II. How POW works - Operation, transformation, and long-term maintenance (2014-2022)**
- III. Advantages - The revolutionary nature of Proof of Work and its shaping of how money is tokenized.**
- IV. Limitations - Transactions, gas fees, and ethical questions.**
- V. 51% Attack**
- VI. Mining Centralization - Focuses on the mindset of mining ETH by solving the hashing problem.**
- VII. Comparison with Proof of Stake - Reasons for the fundamental shift in ETH after 2020.**
- VIII. Critical Perspectives**

I. Definition of Proof of Work – The Foundation of decentralized finances

Proof of Work (PoW) is a blockchain consensus mechanism in which participants, commonly known as miners, compete to solve a computationally difficult cryptographic problem to propose a valid new block. The miner must find a value, typically called a nonce, such that the hash of the block header satisfies a predefined difficulty target. While finding such a solution requires significant computational effort and repeated trial and error, verifying the solution is computationally inexpensive. The accumulated computational work is then used by the network to determine which blockchain history should be accepted as the canonical chain. In this way, Proof of Work provides a mechanism for achieving decentralized consensus without requiring central authority or relying solely on the identities of network participants. **This mechanism, originally introduced to crypto by Satoshi Nakamoto in 2008, was adopted by Vitalik Buterin and the crypto community when Ethereum was announced in 2014, creating a seismic shift in how decentralized systems were conceptualized.** At the same time, **Ethereum's early team faced strategic decisions regarding global regulatory clarity, which ultimately led the project to establish its initial foundation in Switzerland.** This relocation underscored how global fundraising for decentralized platforms inevitably intersects with governance and law, shaping Ethereum's trajectory as both a technological and political infrastructure. This completely improved upon what Satoshi announced in 2008, as **Ethereum** not only transported value without intermediaries, but also allowed end users to program through smart contracts and achieve **state execution** consensus at the highest level. By building a transparent and accountable community **initially secured** through Proof of Work, Vitalik and ETH significantly limited the intrusion and control of **centralized entities** in the early stages and consistently respected the vision of a world computing system. Proof of Work transformed problem-solving into a positive binding mechanism, making ETH an irreplaceable infrastructure for the crypto community. It didn't replace Bitcoin but **expanded blockchain capabilities into a Turing-complete global platform** in the years that followed. However, **the early years of Ethereum were also marked by governance challenges and internal philosophical conflicts, such as the departure of co-founders like Charles Hoskinson in 2014 over the project's non-profit direction, the launch of the Olympic TestNet in 2015, and the iconic The DAO Hack in 2016 which stems from smart contract vulnerabilities rather than the consensus layer itself.** These events resulted in deep ideological splits within the decentralized community, where the human element plays a crucial role in shaping consensus. **Furthermore, the inherent scalability and environmental limitations of PoW eventually inspired alternative models, fostering**

both internal evolution toward Proof of Stake and the rise of rivals like Solana and Cardano. These dynamics will be further clarified in subsequent sections.

II. How POW works - Operation, transformation, and long-term maintenance (2014-2022)



Proof of Work (PoW) is a blockchain consensus mechanism that uses computational work to establish agreement among decentralized and potentially anonymous participants. Instead of assigning voting power according to the identity of a participant, PoW links a participant's influence on the amount of computational power they contribute to the network. This approach helps mitigate Sybil attacks, because creating additional identities does not automatically provide additional consensus power. In a PoW blockchain, miners collect valid transactions and construct a candidate block. The block contains information such as a reference to the previous block, transaction-related data, a timestamp, and a nonce. The miner repeatedly changes the nonce and computes the cryptographic hash of the block header until the resulting hash satisfies a predefined difficulty target. In simplified form:

$$H(\text{Block Header} \parallel \text{Nonce}) < \text{Target}$$

Finding a valid nonce requires repeated trial and error, while verifying the resulting proof is relatively inexpensive. The difficulty target is dynamically adjusted so that blocks are

produced at an approximately stable rate despite changes in the total computational power of the network. Once a miner finds a valid block, it is broadcast to the network. Other nodes independently verify the block, including its reference to the previous block, transaction information, difficulty, and Proof of Work. In the Ethereum design described in Buterin's 2013's whitepaper, block validation explicitly includes checking whether the Proof of Work is valid before executing the transactions and verifying the resulting state.

Because multiple miners may occasionally produce blocks at approximately the same time, temporary forks can occur. The network therefore needs a mechanism for selecting the canonical history. In the Nakamoto-style model described by Buterin, the chain supported by the greatest accumulated computational work is treated as the valid chain. An attacker attempting to replace a previous block must therefore reproduce the Proof of Work for that block and continue producing subsequent blocks faster than the honest network. Therefore, PoW can be summarized as the following process:

Transactions → Candidate Block → Computational Work → Valid Block → Chain Selection → Network Consensus

III. Advantages - The revolutionary nature of Proof of Work and its shaping of how money is tokenized.

a. Sybil Resistance

One of the most important contributions of PoW is its ability to reduce the impact of Sybil attacks in permissionless networks. In a traditional voting-based system, an attacker could potentially create many fake identities and use them to gain influence. PoW changes the basis of influence from the number of identities to computational resources. Therefore, creating thousands of additional identities does not automatically provide thousands of additional votes.

b. Permissionless Participation

PoW allows participants to join the consensus process without requiring prior approval from a central authority. A participant can contribute computational resources and compete with other miners to produce blocks. This property is

particularly important for public blockchain networks, where the identities of participants cannot necessarily be assumed to be known or trusted.

c. Simple Verification

Although generating a valid Proof of Work can require a very large number of computational attempts, verifying the result is comparatively simple. A node can calculate the relevant hash and check whether it satisfies the required target. This asymmetry between the cost of producing and verifying a proof is fundamental to the mechanism.

d. Resistance to History Rewriting

Each block is connected to its predecessor through cryptographic hashes. Furthermore, the block's transaction data is represented through a Merkle tree. Modifying a transaction changes the Merkle root, which changes the block hash and invalidates the original Proof of Work. All subsequent blocks would also need to be recomputed. Consequently, the deeper a transaction is embedded in the blockchain, the greater the accumulated computational work an attacker must reproduce to replace its history.

e. Objective Chain Selection

PoW provides an objective basis for resolving competing blockchain histories. Instead of relying on a central authority to determine which chain is correct, nodes can compare the accumulated computational work supporting competing chains. This allows independent participants to converge toward a common history.

IV. Limitations - Transactions, gas fees, and ethical questions.

Despite its revolutionary contribution to decentralized consensus, Proof of Work introduces significant technical and economic limitations, including high energy

consumption, scalability bottlenecks, and vulnerability to centralization through mining pools.

a. High Computational and Energy Costs

PoW intentionally requires miners to perform large amounts of computation. This computational expenditure is fundamental to its security model, but it also means that maintaining network security requires substantial real-world resources.

The security of the blockchain is therefore connected to an external cost:

Security→Computation→Energy + Hardware

This creates an important trade-off: increasing the cost of attacking the network also increases the resources consumed by honest participants.

b. Mining Centralization

One of the most significant limitations discussed by Buterin is mining centralization. Specialized mining hardware such as ASICs can provide substantial advantages over general-purpose hardware. As mining becomes increasingly specialized, participation can require significant capital investment.

Mining pools introduce another form of centralization. Individual miners may combine their computational resources into large pools to obtain more predictable rewards. Buterin notes that large mining pools can consequently control a substantial proportion of the network's computational power.

Thus, PoW solves the problem of identity-based Sybil attacks but does not guarantee perfect decentralization.

c. Scalability

PoW systems must balance security, block production, and network propagation. If blocks are produced too frequently or become too large, different parts of the network may temporarily see different versions of the blockchain.

Buterin identifies this as a scalability problem: increasing transaction throughput by increasing block size or reducing block intervals can increase propagation delays and the frequency of stale blocks.

d. State Blocks

Two miners can independently discover valid blocks at approximately the same time:

Block N

/ \

Block A Block B

Only one branch may eventually become part of the canonical chain. The other becomes stale.

Buterin points out that a high stale-block rate can reduce effective security because some computational work is excluded from the main chain. It can also favor large mining pools because they may receive information about newly discovered blocks more quickly.

Ethereum's early design therefore explored the **GHOST (Greedy Heaviest Observed Subtree)** protocol and uncle rewards to incorporate some of the security contribution of stale blocks and reduce centralization pressure.

V. 51% Attack

The 51% attack is one of the most important security concerns associated with PoW.

The basic assumption of Nakamoto consensus is that the honest network controls more computational power than an attacker. Let:

H^h = Honest network hash power.

H^a = Attacker hash power.

The security assumption is approximately:

$H^h = \text{Honest network hash power} > H^a = \text{Attacker hash power}.$

If an attacker controls more than half of the network's computational power, the attacker can potentially produce an alternative chain faster than the honest network.

Honest chain:

$A \rightarrow B \rightarrow C \rightarrow D \rightarrow E \rightarrow F$

↑

Transaction

Attacker:

$A \rightarrow B \rightarrow C' \rightarrow D' \rightarrow E' \rightarrow F'$

↑

Alternative TX

The attacker attempts to create a competing history and eventually make it the canonical chain by accumulating more computational work.

But this does not mean that a 51% attacker can arbitrarily create coins or forge valid digital signatures. Cryptographic ownership mechanisms remain separate from consensus. The attack primarily concerns the ordering and selection of blockchain history. Buterin describes this distinction explicitly when discussing an attacker attempting to reverse a transaction after it has been included in the blockchain.

Therefore:

A 51% attack is fundamentally an attack on consensus and transaction history, rather than a direct break of the underlying cryptographic signature system.

VI. Mining Centralization

Mining centralization represents a deeper economic limitation of PoW.

The original vision of permissionless mining suggests:

Miner A —┐

Miner B —┐

Miner C —┐

Miner D —┐ → Competitive Mining

Miner E —┐

However, economies of scale can change this structure:

More Capital

↓

More Hardware

↓

Higher Hash rate

↓

Higher Probability of Rewards

↓

More Capital

This creates a positive feedback loop.

Specialized ASIC hardware can further increase the advantage of large-scale operators. Buterin discusses this concern in the Ethereum whitepaper and explores alternative mining designs intended to reduce specialized hardware advantages. Mining pools create another layer of coordination:

Miner 1 —

Miner 2 —

Miner 3 —

Miner 4 —

↓

Mining Pool

↓

Block Mining

Although individual miners may retain the ability to leave a pool, the existence of large pools introduces concentration at the coordination level. Buterin explicitly identifies this as a concern in the discussion of mining centralization. This leads to an important observation for our research:

PoW replaces identity-based voting power with resource-based voting power, but resource concentration can itself create centralization.

VII. Comparison with Proof of Stake - Reasons for the fundamental shift in ETH after 2020.

Proof of Stake (PoS) attempts to achieve Sybil resistance without requiring participants to continuously perform large amounts of computational work.

The fundamental difference can be expressed as:

PoW: Consensus Power ~ Computational Work

While:

PoS: Consensus Power ~ Economic Stake

In PoW, a participant demonstrates commitment to the network by expending computational resources. In PoS, participants instead commit capital by locking or staking assets within the protocol.

Criterion	Proof of Work	Proof of Stake
Consensus	Computational work	Economic stake
Main participants	Miners	Validators
Sybil resistance	Computing resources	Staked capital
Energy consumption	High	Significantly lower
Hardware requirement	Potentially specialized	Generally lower
Attack resource	Hashing power	Economic stake
Centralization pressure	Mining hardware and pools	Stake concentration and validators
Chain selection	Accumulated work	Protocol-defined validator voting/finality
Finality	Generally probabilistic in Nakamoto-style systems	Can provide explicit/economic finality depending on protocol.
Major concern	Energy, mining concentration, scalability	Stake concentration, validator concentration and governance/security assumptions

The comparison reveals that PoS does not eliminate the fundamental problem of Sybil resistance; instead, it **changes the resource used to establish consensus authority**.

This gives the central conceptual transition for our project:

PoW: Prove that you performed work.

PoS: Prove that you have economic stake at risk

VIII. Critical Perspective

The most important conclusion is that Proof of Work should not be understood merely as a mining algorithm. It is a mechanism for converting real-world resource expenditure into decentralized consensus authority.

The complete relationship can be represented as:

Real-world resources

↓

Computational work

↓

Cryptographic proof

↓

Block production

↓

Accumulated work

↓

Chain selection

↓

Decentralized consensus

Its revolutionary contribution is therefore not simply that miners calculate hashes. Rather, PoW provides a mechanism through which an open network of unknown participants can coordinate on a common blockchain history without relying on a central authority. However, the same mechanism creates fundamental trade-offs. Computational security requires real-world expenditure, while economies of scale can encourage mining centralization. Consequently, the central research question is not simply **whether PoW is good or bad**, but rather: What type of resource should determine a participant's influence over consensus in a decentralized system? This question naturally leads to the next part of our research: **whether Proof of Stake can preserve the decentralization and security properties of PoW while addressing its energy consumption, scalability, and mining-centralization limitations.**

Source:

[1] Ethereum. (k.n.). *Ethereum whitepaper*. Ethereum.org. Retrieved August 24, 2026, from <https://ethereum.org/vi/whitepaper/>

[2] Nakamoto, S. (2008). *Bitcoin: A Peer-to-Peer Electronic Cash System*

[3] Li, J. (2021). *Decentralized Mining in Centralized Pools*. The Review of Financial Studies, 34(3), 1194–1230.

[4] Decker, C., & Wattenhofer, R. (2013). *Information Propagation in the Bitcoin Network*. In: IEEE P2P 2013 Proceedings.

[5] Sompolinsky & Zohar (2013), “Accelerating Bitcoin's Transaction Processing: Fast Money Grows on Trees, Not Chains.”

[6] Sayeed & Marco-Gisbert (2019), “Assessing Blockchain Consensus and Security Mechanisms against the 51% Attack”

[7] Ethereum Foundation. *Ethereum Proof-of-Stake Consensus Specifications / Ethereum Consensus Documentation*.