

The Revolution and Limitations of Proof-of-Stake: A Study of Blockchain Consensus Mechanisms

Group 4 - CS372 Blockchain Consensus Research Project

Nguyen Duc Tri · Nghiem Xuan Khai · Nguyen Trung Hieu · Tran Long · Vu Duc Manh

Summary of Member Contributions

Member	Role (per project proposal)	Documented contribution to this report
Nguyen Duc Tri	Research & Technical Analysis	Authored the Proof of Work analysis (Section 3.1); authored the Discussion and answer to the research question (Sections 3.5-3.6); coordinated task assignment and revisions.
Nghiem Xuan Khai	Literature Review & Data Collection	Compiled the literature review across foundational, PoS-limitation, and PoS-mechanism sources; merged duplicate Proof-of-Stake drafts; compiled, restructured, and formatted the complete final report; verified citations and cross-checked factual claims throughout.
Nguyen Trung Hieu	Case Studies & Presentation	Authored an independent Proof-of-Stake analysis report (merged into Section 3.2), covering validators, staking mechanics, crypto-economic security, and governance.
Tran Long	Documentation & Report Formatting	Authored an extensive Proof-of-Stake analysis (merged into Section 3.2), including PoS variant taxonomy, quantitative energy/centralization data, and future-outlook research; contributed to report formatting.
Vu Duc Manh	Emerging Consensus Protocols (joined during project)	Authored the Emerging Consensus Protocols section (Section 3.3), covering Tendermint (BFT-based PoS) and Avalanche (DAG-based PoS).

Table of Contents

1. Introduction

2. Methodology

3. Results and Discussions

3.1 Proof of Work

3.2 Proof of Stake

3.3 Emerging Consensus Protocols

3.4 Comparative Analysis: PoW vs. PoS vs. Emerging Protocols

3.5 Discussion: Is Proof of Stake the Ultimate Consensus Mechanism?

3.6 Conclusion

4. References

Appendix A - Project Working Plan

Appendix B - Simplified Proof-of-Stake Consensus Flow

Appendix C - Summary of Major PoS Attack Vectors

Appendix D - Overall Assessment

1. Introduction

1.1 Project Name and Description

Project name: "The Revolution and Limitations of Proof-of-Stake: A Study of Blockchain Consensus Mechanisms."

Blockchain technology has transformed decentralized computing by enabling secure and trustless transactions through consensus mechanisms. Proof of Work (PoW) pioneered decentralized consensus [1] but suffers from high energy consumption [2] and mining-hardware centralization [3]. Proof of Stake (PoS) has emerged as a more energy-efficient alternative [4] and has been adopted by major blockchain platforms such as Ethereum. Despite its advantages, PoS introduces new challenges including wealth concentration, validator centralization, governance risks, long-range attacks, and weak subjectivity.

1.2 Research Problem

Current blockchain consensus mechanisms must balance three important properties: security, decentralization, and scalability. Although Proof of Stake significantly reduces energy consumption compared with Proof of Work, several unresolved issues remain regarding decentralization, fairness, and long-term security. This project investigates the following research question:

“Is Proof of Stake the ultimate consensus mechanism for blockchain systems, or are new consensus models required to address its limitations?”

1.3 Project Requirements

- Academic papers on blockchain and distributed systems.
- Technical documentation from Bitcoin and Ethereum.
- Research on consensus algorithms, including both foundational and emerging protocols.
- Team collaboration through shared documents and version control.
- Regular internal meetings to monitor project progress and assign tasks.

1.4 Intended Solving Approach and Strategy

The project addresses the research question through five sequential objectives: (1) explain the principles of blockchain consensus mechanisms; (2) analyze the evolution from Proof of Work to Proof of Stake; (3) evaluate the advantages and limitations of Proof of Stake, using Ethereum as the primary case study; (4) compare PoS with emerging consensus mechanisms (Tendermint and Avalanche); and (5) discuss future directions for blockchain consensus. The detailed methods used to pursue these objectives are described in Section 2.

2. Methodology

This research follows a secondary research (literature review and comparative case-study analysis) methodology rather than an original simulation or implementation study. Three methods were used in combination.

2.1 Literature Review

The group collected and annotated academic papers, protocol whitepapers, and official technical documentation across three categories: (a) foundational consensus protocol designs - Bitcoin [1], Ethereum [5], PBFT [6], Ouroboros [7], and Casper FFG [8]; (b) formal and empirical studies of PoS security and centralization - weak subjectivity [9][10], long-range and stake-bleeding attacks [11][12], and validator centralization [13][14][15][16]; and (c) emerging consensus protocols - Tendermint [17] and Avalanche [18]. Source accessibility (open-access preprint vs. paywalled peer-reviewed publication) was tracked so that citations could be verified independently by readers.

2.2 Case-Study Selection

Rather than building new simulations, the group used Ethereum as the primary PoS case study because its architecture (Gasper: Casper FFG + LMD-GHOST) is the largest production deployment of PoS and is extensively documented and independently measured by researchers [13][14]. Bitcoin was used as the PoW case study for the same reason. Tendermint (Cosmos ecosystem) and Avalanche were selected as emerging-protocol case studies because they represent the two dominant architectural departures from linear, Nakamoto-style PoS: classical Byzantine Fault Tolerance [6][17] and Directed Acyclic Graph-based metastable consensus [18], respectively.

2.3 Comparative Evaluation Framework

Each consensus mechanism was evaluated against a consistent set of criteria: security model, energy efficiency, finality (deterministic vs. probabilistic), messaging/communication complexity, validator-set scalability, resistance to the nothing-at-stake problem, exposure to long-range attacks, and primary centralization risk. This framework, adapted from the taxonomy proposed by Xiao et al. [19], was applied consistently across Sections 3.1-3.3 and synthesized into the comparison table in Section 3.4.

2.4 Use of Empirical Data in Place of Simulation

Because the project timeline did not allow for building and running new blockchain simulations, the group instead relied on empirical measurement studies already published by other researchers as proxy evidence - for example, the Crypto Carbon Ratings Institute's direct measurement of Ethereum's energy consumption before and after its transition to PoS [20], and Grandjean, Heimbach, and Wattenhofer's longitudinal measurement of validator concentration on Ethereum's live beacon chain [14]. This is

noted here as a limitation of the present study: future work could validate the group's comparative conclusions using original simulation tools (e.g., a discrete-event simulator of Tendermint's $O(n^2)$ messaging overhead under varying validator-set sizes).

3. Results and Discussions

3.1 Proof of Work

Proof of Work (PoW) is a blockchain consensus mechanism in which participants, commonly known as miners, compete to solve a computationally difficult cryptographic problem to propose a valid new block [1]. The miner must find a nonce such that the hash of the block header satisfies a predefined difficulty target. While finding a solution requires significant computational effort, verifying it is computationally inexpensive.

$$H(\text{Block Header} \parallel \text{Nonce}) < \text{Target}$$

Because multiple miners may occasionally produce blocks at approximately the same time, the network resolves temporary forks using a longest-chain rule: the chain with the greatest accumulated computational work is treated as valid [1].

Advantages

- Sybil resistance: influence is tied to computational resources rather than identity count.
- Permissionless participation: no central authority approval is required to mine.
- Simple verification: proofs are expensive to generate but cheap to verify.
- Resistance to history rewriting: modifying any past transaction invalidates all subsequent proofs.
- Objective chain selection: competing histories are resolved by comparing accumulated work, without a central authority.

Limitations

PoW introduces significant technical and economic limitations, including high energy consumption, scalability bottlenecks, and vulnerability to centralization through mining pools. Security is tied to an external cost - energy and hardware - meaning that increasing attack cost also increases the resources consumed by honest participants [2]. Specialized mining hardware (ASICs) provides substantial advantages over general-purpose hardware, and empirical studies confirm that a small number of mining pools (often three to five) have controlled more than half of total Bitcoin hashrate for extended periods [21]. Increasing throughput by enlarging block size or shortening block intervals increases propagation delay and the frequency of stale ("orphaned") blocks, a relationship formally measured by Decker and Wattenhofer [22]. Ethereum's early design explored the GHOST protocol and uncle rewards, based on a proposal by Sompolinsky and Zohar to accelerate

Bitcoin's transaction processing [23], to incorporate some of the security value of stale blocks.

The 51% Attack

If an attacker controls more than half of network computational power, it can potentially produce an alternative chain faster than the honest network and attempt to reverse previously included transactions. This does not allow the attacker to forge signatures or create coins arbitrarily - cryptographic ownership remains separate from consensus. Economic analyses using rational protocol-design frameworks show that, for large networks such as Bitcoin, the cost of sustaining a successful attack can run into the hundreds of billions of dollars per hour, making it economically irrational for most adversaries, while smaller PoW chains with lower hashrate remain meaningfully more exposed [24].

Comparison with Proof of Stake

PoS attempts to achieve Sybil resistance without continuous computational work: PoW ties consensus power to computational work, while PoS ties it to economic stake [4].

Criterion	Proof of Work	Proof of Stake
Consensus	Computational work	Economic stake
Main participants	Miners	Validators
Sybil resistance	Computing resources	Staked capital
Energy consumption	High	Significantly lower
Hardware requirement	Potentially specialized	Generally lower
Attack resource	Hashing power	Economic stake
Centralization pressure	Mining hardware and pools	Stake concentration and validators
Chain selection	Accumulated work	Protocol-defined validator voting/finality
Finality	Generally probabilistic	Can provide explicit/economic finality
Major concern	Energy, mining concentration, scalability	Stake concentration, governance/security assumptions

3.2 Proof of Stake

Historical Evolution

Stake-based consensus was proposed in 2011 on the BitcoinTalk forum [25] and first implemented via Peercoin in 2012 [4]. In 2017, Kiayias, Russell, David, and Oliynykov introduced Ouroboros, the first provable security model for PoS [7], extended shortly after by Ouroboros Praos [26]. Casper the Friendly Finality Gadget introduced economically accountable finality [8]. In 2022, Ethereum completed its transition to PoS ('The Merge'), the largest PoS deployment to date [27].

PoW vs. PoS: Energy and Security Model

PoW ties transaction-validation rights to the expenditure of unforgeable physical capital [1][28]; PoS instead binds security to internal financial capital held within the protocol ledger [4]. When Ethereum transitioned to PoS in September 2022, the Crypto Carbon Ratings Institute measured an immediate reduction in network electricity use of approximately 99.9%, from roughly 23 TWh to under 0.0026 TWh annually [20].

Ethereum as a Case Study: Core Mechanics

Ethereum's PoS architecture (Gasper) combines Casper FFG for finality with LMD-GHOST for fork choice [29]. A participant becomes a validator by depositing 32 ETH as collateral; honest behavior earns rewards while malicious behavior or downtime results in penalties [30]. Validator selection uses RANDAO-driven pseudorandom sampling, with selection probability strictly proportional to stake share, following the Follow-the-Satoshi mechanism formalized by Ouroboros [7] and later made non-interactive via a Verifiable Random Function in Ouroboros Praos [26]. To solve the historic 'nothing-at-stake' problem, Casper FFG enforces two slashing rules: no double voting and no surround voting [8]. Casper FFG provides deterministic, economic finality once two-thirds of staked value votes for successive checkpoints, typically within 12-15 minutes on Ethereum today [29].

A Taxonomy of PoS Protocol Variants

Following the classification proposed by Xiao et al. [19], modern PoS protocols fall into four architectural paradigms:

- Chain-based (Nakamoto-style) PoS, e.g., Peercoin [4]: dynamic availability, but probabilistic finality.
- Committee-based PoS, e.g., Ouroboros [7][26]: coordinated scheduling, sensitive to synchrony assumptions.
- Delegated PoS (DPoS), e.g., EOS [31], TRON [32], BitShares [33]: high throughput, but significant oligopoly risk.
- BFT-based PoS, e.g., Tendermint [17], Algorand [34], Casper FFG [8]: deterministic finality, but halts if more than one-third of stake is offline.

Crypto-Economic Security

Security depends on the amount of stake at risk, the probability of detection, and the severity of punishment. Attack cost is not identical to market capitalization; an attacker must also weigh liquidity and price impact. Formal analysis shows that finalizing two conflicting Casper FFG checkpoints requires sustaining a qualifying network partition for a minimum of roughly three weeks [35], indicating that Casper's design prioritizes short-term safety while preserving long-run liveness.

Stake Concentration, Validator Centralization, and Governance

PoS removes specialized mining hardware as the dominant security resource but does not eliminate economic concentration. A longitudinal measurement study of the Ethereum beacon chain finds staking power concentrated among a small number of large operators, with Ethereum's PoS network faring similarly to its former PoW counterpart in overall decentralization [14] - a finding echoed by a broader security review of Ethereum's PoS design [13]. Designing a protocol that incentivizes broad participation while preventing wealth monopolization remains an unsolved game-theoretic challenge [15], and comparative wealth-distribution studies find persistently high concentration across coins and tokens [16].

Security Analysis and Attack Vectors

Because validating an alternative PoS chain history requires no physical resource expenditure, an attacker who previously held stake can construct a rival chain branching from far in the past - a vulnerability with no equivalent in PoW [11]. The standard mitigation, weak subjectivity [9], requires nodes to trust a recent checkpoint rather than verifying the full chain from genesis; however, former validators who have already withdrawn stake retain nothing to lose and can still pose a systemic threat, so weak subjectivity does not fully solve the underlying problem [10]. A related attack, stake-bleeding, allows an adversary controlling any constant fraction of stake to gradually siphon block-production advantage over several years without ever directly violating a slashing condition [12]. A systematic review across 26 research articles finds that PoW's longest-chain rule provides the strongest formal security guarantees among the mechanisms studied, but PoS protocols can approach comparable guarantees through hybrid designs [36].

Advantages and Trade-Offs

- Environmental sustainability: >99.9% reduction in energy consumption relative to comparable PoW deployment [20].
- Enhanced economic cost of attack: programmatic slashing destroys attacker capital.
- Strong, explicit finality within minutes rather than hours.
- Trade-off - wealth concentration: reward allocation can compound wealth toward early, large stakeholders [37], though this remains a live empirical debate; other studies find staked-wealth shares remain stable over time among buy-and-hold participants [38].
- Trade-off - staking/liquid-staking centralization, capital lockup, governance concentration, and protocol complexity [39].

3.3 Emerging Consensus Protocols

PoW anchored its security in thermodynamics but revealed critical limitations regarding sustainability, throughput, and probabilistic finality; traditional PoS eliminated physical energy expenditure but introduced weak subjectivity, long-range attacks, and validator centralization. In response, the industry has developed protocols that depart from linear blockchains and probabilistic finality, integrating classical Byzantine Fault Tolerance and Directed Acyclic Graphs with PoS economic weighting.

Theoretical Foundation: BFT and Liveness Assumptions

Practical Byzantine Fault Tolerance (PBFT) ensures both safety and liveness in asynchronous environments provided the number of faulty nodes (f) does not equal or exceed one-third of total nodes (n): safety requires $n \geq 3f + 1$ [6]. Applying PBFT to public blockchains requires merging its mechanics with PoS economic weighting, since identity-based Sybil resistance is unavailable in a permissionless setting. This represents a philosophical departure from liveness-prioritizing models such as the Sleepy Model of consensus, which tolerates intermittently-online participants [40]; BFT-based models instead strictly prioritize safety, halting entirely rather than risking a chain split.

Tendermint Consensus

Created in 2014, Tendermint adapts classical PBFT for permissionless blockchains by replacing identity-based weighting with stake-based weighting [17]. Each block height proceeds through three phases: Propose (a stake-weighted, round-robin-selected validator broadcasts a candidate block), Prevote (validators verify and broadcast signed prevotes until two-thirds of voting power agrees), and Precommit (once two-thirds of voting power precommits, the block is instantly and irreversibly committed).

Tendermint's primary advantage is deterministic, absolute finality, eliminating the multi-minute delay of checkpoint-based systems such as Casper FFG. Any equivocation produces permanent cryptographic evidence that is automatically slashed. However, because it relies on classical BFT, validators must communicate all-to-all, resulting in $O(n^2)$ message complexity; Tendermint networks must therefore cap active validator sets (often 100-150 nodes), inherently trading participation for decentralization [15].

Tendermint also inherits the weak-subjectivity vulnerability described above: because there is no physical cost anchoring chain history, a newly joining node must trust a recent checkpoint, and validators who have exited staking can collude to build a fake alternate chain, since historical signatures remain cryptographically valid even after stake withdrawal. Tendermint mitigates this with unbonding periods (e.g., 21 days), but the reliance on social consensus for checkpoints remains a fundamental friction point relative to pure PoW.

Avalanche Consensus

Avalanche departs from both Nakamoto consensus and classical BFT, using a Directed Acyclic Graph (DAG) in which transactions are processed individually and linked to multiple predecessors [18]. Instead of all-to-all communication, Avalanche uses repeated random subsampling and metastability: a validator (Slush) samples a small fixed-size set of peers (k) and adopts the majority preference; stateful counters (Snowflake/Snowball) prevent malicious actors from endlessly flipping states; and voting for a DAG vertex (Avalanche) implicitly votes for all its ancestors. Even a perfectly split network eventually tips toward one outcome through statistical variance during subsampling.

Avalanche's paramount advantage is scalability: each validator communicates with only a small, constant number of peers, giving $O(1)$ overhead per node and supporting thousands of independent validators without degrading performance, with transactions typically finalized in under 500 milliseconds. Unlike Tendermint's absolute finality, Avalanche provides probabilistic finality: reversal probability decreases exponentially but is never strictly zero. Because Avalanche layers PoS on top of subsampling (selection probability proportional to staked capital) to defend against Sybil attacks, it reintroduces the same validator-centralization risks observed on Ethereum [13][14].

Comparative Analysis: Overcoming Traditional PoS Limitations

Traditional PoS systems suffer extended finality delays - Casper FFG requires roughly 12-15 minutes before a transaction is economically irreversible [29]. Tendermint solves this by finalizing every block instantly; Avalanche solves it by finalizing DAG vertices in under one second. Mitigating long-range attacks in traditional PoS requires complex mechanisms such as decentralized checkpointing [41]; Tendermint and Avalanche instead tightly couple consensus with strict weak-subjectivity checkpoints and fast slashing. However, neither protocol fully escapes validator centralization: Tendermint sacrifices decentralization by capping validators for $O(n^2)$ performance, while Avalanche's PoS economic weighting naturally leads to wealth concentration, mirroring the empirical centralization metrics observed in Ethereum's consensus layer [14].

3.4 Comparative Analysis: PoW vs. PoS vs. Emerging Protocols

The following table synthesizes the comparisons developed in Sections 3.1-3.3 into a single cross-cutting view of the four consensus families examined in this report.

Dimension	PoW (Bitcoin-style)	Traditional PoS (Ouroboros/Gasper)	BFT-based PoS (Tendermint)	DAG-based PoS (Avalanche)
Security resource	Computational work	Economic stake	Economic stake + BFT voting	Economic stake + subsampling
Energy use	High	Very low (~99.9% below PoW)	Very low	Very low
Finality	Probabilistic (hours)	Economic, ~12-15 min	Instant, deterministic	Sub-second, probabilistic
Messaging complexity	O(1) broadcast	O(committee)	O(n ²) all-to-all	O(1) per node
Validator set size	Unlimited (hashpower-gated)	Large (thousands)	Capped (~100-150)	Unlimited (thousands+)
Nothing-at-stake	N/A	Mitigated via slashing	Mitigated via slashing	Mitigated via PoS layer
Long-range attack exposure	None (physical cost)	Present - needs weak subjectivity	Present	Present
Primary centralization risk	Mining hardware & pools	Stake & liquid-staking concentration	Validator-set cap	Stake concentration in subsampling
Representative case	Bitcoin	Ethereum (post-Merge)	Cosmos Hub	Avalanche network

Read across the table, a consistent pattern emerges: each successive design choice trades one limitation for another rather than eliminating the underlying trilemma. PoW purchases objective chain selection at the cost of energy and mining-pool centralization. Traditional PoS removes the energy cost but reintroduces a social trust assumption and shifts centralization from hardware to capital. BFT-based PoS purchases instant finality by capping the validator set. DAG-based PoS removes that cap through subsampling, but finality becomes probabilistic again and stake concentration re-emerges through the PoS weighting layer it depends on.

3.5 Discussion: Is Proof of Stake the Ultimate Consensus Mechanism?

Proof of Stake represents a major improvement in blockchain consensus, particularly compared with Proof of Work. By replacing computational competition with economic commitment, PoS significantly reduces energy consumption while providing strong incentives for validators to behave honestly. Modern PoS systems such as Ethereum further strengthen these properties through validator rewards, penalties, slashing, checkpoint-based finality, and inactivity mechanisms. PoS should therefore not be viewed as an unsuccessful consensus mechanism; rather, it has become one of the most mature and practical approaches for securing large-scale blockchain networks.

However, the strengths of PoS do not imply that it is the ultimate consensus mechanism for all blockchain systems. PoS changes the source of security from computational resources to economic resources; consequently, some limitations are transformed rather than eliminated. Validator influence is fundamentally related to the amount of stake controlled, creating concerns about wealth concentration, validator centralization, and the influence of large staking providers. Sophisticated attacks can still target chain liveness, validator coordination, fork choice, and network communication. Ethereum's current security model, for example, identifies different attack thresholds at approximately 33%, 51%, and 66% of total stake, demonstrating that economic security remains dependent on the distribution and behavior of stake across the network [42].

Another important limitation is that PoS is not a single universal design. Different blockchain systems have different requirements concerning scalability, decentralization, latency, fault tolerance, governance, and resource constraints, as demonstrated by the divergent trade-offs of Tendermint and Avalanche in Section 3.3. A consensus mechanism optimized for a permissionless global blockchain may not be optimal for a high-throughput application-specific network, an enterprise environment, or an Internet-of-Things system. The question is therefore not whether PoS can replace every other consensus mechanism, but whether its security and coordination assumptions remain appropriate for a particular application.

Furthermore, PoS demonstrates that blockchain consensus extends beyond the consensus algorithm itself. Ethereum's documentation explicitly recognizes the importance of the social layer as a final line of defense in extreme consensus failures [42]. In severe cases such as double finality or a dishonest finalized chain, technical mechanisms alone may not be sufficient, and the community may need to coordinate around an honest fork. Blockchain security therefore ultimately depends on a combination of protocol rules, economic incentives, network assumptions, validator behavior, and social coordination.

For these reasons, new consensus models remain necessary - not necessarily to replace PoS entirely, but to extend, combine, or modify its principles to address specific weaknesses. Hybrid and application-specific approaches, as demonstrated by Tendermint

and Avalanche, can combine economic stake with other forms of evidence or contribution. The objective is therefore not to search for one universally superior consensus mechanism, but to develop mechanisms whose security assumptions match the requirements of different blockchain environments.

3.6 Conclusion

Based on the comparison of PoS with alternative consensus approaches, Proof of Stake should be considered a highly effective and mature consensus paradigm, but not the ultimate consensus mechanism for all blockchain systems. It solves major problems associated with PoW, particularly energy consumption and the repeated computational cost of attacks, while introducing new challenges involving stake concentration, validator centralization, economic incentives, network coordination, and dependence on social recovery mechanisms.

Therefore, the answer to the research question is no: PoS is not the ultimate consensus mechanism. However, this conclusion does not imply that PoS should be abandoned. Instead, it suggests that blockchain research should move toward pluralistic, hybrid, and application-specific consensus models. The future of blockchain consensus is likely not a single mechanism replacing all others, but a spectrum of mechanisms designed around different assumptions, threats, resources, and system objectives. In this sense, the evolution of consensus can be understood as:

Proof of Work -> Proof of Stake -> Hybrid/Application-Specific
Consensus -> New forms of evidence and contribution

The fundamental research challenge is therefore no longer simply how to achieve consensus, but what should count as sufficient evidence for a participant to influence the state of a decentralized system - opening the possibility of future mechanisms based not only on computational work or financial stake, but also on useful work, knowledge, reputation, identity, trust, or other forms of verifiable contribution.

4. References

- [1] S. Nakamoto, "Bitcoin: A Peer-to-Peer Electronic Cash System," 2008.
- [2] A. de Vries, "Bitcoin's Growing Energy Problem," *Joule*, vol. 2, no. 5, pp. 801-805, 2018.
- [3] A. Gervais, G. O. Karame, K. Wüst, V. Glykantzis, H. Ritzdorf, and S. Capkun, "On the Security and Performance of Proof of Work Blockchains," in *Proc. ACM SIGSAC Conf. Computer and Communications Security*, 2016, pp. 3-16.
- [4] S. King and S. Nadal, "PPCoin: Peer-to-Peer Crypto-Currency with Proof-of-Stake," self-published paper, 2012.
- [5] V. Buterin, "Ethereum Whitepaper: A Next-Generation Smart Contract and Decentralized Application Platform," 2014.
- [6] M. Castro and B. Liskov, "Practical Byzantine Fault Tolerance," in *Proc. 3rd Symp. Operating Systems Design and Implementation (OSDI '99)*, 1999, pp. 173-186.
- [7] A. Kiayias, A. Russell, B. David, and R. Oliynykov, "Ouroboros: A Provably Secure Proof-of-Stake Blockchain Protocol," in *Advances in Cryptology - CRYPTO 2017*, 2017, pp. 357-388.
- [8] V. Buterin and V. Griffith, "Casper the Friendly Finality Gadget," *arXiv:1710.09437*, 2017.
- [9] V. Buterin, "Proof of Stake: How I Learned to Love Weak Subjectivity," *Ethereum Foundation Blog*, Nov. 25, 2014.
- [10] J. Eze et al., "STAKESURE: Proof of Stake Mechanisms with Strong Cryptoeconomic Safety," *arXiv:2401.05797*, 2024.
- [11] E. Deirmentzoglou, G. Papakyriakopoulos, and C. Patsakis, "A Survey on Long-Range Attacks for Proof of Stake Protocols," *IEEE Access*, vol. 7, pp. 28712-28725, 2019.
- [12] P. Gaži, A. Kiayias, and A. Russell, "Stake-Bleeding Attacks on Proof-of-Stake Blockchains," in *Proc. Crypto Valley Conf. Blockchain Technology (CVCBT)*, 2018, pp. 85-92.
- [13] V. Buterin, D. Herman, D. Reijnders, and S. Leonardos, "Ethereum Proof-of-Stake under Scrutiny," in *Proc. 38th ACM/SIGAPP Symp. Applied Computing (SAC '23)*, 2023.
- [14] D. Grandjean, L. Heimbach, and R. Wattenhofer, "Ethereum Proof-of-Stake Consensus Layer: Participation and Decentralization," *arXiv:2306.10777*, 2023.
- [15] A. Kiayias, E. Koutsoupias, F. Marmolejo-Cossio, and A. Stouka, "Balancing Participation and Decentralization in Proof-of-Stake Cryptocurrencies," *arXiv:2407.08686*, 2024.
- [16] B. Kuśmierz and A. Overko, "How Centralized is Decentralized? Comparison of Wealth Distribution in Coins and Tokens," *arXiv:2207.01340*, 2022.

- [17] J. Kwon, "Tendermint: Consensus without Mining," Technical Report, 2014.
- [18] Team Rocket, "Snowflake to Avalanche: A Novel Metastable Consensus Protocol Family for Cryptocurrencies," Avalanche Whitepaper, 2018.
- [19] Y. Xiao, N. Zhang, W. Lou, and Y. T. Hou, "A Survey of Distributed Consensus Protocols for Blockchain Networks," IEEE Commun. Surveys Tuts., vol. 22, no. 2, pp. 1432-1465, 2020.
- [20] CCRI, "The Merge - Implications on the Electricity Consumption and Carbon Footprint of the Ethereum Network," Crypto Carbon Ratings Institute, 2022.
- [21] L. W. Cong, Z. He, and J. Li, "Decentralized Mining in Centralized Pools," Rev. Financial Studies, vol. 34, no. 3, pp. 1194-1230, 2021.
- [22] C. Decker and R. Wattenhofer, "Information Propagation in the Bitcoin Network," in Proc. IEEE P2P, 2013.
- [23] Y. Sompolinsky and A. Zohar, "Secure High-Rate Transaction Processing in Bitcoin," in Financial Cryptography and Data Security (FC 2015), 2015, pp. 507-527.
- [24] S. Sayeed and H. Marco-Gisbert, "Assessing Blockchain Consensus and Security Mechanisms against the 51% Attack," Applied Sciences, 2019.
- [25] "Proof of Stake Instead of Proof of Work," Bitcointalk.org forum post, Jul. 11, 2011.
- [26] B. David, P. Gaži, A. Kiayias, and A. Russell, "Ouroboros Praos: An Adaptively-Secure, Semi-Synchronous Proof-of-Stake Blockchain," in Advances in Cryptology - EUROCRYPT 2018, 2018, pp. 66-98.
- [27] Ethereum.org, "The Merge," Ethereum Roadmap, 2025.
- [28] C. Dwork and M. Naor, "Pricing via Processing or Combatting Junk Mail," in Advances in Cryptology - CRYPTO '92, 1992, pp. 139-147.
- [29] Ethereum.org, "Proof-of-Stake (PoS)," Ethereum Developer Documentation, 2025.
- [30] Ethereum Foundation, "The Beacon Chain - Ethereum Consensus Specs," ethereum.github.io/consensus-specs, n.d.
- [31] D. Larimer, "EOS.IO Technical White Paper," Block.one, 2017.
- [32] TRON Foundation, "TRON: Advanced Decentralized Blockchain Platform," Whitepaper v2.0, 2018.
- [33] D. Larimer, "Delegated Proof-of-Stake (DPOS)," BitShares Whitepaper, 2014.
- [34] J. Chen and S. Micali, "Algorand," arXiv:1607.01341, 2016.

- [35] V. Buterin, D. Reijnders, S. Leonardos, and G. Piliouras, "Incentives in Ethereum's Hybrid Casper Protocol," in Proc. IEEE Int. Conf. Blockchain and Cryptocurrency (ICBC), 2019, pp. 236-244.
- [36] I. Abellán Álvarez, V. Gramlich, and J. Sedlmeir, "Unsealing the Secrets of Blockchain Consensus: A Systematic Comparison of the Formal Security of Proof-of-Work and Proof-of-Stake," in Proc. 39th ACM/SIGAPP Symp. Applied Computing, 2024, pp. 278-287.
- [37] G. Fanti, L. Kogan, S. Oh, K. Ruan, P. Viswanath, and G. Wang, "Compounding of Wealth in Proof-of-Stake Cryptocurrencies," in Financial Cryptography and Data Security - FC 2019, 2019, pp. 42-61.
- [38] I. Roşu and F. Saleh, "Evolution of Shares in a Proof of Stake Cryptocurrency," Management Science, vol. 67, no. 2, pp. 661-672, 2021.
- [39] F. Schär, "Decentralized Finance: On Blockchain- and Smart Contract-Based Financial Markets," Federal Reserve Bank of St. Louis Review, vol. 103, no. 2, pp. 153-174, 2021.
- [40] R. Pass and E. Shi, "The Sleepy Model of Consensus," in Advances in Cryptology - ASIACRYPT 2017, 2017.
- [41] S. Azouvi, G. Danezis, and V. Konstantopoulos, "Winkle: Foiling Long-Range Attacks in Proof-of-Stake Systems," IACR ePrint Archive, 2019/1440, 2019.
- [42] Ethereum.org, "A More Secure Ethereum," Ethereum Roadmap, 2026.

Appendix A - Project Working Plan

The table below reproduces the group's original work plan as defined in the project proposal.

Objective	Activities / Tasks	Expected Results	Who	When
Understand blockchain consensus	Collect books, papers and technical documents	Literature review completed	All members	Week 1
Study Proof of Work	Research PoW architecture, mining, security and limitations	PoW analysis report	Tri & Khai	Week 1
Study Proof of Stake	Research staking, validators, slashing and protocol design	PoS analysis report	Hieu & Long	Week 2
Compare consensus mechanisms	Compare PoW, PoS and emerging consensus protocols	Comparison table and discussion	All members	Week 3
Analyze limitations of PoS	Investigate security, decentralization and governance issues	Critical analysis section	Tri	Week 3
Preparing final report	Write, edit and format the report	Final research paper	Long & Khai	Week 4
Prepare presentation	Design slides and practice presentation	Presentation slides	Hieu & Tri	Week 4

Actual execution updated this plan in two respects. First, Vu Duc Manh joined the group during the project and was assigned a new task - researching emerging consensus protocols (Tendermint and Avalanche) - to compare against PoS's inherent limitations. Second, the official submission deadline (September 3, 2026) compressed the original four-week plan into approximately ten working days (August 24 - September 3, 2026), requiring the Proof-of-Stake analysis, Proof-of-Work revision, and comparative analysis to proceed in parallel rather than strictly sequentially.

Appendix B - Simplified Proof-of-Stake Consensus Flow

- 1. Validators stake cryptocurrency

- 2. Protocol selects a block proposer
- 3. Proposer creates and broadcasts a block
- 4. Other validators verify the block
- 5. Validators submit attestations/votes
- 6. Fork-choice algorithm determines the canonical head
- 7. Votes contribute to checkpoint justification
- 8. Sufficient voting power produces finality
- 9. Honest validators receive rewards
- 10. Offline validators lose rewards or receive penalties
- 11. Malicious validators may be slashed

Appendix C - Summary of Major PoS Attack Vectors

Attack	Main Idea	Main Defense
Nothing-at-stake	Vote on multiple forks	Slashing
Majority stake	Control a large stake share	Economic cost + social recovery
Long-range attack	Rewrite history using former validators	Finality + weak subjectivity
Stake-bleeding	Gradually siphon block-production advantage via fee replay	Reward/fee-structure design
Stake grinding	Manipulate validator selection	Secure randomness (VRF)
Censorship	Prevent transactions from being included	Validator diversity + protocol/social responses
Finality attack	Prevent supermajority agreement	Inactivity leak
Validator collusion	Coordinate malicious behavior	Correlation penalties
Centralization attack	Concentrate staking power	Validator diversity and decentralized staking

Appendix D - Overall Assessment

Strengths: low energy consumption; strong economic incentives; explicit finality (in BFT-style variants); no specialized mining hardware; scalable validator architecture (in DAG-based variants); direct punishment of malicious behavior.

Weaknesses: stake concentration; staking-provider centralization; governance concentration; complex protocol design; capital requirements; weak subjectivity; dependence on token economic value.

Overall conclusion: no consensus mechanism examined in this report - PoW, traditional PoS, or emerging BFT/DAG-based protocols - simultaneously maximizes security, decentralization, and scalability. Each represents a different point on that trade-off surface, and progress in the field has consisted of shifting the trade-off rather than eliminating it.