Assembly: SOURCE PIN -> DESTINATION PIN / 7

Every canonical row is shown exactly once. INTERNAL_VERIFY is an existing module bond to inspect, not a wire to add.

E2 DESIGN HOLD | Physical connections unapproved | Generic ports require actual-part mapping | 08 Nov 2026

W133	**ESP1.GPIO32 -> R6.1** TF_3V3 | WIRE | 0/3.3 V	BLOCKED_MISSING
W134	**U1.7 (2Y2) -> US_F.TRIG** TF_5V | WIRE | 0/5 V	BLOCKED_MISSING
W135	**ESP1.GPIO33 -> U1.15 (2A3)** TL_3V3 | WIRE | 0/3.3 V	BLOCKED_MISSING
W136	**ESP1.GPIO33 -> R7.1** TL_3V3 | WIRE | 0/3.3 V	BLOCKED_MISSING
W137	**U1.5 (2Y3) -> US_L.TRIG** TL_5V | WIRE | 0/5 V	BLOCKED_MISSING
W138	**ESP1.GPIO13 -> U1.17 (2A4)** TR_3V3 | WIRE | 0/3.3 V	BLOCKED_MISSING
W139	**ESP1.GPIO13 -> R8.1** TR_3V3 | WIRE | 0/3.3 V	BLOCKED_MISSING
W140	**U1.3 (2Y4) -> US_R.TRIG** TR_5V | WIRE | 0/5 V	BLOCKED_MISSING
W141	**S2.EN_NC -> DRV_L.R_EN** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W142	**S2.EN_NC -> DRV_L.L_EN** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W143	**S2.EN_NC -> DRV_R.R_EN** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W144	**S2.EN_NC -> DRV_R.L_EN** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W145	**S2.EN_NC -> DRV_A.ENA** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W146	**S2.EN_NC -> DRV_A.ENB** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W147	**S2.EN_NC -> R13.1** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W148	**S2.EN_NC -> R14.1** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W149	**S2.EN_NC -> R15.1** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W150	**S2.EN_NC -> R16.1** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W151	**S2.EN_NC -> R17.1** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W152	**S2.EN_NC -> R18.1** EN_DRIVER_5V | WIRE | 0/5 V; LOW disabled	BLOCKED_MISSING
W153	**ESP1.GPIO21 -> DRV_A.IN1** BRUSH_IN1 | WIRE | 0/3.3 V	PROVISIONAL
W154	**ESP1.GPIO21 -> R9.1** BRUSH_IN1 | WIRE | 0/3.3 V	PROVISIONAL

Red +supply | Black GND | Blue control | Green sensor | Orange motor | Thick = high-current | Dashed = missing/blocked

Net labels join across sheets. Crossings alone do not join. No component footprint / connector orientation is implied.