Assembly: SOURCE PIN -> DESTINATION PIN / 8

Every canonical row is shown exactly once. INTERNAL_VERIFY is an existing module bond to inspect, not a wire to add.

E2 DESIGN HOLD | Physical connections unapproved | Generic ports require actual-part mapping | 08 Nov 2026

W155	**ESP1.GPIO22 -> DRV_A.IN2** BRUSH_IN2 | WIRE | 0/3.3 V	PROVISIONAL
W156	**ESP1.GPIO22 -> R10.1** BRUSH_IN2 | WIRE | 0/3.3 V	PROVISIONAL
W157	**ESP1.GPIO23 -> DRV_A.IN3** CONVEYOR_IN3 | WIRE | 0/3.3 V	PROVISIONAL
W158	**ESP1.GPIO23 -> R11.1** CONVEYOR_IN3 | WIRE | 0/3.3 V	PROVISIONAL
W159	**ESP1.GPIO25 -> DRV_A.IN4** CONVEYOR_IN4 | WIRE | 0/3.3 V	PROVISIONAL
W160	**ESP1.GPIO25 -> R12.1** CONVEYOR_IN4 | WIRE | 0/3.3 V	PROVISIONAL
W161	**US_F.ECHO -> R23.1** EF_RAW | WIRE | Standard module: potentially 0/5 V	BLOCKED_MISSING
W162	**R23.2 -> R24.1** EF_DIV | WIRE | Nominal 3.0 V at 5.0V ECHO	BLOCKED_MISSING
W163	**R23.2 -> U2.1 (1A)** EF_DIV | WIRE | Nominal 3.0 V at 5.0V ECHO	BLOCKED_MISSING
W164	**U2.7 (1Y) -> ESP1.GPIO34** EF_SAFE | WIRE | 0 / MCU-derived 3.3V; U2 off -> high impedance	BLOCKED_MISSING
W165	**U2.7 (1Y) -> R30.1** EF_SAFE | WIRE | 0 / MCU-derived 3.3V; U2 off -> high impedance	BLOCKED_MISSING
W166	**US_L.ECHO -> R25.1** EL_RAW | WIRE | Standard module: potentially 0/5 V	BLOCKED_MISSING
W167	**R25.2 -> R26.1** EL_DIV | WIRE | Nominal 3.0 V at 5.0V ECHO	BLOCKED_MISSING
W168	**R25.2 -> U2.3 (2A)** EL_DIV | WIRE | Nominal 3.0 V at 5.0V ECHO	BLOCKED_MISSING
W169	**U2.5 (2Y) -> ESP1.GPIO35** EL_SAFE | WIRE | 0 / MCU-derived 3.3V; U2 off -> high impedance	BLOCKED_MISSING
W170	**U2.5 (2Y) -> R31.1** EL_SAFE | WIRE | 0 / MCU-derived 3.3V; U2 off -> high impedance	BLOCKED_MISSING
W171	**US_R.ECHO -> R27.1** ER_RAW | WIRE | Standard module: potentially 0/5 V	BLOCKED_MISSING
W172	**R27.2 -> R28.1** ER_DIV | WIRE | Nominal 3.0 V at 5.0V ECHO	BLOCKED_MISSING
W173	**R27.2 -> U2.6 (3A)** ER_DIV | WIRE | Nominal 3.0 V at 5.0V ECHO	BLOCKED_MISSING
W174	**U2.2 (3Y) -> ESP1.GPIO36** ER_SAFE | WIRE | 0 / MCU-derived 3.3V; U2 off -> high impedance	BLOCKED_MISSING
W175	**U2.2 (3Y) -> R32.1** ER_SAFE | WIRE | 0 / MCU-derived 3.3V; U2 off -> high impedance	BLOCKED_MISSING
W176	**DRV_L.M+ -> FM1.IN** DRV_L_MP | WIRE | Bidirectional / PWM bridge output; not a supply rail	BLOCKED_RATING

Red +supply | Black GND | Blue control | Green sensor | Orange motor | Thick = high-current | Dashed = missing/blocked

Net labels join across sheets. Crossings alone do not join. No component footprint / connector orientation is implied.