Complete schematic - sheet 6

Every component terminal is shown. Equal net labels are connected; use connection IDs in the CSV for physical routing.

E2 DESIGN HOLD | Physical connections unapproved | Generic ports require actual-part mapping | 08 Nov 2026

R15 | DRV_R.R_EN local EN pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — EN_DRIVER_5V
2 — GND

R16 | DRV_R.L_EN local EN pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — EN_DRIVER_5V
2 — GND

R17 | DRV_A.ENA local EN pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — EN_DRIVER_5V
2 — GND

R18 | DRV_A.ENB local EN pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — EN_DRIVER_5V
2 — GND

R19 | L_FWD receiver pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — L_FWD_5V
2 — GND

R20 | L_REV receiver pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — L_REV_5V
2 — GND

R21 | R_FWD receiver pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — R_FWD_5V
2 — GND

R22 | R_REV receiver pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — R_REV_5V
2 — GND

R29 | E-stop feedback pull-down
ADDITIONAL / MISSING OR SELECT
10k 1%, >=1/8 W
1 — ESTOP_OK
2 — GND

C_U1 | local ceramic bypass
ADDITIONAL / MISSING OR SELECT
100nF, >=10V
1 — V5_LOGIC
2 — GND

C_F | local ceramic bypass
ADDITIONAL / MISSING OR SELECT
100nF, >=10V
1 — V5_LOGIC
2 — GND

C_L | local ceramic bypass
ADDITIONAL / MISSING OR SELECT
100nF, >=10V
1 — V5_LOGIC
2 — GND

C_R | local ceramic bypass
ADDITIONAL / MISSING OR SELECT
100nF, >=10V
1 — V5_LOGIC
2 — GND

C_BL | local motor-bus reservoir
ADDITIONAL / MISSING OR SELECT
C / ESR / voltage TBD
+ — LEFT_SUPPLY
- — GND

C_BR | local motor-bus reservoir
ADDITIONAL / MISSING OR SELECT
C / ESR / voltage TBD
+ — RIGHT_SUPPLY
- — GND

C_BA | local motor-bus reservoir
ADDITIONAL / MISSING OR SELECT
C / ESR / voltage TBD
+ — AUX_SUPPLY
- — GND

Red +supply | Black GND | Blue control | Green sensor | Orange motor | Thick = high-current | Dashed = missing/blocked

Net labels join across sheets. Crossings alone do not join. No component footprint / connector orientation is implied.