Complete schematic - sheet 7

Every component terminal is shown. Equal net labels are connected; use connection IDs in the CSV for physical routing.

E2 DESIGN HOLD | Physical connections unapproved | Generic ports require actual-part mapping | 08 Nov 2026

U2 | SN74LVC3G34DCU ECHO isolation

ADDITIONAL / MISSING OR SELECT

SN74LVC3G34DCU

1 / 1A	EF_DIV
2 / 3Y	ER_SAFE
3 / 2A	EL_DIV
4 / GND	GND
5 / 2Y	EL_SAFE
6 / 3A	ER_DIV
7 / 1Y	EF_SAFE
8 / VCC	V3V3

C_U2 | local ceramic bypass

ADDITIONAL / MISSING OR SELECT

100nF, >=10V

1	V3V3
2	GND

R30 | ECHO output default-low

ADDITIONAL / MISSING OR SELECT

100k 1%, >=1/8 W

1	EF_SAFE
2	GND

R31 | ECHO output default-low

ADDITIONAL / MISSING OR SELECT

100k 1%, >=1/8 W

1	EL_SAFE
2	GND

R32 | ECHO output default-low

ADDITIONAL / MISSING OR SELECT

100k 1%, >=1/8 W

1	ER_SAFE
2	GND

Red +supply | Black GND | Blue control | Green sensor | Orange motor | Thick = high-current | Dashed = missing/blocked

Net labels join across sheets. Crossings alone do not join. No component footprint / connector orientation is implied.