

Your own trade receiver

TradingView → your receiver on Cloudflare → MetaApi → FxPro MT5. No MT5 to keep running, no VPS, no laptop, and no daily webhook limit. The strategy does not change.

CODE

metaapi_receiver/worker.js

MT5 CONNECTION

MetaApi (metaapi.cloud)

YOUR TIME

about 1 hour, then 2 weeks on demo

RUNS ON

Cloudflare Workers (free plan)

BROKER

FxPro MT5 - demo first

SWITCH BACK

change one URL in the alert

Do everything on a DEMO account first and trade it there for two weeks before going live. Cloudflare's and MetaApi's menus change from time to time; where a button name may differ, this guide says what the screen is for. Not financial advice.

SECTION 1

How it works

Four pieces. You set up two accounts, paste one file and fill in a few settings.

	Piece	What it does	Cost
1	TradingView (your strategy)	An order of the strategy fills → the alert sends its message to your receiver's URL	your paid plan (webhooks)
2	Your receiver (Cloudflare Worker)	Checks the secret and the sender, reads the message, sends the order to MetaApi, closes by the trade's tag	free plan
3	MetaApi	Keeps the connection to your FxPro MT5 account on its own servers - no terminal on your side	free tier to test; then a monthly fee per MT5 account - see metaapi.cloud
4	FxPro MT5	Opens the trade with its own stop and target; closes it when told	your account

What the receiver does with each alert

The alert says	The receiver
buy / sell, with lots, stop, target and the trade's tag	Sends a market order with that exact stop and target, marked with the tag (MetaApi's <i>clientId</i>).
closelong / closeshort with a tag	Closes only the position carrying that tag - stacked BOS trades stay independent.
a close for a trade FxPro already closed (its own stop or target)	Finds nothing and does nothing. This is normal.
a close that arrives before its own entry was placed	Looks again for up to 17 seconds and closes the trade once it appears - no trade is left behind.
the same alert twice	Trades it once.
no stop or no target, a wrong message, or too many lots	Sends nothing, and tells you on Telegram (optional).
not from TradingView's addresses, or without your secret	Refuses it.

The strategy does not change

The receiver reads exactly the message the strategy already sends for TheConnector. Your alert keeps the condition **Order fills only** and the message **only** `{{strategy.order.alert_message}}`; only the webhook URL changes. To go back to TheConnector, put its URL back (its robot must then be running in MT5 again).

Check these strategy settings once

Group	Setting	Must be
22	Message format	TheConnector
22	Quantity to send	Lots (units divided by the contract size)
30	TheConnector stop / target fields	sl_price / tp_price - exact prices (recommended)
30	TheConnector tag	smcgold (never blank - each trade's close depends on it)
30	Symbol to send	blank, unless FxPro spells the symbol differently

Before you start, and Part A - MetaApi

Part A connects MetaApi to your FxPro demo account and gives you three values for the receiver.

You need

Item
[] A paid TradingView plan (webhook alerts).
[] Your FxPro MT5 demo login number, main (trading) password - not the investor password - and the server name exactly as MT5 shows it.
[] An e-mail address for a MetaApi account and one for a Cloudflare account (both free to open).
[] Optional: Telegram on your phone, for a message whenever something goes wrong.
[] The file <code>worker.js</code> (folder <code>metaapi_receiver</code>).

Keep these private

Your MetaApi token, your receiver's SECRET, your MT5 password and your Telegram bot token. Never paste them into a chat, an e-mail, a screenshot or the code. They go only into MetaApi's and Cloudflare's own secret fields.

Part A - MetaApi

- 1 Open metaapi.cloud and create an account.
- 2 Add your **MT5 account** (the accounts page): platform **MT5**, your **login**, the **main password**, and the **server** name exactly as MT5 shows it. Leave the other options at their defaults.
- 3 Wait until the account shows as **deployed** and **connected** (a few minutes).
- 4 Write down the account's **id** (a long code) - this is **ACCOUNT_ID**.
- 5 Write down the account's **region** (for example `new-york` or `London`) - this is **REGION**.
- 6 Open MetaApi's API-token page and create a token. Copy it straight into Part B, step 6 - this is **METAAPI_TOKEN**. Do not save it in a file or a chat.

Costs

MetaApi charges per connected MT5 account while it is deployed; a free tier is offered for testing. Check the current prices on metaapi.cloud before you connect a live account. Undeploying the account in MetaApi stops the charge - and stops trading.

SECTION 3

Part B - the receiver on Cloudflare

Paste the code, fill in the settings, and switch on the memory that stops a repeated alert from trading twice.

- 1 Open **cloudflare.com** and create a free account.
- 2 In the dashboard open **Workers & Pages** → **Create** → create a **Worker** (start from the "Hello World" example). Name it **smc-receiver** and deploy it.
- 3 Open the Worker → **Edit code**. Delete everything in the editor, paste the whole of `worker.js`, and click **Deploy**.
- 4 Your receiver's address is shown on the Worker's page, like `https://smc-receiver.YOUR-NAME.workers.dev`. Write it down.
- 5 Make your **SECRET**: 32 random letters and digits (a password manager can generate it). It becomes the end of your webhook URL.
- 6 Worker → **Settings** → **Variables and Secrets** → add each row of the table below. Type **Secret** for the secret ones, **Text** for the others. Save and deploy.
- 7 **Memory against repeats**: in the dashboard create a **KV namespace** (Storage & Databases → KV) called **smc-seen**. Then Worker → Settings → **Bindings** → add a KV namespace binding with the variable name **SEEN** and pick **smc-seen**.
- 8 **Logs**: Worker → Settings → **Observability** - switch on **Workers Logs**, so you can read what the receiver did.
- 9 Optional **Telegram**: in Telegram open **@BotFather**, send `/newbot`, follow it, and copy the bot token into **TELEGRAM_BOT_TOKEN**. Send any message to your new bot, then get your chat id (for example from **@userinfobot**) into **TELEGRAM_CHAT_ID**.

Name	Type	Value
SECRET	Secret	your 32 random letters and digits
METAAPI_TOKEN	Secret	the token from Part A, step 6
ACCOUNT_ID	Text	the account id from Part A, step 4
REGION	Text	the region from Part A, step 5, e.g. <code>London</code>
MAX_LOTS	Text	the most lots one order may have, e.g. <code>1</code> - anything above is refused
DRY_RUN	Text	<code>1</code> for the first test (logs only, sends no order); <code>0</code> after it
TELEGRAM_BOT_TOKEN	Secret	optional
TELEGRAM_CHAT_ID	Secret	optional
NOTIFY_TRADES	Text	optional: <code>1</code> = a Telegram message for every trade too
SYMBOL_MAP	Text	optional: <code>{"XAUUSD": "GOLD"}</code> only if FxPro spells a symbol differently
TV_IPS_ONLY	Text	leave it out (= only TradingView may send)

Part C - check it, Part D - test it on demo

Part C checks the whole chain without trading. Part D sends real demo orders from TradingView.

Part C - the health check

- 1 In a browser open `https://smc-receiver.YOUR-NAME.workers.dev/YOUR_SECRET/health`.
- 2 You should see `"ok": true`, `"broker"`, your balance and `"dryRun": true`. Nothing is traded by this page.
- 3 An error there tells you what to fix: **not set** = a setting is missing (Part B, step 6); **MetaApi 401** = wrong token; **MetaApi 404** = wrong ACCOUNT_ID or REGION; **MetaApi 504** = the MetaApi account is not deployed or not connected yet.

Part D - the test, on the demo account

- 1 **Dry run** (DRY_RUN = 1). In TradingView create a temporary test alert that fires within minutes, with the webhook URL `https://smc-receiver.YOUR-NAME.workers.dev/YOUR_SECRET` and this hand-typed message - put real prices: the stop about 5 below and the target about 5 above gold's current price:
`{"action":"buy","symbol":"XAUUSD","volume":0.01,"sl_price":STOP,"tp_price":TARGET,"tag":"test-0001"}`
- 2 When it fires: Worker → **Logs** shows **DRY RUN - would send** with your order. Nothing reaches FxPro.
- 3 Set **DRY_RUN = 0**, deploy, and fire the same test alert again (new prices). A **0.01-lot buy with its stop and target** must appear in MT5 (phone is fine).
- 4 Close it with a second test alert: `{"action":"closeLong","symbol":"XAUUSD","tag":"test-0001"}`. The trade must close; the log says **CLOSED**.
- 5 **Delete both test alerts**. Hand-typed messages are only for this test. Then make the strategy's own alert: condition **Order fills only**, message only `{{strategy.order.alert_message}}`, webhook URL `https://smc-receiver.YOUR-NAME.workers.dev/YOUR_SECRET`.
- 6 Trade the demo account for **two weeks**. Compare FxPro's history with TradingView's List of Trades: the same trades, the same lots, each closed by its own stop, target or close.

Side by side, if you like

TradingView lets one strategy have two alerts. You can keep TheConnector on one account and the receiver on the demo account at the same time, each alert with its own webhook URL.

Going live, and every day

What to change for the live account, what the log lines mean, and how to switch back.

Going live

- 1 In MetaApi add your **live** FxPro MT5 account (Part A) and note its id and region.
- 2 Best: a **second Worker (smc-receiver-live)** with its own SECRET, the live ACCOUNT_ID and REGION, DRY_RUN = 0 and a MAX_LOTS that fits your risk. The demo receiver keeps working for tests.
- 3 Create the strategy's alert on the live chart with the live receiver's URL. Check the first live trade's lot size in MT5 yourself.

What the log says

Log line	Meaning	Do
OPENED ... / CLOSED ...	An order went through	Nothing
NOTHING TO CLOSE (already closed at the broker)	FxPro's own stop or target closed it first	Nothing - normal
SKIPPED: the same alert arrived twice	A repeated alert	Nothing
REFUSED: ... above MAX_LOTS	The order was bigger than your limit	Check group 22 'Quantity to send' = Lots, or raise MAX_LOTS
REJECTED: ...	A message it could not use (no stop, wrong format)	Read the reason; check the strategy settings in Section 1
REJECTED: not a TradingView address	Someone else tried your URL	Make a new SECRET and update the alert
ERROR open failed / close failed	MetaApi or FxPro refused or did not answer	Look at MT5 at once; the reason is in the line

Once a week - two minutes

Open the health page (Part C); compare FxPro's trades with TradingView's List of Trades; check that MetaApi still shows the account deployed and connected, and that your TradingView alert is active.

Switching back to TheConnector

Start MT5 with TheConnector's robot again (laptop or VPS - see the MQL5 VPS guide), and put TheConnector's webhook URL back into the strategy's alert. Nothing else changes.

SECTION 6

Troubleshooting, and how it was tested

What to look at when a trade did not happen, and what was proven before you got the file.

What you see	Most likely cause	Fix
Alert fired, nothing in the log	Wrong URL in the alert, or the Worker is not deployed	Copy the URL again; deploy the Worker
Log: REJECTED: not JSON	Message format is not TheConnector, or the alert message is not only <code>{{strategy.order.alert_message}}</code>	Group 22 = TheConnector; fix the alert message
Log: stop sent as 'sl'	Group 30 stop / target fields on the robot's own mode	Group 30 = sl_price / tp_price
ERROR ... MetaApi 401 / 404 / 504	Token / account id or region / account not connected	Health page (Part C) tells you which
ERROR ... INVALID_STOPS	The stop or target is too close to the price for FxPro	Group 24: a minimum stop distance
ERROR ... NO_MONEY	Not enough free margin at FxPro	Lower the risk or check the account
ERROR ... symbol	FxPro spells the symbol differently	SYMBOL_MAP, or group 30 'Symbol to send'
Trades open but never close	The tag is blank, or the close alerts go to another URL	Group 30 tag = smcgold; one URL per alert

How it was tested

Test	Result
36 checks against a fake MetaApi: messages, secret, TradingView addresses, lot limit, dry run, symbol names, broker refusals, lost answers, repeats, stacked closes by tag, a close arriving before its entry	36 of 36
The strategy's own alert stream from the simulator - CHOCCH only, CHOCCH and BOS, BOS only, with and without the step stop, 2 markets: 2,840 alerts, sent one by one and again with every candle's alerts at the same moment; a fake FxPro also closing trades at their own stop or target	24 of 24 runs: after every alert the broker held exactly TradingView's open trades
The same replay with a deliberately broken receiver (closing all trades of a side instead of the tagged one)	caught: 16 of 24 runs failed, as they must
worker.js in Cloudflare's own runtime (workerd) and Cloudflare's deploy check	loads, 7 of 7 end-to-end checks, deploy check clean

What could not be tested here

MetaApi's real servers are not reachable from my test machine, so the receiver has not yet placed an order at MetaApi. The API calls follow MetaApi's official code package and REST documentation; Part D on your demo account is the real proof. If Part D shows an error, send me the log line - not your token or secret.