

Scala Notes (Week 1–6)

Contents

Scala	3
Content Page	3
Lambda Calculus to Scala	5
Other Terminologies	5
Running Scala	6
Using Scalac and Scala commands	7
Using build.sbt (Alternative)	7
VSC inbuilt run (Another alternative way to run scala)	7
Running test cases in cohort	7
Functions and Methods	8
OOP in Scala	8
Variable Types	9
Val vs Var	9
Type Inference	9
Expressions vs Statements	9
If Else	10
Recursion	10
Regular Recursion	10
Tail Recursion Optimisation	10
Map	11
FlatMap	12
Fold	13
foldRight vs foldLeft	13
Filter	14
For expression in Scala	14
Enum (Algebraic Data Type example)	14
Using enum (ADT example)	15
List	15
Creating an immutable list	15
Accessing Elements	16
Attempting to Modify a list	16
Iterating over a list	16
Flattening a list	16

Pattern Matching with Lists	16
Pattern Constructors	16
Match	17
Summing a List (match)	17
Indexing an element (match)	18
findMax() function (match)	18
Span Function	20
Currying	20
Function Composition	21
Generic/ Polymorphic ADT	21
Subtyping inside Enum	21
Covariant and Invariant	22
Function Overloading	22
case Class	22
Type Class (Traits)	23
Higher Kinded Type & Functor Type Class	25
Without Functor	25
With Functor	25
Kinds vs Types	26
Functor Laws	26
Foldable Type Class	27
Option	28
Error Handling with Option Type	28
Error Handling with Either Type	29
Derived Type Class	30
Example of Derived Type Class	30
(Continued) Derived show implementation	31
Applicative Functor	31
Applicative Laws	33
Monad	33
Example with Option	34
Functor, Applicative and Monad	34
Syntax Analysis (5A)	35
Lexing	35
Example (Simple)	35
Example (JSON)	36
Parsing	36
Example	36
Continued from Lexer Example (JSON)	37
Deep Dive and How it Works	37
Top Down Parsing	39
Big Picture:	39
Naive Top Down Parsing	41
Predictive Top Down Parsing (better alternative)	41
Parsec	42
Setting Up	42

Naive Implementation	42
Monad Option (Better)	43
Dealing with Left Recursion	44
Math Exp Example	45

Scala

Statically typed → compiler knows the type of every value before the program runs

This markdown file documents everything learned in Week 1 to 6 of 50.054 Compiler Design and Program Analysis related to Scala

Content Page

- Scala
- Lambda Calculus to Scala
- Other Terminologies
 - REPL
 - Immutable
 - Try
 - Success and Failure
 - Some and None
- Running Scala
 - Using Scalac and Scala commands
 - Using build.sbt (Alternative)
 - VSC inbuilt run (Another alternative way to run scala)
- Running test cases in cohort
- Functions and Methods
- OOP in Scala
- Variable Types
 - Val vs Var
- Type Inference
- Expressions vs Statements
- If Else
- Recursion
 - Regular Recursion
 - Tail Recursion Optimisation
- Map
 - FlatMap
- Fold
 - foldRight vs foldLeft
- Filter
- For expression in Scala

-
- Enum (Algebraic Data Type example)
 - Using enum (ADT example)
 - List
 - Creating an immutable list
 - Accessing Elements
 - Attempting to Modify a list
 - Iterating over a list
 - Flattening a list
 - Pattern Matching with Lists
 - Pattern Constructors
 - Match
 - Summing a List (match)
 - Indexing an element (match)
 - findMax() function (match)
 - * Case #1
 - * Case #2
 - Span Function
 - Currying
 - Function Composition
 - Generic/ Polymorphic ADT
 - Subtyping inside Enum
 - Covariant and Invariant
 - Function Overloading
 - case Class
 - Type Class (Traits)
 - Higher Kinded Type & Functor Type Class
 - Without Functor
 - With Functor
 - Kinds vs Types
 - Functor Laws
 - Foldable Type Class
 - Option
 - Error Handling with Option Type
 - Error Handling with Either Type
 - Derived Type Class
 - Example of Derived Type Class
 - (Continued) Derived show implementation
 - Applicative Functor
 - Explanation
 - The for-comprehension
 - Execution
 - Applicative Laws
 - * Identity
 - * Homomorphism
 - * Interchange
 - * Composition

-
- Monad
 - Syntax Analysis
 - Lexing
 - Example (Simple)
 - Example (JSON)
 - Lexer Token Data Type Enum
 - Parsing
 - Example
 - Continued from Lexer Example (JSON)
 - Deep Dive and How it Works
 - Top Down Parsing
 - Naive Top Down Parsing
 - Parsec
 - Setting Up
 - Naive Implementation
 - Monad Option (Better)
 - Dealing with Left Recursion
 - Math Exp Example
-

Lambda Calculus to Scala

back-to-top | Lambda Calculus | Scala | | _____ | _____
| | Variable | x | | Constant | 1, 2, true, false | | Lambda abstraction $\lambda x.t$ | (x: T) \square e
| | Function application $t_1 t_2$ | e1(e2) | | Conditional | if (e1) { e2 } else { e3 } | | Let
Binding | val x = e1; e2 | | Recursion | def f(x: Int): Int = f(x); f(1) |

Every Scala expression can be represented in lambda calculus form.

Scala runs imperatively \rightarrow step-by-step like C or Java

Other Terminologies

back-to-top

REPL Read-Eval-Print Loop \rightarrow an interactive programming environment where you can type code line by line and immediately see the result.

Scala is a REPL

Immutable Cannot be changed after creation

Try

- A container type that represents a computation that may either result in a value (Success) or an exception (Failure). It is used for error handling without throwing exceptions

Why for what?

Try (with Success and Failure) lets you represent computations that can fail, capturing either the result (Success) or the error (Failure) without throwing exceptions.

Success and Failure

- A subclass of Try

```
Success(42)
```

```
// means the computation succeeded and produced the value 42
```

Some and None

- a subclass of Option that wraps a value to indicate presence.

```
Some(2)
```

↑ This means the option contains value 2, if there is no value, use None

Why for what?

Lets you represent the presence and/or absence of a value safely → a function that might not return a result can returnOption[Int] instead of just Int

Running Scala

back-to-top Make sure your file extensions is .scala

Make sure all your code is nested under an object that extends app

```
object name_of_file extends App {
```

```
  // Code here
```

```
}
```

Using Scalac and Scala commands

Make sure to cd into the right directory first

```
# Compile
scalac name_of_file.scala
```

```
# Run
scala name_of_file.scala
```

Using build.sbt (Alternative)

Make sure the scala files you are running is in exactly:

- src
 - main
 - * scala
 - name_of_file.scala

```
# Activate sbt at the root directory
sbt
```

```
# Running
clean
compile
run
```

```
# If you want it to compile and run everytime u save
~run
```

```
# For specific files
~runMain name_of_file
```

VSC inbuilt run (Another alternative way to run scala)

Need to download Scala CLI first

Running test cases in cohort

back-to-top

```
# Running all Test Cases
test
```

```
# Running one Specific Test Case
testOnly *TestEx1
```

Functions and Methods

[back-to-top](#)

```
def name_of_function (name_of_parameters : type_of_parameter) : return_type = {
  body_of_function
}
```

// Example:

```
def add(x:Int, y:Int): Int = {
  x + y
}
```

- def
 - Keyword to define a function with type parameters
 - add
 - Function name
 - (x:Int, y:Int)
 - Function will take in parameter x, with type Integer and y, with type Integer as well
 - :Int
 - Return type will be an Int
-

Another Example

```
def flatten[A](l: List[List[A]]) = { }
```

- [A] → Type parameter
 - it makes the function generic, meaning it can work on lists of any type
 - (l :List[List[A]]) → Parameter list
 - function takes one parameter called l
 - = {} → {} is the function body
-

OOP in Scala

[back-to-top](#)

```
trait FlyBehavior{
  def fly()
```

```
}

abstract class Bird(species:String, fb:FlyBehavior){
  def getSpecies():String = this.species
  def fly():Unit=this.fb.fly()
}

class Duck extends Bird("Duck", new FlyBehavior(){
  override def fly() = println("I can't fly!")
})

class BlueJay extends Bird("BlueJay", new FlyBehavior(){
  override def fly() = println("Swoosh")
})
```

- trait defines an interface
 - class constructors are in-line
 - Unit is a type, similar to void in Java
 - Functions and methods' return types can be inferred by compiler
-

Variable Types

[back-to-top](#)

Val vs Var

```
// immutable
val x = 5
```

```
// mutable
var y = 10
```

Type Inference

Scala often figures out type automatically

```
val n = 42 //inferred as Integer
val s = "hi" //inferred as String
val n: Int = 42 //or you can declare yourself
```

Expressions vs Statements

[back-to-top](#)

-
- Expression has value *e.g. 1+2 evaluates to 3*
 - Statement does something but has no meaningful value *e.g. println("hi")*
-

If Else

back-to-top

```
val max = if (a>b) a else b
```

- if a is bigger than b, return a, else return b
-

Recursion

back-to-top

Regular Recursion

```
def sum(l: List[Int]): Int = l match {  
  case Nil      => 0  
  case x :: xs  => x + sum(xs)  
}
```

```
sum(List(1,2,3))
```

```
// sum(1::2::3::Nil)  
// → 1 + sum(2::3::Nil)  
// → 1 + (2 + sum(3::Nil))  
// → 1 + (2 + (3 + 0))  
// Unwind call stack  
// → 1 + (2 + 3 )  
// → 1 + 5  
// → 6
```

Each recursive call has to wait for the next one to finish

Tail Recursion Optimisation

- recursive call is the last operation
- "throws" away the previous recursion

```
import scala.annotation.tailrec
```

```
def sumTail(l: List[Int]): Int = {
```

```

@tailrec
def go(lst: List[Int], acc: Int): Int = lst match {
  case Nil      => acc
  case x :: xs  => go(xs, acc + x) // recursive call is LAST
}
go(1, 0)
}

```

```
sumTail(List(1,2,3))
```

```

// go([1,2,3], 0)
// → go([2,3], 1)
// → go([3], 3)
// → go([], 6)
// → 6
// Done ~

```

- acc
 - the 'accumulator', a variable that accumulates or keeps track of the running total of the computations as we go deeper into recursion
 - instead of waiting to add everything after coming back up, just add along the way
-

Map

back-to-top

- Idea: apply the function to every element in the list

```

val nums = List(1,2,3,4)
val doubled = nums.map(x => x * 2)
println(doubled)

```

```
// Output: List(2,4,6,8)
```

[Bad Example] Trying to add 10 to each elements in the list

```

def addToEach(x:Int, l:List[Int]):List[Int] = l match {
  case Nil => Nil
  case (y::ys) => {
    val yx = y+x
    yx::addToEach(x,ys)
  }
}

```

```
// addToEach(10, List(1,2,3))

// Input x=10, l = [1,2,3]
// y = 1, ys = [2,3]
// Compute yx = 1 + 10 = 11
// Call yx::addToEach(10, [2,3])

// Input x=10, l = [2,3]
// y = 2, ys = [3]
// yx = 2 + 10 = 12
// Call yx::addToEach(10, [3])

// Input x=10, l = [3]
// y = 3, ys = []
// yx = 3 + 10 = 13
// Call yx::addToEach(10, [])

// Final call his Nil

// 13 :: Nil
// 12 :: (13::Nil)
// 11 :: (12 :: (13::Nil))
// Result = List(11, 12, 13)
```

From ↑ to ↓

```
def addToEach(x:Int, l:List[Int]):List[Int] = l.map(y=>y+x)
```

FlatMap

- Map + Flatten (joining multiple lists into 1)

```
// Regular Map
val nums = List(1, 2, 3)
val result = nums.map(x => List(x, x + 1))

// List(List(1, 2), List(2, 3), List(3, 4))

// FlatMap
val nums = List(1, 2, 3)
val result = nums.flatMap(x => List(x, x + 1))

// List(1, 2, 2, 3, 3, 4)
```

Fold

back-to-top

- Reduce a collection down to a single value by repeatedly applying a function
- has:
 - foldLeft → process left to right
 - foldRight → process right to left
 - fold → pick a direction depending on the collection, usually left
- Requires:
 - A starting value (the accumulator).
 - A binary operation (a function that combines the accumulator with each element).

General Form

```
list.fold(initialValue)((acc,element) => newAcc)
```

```
// Start with initialValue,  
// then for each element,  
// update the acc (accumulator).
```

Example

```
// Goal : 1 + 2 + 3 + 4  
val nums = List(1, 2, 3, 4)  
val result = nums.fold(0)((acc, x) => acc + x)  
println(result)  
  
// Step 0: acc = 0, x = null, new acc = null  
// Step 1: acc = 0, x = 1, new acc = acc + x = 1  
// Step 2: acc = 1, x = 2, new acc = acc + x = 3  
// Step 3: acc = 3, x = 3, new acc = acc + x = 6  
// Step 4: acc = 6, x = 4, new acc = acc + x = 10  
  
// Final output: ((0 + 1) +2) +3) +4
```

foldRight vs foldLeft

- foldLeft → Tail-recursive

```
List(1,2,3).foldLeft(0)(_ - _)
```

```
// ((0-1)-2)-3 = -6
```

```
List(1,2,3).foldRight(0)(_ - _)
// 1-(2-(3-0)) = 2
```

Filter

back-to-top

- Takes a predicate function (a function that returns true/false)
- Keeps only elements for which the function is true
- Returns a new list, original stays unchanged

```
val nums = List(1,2,3,4,5,6)
val evens = nums.filter(x => x % 2 == 0)
println(evens)
```

Output:

```
List(2,4,6)
```

For expression in Scala

back-to-top

- combination of flatmap and map

```
for x in [1,2,3]
  x+1
```

is the same as:

```
map(lambda x:x+1, [1,2,3])
```

in Scala

```
for {x <- List(1,2,3)} yield (x+1)
```

using map

```
List(1,2,3).map(x=>x+1)
```

Enum (Algebraic Data Type example)

back-to-top

```
enum MathExp {
  case Plus(e1:MathExp, e2:MathExp)
  case Minus(e1:MathExp, e2:MathExp)
  case Multiply(e1:MathExp, e2:MathExp)
  case Div(e1:MathExp, e2:MathExp)
  case Const(v:Int)
}

import MathExp.*
val

def eval(e:MathExp):Int = e match {
  case Plus(e1, e2) => eval(e1) + eval(e2)
  case Minus(e1, e2) => eval(e1) - eval(e2)
  case Mult(e1, e2) => eval(e1) * eval(e2)
  case Div(e1, e2) => eval(e1) / eval(e2)
  case Const(i) => i
}
```

- enum keyword lets you define a closed set of possible values for a type
- MathExp is a type
- Each case (like Plus, Minus, etc) is a **constructor** → a way to create one “variant” of that type
- As all case belong to the same enum, the compiler knows all possibilities

Using enum (ADT example)

```
import MathExp.*
val expression = Mult(Plus(Const(1), Const(2), Const(3)))

// (1+2)*3
```

List

back-to-top

Creating an immutable list

```
val l = List(1, 2, 3)
```

- recall ‘val’ defines an immutable variable

Accessing Elements

```
l(1)
```

- Similar to python's indexing

Attempting to Modify a list

```
l(1) = 3
```

- *ERROR* → Scala's list are immutable

Iterating over a list

```
for (i <- l) {println(i)}
```

Output:

```
1
2
3
```

Flattening a list

```
def flatten[A](l: List[List[A]]): List[A] =  
  l.flatMap(inner => inner)
```

```
flatten(List(List(1,2), List(3,4), List(5)))  
// Result: List(1, 2, 3, 4, 5)
```

Pattern Matching with Lists

- use Match

```
l match {  
  case Nil => "empty"  
  case (x :: xs) => "not empty"  
}
```

Pattern Constructors

```
//Nil and '::'
```

Nil -> represents the empty list

:: -> constructs a list by perpending an element to another list

E.g.

```
1 :: 2 :: Nil = List(1,2)
```

- A list in scala is either:
 - Empty → Nil
 - Non-empty → a head element plus a tail list, written as head :: tail
-

Match

back-to-top

```
1 match {  
  case Nil      => "empty"  
  case (x :: xs) => "not empty"  
}
```

- match is like a switch-case for structured data
- in the above code, we are matching l with 2 potential patterns, an empty list or a non-empty list
- l is being tested against 2 patterns
- if l is an empty list, it will return "empty"
- if l is a non-empty list, it means x will match the first element (the head) and xs will match the tail (a list of all the remaining elements)

```
val list = List(10, 20, 30)
```

```
list match {  
  case Nil      => println("empty")  
  case (x :: xs) => println(s"head = $x, tail = $xs")  
}
```

Output:

```
head = 10, tail = List(20,30)
```

Summing a List (match)

back-to-top

```
def sum(l: List[Int]): Int = {  
  1 match {  
    case Nil      => 0  
    case (x::xs) => x + sum(xs)  
  }  
}
```

-
- If the list is empty (Nil), return 0.
 - If the list has a head (x) and tail (xs), return x + sum(xs). → This recursively sums all elements.

Example:

```
sum(List(1,2,3))
// = 1 + sum(List(2,3))
// = 1 + (2 + sum(List(3)))
// = 1 + (2 + (3 + sum(Nil)))
// = 1 + (2 + (3 + 0))
// = 6
```

Indexing an element (match)

back-to-top

```
def first(l: List[Int]): Int = l match {
  case Nil => None
  case (x::xs) => x
}
```

- This is like accessing an element but with extra steps
 - Why is this better? It handles an OutOfBounds error by returning None instead
 - def first(...) → defining a function named first
 - Parameter: l:List[Int] → l is a list of integers
 - : Int → the function returns an Int
-

findMax() function (match)

back-to-top

```
def findMax(l:List[Int]):Int = {
  l match{

    case Nil => Int.MinValue
    case (x::xs) =>
      val tailMax = findMax(xs)
      if (x>tailMax) x else tailMax
  }
}
```

- def findMax → defines a function named findMax
- (l: List[Int]) → takes one parameter l, which must be a list of integers
- : Int → return type is an integer
- = → everything after the = is the body

Case #1

case Nil => Int.MinValue

- if l is empty, return Int.MinValue
- MinValue is the built-in smallest integer of scala (-2,147,483,648)
- We need to return this because we are guaranteeing that any real integer in the list will be greater than this
- In the event the list has only 1 value that is -50 for sure, it is STILL the biggest one despite being the only one, so it will be compared to the Int.MinValue and "win"

Case #2

case x :: xs =>

val tailMax = findMax(xs)

if (x > tailMax) x **else** tailMax

- if l is non-empty, Scala splits it into
 - x → the head (first element)
 - xs → the tail (the rest of the list)
- Then, it recursively calls findMax on the tail(xs) which will find the maximum of the rest of the listL
- it compares the head of the list(x) with the maximum of the tail (tailMax)
- if head is larger, return x, else return tailMax

Example

1. Start

- l = List(3, 7, 2) → not empty
 - x = 3, xs = List(7, 2)
 - tailMax = findMax(List(7, 2))
-

2. Recursive call: findMax(List(7, 2))

- x = 7, xs = List(2)
 - tailMax = findMax(List(2))
-

3. Recursive call: findMax(List(2))

- x = 2, xs = Nil
 - tailMax = findMax(Nil)
-

4. Base case: findMax(Nil)

- Returns Int.MinValue
-

5. Unwinding recursion

- Compare 2 vs Int.MinValue → 2
- Compare 7 vs 2 → 7
- Compare 3 vs 7 → 7

□ Final result: 7

Span Function

back-to-top

INCOMPLETE

```
// span function takes a list and returns a list of pairs
// each pair consists of the first element and each of the other elements in the list
// span(List(1, 2, 3, 4))
// Output: List((1,2), (1,3), (1,4))
def span[A](l: List[A], check: A => Boolean): (List[A], List[A]) = l match {
  case Nil => Nil
  case (x::xs) if check(x) => {
    val (ys, zs) = span(xs, check)
    (x::ys, zs)
  }
}
```

Currying

back-to-top

Normal Form

```
def tax(price:Double, rate:Double):Double = price * rate
```

// When calling tax, need to always provide price and rate as arguments

Currying Ver/Form

```
def curriedTax(rate: Double)(price: Double): Double = price * rate
val gst_with_rate = curriedTax(0.08)(_: Double)
val gst_with_price = curriedTax(_: Double)(100)
```

// Good because i can FIX rate and have price as argument or FIX price and have rate as argument

Why?

- Code reusability

-
- Partial application, plus one becomes a function, don't need 2 parameters
-

Function Composition

back-to-top

- Combining 2 or more functions to produce a new function

```
def f(x: Int): Int = x + 1
def g(x: Int): Int = x * 2
```

```
val h = f andThen g // h(x) = g(f(x))
val k = f compose g // k(x) = f(g(x))
```

```
h(3) // f(3) = 4, g(4) = 8 → result: 8
k(3) // g(3) = 6, f(6) = 7 → result: 7
```

```
andThen: f andThen g = g(f(x))
compose: f compose g = f(g(x))
```

Generic/ Polymorphic ADT

back-to-top

recall ADT

```
enum List[+A] {
  case Nil
  case Cons(x: A, xs: MyList[A])
}
```

- List[+A] is generic: it can be List[Int], List[String], etc.
- BUT it cannot have both Int and String in the same

Subtyping inside Enum

back-to-top

```
enum Shape {
  case Circle(radius: Double)
  case Rectangle(width: Double, height: Double)
}
```

// Double is a variable type in Scala, similar to float

```
val c: Shape = Shape.Circle(2.0)
val r: Shape = Shape.Rectangle(3.0, 4.0)

println(area(c)) // Output: 12.566...
println(area(r)) // Output: 12.0
```

- Shape.Circle and Shape.Rectangle are both subtypes of Shape
 - You can write functions that accept Shape and use pattern matching to handle each subtype
 - It allows you to treat all cases as the same base type (Shape), but also access specific data for each subtype
-

Covariant and Invariant

back-to-top (*not tested*)

```
class InvariantBox[A]
class CovariantBox[+A]
```

```
val cov: CovariantBox[Any] = new CovariantBox[String] // OK
val inv: InvariantBox[Any] = new InvariantBox[String] // Error
```

- the + determines whether its Co or In
-

Function Overloading

back-to-top

- Using the same function name for multiple implementations in different type context

```
def greet(name: String): String = s"Hello, $name!"
def greet(name: String, age: Int): String = s"Hello, $name! You are $age years old."
```

- Issue 1: Type mismatch error
 - Issue 2: Duplicated Code
-

case Class

back-to-top

- An enum with only 1 constructor can be rewritten as a case class

```
enum Person {  
  case Person (name: String, contacts: List[Contact])  
}
```

// can be written as:

```
case class Person(name: String, contacts: List[Contact])
```

- For what?
 - name and contacts are immutable → once you create a Person, you cannot change their name or contacts
 - Less boilerplate
 - Access to automatic methods like equals, hashCode, toString, and copy
 -
-

Type Class (Traits)

back-to-top

- recall Trait in Java is a class where its methods are compulsory when instantiated
- a “contract” for behavior that you can give to any type, even those you didn’t write yourself

Imagine you have different kinds of vehicles: cars, bikes, boats. You want to “drive” them, but not all vehicles have a steering wheel or pedals. Instead of forcing every vehicle to inherit from a “Drivable” class, you create a “Drivable” contract. If a vehicle can be driven, you provide instructions for how to drive it.

Type class: The “Drivable” contract. **Type class instance:** The specific instructions for each vehicle. **Generic function:** A function that can “drive” any vehicle, as long as it has instructions.

```
// Define a type class called Drivable for any type A  
trait Drivable[A] = {  
  // Specifies that any type A with a Drivable instance MUST HAVE the drive method  
  def drive(a: A): String  
}
```

```
// Type Class instances  
// These are case classes representing different vehicle types  
case class Car(model: String)  
case class Bike(brand: String)  
case class Boat(name: String)
```

```
////////////////////////////////////  
// You only need a case class when you want to create a new type.  
// For built-in types, you can directly create type class instances.  
////////////////////////////////////
```

```
// Drivable instance for Car (Preferred for Scala 3)  
given Drivable[Car] with {  
  def drive (c:Car): String = s"Driving car: ${c.model}"  
}
```

```
// Drivable instance for Car (Older but still works)  
given carDrivable: Drivable[Car] = new Drivable[Car] {  
  def drive(c: Car): String = s"Driving car: ${c.model}"  
}  
// c is the name  
// Car is the type class instance
```

- given → the type class instance keyword

Class Example

```
trait JS[A] {  
  def toJS(v:A):String  
}
```

```
// Type class instance for Int  
given JS[Int] with {  
  def toJS(v: Int): String = v.toString  
}
```

```
// Type class instance for String  
given JS[String] with {  
  def toJS(v: String): String = s"'${v}'"  
}
```

```
given toJSList[A](using jsa:JS[A]):JS[List[A]] = new JS[List[A]] {  
  def toJS(as:List[A]):String = {  
    val j = as.map(a=>jsa.toJS(a)).mkString(",")  
    s"[$j]"  
  }  
}
```

- toJSList is used to define a type class instance for List[A]
- val j...mkString(" ", " ") → For each element a in the list, convert it to

-
- JS using
- enum variable type is private, whereas type class can still change (recall enum)
-

Higher Kinded Type & Functor Type Class

back-to-top

```
// General 'Formula'
trait Functor[F[_]] {
  def map[A,B](ta:F[A])(f:A => B):F[B]
}
```

- [F[_]] means the trait Functor is taking in a type F that has type generic
- [A,B] → A is the type of the elements inside the container F.
- B is the type you get after applying the function f to each element.
- (ta:F[A]) → Argument: Container is a F of A which can be a list of Int for e.g. -(f:A => B) → The Function that transfer A to B -F[B] → the output is a container of B

Why for what?

- Lets you transform data inside containers in a safe, consistent way
- Keeps the structure, if you map over a list, you still get a list

Without Functor

```
def do10xList(list: List[Int]): List[Int] = list.map(x => x * 10)
def do10xListOption(opt: Option[Int]): Option[Int] = opt.map(x => x * 10)
def do10xListTry(t: Try[Int]): Try[Int] = t.map(x => x * 10)
```

With Functor

```
// General
trait Functor[F[_]] {
  def map[A,B](ta:F[A])(f:A => B):F[B]
}

// Instantiating it --> example of using a List
def do10xListGeneric[F[_]](
  container: F[Int]
)(using functor: Functor[F]): F[Int] = {
  functor.map(container)(x => x * 10)
}

// Using the functor
```

```
println(do10xListGeneric(List(1, 2, 3)))
println (do10xListGeneric(Option(5)))
println(do10xListGeneric(Try(7)))
```

// Now we can use the do10xListGeneric method with Int, Try, Option

Kinds vs Types

back-to-top

- **Values** like 42, "hello" have **Types** Int, String respectively
- **Types** themselves have a "type of types" \rightarrow and those are called **KINDS**
- **Kinds** describes what shape of type arguments a type constructor accepts
- Kinds are to types what types are to values
- A type constructor like List has kind $_ \rightarrow _$
- List[] by itself is not a type \rightarrow takes 1 type argument (of kind $_$) *and produces a new type (also of kind $_$)*

```
val list = List(1,2,3)
```

- list.head has value: 1, Type: Int, Kind: *
- list has value List(1,2,3), Type: List(Int), Kind : *
- List(the type constructor) has Kind: $_ \rightarrow _$

Functor Laws

back-to-top

1. Identity Law

Mapping with the identity function ($\text{id}(x) = x$) should not change the functor's contents.

```
List(1,2,3).map(x => x) == List(1,2,3)
```

2. Composition Law

Recall function composition

```
fa.map(f).map(g) == fa.map(g compose f)
```

```
val f: Int => Double = _ * 2.0
val g: Double => String = _.toString
```

```
List(1,2,3).map(f).map(g)
// = List("2.0", "4.0", "6.0")
```

```
List(1,2,3).map(g compose f)
// = List("2.0", "4.0", "6.0")
```

Why the need?

A 'bad' functor could cheat:

- ignore the function you give to map
 - apply the function multiple times/ in the wrong order
 - randomly shuffle or duplicate elements
-

Foldable Type Class

back-to-top recall fold

Just a trait that defines foldLeft and/or foldRight methods → lets you write code that can fold any foldable type, not just lists

Why for what?

Lets you write functions that work for any foldable type, not just List or Option that Scala has inbuilt foldLeft and foldRight for.

For example you may want to fold other things like trees, with foldable type class you can define how folding works for your tree type where inside it you can use generic code like foldLeft

```
// Define a binary tree
// Goal: Reduce all values in binary tree into a single result
sealed trait Tree[+A]
case class Leaf[A](value: A) extends Tree[A]
case class Branch[A](left: Tree[A], right: Tree[A]) extends Tree[A]

// Implement fold for Tree
def foldTree[A, B](tree: Tree[A], acc: B)(f: (B, A) => B): B = tree match {
  case Leaf(value)      => f(acc, value)
  case Branch(l, r)     =>
    val leftFolded = foldTree(l, acc)(f)
    foldTree(r, leftFolded)(f)
}

// Example usage: sum all values in a tree
val tree: Tree[Int] = Branch(Leaf(1), Branch(Leaf(2), Leaf(3), Leaf(4)))
val sum = foldTree(tree, 0)(_ + _)
println(sum)
```

- foldTree recursively visits every node and combines values using the function f
 - You can use it to sum, multiply, or process any tree of values
-

Option

back-to-top

- The Option type in Scala is used to represent a value that may or may not exist → safer alternative to null
- Option[A] is a container that represents “maybe a value” → either Some(a:A) when a value exists, or None when it doesn’t.

It is Scala’s safe alternative to null and expresses optionality in the type system.

```
val s: Option[String] = Some("hello")
val n: Option[String] = None
val maybe = Option(null)    // => None
val also = Option("world")  // => Some("world")
```

Uses of Option Replacing null

```
// before:
val name: String = System.getenv("NAME")
val display = if (name!=null) name else "Guest"

// Option
val nameOpt: Option[String] = Option(System.getenv("NAME"))
val display = nameOpt.getOrElse("Guest")
```

Error Handling with Option Type

back-to-top A better alternative to try-catch exception

```
enum Option[+A] {
  case None
  case Some(v:A)
}
```

Some is a case class that represents the presence of a value in an Option.

Some(value) is the alternative to None in Scala’s Option type

- Some(value) means there is a value
- None means there is no value

Both together are the 2 possible cases for an Option

```
def eval(e:MathExp):Option[Int] = e match {
case MathExp.Plus(e1, e2) => eval(e1) match {
  case None => None
  case Some(v1) => eval(e2) match {
```

```

        case None => None
        case Some(v2) => Some(v1 + v2)
    }
}
// case for catching division by 0
// if u divide by 0 it just returns 'None' by checking the denominator
case MathExp.Div(e1, e2) => eval(e1) match {
    case None => None
    case Some(v1) => eval(e2) match {
        case None => None
        case Some(0) => None
        case Some(v2) => Some(v1 / v2)
    }
}
case MathExp.Const(i) => Some(i)
}

eval(Div(Const(1), Minus(Const(2), Const(2))))
// Output: None

```

Error Handling with Either Type

back-to-top

- Handle Errors with Option Type has one remaining issue
 - i.e. there is no info with the error in None → if got multiple cases to check multiple errors, we don't if the error is us trying to divide by 0 or sth else

```

def eval(e: MathExp): Either[ErrMsg, Int] = e match {
    case MathExp.Plus(e1, e2) =>
        eval(e1) match {
            case Left(m) => Left(m)
            case Right(v1) => eval(e2) match {
                case Left(m) => Left(m)
                case Right(v2) => Right(v1 + v2)
            }
        }
}
// cases omitted for Minus and Mult
case MathExp.Div(e1, e2) =>
    eval(e1) match {
        case Left(m) => Left(m)
        case Right(v1) => eval(e2) match {
            case Left(m) => Left(m)
            case Right(0) => Left(s"div by zero caused by ${e.toString}")
        }
    }

```

```

    case Right(v2) => Right(v1 / v2)
  }
}
case MathExp.Const(i) => Right(i)
}
eval(Div(Const(1), Minus(Const(2), Const(2))))
// yields Left(div by zero caused by Div(Const(1),Minus(Const(2),Const(2))))

```

Derived Type Class

back-to-top

- A trait that extends trait
- for what? Dont need nearly identical boilerplate for every case class

```

trait Rectangle[A] {

}

trait Square[A] extends Eq[A] {

}

```

- Every Square is also a Rectangle, but not every Rectangle is a Square

Example of Derived Type Class

```

case class Person(name: String, age: Int)

given Show[Person] with
  def show(p: Person): String =
    s"Person(name=${p.name}, age=${p.age})"

// Implicit Instantiation --> "Whenever you need a Show[Person], use it like this"

val p = Person("Ada", 30)
println(summon[Show[Person]].show(p))
// Output: Person(name=Ada, age=30)

```

Now you add a field to the model: Person has country and you did not change the Show

```

case class Person(name:String, age:Int, country: String)

val p2 = Person("Ada", 30, "UK")
println(summon[Show[Person]].show(p2))

```

Output: Person(name=Ada, age=30) The country is missing from the output!

Manual Solution : Edit the Show instance to include the new field

```
given Show[Person] with
  def show(p: Person): String =
    s"Person(name=${p.name}, age=${p.age}, country=${p.country})"
```

Now imagine you have 500 new field to add.

(Continued) Derived show implementation

[back-to-top](#)

Using the derives keyword → indicating it is a derived type class

```
case class Person(name: String, age: Int) derives Show
val p = Person("Ada", 30)
println(summon[Show[Person]].show(p))
// Person(Ada, 30)
```

Now if you need to add a field

```
case class Person(name: String, age: Int, country: String) derives Show
val p = Person("Ada", 30, "UK")
println(summon[Show[Person]].show(p))
// Person(Ada, 30, UK)
```

- tells Scala to automatically generate (derive) an implicit Show[Person] instance for you.

Applicative Functor

[back-to-top](#)

- Sits between Functor and Monad
- Allows us to apply functions that take multiple arguments to values

```
// General 'formula'
trait Applicative[F[_]] extends Functor[F] {
  def pure[A](a: A): F[A]
  def ap[A, B](ff: F[A => B])(fa: F[A]): F[B]
  def map[A, B](fa: F[A])(f: A => B): F[B] = ap(pure(f))(fa)
}
```

1. pure: put a plain value into the context
2. map2/ap: apply a function to values that are inside contexts

Think of context as a box around a value

- Option[A] = maybe-a-value box
- List[A] = many-values box

-
- Future[A] = value-arrives-later box

```
def add (a: Int, b: Int): Int = a + b
```

Applicative Functor allows you to use the same add but on numbers that are inside context without opening the context

Difference with Functor Functor = you have one box F[A]. You can run a 1-arg function on what's inside that one box.

Applicative = you have several boxes F[A], F[B], ... You can run a normal multi-arg function on the contents of all those boxes at once (as long as they don't depend on each other).

Example To list all outfits, pair every shirt with every pant

```
def map2[A, B, C](fa: List[A], fb: List[B])(f: (A, B) => C): List[C] =  
  for { a <- fa; b <- fb } yield f(a, b)
```

```
val shirts = List("Blue", "White")  
val pants  = List("Jeans", "Khakis")
```

```
val outfits = map2(shirts, pants)((s, p) => s"$s + $p")  
// List("Blue + Jeans", "Blue + Khakis", "White + Jeans", "White + Khakis")
```

Explanation: map2: take two wrapped values (lists) and a pure function → combine all values inside using that function.

1. Parameter #1: the containers

```
(fa: List[A], fb: List[B])
```

fa is a list of shirts fb is a list of pants

2. Parameter #2: the combining function

```
(f: (A, B) => C)
```

Takes one A and one B and produces a C (e.g. a full outfit).

```
for { a <- fa; b <- fb } yield f(a, b)
```

// Scala automatically rewrites as:

```
fa.flatMap(a => fb.map(b => f(a, b)))
```

Part	What it does
a <- fa flatMap	Pull out each element a from the first list fa ("outer loop"). Handles iterating the outer list and <i>flattening</i> the nested lists produced later.
b <- fb map yield f(a,b)	For each a, iterate through all elements b of the second list (fb). Transforms each b into f(a, b) and returns a List[C]. Collects each computed value into the resulting list.

Execution:

1. s = "Blue" → map over pants: "Blue + Jeans", "Blue + Khakis"
2. s = "White" → map over pants: "White + Jeans", "White + Khakis"

Then flatMap joins them into:

```
List("Blue + Jeans", "Blue + Khakis", "White + Jeans", "White + Khakis")
```

Applicative Laws

back-to-top

Identity

```
ap(pure(x => x))(v) == v
```

If you lift the *identity function* (x => x) into the Applicative and apply it to any wrapped value v, nothing changes

Homomorphism

Interchange

Composition

Monad

Monad = Applicative + the power to let each next step depend on the previous result (via flatMap / bind).

- Functor: you can transform the thing inside one box (map).

- Applicative: you can use a normal multi-arg function on several independent boxes (map2, mapN).
- Monad: you can decide the next box based on the previous box's value (flatMap / bind).

In other words: later steps may depend on earlier results.

Think: "run step 1; see its result; based on that, choose step 2."

// General 'Formula'

```
trait Monad[F[_]] /* extends Applicative[F] */ {
  def pure[A](a: A): F[A]
  def flatMap[A,B](fa: F[A])(f: A => F[B]): F[B] // aka bind
  // map & ap can be derived if you have flatMap + pure
}
```

Example with Option

```
def parseInt(s: String): Option[Int] =
  s.toIntOption

def safeDiv(a: Int, b: Int): Option[Int] =
  if b == 0 then None else Some(a / b)

// Monad style (flatMap = "then" that can *depend* on the previous value)
val result: Option[Int] =
  parseInt("42").flatMap { n =>
    parseInt("7").flatMap { d =>
      safeDiv(n, d) // choice depends on d
    }
  }
// for-comprehension sugar:
### The for-comprehension {#the-for-comprehension}
val result2 =
  for {
    n <- parseInt("42")
    d <- parseInt("7")
    q <- safeDiv(n, d) // we can *branch* here
  } yield q
```

We use d to decide to continue safeDiv → that is the Monad dependency.

Applicative cannot express that branching.

Functor, Applicative and Monad

When do I use which?

-
- Functor for when you need to map over one container
 - Applicative when you need to combine several containers independently
 - Monad when there is a Step B that depends on Step A
-

Syntax Analysis (5A)

back-to-top

- A compiler turns source text into target code by moving through distinct stages
- Source Text \rightarrow [Lexing] \rightarrow [Parsing] \rightarrow [Semantic Analysis] \rightarrow [Optimization] \rightarrow [Code Generation]

Lexing

back-to-top

- **Input:** Source program in string (a list of characters)
- **Output:** a list of lexical tokens
- **Method:** Break things up into a sequence of tokens and ignore irrelevant things like whitespace and comments
- Fails when something can't be recognised as a lexical token

Grammar Notation

```
(JSON) J ::= i | 's' | [] | [IS] | {NS}
(Items) IS ::= J , IS | J
(Named Objects) NS ::= N, NS | N
(Named Object) N ::= 's' : J
```

- Left Hand Side \rightarrow Non-Terminals
- Right Hand Side \rightarrow Terminals (Tokens) and Non-Terminals (Grammar Variables)
- *i* denotes an integer
- 's' denotes a string

Example (Simple)

```
val x = 2
```

We put the above into a lexer and it would produce:

```
[val][identifier:x][=][number:42]
```

Example (JSON)

Lexer Token Data Type Enum All possible tokens the lexer can output

```
enum LToken {
    case IntTok(v:Int)
    case StrTok(v:String)
    case SQuote
    case LBracket; case RBracket
    case LBrace; case RBrace
    case Colon; case Comma
    case WhiteSpace
}

{'k1':1, 'k2':[]}
```

We put the above into a lexer and it would produce:

```
List(LBRace, SQuote, StrTok("k1"), SQuote, Colon, IntTok(1), Comma, SQuote,
     StrTok("k2"), SQuote, Colon, LBracket, RBracket, RBrace)
```

Notice this illustrates how characters are grouped into tokens—e.g., all digits 1 became `IntTok(1)`; quoted `k1/k2` became `StrTok("k1")`, `StrTok("k2")`, with surrounding quotes as `SQuote`.

The lexer does not understand the structure of the code, it doesn't know anything, it just groups characters into meaningful chunks for the parser to make sense of it.

Parsing

- **Input:** A list of lexical tokens
- **Output:** A parse tree
- **Method:**
- Fails when the input cannot be parsed by grammar rule

Example


$$1 + 2 * 3$$

↓ Lexing ↓

[NUMBER:1] [PLUS:+] [NUMBER:2] [STAR:*] [NUMBER:3]

↓ Parsing ↓ Takes the tokens and builds a tree that represents the structure (syntax) of the expression, according to grammar rules

$$\begin{array}{c} (+) \\ / \quad \backslash \end{array}$$



This is called an Abstract Syntax Tree (AST).

The root is + The left child is 1 The right child is *, which has children 2 and 3

Continued from Lexer Example (JSON)

JSON Enum for Parser

```
enum Json {
  case IntLit(v: Int)
  case StrLit(v: String)
  case JsonList(vs: List[Json])
  case JsonObject(flds: Map[String, Json])
}
```

After passing the lexer output into the parser, the parser will output the following:

```
// Initial pre-lexer input
{'k1':1, 'k2':[]}
```

```
val expected = Some(JsonObject(
  Map(
    "k1" -> IntLit(1),
    "k2" -> JsonList(Nil)
  )
))
```

`Some(...)` → the parser succeeded (it returns `Option[Json]`).

If parsing failed, you'd get `None`.

`JsonObject(Map(...))` → the root AST node is an object with fields stored in a Scala `Map[String, Json]`.

`"k1" -> IntLit(1)` → field `k1` has an integer literal value 1.

`"k2" -> JsonList(Nil)` → field `k2` has a list value that is empty (`Nil` means empty list), i.e. `[]`.

Deep Dive and How it Works

A **dispatcher** for the parser decides which grammar rule to use by peeking at the first token (the 'lookahead')

```
def parse(toks:List[LToken]):Option[Json] = toks match {
  case Nil => // Done? what to return?
  case (t::ts) if t is digit => {
    val i = parse_an_int(toks); Some(IntLit(i)) }
  case (t::ts) if t is '\'' => {
    val s = parse_a_str(toks); Some(StrLit(s)) }
  case (t::ts) if t is '[' => {
    val l = parse_a_list(toks); Some(JsonList(l)) }
  case (t::ts) => {
    val m = parse_a_map(toks); Some(JsonObject(m)) }
}
```

The Parser receives the following output from lexer:

LBrace, SQuote, StrTok("k1"), SQuote, Colon, IntTok(1),
Comma, SQuote, StrTok("k2"), SQuote, Colon, LBracket, RBracket, RBrace

Then it looks at the first token LBrace → it falls into the object/map branch → use parse_a_map

In other words, the parser knows that "this is a JSON object starting now"

1. Dispatch: LBrace tells the parser to call the object routine (e.g., parse_a_map).
2. Consume & discard: the parser consumes the LBrace token (moves the cursor forward). The brace itself is not kept in the AST.
3. Parse contents: inside, it parses one or more "key" : value pairs, separated by commas.
4. Close: it expects and consumes the matching RBrace.
5. Build AST: it returns a JsonObject(Map[String, Json]) built from those pairs.

```
val m = parse_a_map(toks)
Some(JsonObject(m))
```

FIRST TOKEN PARSED

- Parse first pair key "k1"

Expect 's': consume SQuote, StrTok("k1"), SQuote → key = "k1".

- Parse colon

Consume Colon.

...

- Close object

Lookahead: RBrace → consume it; object ends

Top Down Parsing

back-to-top

Big Picture:

- Solves grammar ambiguity and left recursion

Grammar Ambiguity → what does the 2 E mean?

$E ::= E + E \mid E * E \mid i$

E, T, F are Non-terminal **expression** (will **expand** further)
+, -, id, num etc are terminal (literal token from the lexer)

1. Flatten

$E ::= E + E$

$E ::= E * E$

$E ::= i$

2. Resolve Ambiguity by introducing more non-terminals

$E ::= T + E$

$E ::= T$

$T ::= T * F$

$T ::= F$

$F ::= i$

Left Recursion

...

$T ::= T * F$ //will keep looping

...

1. Resolve left recursion

Formula:

$A ::= A \alpha \mid \beta$

turns into

$A ::= \beta A'$

$A' ::= \alpha A' \mid \epsilon$

$A \leftrightarrow T$
 $\alpha \leftrightarrow * F$ (everything after the leading T in the left-recursive alt)
 $\beta \leftrightarrow F$ (the alternative that doesn't start with T)

...
 $T ::= F T'$
 $T' ::= * F T' \mid \epsilon$
 ...

What about the rest?

After resolving the left recursion, you have this:

$E ::= T + E$
 $E ::= T$
 $T ::= F T'$
 $T' ::= * F T' \mid \epsilon$
 $T ::= F$
 $F ::= i$

1. Remove the extra $T ::= F$

$E ::= T + E$
 $E ::= T$
 $T ::= F T'$
 $T' ::= * F T' \mid \epsilon$
 $F ::= i$

2. Resolve FIRST-FIRST conflict --> E is $T + E$ or E ?

Formula:

$A ::= \alpha \beta_1 \mid \alpha \beta_2 \ (E ::= T + E \mid T)$

turns into

$A ::= \alpha A'$
 $A' ::= \beta_1 \mid \beta_2$

$A \leftrightarrow E$
 $\alpha \leftrightarrow T$
 $\beta_1 \leftrightarrow +E$
 $\beta_2 \leftrightarrow \epsilon$

Final Grammar:

$E ::= T E'$
 $E' ::= + E E' \mid \epsilon$

```
T ::= F T'
T' ::= * F T' | ε
F ::= i
```

First-Follow Problem

Initial Grammar

```
S ::= A a
A ::= a | ε
```

```
A ::= α | ε
P ::= γ1 A γ2
// with FIRST(α) ∩ FOLLOW(A) ≠ ∅ (conflict)
```

turns into

```
P ::= γ1 α γ2 | γ1 γ2
```

```
P ↔ S
A ↔ A
a ↔ a
γ1 ↔ ε (nothing before A)
γ2 ↔ a (the terminal after A)
```

Final Output

```
S ::= a a | a
```

Naive Top Down Parsing

Think “match the next symbol, recurse.” If next grammar symbol is a terminal, check the next token; if it’s a nonterminal, try each alternative until one succeeds; accept ϵ (empty) only when allowed.

Predictive Top Down Parsing (better alternative)

- Builds a parse from the start symbol downward, using 1 lookahead token to predict exactly which production to apply—no backtracking.
-

Parsec

back-to-top

- Parser as a Monad: sequencing without boilerplate
 - Wraps the function and give it `map` and `flatMap`, so you can chain steps in order :
1. Parse this
 2. Then parse that
 3. Combine results

Setting Up

```
// Grammar Rules
(1) T ::= xx //T can be 2 x tokens in a row
(2) T ::= yx //T can be a Y token followed by a X token

// These represents the possible tokens your parser can see
// Data Structure
enum LToken{
  case XTok
  case YTok
}

// Parse result types
enum T {
  case XX
  case YX
}
```

Naive Implementation → we will need one function for every grammar rule (or pattern) :

- One function to parse XX (two XTok in a row)
- One function to parse YX (YTok followed by XTok)

Naive Implementation

```
enum Result[A] {
  case Failed(msg:String)
  case Ok(v:A)
}

def item(toks:List[LToken]):Result[(LToken, List[Token])] = toks match {
  case Nil => Failed("item() is called with an empty input")
  case (t::ts) => Ok((t, ts))
}
```

```
def sat(toks: List[LToken])(p: LToken => Boolean): Result[(LToken, List[LToken])] = toks match {
  case Nil => Failed("sat() is called with an empty input")
  case (t::ts) if p(t) => Ok((t, ts))
  case (t::ts) => Failed("sat() is called with an input that does not satisfy the input predicate.")
}
```

- Sat is called twice
 - A lot of boilerplate codes for parseXX and parseYX
-

Monad Option (Better)

refer to parsec.scala for output

0. Monad Boilerplate

```
case class Parser[T, A](p: List[T] => Result[(A, List[T])]) {
  def map[B](f: A => B): Parser[T, B] = Parser { toks =>

    // Consume
    p(toks) match {
      case Failed(err) => Failed(err)
      // f(a) turns A into B
      case Ok((a, toks1)) => Ok((f(a), toks1))
    }
  }

  def flatMap[B](f: A => Parser[T, B]): Parser[T, B] = Parser { toks =>
    p(toks) match {
      case Failed(err) => Failed(err)
      case Ok((a, toks1)) => f(a).p(toks1)
    }
  }
}
```

1. Define basic token parsers

```
def xTok: Parser[LToken, LToken] =
  Parser {
    case XTok :: rest => Ok((XTok, rest))
    case _ => Failed("Expected XTok")
  }

def yTok: Parser[LToken, LToken] =
  Parser {
    case YTok :: rest => Ok((YTok, rest))
  }
```

```

    case _ => Failed("Expected YTok")
  }

```

2. Compose for xx and yx using flatmap/map

This part “brute forces” functions that matches specific sequence of tokens, i.e. if the tokens match the expected patter, the parser returns the corresponding result from your enum, if not it will just fail

```

// T ::= xx
val parseXX: Parser[LTOKEN, T] =
  for {
    _ <- xTok
    _ <- xTok
  } yield T.XX

```

```

// T ::= yx
val parseYX: Parser[LTOKEN, T] =
  for {
    _ <- yTok
    _ <- xTok
  } yield T.YX

```

3. Combine all alternatives (not xx and yx)

```

def or[A](p1: Parser[LTOKEN, A], p2: Parser[LTOKEN, A]): Parser[LTOKEN, A] =
  Parser { toks =>
    p1.p(toks) match {
      case Failed(_) => p2.p(toks)
      case ok         => ok
    }
  }

```

```

val parseT: Parser[LTOKEN, T] = or(parseXX, parseYX)

```

Dealing with Left Recursion

Solution : Combinators from Parsec Library

```

def optional[T, A](pa: Parser[T, A]): Parser[T, Either[Unit, A]] = {
  val p1: Parser[T, Either[Unit, A]] = for (a <- pa) yield (Right(a))
  val p2: Parser[T, Either[Unit, A]] = Parser(toks => Ok((Left(()), toks)))
  choice(p1)(p2)
}

```

Math Exp Example

back-to-top

```
//Grammar
E ::= T + E
E ::= T
T ::= T * F
T ::= F
F ::= i
```

The Parser

```
def parseExp: Parser[LToken, Exp] = choice(parsePlusExp)(parseTermExp)
```

```
def parsePlusExp: Parser[LToken, Exp] = for {
  t <- parseTerm
  plus <- parsePlusTok
  e <- parseExp
} yield PlusExp(t, e)
```

The problem: $T ::= T * F$ the parser looks at the rule T is $T * F$, so it starts trying to parse a T . But the first thing on the right-hand side is another T , so it repeats the same rule immediately— T is $T * F$ —and tries to parse a T again. That loop never consumes a token, so it never gets past the first symbol.

The solution: Edit the Grammar

```
E ::= T + E
E ::= T
////////////////////////////////////
T ::= T * F // left recursive!! --> No tokens are ever matched and the parser loops fo
// le-grammar
T ::= FT' // parses the first factor
T' ::= *FT' // handles each additional * factor
T' ::= epsilon // lets you stop when there are no more multiplications
////////////////////////////////////
T ::= F
F ::= i
```

```
// T ::= FT'
def parseTermLE: Parser[LToken, TermLE] = for {
  f <- parseFactor
  tp <- parseTermP
} yield TermLE(f, tp)
```

```
def parseTermP: Parser[LToken, TermLEP] = for {
```

```

omt <- optional(parseMultTermP)
} yield { omt match {
  case Left(_) => Eps
  case Right(t) => t
}}
def parseMultTermP:Parser[LToken, TermLEP] = for {
  asterix <- parseAsterixTok
  f <- parseFactor
  tp <- parseTermP
} yield MultTermLEP(f, tp)

```

Another Example

```

// Grammar
// X ::= XXa | Y
// Y ::= Yb | c

```

```

// Step 1 : Flatten
// X ::= XXa
// X ::= Y
// Y ::= Yb
// Y ::= c

```

```

// Step 2 : Eliminate Left Recursion
// X ::= XXa | Y
// Y ::= cY'
// Y' ::= bY' | ε

```

```

// Step 3 : Eliminate left recursion for X
// X ::= YX'
// X' ::= XaX'
// X' ::= ε
// Y ::= cY'
// Y' ::= bY'
// Y' ::= ε

```

```

// !Left recursion is only when the leftmost symbol is the same as the non-terminal be
// i.e. X ::= Xa... is left recursive because it starts with X
// but X ::= YX is not left recursive because it starts with Y although it ends with X

```
