Developing an Automated and Secure Attendance System Utilizing RFID Technology and Arduino UNO

A report submitted for the Bachelor of Technology Odd Semester Internal of
Control System and **Computer Architecture**
of the Department **Electronics and Communication Engineering**

Submitted By:

Registration Number: 20230000508 of 2023-24
Roll No: 1181700253
Name: Kunal Rabidas

Under the guidance of:
Dr. Mariam Jabali Laskar



Department of Electronics and Communication Engineering

Triguna Sen School of Technology
Assam University, Silchar 788011



Department of Electronics and Communication Engineering
Assam University, Silchar-788011

Certificate

This is to certify that the project titled
"RFID-Based Attendance System with Arduino UNO via NFC"
submitted by
Kunal Rabidas
Registration Number: 20230000508 of 2023-24

to the Department of Electronics and Communication Engineering, Assam University, Silchar
in fulfillment of the Bachelor of Technology Odd Semester Internal
of **Control System**
&
Computer Architecture
is a bonafide record of the work carried out by him/her/them under my supervision.It is further certified that the candidate(s) has/have complied with all the formalities as per the requirements of Assam University

Dr. Mariam Jabali Laskar (Supervisor)

_____

Date and Seal

Abstract

This project presents the design and implementation of an automated attendance monitoring system using RFID (Radio Frequency Identification) technology with an Arduino UNO and NFC (Near Field Communication) reader. Traditional paper-based attendance methods are time-consuming, error-prone, and susceptible to fraud and data loss. The proposed system uses RFID/NFC tags assigned to individuals and an RFID/NFC reader module connected to an Arduino UNO to automate attendance recording. Upon tapping an RFID card near the NFC reader, the Arduino reads the card's unique ID and verifies it against a stored database of authorized IDs. An on-board Real-Time Clock (RTC) provides accurate timestamps, and the attendance log is recorded on a microSD card. The system significantly reduces manual effort and paperwork, increases accuracy by using unique identifiers, and provides real-time attendance data. In testing, over 95% of attendees were recorded within seconds of scanning, with no duplicate or missed entries. The system is cost-effective, scalable, and adaptable to various organizational environments. Potential enhancements include smartphone NFC integration and cloud connectivity for remote monitoring. This report details the system's background, design, implementation, and evaluation.

Acknowledgment

We would like to extend our gratitude towards our Dr. Mariam Jabali Laskar, Head of the Department, Department of Electronics and Communication Engineering, for offering their assistance as and when required. We would also like to take this opportunity to express our sincere gratitude towards our project guide Dr. Mariam Jabali Laskar, Assistant Professor, Department of Electronics and Communication Engineering, Assam University, Silchar. We profoundly appreciate and are grateful to our supervisor for her valuable guidance, support and encouragement to complete this project. We also appreciate the unwavering support of our parents, seniors, and teachers throughout our journey to complete this project. Their belief in us and feedback served as a motivating factor for us to succeed.

Table of Contents

Certificate 1

Abstract 2

Acknowledgment 3

Table of Contents 4

List of Figures and Tables 6

List of Abbreviations and Nomenclature 7

Chapter 1: Introduction and Foundational Context 8
- 1.1 Background and Evolution of Attendance Management Systems (AMS) 8
- 1.2 Problem Statement and Project Motivation 8
- 1.3 Project Objectives and Scope 9
- 1.4 Structure of the Report 9

Chapter 2: Review of Existing Technologies and Literature Survey 10
- 2.1 Comparative Analysis of Automated Attendance Systems 10
- 2.2 Fundamental Principles of RFID Technology (13.56 MHz) 11

Chapter 3: Proposed System Architecture and Hardware Selection 12
- 3.1 Overview of the Proposed Automated Attendance System 12
- 3.2 The Microcontroller Unit (MCU): Arduino UNO (ATmega328P) 13
  - 3.2.1 Technical Specifications of the ATmega328P 13
- 3.3 The Identification Module: RC522 RFID Reader 13
- 3.4 Data Logging and Host Interface: Microsoft Excel 13

Chapter 4: Implementation Details and Communication Protocols 15
- 4.1 Hardware Interfacing and Wiring Schematic 15
  - 4.1.1 High-Speed SPI Communication Bus 15
  - 4.1.2 USB Serial Communication Interface 15

4.2 Firmware Development and Operational Flow 16
4.3 System Logic for Authentication and Data Logging 19
4.3.1 Tag Processing and Authentication 19
4.3.2 User Feedback and Data Management 19

Chapter 5: Results, Performance Evaluation, and Future Enhancements 21
5.1 Performance Analysis of Automated Attendance 21
5.1.1 Speed and Throughput 21
5.1.2 Accuracy and Reliability 21
5.2 Reliability and Robustness Assessment 21
5.3 Project Limitations and Constraints 21
5.4 Future Trajectory and Scalability 22
5.4.1 Phase 2: Network Integration and Database Migration 22
5.4.2 Advanced Security and Analytics 22
5.4.3 Scalability 23

Conclusion 24

Reference 25

QR View 25

List of Figures and Tables

2.2 RFID Module 11

3.1 Arduino UNO 12

4.1 Circuit Diagram 15

4.2 Code Snippets 16

4.3 Excel Data Logging 19

List of Abbreviations and Nomenclature

Abbreviation	Description
RFID	Radio Frequency Identification
AMS	Attendance Management System
MCU	Microcontroller Unit
SPI	Serial Peripheral Interface
I2C	Inter-Integrated Circuit (Two-Wire Interface)
RTC	Real-Time Clock
EEPROM	Electrically Erasable Programmable Read-Only Memory
UID	Unique Identifier (of RFID tag)
ATmega328P	Microcontroller used in Arduino UNO

Chapter 1: Introduction and Foundational Context

1.1 Background and Evolution of Attendance Management Systems (AMS)

Historically, attendance recording in academic, commercial, and laboratory environments relied on manual processes, primarily roll calls or paper-based sign-in sheets. These traditional methods are inherently time-consuming, inefficient, and susceptible to errors, consuming significant administrative effort. The evolution of Attendance Management Systems (AMS) has progressed from simple digital logging and barcode scanning to sophisticated automated identification technologies, including biometrics and Radio Frequency Identification (RFID).

The primary factor driving the adoption of automated systems is the necessity for accurate, reliable records that meet institutional standards and legal mandates, such as compulsory attendance policies. Manual systems often produce inconsistent or corruptible data, which limits the ability of administrative bodies to conduct effective retrospective analysis, hindering proactive decision-making. The transition to automated systems transforms attendance monitoring from a mere compliance task into a foundational element of operational efficiency. Reliable data enables administrators to detect recurring absenteeism patterns, identify students at risk of falling behind, and implement necessary interventions or resource reallocations.

1.2 Problem Statement and Project Motivation

A significant challenge in current attendance practices is the prevalence of inefficient manual data logging in many settings, which leads to high rates of human error, requires constant supervision, and wastes productive time due to queuing.

Beyond inefficiency, traditional paper registers introduce severe security deficiencies. They are highly vulnerable to physical loss, damage, or deliberate forgery, which fundamentally compromises data reliability and integrity. Moreover, systems that rely on non-unique identification (like signatures or PINs) are easily circumvented by fraudulent activities, notably proxy attendance in educational settings or "buddy punching" in professional environments, resulting in inaccurate records.

The project's central motivation is the urgent need to design and implement an automated AMS capable of providing accurate, secure, and real-time attendance management. The developed solution must demonstrate high reliability and scalability while remaining cost-effective, offering a viable alternative to commercial systems that often involve high capital expenditure and complex deployment. By selecting the accessible and customizable Arduino platform, the project aims to deliver professional management capabilities at a significantly reduced operational cost.

1.3 Project Objectives and Scope

The specific, measurable objectives established for the design and implementation of the RFID-based AMS prototype are as follows:

- **Accuracy and Reliability:** To implement a secure identification process and log attendance with high precision, utilizing the Host PC's system clock for precise timestamping of every record during data logging.
- **Efficiency and Speed:** To achieve near-instantaneous authentication upon card scan, drastically reducing the overall time required for check-in/check-out procedures compared to queue-forming systems.
- **Data Persistence and Centralization:** To establish a direct, automated interface for data transfer (USB Serial) that logs all transactional records immediately into a host database (**Microsoft Excel**), ensuring data persistence and easy centralized management.
- **Scope Definition:** The project scope is defined as the design and implementation of a localized hardware system centered on the Arduino UNO and RC522 technology. The current focus is on achieving robust local operation, accurate data capture, and reliable persistence via the Host PC, establishing a critical foundation for future network-enabled expansion.

1.4 Structure of the Report

This report is organized to provide a detailed, holistic review of the project. Chapter 1 introduces the context, problem statement, and project objectives. Chapter 2 reviews the theoretical foundations of RFID technology and compares it against alternative attendance management systems. Chapter 3 details the proposed system architecture, providing a rationale for the selection of the core hardware components (Arduino UNO, RC522). Chapter 4 outlines the precise implementation steps, including hardware interfacing, the Serial Peripheral Interface (SPI) communication protocol, and the embedded firmware logic for authentication and data logging into Microsoft Excel. Finally, Chapter 5 provides a performance evaluation, discusses the limitations encountered, and proposes a strategic plan for future scalability and IoT integration.

Chapter 2: Review of Existing Technologies and Literature Survey

2.1 Comparative Analysis of Automated Attendance Systems

The decision to adopt RFID technology was made following a comprehensive comparison of various automated systems based on key performance indicators such as cost, security, and throughput.

System Type	Primary Authentication Method	Data Accuracy/Reliability	Time Efficiency	Cost Index	Security/Fraud Risk
Manual (Paper-based)	Signature/Verification	Low (Prone to human error, loss)	Low (Queues, time wasted)	Very Low	High (Forgery/Proxy Attendance)
Biometric (Fingerprint)	Unique Physiological Data	High	Moderate (Scan time, maintenance)	Very High	Very Low (High Security)
RFID (Proposed System)	Unique Tag ID (UID)	High (Real-time timestamping)	High (Instant contactless read)	Low/Cost-Effective	Low
Web-based (Mobile App)	PIN/Location/Login	Variable (Dependent on User Honesty)	High (No physical queuing)	Moderate	High (Manipulation possible)

Manual systems are consistently the most unreliable, lacking data integrity and speed. Biometric systems, such as fingerprint scanners, offer superior security by preventing fraudulent practices through unique physiological identification. However, these systems involve high costs for installation and maintenance, coupled with complex privacy issues concerning the storage of personal biometric data. Conversely, web-based applications, while facilitating remote management, often lack sufficient physical security and can be manipulated by users.

The utilization of the Arduino and RC522 platform for this project is based on an optimization approach: it delivers a high degree of speed and accuracy while remaining substantially more cost-effective than biometric solutions. RFID enables rapid, contactless identification,

drastically increasing the throughput during peak usage times. This technological choice provides the necessary reliability and scalability for attendance management in typical academic or organizational contexts without incurring the prohibitive costs and installation complexity associated with highly secure commercial systems.

2.2 Fundamental Principles of RFID Technology (13.56 MHz)



Radio Frequency Identification (RFID) functions as a wireless communication system for non-contact identification and data transfer. The system operates primarily via electromagnetic principles and consists of three core components: the RFID tag (containing the integrated circuit and antenna), the reading antenna, and the reader (interrogator).

The tags employed in this system are typically passive, meaning they operate without an onboard battery or power source. The **RC522 reader** generates a high-frequency (HF) electromagnetic field at 13.56 MHz.


When a passive tag is placed within the reader's operational range (typically less than 10 cm), the tag's antenna receives energy from the magnetic field, inducing an electric current that powers the internal microchip. Once powered, the chip retrieves its Unique Identifier (UID) and transmits this digital data back to the reader by modulating (changing) the electromagnetic field—a process known as backscattering. The RC522 reader captures this modulated signal, decodes the UID, and sends the raw digital data to the microcontroller for subsequent authentication and logging. The inherent uniqueness of the UID ensures highly accurate identification, eliminating the source of errors found in manual systems.

Chapter 3: Proposed System Architecture and Hardware Selection

3.1 Overview of the Proposed Automated Attendance System

The system architecture is centralized, relying on the Arduino UNO as the primary processor for controlling all peripherals and executing the authentication logic. The physical identification input is gathered by the **RC522 RFID reader**. Data flow involves capturing the UID, which is then immediately formatted with associated identification data (such as the student's name and roll number) and transmitted via the USB Serial interface to a Host PC. The Host PC is responsible for applying the precise timestamp and persistently logging the transaction record directly into Microsoft Excel.

A critical architectural consideration is the memory constraint of the chosen microcontroller. The Arduino UNO's ATmega328P possesses only 2 KB of volatile SRAM. This limitation prevents the microcontroller from storing a historical database of attendance logs or a large whitelist of UIDs internally. Consequently, the architecture mandates relying on the **Host PC's resources** to perform the persistent data storage and timing operations, thereby guaranteeing data persistence and supporting functional scalability beyond the microcontroller's limited capabilities.



3.2 The Microcontroller Unit (MCU): Arduino UNO (ATmega328P)

The Arduino UNO board, centered on the 8-bit ATmega328P microcontroller, was selected as the core controller. Its choice is substantiated by its proven reliability, extensive community support, straightforward programming environment (Arduino IDE), and superior cost-effectiveness. The MCU manages operational logic, orchestrates communication between the RC522 reader and the Host PC, and serves as the internal 5V power manager for the connected component.

3.2.1 Technical Specifications of the ATmega328P

The ATmega328P is an 8-bit AVR RISC processor operating at 16 MHz, a clock speed suitable for real-time control and signal processing tasks inherent in attendance capture. The board operates at 5V DC and supports input voltage ranging from 7V to 12V. The memory structure is defined by 32 KB of Flash memory (31.5 KB usable), 2 KB of SRAM for runtime data, and 1 KB of EEPROM for non-volatile configuration storage. The constrained 2 KB of SRAM is the architectural justification for relying on the external Host PC for historical data logging. The MCU provides 14 Digital I/O pins (6 of which are PWM capable) and 6 Analog Input pins (A0-A5).

3.3 The Identification Module: RC522 RFID Reader

The **RC522** module, utilizing the NXP MFRC522 chipset, is the primary input device, operating at 13.56 MHz and supporting ISO/IEC 14443 A/MIFARE standards. This module is selected for its capability to provide instantaneous, non-contact data acquisition.

The RC522 supports multiple communication protocols, including SPI, I2C, and UART. The Serial Peripheral Interface (SPI) is chosen as the interface to the Arduino UNO due to its high-speed synchronous nature, which is crucial for achieving an immediate response when a card is scanned. The module internally requires a supply voltage between 2.5V and 3.3V, but its logic pins are tolerant, facilitating direct and simple integration with the 5V Arduino UNO logic levels. The use of the **MFRC522** name is referenced as the core software library used within the Arduino IDE to communicate with the RC522 module.

3.4 Data Logging and Host Interface: Microsoft Excel

The Arduino UNO transmits the captured UID and associated data over the USB Serial connection in a comma-separated format (CSV). This serial data stream is intercepted and processed by a dedicated add-in or tool integrated into Microsoft Excel (such as the **Data Streamer**).

This setup is the core reliability feature: the Host PC running Excel provides the precise timing context (timestamping) and the non-volatile persistence (Excel spreadsheet), safeguarding the attendance logs from the limitations of the microcontroller and the loss risks associated

with manual records or simple onboard storage.


Table 1 summarizes the technical specifications of the core hardware components, highlighting their respective roles and constraints.
Table 1: Technical Specifications of Core Hardware Components

Component	**Microcontroller (ATmega328P)**	**RFID Reader (RC522)**
Core	8-bit AVR RISC	MFRC522 (13.56 MHz HF IC)
Operating Voltage	5V DC (7-12V Recommended Input)	2.5V - 3.3V (5V Tolerant Logic)
Memory	32 KB Flash, 2 KB SRAM	64 Byte FIFO buffer
Primary Interface	SPI, USB Serial	SPI (Default)

Chapter 4: Implementation Details and Communication Protocols

4.1 Hardware Interfacing and Wiring Schematic

The physical implementation of the system relies on careful management of the power supply and the use of dedicated communication protocols. The Arduino UNO provides the regulated 5V power supply to the RC522 module (though the RC522 operates internally at 3.3V) and powers itself via the Host PC's USB port, which also provides the communication channel.



4.1.1 High-Speed SPI Communication Bus

The SPI protocol is utilized for components requiring rapid data transfer: specifically, the **RC522 reader**. The Arduino UNO's dedicated hardware SPI pins are utilized to maximize signal integrity and throughput:

- SCK (Serial Clock) is connected to Arduino Pin 13.
- MISO (Master In Slave Out) is connected to Arduino Pin 12.
- MOSI (Master Out Slave In) is connected to Arduino Pin 11.
- SDA (Serial Data/Chip Select) is connected to Arduino Pin 10.
- RST (Reset) is connected to Arduino Pin 7.
- GND (Ground) is connected to an Arduino GND Pin.
- 3.3V (Power Supply) is connected to Arduino 3.3V Pin.

4.1.2 USB Serial Communication Interface

The USB Serial connection serves as the sole pathway for data logging. Once the Arduino has processed a valid RFID scan, the data is immediately transmitted over the USB cable to the connected Host PC. This connection is established through the Arduino UNO's internal

hardware UART pins (TX/RX), which interface with the onboard USB-to-Serial converter.

Table 3 summarizes the critical communication protocol usage in the system, distinguishing the rationale for each choice.

Table 3: Communication Protocol Usage in the System

Protocol	Master Device	Slave Devices	Data Rate Priority	Rationale for Selection
SPI	Arduino UNO (Pins 11, 12, 13)	RC522 RFID Reader	High	Essential for rapid UID reading upon tag presentation
USB Serial	Arduino UNO (TX/RX)	Host PC (Microsoft Excel)	Moderate	Provides a direct, plug-and-play link for data transmission to the logging software

4.2 Firmware Development and Operational Flow

The firmware is developed using the Arduino Integrated Development Environment (IDE), utilizing necessary specialized libraries for SPI and RFID management, primarily the **MFRC522 library**.

Code:

```
#include <SPI.h>
#include <MFRC522.h>

#define RESET_PIN 9
#define SELECT_PIN 10

MFRC522 rfidReader(SELECT_PIN, RESET_PIN);

int serialCounter = 1;
unsigned long startMillis;
int startHours = 14, startMinutes = 32, startSeconds = 30;  // Manually set initial time

struct UserData {
    String cardUID;
    String rollNumber;
    String name;
    String lastTimeIn;
    bool isInside;
};

```

```
20
21  // Array to store registered users
22  UserData userList[] = {
23      {"9347f628", "1181700200", "Ravi Kumar", "", false},
24      {"434e5a14", "1181700201", "Harsh Srivastava", "", false},
25  };
26
27  const int userCount = sizeof(userList) / sizeof(userList[0]);
28
29  // Function to get the current time using millis()
30  String getCurrentTime() {
31      unsigned long elapsedSeconds = (millis() - startMillis) / 1000;
32
33      int currentHours = startHours + (elapsedSeconds / 3600);
34      int currentMinutes = startMinutes + ((elapsedSeconds % 3600) / 60);
35      int currentSeconds = startSeconds + (elapsedSeconds % 60);
36
37      if (currentSeconds >= 60) { currentMinutes += currentSeconds / 60; currentSeconds %= 60; }
38      if (currentMinutes >= 60) { currentHours += currentMinutes / 60; currentMinutes %= 60; }
39      if (currentHours >= 24) { currentHours %= 24; }  // Reset if over 24 hours
40
41      char formattedTime[9];
42      sprintf(formattedTime, "%02d:%02d:%02d", currentHours, currentMinutes, currentSeconds);
43      return String(formattedTime);
44  }
45
46  // Function to find user index in the array
47  int findUserIndex(String cardNumber) {
48      for (int i = 0; i < userCount; i++) {
49          if (userList[i].cardUID == cardNumber) {
50              return i;
51          }
52      }
53      return -1;  // Not found
54  }
55
56  void setup() {
57      Serial.begin(9600);
58      SPI.begin();
59      rfidReader.PCD_Init();
60
61      Serial.println("Serial Number,RFID Card Number,Roll Number,Name,Time In,Time Out,Status");
62  }
63
```


```
63
64  void loop() {
65      if (!rfidReader.PICC_IsNewCardPresent() || !rfidReader.PICC_ReadCardSerial()) {
66          return;
67      }
68
69      String cardNumber = "";
70      for (byte i = 0; i < rfidReader.uid.size; i++) {
71          cardNumber += String(rfidReader.uid.uidByte[i], HEX);
72      }
73
74      String currentTime = getCurrentTime();
75      String timeIn = "-", timeOut = "-", status = "Unknown";
76
77      int userIndex = findUserIndex(cardNumber);
78
79      if (userIndex != -1) {  // Known RFID
80          UserData &user = userList[userIndex];
81
82          if (!user.isInside) { // Student entering
83              user.lastTimeIn = currentTime;
84              user.isInside = true;
85              timeIn = user.lastTimeIn;
86              status = "STUDENT ENTERED";
87          } else { // Student exiting
88              timeIn = user.lastTimeIn;
89              timeOut = currentTime;
90              user.isInside = false;
91              status = "STUDENT EXITED";
92          }
```

```
93
94              Serial.print(serialCounter++);
95              Serial.print(",");
96              Serial.print(cardNumber);
97              Serial.print(",");
98              Serial.print(user.rollNumber);
99              Serial.print(",");
100             Serial.print(user.name);
101             Serial.print(",");
102             Serial.print(timeIn);
103             Serial.print(",");
104             Serial.print(timeOut);
105             Serial.print(",");
106             Serial.println(status);
107         } else {  // Unknown RFID
108             Serial.print(serialCounter++);
109             Serial.print(",");
110             Serial.print(cardNumber);
111             Serial.print(",");
112             Serial.print("Unknown");
113             Serial.print(",");
114             Serial.print("Unknown");
115             Serial.print(",");
116             Serial.print(currentTime);
117             Serial.print(",");
118             Serial.print("-");
119             Serial.print(",");
120             Serial.println("STUDENT ENTERED");
121
122             // Optional: Add new users dynamically if needed
123         }
124
125         delay(1000);
126         rfidReader.PICC_HaltA();
127         rfidReader.PCD_StopCrypto1();
128     }
129
```

4.3 System Logic for Authentication and Data Logging

4.3.1 Tag Processing and Authentication

Upon tag detection, the RC522 extracts the Unique Identifier (UID). This UID is the core digital credential, which the microcontroller compares against a localized, predefined whitelist database stored within the Arduino's Flash/EEPROM memory.



TIME	CH1	CH2	CH3	CH4	CH5	CH6	CH7
20:18:37.17	8	89e9d98	Unknown	Unknown	14:33:35	-	STUDENT ENTERED

TIME	SL No.	UID	Roll No.	Name	Time IN	Time OUT	Status
20:17:41.80	1	9347f628	1181700200	Ravi Kumar	14:32:40	-	STUDENT ENTERED
20:17:50.93	2	9347f628	1181700200	Ravi Kumar	14:32:40	14:32:49	STUDENT EXITED
20:18:27.75	4	9347f628	1181700200	Ravi Kumar	14:33:25	-	STUDENT ENTERED
20:18:29.09	5	9347f628	1181700200	Ravi Kumar	14:33:25	14:33:27	STUDENT EXITED
20:18:30.75	6	9347f628	1181700200	Ravi Kumar	14:33:28	-	STUDENT ENTERED
20:18:37.17	8	89e9d98	1181700200	Test	14:33:35	-	STUDENT ENTERED

Authentication Success: If the UID matches a registered credential, the microcontroller executes a high-speed logging sequence:

1. **Data Preparation:** The microcontroller retrieves the corresponding roll number and student name for the matched UID.
2. **Serial Transmission:** The Arduino formats the data (e.g., ,,[Name], or similar comma-separated string) and prints it immediately to the Serial port.
3. **Data Logging (Host PC):** A dedicated software add-in (like Data Streamer or PLX-DAQ) running on Microsoft Excel intercepts this serial stream, adds the precise system time (timestamp) and date, and appends the complete transaction record directly to the spreadsheet.

4.3.2 User Feedback and Data Management

Following a successful transaction, instantaneous feedback can be observed on the Host PC's Serial Monitor, confirming the check-in or check-out event, and the attendance data is simultaneously logged into the Excel spreadsheet. The use of the Host PC for time stamping and storage guarantees that attendance logs are accurate, persistent, and readily available

for administrative processing, directly mitigating the vulnerabilities of traditional systems to corruption or loss.

In the case of an **Authentication Failure** (UID not whitelisted), the Arduino can display "Access Denied" on the Serial Monitor, and may optionally transmit this unrecognized UID and the time of the attempt (logged by the Host PC) for security auditing purposes.

Chapter 5: Results, Performance Evaluation, and Future Enhancements

5.1 Performance Analysis of Automated Attendance

The implemented RFID-based system successfully demonstrated superior performance characteristics compared to manual methods, primarily in terms of efficiency, speed, and accuracy.

5.1.1 Speed and Throughput

The system fundamentally redesigns the attendance process, moving away from time-consuming manual transcription and verification. By employing the high-speed SPI communication interface for data capture and relying on the efficiency of USB Serial for output, the system achieves rapid transaction completion. Practical execution demonstrates that the Authentication Latency—the time from tag presentation to final data logging on the Host PC—is consistently minimized, enabling high user throughput during peak attendance periods.

5.1.2 Accuracy and Reliability

High data accuracy is ensured by basing identification on the unique, immutable UID of the RFID tag, which eliminates transcription errors and reliance on human judgment. The reliance on the Host PC's operating system clock guarantees that all recorded data is accompanied by a precise, reliable timestamp, providing the necessary context for administrative requirements like punctuality tracking. The observed Error Rate for registered tags under intended operating conditions is minimal, confirming the system’s overall reliability.

5.2 Reliability and Robustness Assessment

The system's architectural reliability centers on the synergy between the Arduino's robust serial output and the Host PC's data logging capabilities. This combination ensures data integrity and survivability. By offloading persistence to the Host PC's hard drive (via Microsoft Excel), the system significantly improves robustness compared to non-digital or limited-storage methods.

However, the RC522's short read range (typically up to 60 mm) requires the user to physically place the card in close proximity. Additionally, the reliance on high-frequency electromagnetic fields makes the device susceptible to interference from other electronic equipment, which could potentially impact reading reliability in dense electronic environments.

5.3 Project Limitations and Constraints

The most significant constraint of the current implementation is the **mandatory reliance on the Host PC and specific software**. The system is completely dependent on a dedicated

computer running Microsoft Excel with the necessary serial logging add-in (e.g., Data Streamer or PLX-DAQ) continuously open and monitoring the USB port. If the Host PC is disconnected, shut down, or the logging software crashes, the system cannot log attendance data. This constraint severely restricts the system's scalability and mobility for large institutions or multi-point implementations where centralized, real-time data access and network independence are mandatory.

Furthermore, the choice of the Arduino UNO dictates fundamental hardware constraints. The 2 KB of SRAM and limited processing power of the ATmega328P necessitate a highly efficient coding approach and preclude the implementation of complex onboard database management or computationally intensive functions. Finally, passive HF RFID systems are known to be vulnerable to basic security risks, such as card cloning or unauthorized eavesdropping, a vulnerability that needs mitigation for deployment in higher security scenarios.

5.4 Future Trajectory and Scalability

To transition the system into a modern, highly scalable Attendance Management System, a strategic set of future enhancements is proposed, focusing on network integration and advanced features.

5.4.1 Phase 2: Network Integration and Database Migration

The crucial next phase involves removing the dependence on the Host PC and Microsoft Excel. This requires upgrading the core microcontroller to a Wi-Fi-enabled platform, such as the ESP8266 or NodeMCU, to establish network connectivity. Once network access is established, the data logging process must be migrated from the local Host PC to a centralized, network-accessible database (e.g., SQL, Firebase, or a cloud platform like Adafruit IO).

This migration enables true remote access and real-time management, providing administrators with immediate visibility into attendance status from any location. Crucially, this centralization facilitates powerful retrospective data analysis—a capability superior to spreadsheet-based logging—allowing institutions to track long-term absenteeism patterns and make proactive, data-driven decisions.

5.4.2 Advanced Security and Analytics

Future development should focus on fortifying system security, potentially by implementing encryption standards or challenge-response protocols if utilizing more advanced RFID tags. Furthermore, the reliable stream of time-stamped data generated through database integration opens avenues for applying advanced data analytics, including the integration of Machine Learning (ML) algorithms for predicting attendance trends and optimizing resource planning. The development of a web-based application utilizing this centralized data is also

necessary to provide administrative functions, such as user enrollment management and automated report generation.

5.4.3 Scalability

For future development, the system can incorporate a **Biometric Prompt** or **Device Credential Prompt** using the **NFC feature of smartphones**. This enhancement would ensure that attendance cannot be marked by proxy through another person's RFID tag. By linking authentication to a biometric verification or device-based credential stored on a user's personal smartphone, the system would require both card identification and personal validation. Since it is impractical for someone to lend their phone for extended periods, this method would effectively prevent misuse and ensure genuine attendance logging.

Conclusion

The project successfully developed an automated and reliable attendance logging system by strategically leveraging the cost-effectiveness and simplicity of the **Arduino UNO** and the **RC522 RFID reader**. The design achieved high operational speed and data integrity through the use of optimized **SPI communication** and a robust data offloading mechanism via **USB Serial communication** to a host PC running Microsoft Excel. This prototype effectively mitigates the inefficiencies and security risks inherent in traditional manual attendance methods by introducing automation, accuracy, and digital record-keeping.

However, the current implementation's scalability is constrained by its reliance on a continuously active host computer for data logging and timestamping. To evolve into a fully autonomous and network-independent solution, the next development phase should focus on integrating **Wi-Fi connectivity** (using modules like the ESP8266 or ESP32) and migrating data management to a **cloud-based platform**.

Additionally, implementing a **Biometric Prompt** or **Device Credential Prompt** using smartphone NFC would further enhance security by preventing proxy attendance. Since lending a personal smartphone for extended durations is impractical, this mechanism ensures that attendance can only be authenticated by the genuine user.

With these advancements, the system can progress into a truly **smart, scalable, and secure attendance management platform** capable of real-time monitoring, cloud synchronization, and analytical insights suitable for institutional and industrial deployment.

References

1. RFID Arduino – Read RFID Tag's UID with RC522 [DIY Engineers] ———— link
2. Circuit Diagram ———————————————————————— link
3. RFID Arduino Library for RC522 [GitHub] ———————————————— link
4. Testing Reference [DIY Engineers] ———————————————————— link
5. Arduino RFID Module RC522 - How to Use ———————————————— link
6. MFRC522 Datasheet ———————————————————————— link

QR View

