

Linux LAB-1

Que-7

Question 7 - > Configure file permissions and ownership.

Answer :

Theory:

Linux provides `chmod` to change file permissions, `chown` to change file ownership, and `chgrp` to change group ownership. The `umask` command controls the default permission mask for newly created files and directories. The `ls -l` command is used to verify file permissions, ownership and group information.

Result

File permissions and ownership were successfully configured and verified using `chmod`, `chown`, `chgrp`, `umask` and `ls -l`.

```
shuaib@mshuaibsi:/tmp$ mkdir Q7Files
cd Q7Files
shuaib@mshuaibsi:/tmp/Q7Files$ touch report.txt script.sh data.csv
shuaib@mshuaibsi:/tmp/Q7Files$ chmod 644 report.txt
shuaib@mshuaibsi:/tmp/Q7Files$ chmod +x script.sh
shuaib@mshuaibsi:/tmp/Q7Files$ chmod 750 data.csv
shuaib@mshuaibsi:/tmp/Q7Files$ chmod -R 755 .
shuaib@mshuaibsi:/tmp/Q7Files$ umask 022
shuaib@mshuaibsi:/tmp/Q7Files$ sudo chown $USER:$USER report.txt
[sudo: authenticate] Password:
shuaib@mshuaibsi:/tmp/Q7Files$ sudo chgrp $USER data.csv
shuaib@mshuaibsi:/tmp/Q7Files$ ls -l
total 0
-rwxr-xr-x 1 shuaib shuaib 0 Sep 28 15:07 data.csv
-rwxr-xr-x 1 shuaib shuaib 0 Sep 28 15:07 report.txt
-rwxr-xr-x 1 shuaib shuaib 0 Sep 28 15:07 script.sh
shuaib@mshuaibsi:/tmp/Q7Files$ |
```