toyData

Autogenerated data summary from cleanR

2016-12-13

Part 1

Data cleaning summary

The dataset examined has the following dimensions:

Feature	Result
Number of rows	15
Number of variables	6

Checks performed

The following variable checks were performed, depending on the data type of each variable:

|	character	factor	labelled	numeric	integer	logical
Identify miscoded missing values	×	×	×	×	×	
Identify prefixed and suffixed whitespace	×	×	×			
Identify levels with < 6 obs.	×	×				
Identify case issues	×	×				
Identify misclassified numeric or integer variables	×	×				
Identify outliers				×	×	

Please note that all numerical values in the following have been rounded to 2 decimals.

Part 2

Variable list

var1

Feature	Result
Variable type	factor
Number of missing obs.	2 (13.33 %)
Number of unique values	2
Mode	"red"

- Note that the following levels have at most five observations: "blue".

var2

Feature	Result
Variable type	numeric
Number of missing obs.	3 (20 %)
Number of unique values	8
Median	4.5
1st and 3rd quartiles	1.75; 6
Min. and max.	1; 999

- The following suspected missing value codes enter as regular values: "999", "NaN".

- Note that the following possible outlier values were detected: "82", "999".

var3

Feature	Result
Variable type	factor
Number of missing obs.	0 (0 %)
Number of unique values	7
Mode	"a"

var3

- The following suspected missing value codes enter as regular values: " ", ".".

- The following values appear with prefixed or suffixed white space: " ".

- Note that the following levels have at most five observations: " ", ".", "a", "b", "c", "other", "OTHER".

- Note that there might be case problems with the following levels: "other", "OTHER".

var4

Feature	Result
Variable type	numeric
Number of missing obs.	0 (0 %)
Number of unique values	15
Median	0.1
1st and 3rd quartiles	-0.38; 0.6
Min. and max.	-1.84; 1.02

var4

- Note that the following possible outlier values were detected: "-1.84".

var5

- The variable is a key (distinct values for each observation).

var6

- The variable only takes one (non-missing) value: "1". The variable contains 0 % missing observations.