```
No.     Time            Source              Destination         Protocol Length Info
    385 6.337905331     34.107.221.82       10.1.58.104         HTTP     282    HTTP/1.1 200 OK  (text/plain)
Frame 385: 282 bytes on wire (2256 bits), 282 bytes captured (2256 bits) on interface wlan0, id 0
Ethernet II, Src: HewlettPacka_52:a1:00 (90:20:c2:52:a1:00), Dst: CyberTANTech_d6:7c:a3 (00:45:e2:d6:7c:a3)
Internet Protocol Version 4, Src: 34.107.221.82, Dst: 10.1.58.104
Transmission Control Protocol, Src Port: 80, Dst Port: 47162, Seq: 433, Ack: 931, Len: 216
Hypertext Transfer Protocol
Line-based text data: text/plain (1 lines)
```

```
No.     Time            Source              Destination         Protocol Length Info
    385 6.337905331     34.107.221.82       10.1.58.104         HTTP     282    HTTP/1.1 200 OK  (text/plain)
Frame 385: 282 bytes on wire (2256 bits), 282 bytes captured (2256 bits) on interface wlan0, id 0
Ethernet II, Src: HewlettPacka_52:a1:00 (90:20:c2:52:a1:00), Dst: CyberTANTech_d6:7c:a3 (00:45:e2:d6:7c:a3)
Internet Protocol Version 4, Src: 34.107.221.82, Dst: 10.1.58.104
Transmission Control Protocol, Src Port: 80, Dst Port: 47162, Seq: 433, Ack: 931, Len: 216
Hypertext Transfer Protocol
Line-based text data: text/plain (1 lines)
```