

Cardano.BM - benchmarking and logging

Alexander Diemand

Andreas Triantafyllos

November 2018

Abstract

This is a framework that combines logging, benchmarking and monitoring. Complex evaluations of STM or monadic actions can be observed from outside while reading operating system counters before and after, and calculating their differences, thus relating resource usage to such actions. Through interactive configuration, the runtime behaviour of logging or the measurement of resource usage can be altered. Further reduction in logging can be achieved by redirecting log messages to an aggregation function which will output the running statistics with less frequency than the original message.

Contents

1	Cardano BM	3
1.1	Overview	3
1.2	Introduction	3
1.2.1	Logging with <i>Trace</i>	3
1.2.2	Measuring <i>Observables</i>	3
1.2.3	Monitoring	3
1.2.4	Information reduction in <i>Aggregation</i>	3
1.2.5	Output selection	3
1.2.6	Setup procedure	3
1.3	Examples	3
1.3.1	Observing evaluation of a STM action	3
1.3.2	Observing evaluation of a monad action	3
1.4	Code listings	3
1.4.1	Cardano.BM.Observer.STM	3
1.4.2	Cardano.BM.Observer.Monadlic	6
1.4.3	BaseTrace	7
1.4.4	Cardano.BM.Trace	8
1.4.5	Cardano.BM.Setup	11
1.4.6	Cardano.BM.Counters	12
1.4.7	Cardano.BM.Counters.Common	13
1.4.8	Cardano.BM.Counters.Dummy	14
1.4.9	Cardano.BM.Counters.Linux	14
1.4.10	Cardano.BM.Data.Backend	20
1.4.11	Cardano.BM.Data.Configuration	21
1.4.12	Cardano.BM.Data.Counter	22
1.4.13	Cardano.BM.Data.LogItem	23
1.4.14	Cardano.BM.Data.Observable	24
1.4.15	Cardano.BM.Data.Output	24
1.4.16	Cardano.BM.Data.Severity	25
1.4.17	Cardano.BM.Data.SubTrace	25
1.4.18	Cardano.BM.Data.Trace	25
1.4.19	Cardano.BM.Configuration	26
1.4.20	Cardano.BM.Configuration.Model	26
1.4.21	Cardano.BM.Aggregated	28
1.4.22	Cardano.BM.Output.Switchboard	30
1.4.23	Cardano.BM.Output.Log	31
1.4.24	Cardano.BM.Output.EKGView	36

1.4.25 Cardano.BM.Output.Aggregation	38
--	----

Chapter 1

Cardano BM

1.1 Overview

In figure 1.1 we display the relationships among modules in *Cardano.BM*. The arrows indicate import of a module. The arrows with a triangle at one end would signify "inheritance", but we use it to show that one module replaces the other in the namespace, thus refines its interface.

1.2 Introduction

1.2.1 Logging with *Trace*

1.2.2 Measuring *Observables*

1.2.3 Monitoring

1.2.4 Information reduction in *Aggregation*

1.2.5 Output selection

1.2.6 Setup procedure

1.3 Examples

1.3.1 Observing evaluation of a STM action

1.3.2 Observing evaluation of a monad action

1.4 Code listings

1.4.1 Cardano.BM.Observer.STM

$$\begin{aligned} stmWithLog &:: STM.STM(t, [LogObject]) \rightarrow STM.STM(t, [LogObject]) \\ stmWithLog \ action &= action \end{aligned}$$




Figure 1.1: Overview of module relationships



Figure 1.2: Setup procedure

Observe STM action in a named context

```

bracketObserveIO :: Trace IO → Text → STM.STM t → IO t
bracketObserveIO logTrace0 name action = do
  (subTrace, logTrace) ← subTrace name logTrace0
  bracketObserveIO' subTrace logTrace action
bracketObserveIO' :: SubTrace → Trace IO → STM.STM t → IO t
bracketObserveIO' NoTrace _ action =
  STM.atomically action
bracketObserveIO' subTrace logTrace action = do
  countersid ← observeOpen subTrace logTrace
  -- run action, returns result only
  t ← STM.atomically action
  observeClose subTrace logTrace countersid []
  pure t
  
```

Observe STM action in a named context and output captured log items

```

bracketObserveLogIO :: Trace IO → Text → STM.STM (t, [LogObject]) → IO t
bracketObserveLogIO logTrace0 name action = do
  (subTrace, logTrace) ← subTrace name logTrace0
  bracketObserveLogIO' subTrace logTrace action
bracketObserveLogIO' :: SubTrace → Trace IO → STM.STM (t, [LogObject]) → IO t
bracketObserveLogIO' NoTrace _ action = do
  (t, _) ← STM.atomically $ stmWithLog action
  pure t
bracketObserveLogIO' subTrace logTrace action = do
  countersid ← observeOpen subTrace logTrace
  -- run action, return result and log items
  (t, as) ← STM.atomically $ stmWithLog action
  
```

```
observeClose subTrace logTrace countersid as
pure t
```

1.4.2 Cardano.BM.Observer.Monad

```
-- Observes an action and adds name given in the logger
-- name of the given Trace. If the empty Text is
-- given as name then the logger name remains untouched.
bracketObserveIO :: Trace IO → Text → IO t → IO t
bracketObserveIO logTrace0 name action = do
  (subTrace, logTrace) ← subTrace name logTrace0
  bracketObserveIO' subTrace logTrace action
bracketObserveIO' :: SubTrace → Trace IO → IO t → IO t
bracketObserveIO' NoTrace _ action = action
bracketObserveIO' subTrace logTrace action = do
  countersid ← observeOpen subTrace logTrace
  -- run action
  t ← action
  observeClose subTrace logTrace countersid []
pure t

observeOpen :: SubTrace → Trace IO → IO CounterState
observeOpen subTrace logTrace = do
  identifier ← newUnique
  logInfo logTrace $ "Opening: " <> pack (show $ hashUnique identifier)
  -- take measurement
  counters ← readCounters subTrace
  let state = CounterState identifier counters
  -- send opening message to Trace
  traceNamedObject logTrace $ ObserveOpen state
  return state

observeClose :: SubTrace → Trace IO → CounterState → [LogObject] → IO ()
observeClose subTrace logTrace (CounterState identifier _) logObjects = do
  logInfo logTrace $ "Closing: " <> pack (show $ hashUnique identifier)
  -- take measurement
  counters ← readCounters subTrace
  -- send closing message to Trace
  traceNamedObject logTrace $ ObserveClose (CounterState identifier counters)
  -- trace the messages gathered from inside the action
  forM_ logObjects $ traceNamedObject logTrace
```


1.4.3 BaseTrace

Contravariant

A covariant is a functor: $F A \rightarrow F B$

A contravariant is a functor: $F B \rightarrow F A$

Op a b implements the dual to 'arrow' "*getOp :: b → a*", which when applied to a *BaseTrace* of type "*Op (m ()) s*", yields "*s → m ()*". In our case, *Op* accepts an action in a monad *m* with input type *LogNamed LogObject* (see 'Trace').

```
newtype BaseTrace m s = BaseTrace {runTrace :: Op (m ()) s}
```

contramap

A covariant functor defines the function "*fmap :: (a → b) → f a → f b*". In case of a contravariant functor, it is the dual function "*contramap :: (a → b) → f b → f a*" which is defined.

In the following instance, *runTrace* extracts type "*Op (m ()) s*" to which *contramap* applies *f*, thus "*f s → m ()*". The constructor *BaseTrace* restores "*Op (m ()) (f s)*".

```
instance Contravariant (BaseTrace m) where
  contramap f = BaseTrace ∘ contramap f ∘ runTrace
```

traceWith

Accepts a *Trace* and some payload *s*. First it gets the contravariant from the *Trace* as type "*Op (m ()) s*" and, after "*getOp :: b → a*" which translates to "*s → m ()*", calls the action on the *LogNamed LogObject*.

```
traceWith :: BaseTrace m s → s → m ()
traceWith = getOp ∘ runTrace
```

natTrace

Natural transformation from monad *m* to monad *n*.

```
natTrace :: (forall x ∘ m x → n x) → BaseTrace m s → BaseTrace n s
natTrace nat (BaseTrace (Op tr)) = BaseTrace $ Op $ nat ∘ tr
```

noTrace

A *Trace* that discards all inputs.

```
noTrace :: Applicative m ⇒ BaseTrace m a
noTrace = BaseTrace $ Op $ const (pure ())
```

1.4.4 Cardano.BM.Trace

Enter new named context

The context name is created and checked that its size is below a limit (currently 50 chars). The minimum severity that a log message must be labelled with is looked up in the configuration and recalculated.

```

appendName :: MonadIO m => LoggerName -> Trace m -> m (Trace m)
appendName name (ctx, trace) = do
  let prevLoggerName = loggerName ctx
      prevMinSeverity = minSeverity ctx
      newLoggerName   = appendWithDot prevLoggerName name
      globMinSeverity ← liftIO $ Config.minSeverity (configuration ctx)
      namedSeverity ← liftIO $ Config.inspectSeverity (configuration ctx) newLoggerName
  case namedSeverity of
    Nothing -> return (ctx {loggerName = newLoggerName}, trace)
    Just sev -> return (ctx {loggerName = newLoggerName
                          , minSeverity = max (max sev prevMinSeverity) globMinSeverity}
                      , trace)

appendWithDot :: LoggerName -> LoggerName -> LoggerName
appendWithDot "" newName = T.take 50 newName
appendWithDot xs "" = xs
appendWithDot xs newName = T.take 50 $ xs <> " ." <> newName

-- return a BaseTrace from a TraceNamed
named :: BaseTrace m (LogNamed i) -> LoggerName -> BaseTrace m i
named trace name = contramap (LogNamed name) trace

```

TODO remove *locallock*

```

locallock :: MVar ()
locallock = unsafePerformIO $ newMVar ()

```

Trace that forwards to the Switchboard

Every *Trace* ends in the switchboard which then takes care of dispatching the messages to outputs

```

mainTrace :: Switchboard.Switchboard -> TraceNamed IO
mainTrace sb = BaseTrace $ Op $ \lognamed -> do
  Switchboard.pass sb lognamed

```

Concrete Trace on stdout

This function returns a trace with an action of type `"(LogNamed LogObject) -> IO ()"` which will output a text message as text and all others as JSON encoded representation to the console.

```

stdoutTrace :: TraceNamed IO
stdoutTrace = BaseTrace $ Op $ \lognamed ->

```

```

case lnItem lognamed of
  LP (LogMessage logItem) →
    withMVar locallock $ \_ →
      output (lnName lognamed) $ liPayload logItem
  obj →
    withMVar locallock $ \_ →
      output (lnName lognamed) $ toStrict (encodeToLazyText obj)
where
  output nm msg = TIO.putStrLn $ nm <> " :: " <> msg

```

Concrete Trace into a TVar

```

traceInTVar :: STM.TVar [a] → BaseTrace STM.STM a
traceInTVar tvar = BaseTrace $ Op $ \a → STM.modifyTVar tvar ((:) a)
traceInTVarIO :: STM.TVar [LogObject] → TraceNamed IO
traceInTVarIO tvar = BaseTrace $ Op $ \ln →
  STM.atomicallly $ STM.modifyTVar tvar ((:) (lnItem ln))
traceNamedInTVarIO :: STM.TVar [LogNamed LogObject] → TraceNamed IO
traceNamedInTVarIO tvar = BaseTrace $ Op $ \ln →
  STM.atomicallly $ STM.modifyTVar tvar ((:) ln)

```

Check a log item's severity against the Trace's minimum severity

```

traceConditionally
  :: (MonadIO m)
  ⇒ TraceContext → BaseTrace m LogObject → LogObject
  → m ()
traceConditionally ctx logTrace msg@(LP (LogMessage item)) = do
  globminsev ← liftIO $ Config.minSeverity (configuration ctx)
  globnamesev ← liftIO $ Config.inspectSeverity (configuration ctx) (loggerName ctx)
  let minsev = max (minSeverity ctx) $ max globminsev (fromMaybe Debug globnamesev)
  flag = (liSeverity item) ≥ minsev
  when flag $ traceWith logTrace msg
traceConditionally _ logTrace logObject = traceWith logTrace logObject

```

Enter message into a trace

The function *traceNamedItem* creates a *LogObject* and threads this through the action defined in the *Trace*.

```

traceNamedItem
  :: (MonadIO m)
  ⇒ Trace m
  → LogSelection
  → Severity

```

```

    → T.Text
    → m ()
traceNamedItem (ctx, logTrace) p s m =
  let logmsg = LP $ LogMessage $ LogItem { liSelection = p
    , liSeverity = s
    , liPayload = m
    }
  in
    traceConditionally ctx (named logTrace (loggerName ctx)) $ logmsg
logDebug, logInfo, logNotice, logWarning, logError
  :: (MonadIO m) ⇒ Trace m → T.Text → m ()
logDebug logTrace = traceNamedItem logTrace Both Debug
logInfo logTrace   = traceNamedItem logTrace Both Info
logNotice logTrace = traceNamedItem logTrace Both Notice
logWarning logTrace = traceNamedItem logTrace Both Warning
logError logTrace  = traceNamedItem logTrace Both Error
logDebugS, logInfoS, logNoticeS, logWarningS, logErrorS
  :: (MonadIO m) ⇒ Trace m → T.Text → m ()
logDebugS logTrace = traceNamedItem logTrace Private Debug
logInfoS logTrace   = traceNamedItem logTrace Private Info
logNoticeS logTrace = traceNamedItem logTrace Private Notice
logWarningS logTrace = traceNamedItem logTrace Private Warning
logErrorS logTrace  = traceNamedItem logTrace Private Error
logDebugP, logInfoP, logNoticeP, logWarningP, logErrorP
  :: (MonadIO m) ⇒ Trace m → T.Text → m ()
logDebugP logTrace = traceNamedItem logTrace Public Debug
logInfoP logTrace   = traceNamedItem logTrace Public Info
logNoticeP logTrace = traceNamedItem logTrace Public Notice
logWarningP logTrace = traceNamedItem logTrace Public Warning
logErrorP logTrace  = traceNamedItem logTrace Public Error
logDebugUnsafeP, logInfoUnsafeP, logNoticeUnsafeP, logWarningUnsafeP, logErrorUnsafeP
  :: (MonadIO m) ⇒ Trace m → T.Text → m ()
logDebugUnsafeP logTrace = traceNamedItem logTrace PublicUnsafe Debug
logInfoUnsafeP logTrace   = traceNamedItem logTrace PublicUnsafe Info
logNoticeUnsafeP logTrace = traceNamedItem logTrace PublicUnsafe Notice
logWarningUnsafeP logTrace = traceNamedItem logTrace PublicUnsafe Warning
logErrorUnsafeP logTrace  = traceNamedItem logTrace PublicUnsafe Error

traceNamedObject
  :: Trace m
  → LogObject
  → m ()
traceNamedObject (ctx, logTrace) = traceWith (named logTrace (loggerName ctx))

```

subTrace

Transforms the *Trace* according to the *Configuration* using the logger name of the current *Trace* appended with the given name. If the empty *Text* is given as name then the logger name remains untouched.

```

subTrace :: MonadIO m => T.Text -> Trace m -> m (SubTrace, Trace m)
subTrace name tr@(ctx, _) = do
  let newName = appendWithDot (loggerName ctx) name
  traceTrafo0 <- liftIO $ Config.findSubTrace (configuration ctx) newName
  let traceTrafo = case traceTrafo0 of Nothing -> Neutral; Just trafo -> trafo
  case traceTrafo of
    Neutral      -> do
      tr' <- appendName name tr
      return $ (traceTrafo, tr')
    UntimedTrace -> do
      tr' <- appendName name tr
      return $ (traceTrafo, tr')
    NoTrace      -> return (traceTrafo, (ctx, BaseTrace $ Op $ \_ -> pure ()))
    DropOpening  -> return (traceTrafo, (ctx, BaseTrace $ Op $ \lognamed -> do
      case lnItem lognamed of
        ObserveOpen _ -> return ()
        obj -> traceNamedObject tr obj))
    ObservableTrace _ -> do
      tr' <- appendName name tr
      return $ (traceTrafo, tr')

```


1.4.5 Cardano.BM.Setup

Figure 1.3: Setup procedure

setupTrace

Setup a new *Trace* (*Trace*) with either a given *Configuration* (*Configuration.Model*) or a *FilePath* to a configuration file.

```

setupTrace :: MonadIO m => Either FilePath Config.Configuration -> Text -> m (Trace m)
setupTrace (Left cfgfp) name = do
  c ← liftIO $ Config.setup cfgfp
  setupTrace_ c name
setupTrace (Right c) name = setupTrace_ c name
setupTrace_ :: MonadIO m => Config.Configuration -> Text -> m (Trace m)
setupTrace_ c name = do
  sb ← liftIO $ Cardano.BM.Output o Switchboard.setup c
  sev ← liftIO $ Config.minSeverity c
  ctx ← liftIO $ newContext name c sev
  let logTrace = (ctx, natTrace liftIO (mainTrace sb))
  (_, logTrace') ← subTrace "" logTrace
  return logTrace'

```

withTrace

```

withTrace :: MonadIO m => Config.Configuration -> Text -> (Trace m -> m t) -> m t
withTrace cfg name action = do
  logTrace ← setupTrace (Right cfg) name
  action logTrace

```

newContext

```

newContext :: LoggerName -> Config.Configuration -> Severity -> IO TraceContext
newContext name cfg sev = do
  return $ TraceContext {
    loggerName = name
    , configuration = cfg
    , minSeverity = sev
  }

```

1.4.6 Cardano.BM.Counters

Here the platform is chosen on which we compile this program.

Currently, we only support *Linux* with its 'proc' filesystem.

```

{-# LANGUAGE CPP #-}
# if defined (linux_HOST_OS)
# define LINUX
# endif

```

```

module Cardano.BM.Counters
  (
    Platform.readCounters
  , diffTimeObserved
  , getMonoClock
  ) where
  # ifdef LINUX
  import qualified Cardano.BM.Counters.Linux as Platform
  # else
  import qualified Cardano.BM.Counters.Dummy as Platform
  # endif
  import Cardano.BM.Counters.Common (getMonoClock)
  import Cardano.BM.Data.Counter
  import Data.Time.Units (Microsecond)

```

Calculate difference between clocks

```

diffTimeObserved :: CounterState → CounterState → Microsecond
diffTimeObserved (CounterState id0 startCounters) (CounterState id1 endCounters) =
  let
    startTime = getMonotonicTime startCounters
    endTime = getMonotonicTime endCounters
  in
    if (id0 ≡ id1)
      then endTime − startTime
      else error "these clocks are not from the same experiment"
  where
    getMonotonicTime counters = case (filter isMonotonicClockCounter counters) of
      [(MonotonicClockTime _ micros)] → micros
      _ → error "A time measurement is missing!"
    isMonotonicClockCounter :: Counter → Bool
    isMonotonicClockCounter (MonotonicClockTime _) = True
    isMonotonicClockCounter _ = False

```

1.4.7 Cardano.BM.Counters.Common

Common functions that serve *readCounters* on all platforms.

```

nominalTimeToMicroseconds :: Word64 → Microsecond
nominalTimeToMicroseconds = fromMicroseconds ∘ toInteger ∘ ('div' 1000)

getMonoClock :: IO [Counter]
getMonoClock = do
  t ← getMonotonicTimeNSec
  return [MonotonicClockTime "monoclock" $ nominalTimeToMicroseconds t]

```

1.4.8 Cardano.BM.Counters.Dummy

This is a dummy definition of *readCounters* on platforms that do not support the 'proc' filesystem from which we would read the counters.

The only supported measurement is monotonic clock time for now.

we could well imagine that some day we support all platforms

```
readCounters :: SubTrace → IO [Counter]
readCounters NoTrace      = return []
readCounters Neutral      = return []
readCounters UntimedTrace = return []
readCounters DropOpening  = return []
readCounters (ObservableTrace tts) = foldrM (\sel,fun) a →
  if sel 'member' tts
  then (fun >>= λxs → return $ a ++ xs)
  else return a) [] selectors
where
  selectors = [(MonotonicClock, getMonoClock)
    -- , (MemoryStats, readProcStatM)
    -- , (ProcessStats, readProcStats)
    -- , (IOStats, readProcIO)
  ]
```

1.4.9 Cardano.BM.Counters.Linux

we have to expand the *readMemStats* function to read full data from *proc*

```
readCounters :: SubTrace → IO [Counter]
readCounters NoTrace      = return []
readCounters Neutral      = return []
readCounters UntimedTrace = return []
readCounters DropOpening  = return []
readCounters (ObservableTrace tts) = foldrM (\sel,fun) a →
  if sel 'member' tts
  then (fun >>= λxs → return $ a ++ xs)
  else return a) [] selectors
where
  selectors = [(MonotonicClock, getMonoClock)
    , (MemoryStats, readProcStatM)
    , (ProcessStats, readProcStats)
    , (IOStats, readProcIO)
  ]

pathProc :: FilePath
pathProc = "/proc/"
pathProcStat :: ProcessID → FilePath
```



```

pathProcStat pid = pathProc < / > (show pid) < / > "stat"
pathProcStatM :: ProcessID → FilePath
pathProcStatM pid = pathProc < / > (show pid) < / > "statm"
pathProcIO :: ProcessID → FilePath
pathProcIO pid = pathProc < / > (show pid) < / > "io"

```

Reading from a file in /proc/<pid >

```

readProcList :: FilePath → IO [Integer]
readProcList fp = do
  cs ← readFile fp
  return $ map (λs → maybe 0 id $ (readMaybe s :: Maybe Integer)) (words cs)

```

readProcStatM - /proc/<pid >/statm

```

/proc/[pid]/statm
  Provides information about memory usage, measured in pages. The columns are:
    size      (1) total program size
                (same as VmSize in /proc/[pid]/status)
    resident  (2) resident set size
                (same as VmRSS in /proc/[pid]/status)
    shared    (3) number of resident shared pages (i.e., backed by a file)
                (same as RssFile+RssShmem in /proc/[pid]/status)
    text      (4) text (code)
    lib       (5) library (unused since Linux 2.6; always 0)
    data      (6) data + stack
    dt        (7) dirty pages (unused since Linux 2.6; always 0)

```

```

readProcStatM :: IO [Counter]
readProcStatM = do
  pid ← getProcessID
  ps0 ← readProcList (pathProcStatM pid)
  ps ← return $ zip colnames ps0
  forM ps (λ(n,i) → return $ MemoryCounter n i)
  where
    colnames :: [Text]
    colnames = ["size", "resident", "shared", "text", "unused", "data", "unused"]

```

readProcStats - //proc//<pid >//stat

```

/proc/[pid]/stat
  Status information about the process. This is used by ps(1). It is defined in the kernel source file
  fs/proc/array.c.

```

The fields, in order, with their proper scanf(3) format specifiers, are listed below. Whether or not certain of these fields display valid information is governed by a ptrace access mode `PTRACE_MODE_READ_FSCREDS | PTRACE_MODE_NOAUDIT` check (refer to `ptrace(2)`). If the check denies access, then the field value is displayed as 0. The affected fields are indicated with the marking [PT].

- (1) pid %d
The process ID.
- (2) comm %s

The filename of the executable, in parentheses. This is visible whether or not the executable is swapped out.

- (3) state %c
One of the following characters, indicating process state:
- R Running
 - S Sleeping in an interruptible wait
 - D Waiting in uninterruptible disk sleep
 - Z Zombie
 - T Stopped (on a signal) or (before Linux 2.6.33) trace stopped
 - t Tracing stop (Linux 2.6.33 onward)
 - W Paging (only before Linux 2.6.0)
 - X Dead (from Linux 2.6.0 onward)
 - x Dead (Linux 2.6.33 to 3.13 only)
 - K Wakekill (Linux 2.6.33 to 3.13 only)
 - W Waking (Linux 2.6.33 to 3.13 only)
 - P Parked (Linux 3.9 to 3.13 only)
- (4) ppid %d
The PID of the parent of this process.
- (5) pgrp %d
The process group ID of the process.
- (6) session %d
The session ID of the process.
- (7) tty_nr %d
The controlling terminal of the process. (The minor device number is contained in the combination of bits 31 to 20 and 7 to 0; the major device number is in bits 15 to 8.)
- (8) tpgid %d
The ID of the foreground process group of the controlling terminal of the process.
- (9) flags %u
The kernel flags word of the process. For bit meanings, see the PF_* defines in the Linux kernel source file include/linux/sched.h. Details depend on the kernel version.
- The format for this field was %lu before Linux 2.6.
- (10) minflt %lu
The number of minor faults the process has made which have not required loading a memory page from disk.
- (11) cminflt %lu
The number of minor faults that the process's waited-for children have made.
- (12) majflt %lu
The number of major faults the process has made which have required loading a memory page from disk.
- (13) cmajflt %lu
The number of major faults that the process's waited-for children have made.
- (14) utime %lu
Amount of time that this process has been scheduled in user mode, measured in clock ticks

- (divide by `sysconf(_SC_CLK_TCK)`). This includes guest time, `guest_time` (time spent running a virtual CPU, see below), so that applications that are not aware of the guest time field do not lose that time from their calculations.
- (15) `stime` %lu
Amount of time that this process has been scheduled in kernel mode, measured in clock ticks (divide by `sysconf(_SC_CLK_TCK)`).
- (16) `cutime` %ld
Amount of time that this process's waited-for children have been scheduled in user mode, measured in clock ticks (divide by `sysconf(_SC_CLK_TCK)`). (See also `times(2)`.) This includes guest time, `cguest_time` (time spent running a virtual CPU, see below).
- (17) `cstime` %ld
Amount of time that this process's waited-for children have been scheduled in kernel mode, measured in clock ticks (divide by `sysconf(_SC_CLK_TCK)`).
- (18) `priority` %ld
(Explanation for Linux 2.6) For processes running a real-time scheduling policy (policy below; see `sched_setscheduler(2)`), this is the negated scheduling priority, minus one; that is, a number in the range -2 to -100, corresponding to real-time priorities 1 to 99. For processes running under a non-real-time scheduling policy, this is the raw nice value (`setpriority(2)`) as represented in the kernel. The kernel stores nice values as numbers in the range 0 (high) to 39 (low), corresponding to the user-visible nice range of -20 to 19.
- (19) `nice` %ld
The nice value (see `setpriority(2)`), a value in the range 19 (low priority) to -20 (high priority).
- (20) `num_threads` %ld
Number of threads in this process (since Linux 2.6). Before kernel 2.6, this field was hard coded to 0 as a placeholder for an earlier removed field.
- (21) `itrealvalue` %ld
The time in jiffies before the next SIGALRM is sent to the process due to an interval timer. Since kernel 2.6.17, this field is no longer maintained, and is hard coded as 0.
- (22) `starttime` %llu
The time the process started after system boot. In kernels before Linux 2.6, this value was expressed in jiffies. Since Linux 2.6, the value is expressed in clock ticks (divide by `sysconf(_SC_CLK_TCK)`).

The format for this field was %lu before Linux 2.6.
- (23) `vsize` %lu
Virtual memory size in bytes.
- (24) `rss` %ld
Resident Set Size: number of pages the process has in real memory. This is just the pages which count toward text, data, or stack space. This does not include pages which have not been demand-loaded in, or which are swapped out.
- (25) `rsslim` %lu
Current soft limit in bytes on the rss of the process; see the description of `RLIMIT_RSS` in `getrlimit(2)`.
- (26) `startcode` %lu [PT]
The address above which program text can run.
- (27) `endcode` %lu [PT]
The address below which program text can run.
- (28) `startstack` %lu [PT]
The address of the start (i.e., bottom) of the stack.
- (29) `kstkesp` %lu [PT]
The current value of ESP (stack pointer), as found in the kernel stack page for the process.

- (30) `kstkeip %lu [PT]`
The current EIP (instruction pointer).
- (31) `signal %lu`
The bitmap of pending signals, displayed as a decimal number. Obsolete, because it does not provide information on real-time signals; use `/proc/[pid]/status` instead.
- (32) `blocked %lu`
The bitmap of blocked signals, displayed as a decimal number. Obsolete, because it does not provide information on real-time signals; use `/proc/[pid]/status` instead.
- (33) `sigignore %lu`
The bitmap of ignored signals, displayed as a decimal number. Obsolete, because it does not provide information on real-time signals; use `/proc/[pid]/status` instead.
- (34) `sigcatch %lu`
The bitmap of caught signals, displayed as a decimal number. Obsolete, because it does not provide information on real-time signals; use `/proc/[pid]/status` instead.
- (35) `wchan %lu [PT]`
This is the "channel" in which the process is waiting. It is the address of a location in the kernel where the process is sleeping. The corresponding symbolic name can be found in `/proc/[pid]/wchan`.
- (36) `nswap %lu`
Number of pages swapped (not maintained).
- (37) `cnswap %lu`
Cumulative `nswap` for child processes (not maintained).
- (38) `exit_signal %d` (since Linux 2.1.22)
Signal to be sent to parent when we die.
- (39) `processor %d` (since Linux 2.2.8)
CPU number last executed on.
- (40) `rt_priority %u` (since Linux 2.5.19)
Real-time scheduling priority, a number in the range 1 to 99 for processes scheduled under a real-time policy, or 0, for non-real-time processes (see `sched_setscheduler(2)`).
- (41) `policy %u` (since Linux 2.5.19)
Scheduling policy (see `sched_setscheduler(2)`). Decode using the `SCHED_*` constants in `linux/sched.h`.

The format for this field was `%lu` before Linux 2.6.22.
- (42) `delayacct_blkio_ticks %llu` (since Linux 2.6.18)
Aggregated block I/O delays, measured in clock ticks (centiseconds).
- (43) `guest_time %lu` (since Linux 2.6.24)
Guest time of the process (time spent running a virtual CPU for a guest operating system), measured in clock ticks (divide by `sysconf(_SC_CLK_TCK)`).
- (44) `cguest_time %ld` (since Linux 2.6.24)
Guest time of the process's children, measured in clock ticks (divide by `sysconf(_SC_CLK_TCK)`).
- (45) `start_data %lu` (since Linux 3.3) [PT]
Address above which program initialized and uninitialized (BSS) data are placed.
- (46) `end_data %lu` (since Linux 3.3) [PT]
Address below which program initialized and uninitialized (BSS) data are placed.
- (47) `start_brk %lu` (since Linux 3.3) [PT]
Address above which program heap can be expanded with `brk(2)`.
- (48) `arg_start %lu` (since Linux 3.5) [PT]
Address above which program command-line arguments (`argv`) are placed.

- (49) `arg_end %lu` (since Linux 3.5) [PT]
Address below program command-line arguments (`argv`) are placed.
- (50) `env_start %lu` (since Linux 3.5) [PT]
Address above which program environment is placed.
- (51) `env_end %lu` (since Linux 3.5) [PT]
Address below which program environment is placed.
- (52) `exit_code %d` (since Linux 3.5) [PT]
The thread's exit status in the form reported by `waitpid(2)`.

```
readProcStats :: IO [Counter]
```

```
readProcStats = do
```

```
    pid ← getProcessID
```

```
    ps0 ← readProcList (pathProcStat pid)
```

```
    ps ← return $ zip colnames ps0
```

```
    forM ps (\(n,i) → return $ StatInfo n i)
```

```
where
```

```
    colnames :: [Text]
```

```
    colnames = [ "pid", "unused", "unused", "ppid", "pgrp", "session", "ttynr", "tpgid", "flags", "minfl",
                  "cminflt", "majflt", "cmajflt", "utime", "stime", "cutime", "cstime", "priority", "nice", "num",
                  "itrealvalue", "starttime", "vsize", "rss", "rsslim", "startcode", "endcode", "startstack",
                  "signal", "blocked", "sigignore", "sigcatch", "wchan", "nswap", "cnsnap", "exitsignal", "proc",
                  "policy", "blkio", "guesttime", "cguesttime", "startdata", "enddata", "startbrk", "argstart",
                  "envend", "exitcode"
                ]
```

readProcIO - //proc//<pid >//io

```
/proc/[pid]/io (since kernel 2.6.20)
```

This file contains I/O statistics for the process, for example:

```
# cat /proc/3828/io
rchar: 323934931
wchar: 323929600
syscr: 632687
syscw: 632675
read_bytes: 0
write_bytes: 323932160
cancelled_write_bytes: 0
```

The fields are as follows:

rchar: characters read

The number of bytes which this task has caused to be read from storage. This is simply the sum of bytes which this process passed to `read(2)` and similar system calls. It includes things such as terminal I/O and is unaffected by whether or not actual physical disk I/O was required (the read might have been satisfied from pagecache).

wchar: characters written

The number of bytes which this task has caused, or shall cause to be written to disk. Similar caveats apply here as with `rchar`.

syscr: read syscalls

Attempt to count the number of read I/O operations—that is, system calls such as `read(2)` and `pread(2)`.

```

syscw: write syscalls
    Attempt to count the number of write I/O operations—that is, system calls such as write(2) and
    pwrite(2).

read_bytes: bytes read
    Attempt to count the number of bytes which this process really did cause to be fetched from the
    storage layer. This is accurate for block-backed filesystems.

write_bytes: bytes written
    Attempt to count the number of bytes which this process caused to be sent to the storage layer.

cancelled_write_bytes:
    The big inaccuracy here is truncate. If a process writes 1MB to a file and then deletes the
    file, it will in fact perform no writeout. But it will have been accounted as having caused 1MB
    of write. In other words: this field represents the number of bytes which this process caused
    to not happen, by truncating pagecache. A task can cause "negative" I/O too. If this task
    truncates some dirty pagecache, some I/O which another task has been accounted for (in its
    write_bytes) will not be happening.

```

Note: In the current implementation, things are a bit racy on 32-bit systems: if process A reads process B's `/proc/[pid]/io` while process B is updating one of these 64-bit counters, process A could see an intermediate result.

Permission to access this file is governed by a ptrace access mode `PTRACE_MODE_READ_FSCREDS` check; see `ptrace(2)`.

```

readProcIO :: IO [Counter]
readProcIO = do
    pid ← getProcessID
    ps0 ← readProcList (pathProcIO pid)
    ps ← return $ zip colnames ps0
    forM ps (\(n,i) → return $ IOCounter n i)
  where
    colnames :: [Text]
    colnames = ["rchar", "wchar", "syscr", "syscw", "rbytes", "wbytes", "cxwbytes"]

```

1.4.10 Cardano.BM.Data.Backend

BackendKind

This identifies the backends that can be attached to the Switchboard.

```

data BackendKind = AggregationBK
    | EKGVViewBK
    | KatipBK
    | DevNullBK
deriving (Generic, Eq, Show)

```

Accepts a Type of a logged item

```

class HasPass t where
    pass :: t → NamedLogItem → IO ()

```

Backend

A backend is referenced through the function *pass'* which accepts a Type of a logged item.

```
data Backend = MkBackend {pass' :: NamedLogItem → IO ()}
```

1.4.11 Cardano.BM.Data.Configuration**Representation**

```
type Port = Int
data Representation = Representation
  {
    rotation :: RotationParameters
  , backends :: [LogBackend]
  , hasEKG :: Maybe Port
  , hasGUI :: Maybe Port
  }
deriving (Generic, Show, ToJSON, FromJSON)
```

RotationParameters

```
data RotationParameters = RotationParameters
  { rpLogLimitBytes :: !Word64 -- max size of file in bytes
  , rpMaxAgeHours :: !Word -- hours
  , rpKeepFilesNum :: !Word -- number of files to keep
  } deriving (Generic, Show, Eq, FromJSON, ToJSON)
```

LogBackend

```
data LogBackend = LogBackend
  { lbKind :: ScribeKind
  , lbName :: LoggerName
  , lbTrace :: SubTrace
  , lbSeverity :: Severity
  } deriving (Generic, Show, FromJSON, ToJSON)
```

```
test_log_backend_1 =
  BS.putStrLn $
    encode $ LogBackend {lbKind = StdoutSK
      , lbName = "test 1"
      , lbTrace = Neutral
      , lbSeverity = Info
    }
test_log_backend_2 =
```

```

BS.putStrLn $
  encode $ LogBackend {lbKind = StdoutSK
    ,lbName = "test 2"
    ,lbTrace = ObservableTrace (fromList [ MonotonicClock
      ,MemoryStats
      ,ProcessStats])
    ,lbSeverity = Info
    }
test_conf_representation_1 =
  BS.putStrLn $
    encode $ Representation
      (RotationParameters 5000000 24 10)
      [LogBackend {lbKind = StdoutSK,lbName = "stdout"
        ,lbTrace = UntimedTrace,lbSeverity = Info}
      ]
      (Just 12789)
      (Just 18321)
test_conf_representation_2 fp =
  decodeFileThrow fp :: IO Representation

```

1.4.12 Cardano.BM.Data.Counter

Counter

```

data Counter = MonotonicClockTime Text Microsecond
  | MemoryCounter Text Integer
  | StatInfo Text Integer
  | IOCounter Text Integer
  | CpuCounter Text Integer
  deriving (Eq, Show, Generic, ToJSON)
instance ToJSON Microsecond where
  toJSON = toJSON ◦ toMicroseconds
  toEncoding = toEncoding ◦ toMicroseconds

```

CounterState

```

data CounterState = CounterState {
  csIdentifier :: Unique
  ,csCounters :: [Counter]
  }
  deriving (Generic, ToJSON)
instance ToJSON Unique where
  toJSON = toJSON ◦ hashUnique
  toEncoding = toEncoding ◦ hashUnique
instance Show CounterState where

```



```
show cs = (show ◦ hashUnique) (csIdentifier cs)
  <> " => " <> (show $ csCounters cs)
```

1.4.13 Cardano.BM.Data.LogItem

```
type LoggerName = Text
```

Type of a logged item

```
type NamedLogItem = LogNamed LogObject
```

LogItem

TODO *liPayload* :: *ToObject*

```
data LogItem = LogItem
  { liSelection :: LogSelection
  , liSeverity  :: Severity
  , liPayload  :: Text -- TODO should become ToObject
  } deriving (Show, Generic, ToJSON)
```

```
data LogSelection =
  Public    -- only to public logs.
  | PublicUnsafe -- only to public logs, not console.
  | Private  -- only to private logs.
  | Both     -- to public and private logs.
  deriving (Show, Generic, ToJSON, FromJSON)
```

LogObject

```
data LogPrims = LogMessage LogItem
  | LogValue Text Integer
  deriving (Generic, Show, ToJSON)
data LogObject = LP LogPrims
  | ObserveOpen CounterState
  | ObserveClose CounterState
  deriving (Generic, Show, ToJSON)
```

LogNamed

A *LogNamed* contains of a list of context names and some log item.

```
data LogNamed item = LogNamed
  { lnName :: LoggerName
  , lnItem :: item
  } deriving (Show)
deriving instance Generic item  $\Rightarrow$  Generic (LogNamed item)
deriving instance (ToJSON item, Generic item)  $\Rightarrow$  ToJSON (LogNamed item)
```

1.4.14 Cardano.BM.Data.Observable**ObservableInstance**

```
data ObservableInstance = MonotonicClock
  | MemoryStats
  | ProcessStats
  | IOStats
  deriving (Generic, Eq, Ord, Show, FromJSON, ToJSON)
```

1.4.15 Cardano.BM.Data.Output**OutputKind**

```
data OutputKind = StdOut
  | TVarList (STM.TVar [LogObject])
  | TVarListNamed (STM.TVar [LogNamed LogObject])
  | Null
  deriving (Eq)
```

ScribeKind

This identifies katip's scribes by type.

```
data ScribeKind = FileTextSK
  | FileJsonSK
  | StdoutSK
  | StderrSK
  | DevNullSK
  deriving (Generic, Eq, Show, FromJSON, ToJSON)
```

1.4.16 Cardano.BM.Data.Severity**Severity**

```

data Severity = Debug | Info | Warning | Notice | Error
  deriving (Show, Eq, Ord, Generic, ToJSON)
instance FromJSON Severity where
  parseJSON = withText "severity" $ \case
    "Debug"    → pure Debug
    "Info"     → pure Info
    "Notice"   → pure Notice
    "Warning"  → pure Warning
    "Error"    → pure Error
    –          → pure Info-- catch all

```

1.4.17 Cardano.BM.Data.SubTrace**SubTrace**

```

data SubTrace = Neutral
  | UntimedTrace
  | NoTrace
  | DropOpening
  | ObservableTrace (Set ObservableInstance)
  deriving (Generic, Show, FromJSON, ToJSON)

```

1.4.18 Cardano.BM.Data.Trace**Trace**

A *Trace* consists of a *TraceContext* and a *TraceNamed* in *m*.

```

type Trace m = (TraceContext, TraceNamed m)

```

TraceNamed

A *TraceNamed* is a specialized Contravariant of type *LogNamed* with payload *LogObject*.

```

type TraceNamed m = BaseTrace m (LogNamed LogObject)

```

TraceContext

We keep the context's name and a reference to the *Configuration* in the *TraceContext*.

```

data TraceContext = TraceContext {
  loggerName :: LoggerName
  , configuration :: Configuration
  , minSeverity :: Severity
  }

```

1.4.19 Cardano.BM.Configuration

see `Cardano.BM.Configuration.Model` for the implementation.

```
getOptionOrDefault :: CM.Configuration → Text → Text → IO (Text)
getOptionOrDefault cg name def = do
  opt ← CM.getOption cg name
  case opt of
    Nothing → return def
    Just o → return o

parseFrom :: FilePath → IO (CM.Configuration)
parseFrom fp = CM.setup fp
```

1.4.20 Cardano.BM.Configuration.Model

Configuration.Model

<<Model>>	
Configuration	
cgMapSeverity	: Map = Text -> Severity
cgMapOutput	: Map [*] = Text -> [Backend]
cgMapSubtrace	: Map = Text -> SubTrace
cgOptions	: Map = Text -> Aeson.Object
cgMinSeverity	: Severity
cgDefBackends	: Backend [*]

Figure 1.4: Configuration model

```
type ConfigurationMVar = MVar ConfigurationInternal
newtype Configuration = Configuration
  {getCG :: ConfigurationMVar}
-- Our internal state; see -"Configuration model"-
data ConfigurationInternal = ConfigurationInternal
  {cgMapSeverity :: HM.HashMap Text Severity
  ,cgMapOutput :: HM.HashMap Text [Backend]
  ,cgMapSubtrace :: HM.HashMap Text SubTrace
  ,cgOptions :: HM.HashMap Text Aeson.Object
  ,cgMinSeverity :: Severity
  ,cgDefBackends :: [Backend]
  }
-- options: config.logrotation = maxFiles = 10; maxSize = 5000000
-- config.logprefix = path = "/mnt/disk/spacy"
```

Backend relation

```

getBackends :: Configuration → Text → IO (Maybe [Backend])
getBackends configuration name =
  withMVar (getCG configuration) $ \cg → do
    let outs = HM.lookup name (cgMapOutput cg)
    case outs of
      Nothing → do
        return $ Just (cgDefBackends cg)
      Just os → return $ Just os

setDefaultBackends :: Configuration → [Backend] → IO ()
setDefaultBackends configuration bes = do
  cg ← takeMVar (getCG configuration)
  putMVar (getCG configuration) $ cg {cgDefBackends = bes}

registerBackend :: Configuration → Text → Maybe Backend → IO ()
registerBackend _ kn _f = pure () -- TODO
  -- registerBackend "some" (Just Backend pass' = Katip.pass (show StdoutSK) )
  -- registerBackend "severe.error" (Just Backend pass' = Katip.pass "StdoutSK::severe.1

```

Options

```

getOption :: Configuration → Text → IO (Maybe Text)
getOption configuration name = do
  withMVar (getCG configuration) $ \cg →
    case HM.lookup name (cgOptions cg) of
      Nothing → return Nothing
      Just o → return $ Just $ pack $ show o

```

Global setting of minimum severity

```

minSeverity :: Configuration → IO Severity
minSeverity configuration = withMVar (getCG configuration) $ \cg →
  return $ cgMinSeverity cg

setMinSeverity :: Configuration → Severity → IO ()
setMinSeverity configuration sev = do
  cg ← takeMVar (getCG configuration)
  putMVar (getCG configuration) $ cg {cgMinSeverity = sev}

```

Relation of context name to minimum severity

```

inspectSeverity :: Configuration → Text → IO (Maybe Severity)
inspectSeverity configuration name = do
  withMVar (getCG configuration) $ \cg →

```

```

    return $ HM.lookup name (cgMapSeverity cg)
-- if Maybe Severity given is Nothing then the entry for this name is deleted.
setSeverity :: Configuration → Text → Maybe Severity → IO ()
setSeverity configuration name sev = do
  cg ← takeMVar (getCG configuration)
  putMVar (getCG configuration) $ cg {cgMapSeverity = HM.alter (\_ → sev) name (cgMapSeverity cg)}

```

Relation of context name to SubTrace

A new context may contain a different type of *Trace*. The function *appendName* (Enter new named context) will look up the *SubTrace* for the context's name.

```

findSubTrace :: Configuration → Text → IO (Maybe SubTrace)
findSubTrace configuration name = do
  withMVar (getCG configuration) $ λcg →
    return $ HM.lookup name (cgMapSubtrace cg)
setSubTrace :: Configuration → Text → Maybe SubTrace → IO ()
setSubTrace configuration name trafo = do
  cg ← takeMVar (getCG configuration)
  putMVar (getCG configuration) $ cg {cgMapSubtrace = HM.alter (\_ → trafo) name (cgMapSubtrace cg)}

```

Configuration.Model.setup

```

setup :: FilePath → IO Configuration
setup fp = do
  cgref ← newEmptyMVar
  putMVar cgref $ ConfigurationInternal HM.empty HM.empty HM.empty HM.empty Debug [ ]
  return $ Configuration cgref

```

1.4.21 Cardano.BM.Aggregated

```

module Cardano.BM.Aggregated
(
  Aggregated(..)
, Stats(..)
, updateAggregation
) where

data Stats = Stats {
  fmin :: Integer,
  fmax :: Integer,
  fcount :: Integer,
  fsum_A :: Integer,
  fsum_B :: Integer

```

```

    } deriving (Show, Eq)
data Aggregated = Aggregated {
  fstats :: Stats,
  flast  :: Integer,
  fdelta :: Stats
  } deriving (Show, Eq)

```

Update aggregation

We distinguish an uninitialized from an already initialized aggregation:

```

updateAggregation :: Integer → Maybe Aggregated → Maybe Aggregated
updateAggregation v Nothing =
  Just $
    Aggregated {fstats = Stats {
      fmin = v, fmax = v, fcount = 1
      , fsum_A = v, fsum_B = v * v}
      , flast = v
      , fdelta = Stats {
        fmin = 0, fmax = 0, fcount = 0
        , fsum_A = 0, fsum_B = 0}
      }
updateAggregation v (Just (Aggregated (Stats _min _max _count _sumA _sumB)
  _last
  (Stats _dmin _dmax _dcount _dsumA _dsumB)
  )) =
  let delta = v - _last
  in
  Just $
    Aggregated {fstats = Stats {
      fmin = (min _min v)
      , fmax = (max _max v)
      , fcount = (_count + 1)
      , fsum_A = (_sumA + v)
      , fsum_B = (_sumB + v * v)
      }
      , flast = v
      , fdelta = Stats {
        fmin = (min _dmin delta)
        , fmax = (max _dmax delta)
        , fcount = (_dcount + 1)
        , fsum_A = (_dsumA + delta)
        , fsum_B = (_dsumB + delta * delta)
        }
      }

```

1.4.22 Cardano.BM.Output.Switchboard

Switchboard

The switchboard is a singleton.

```
type SwitchboardMVar = MVar SwitchboardInternal
newtype Switchboard = Switchboard
    {getSB :: SwitchboardMVar}
-- Our internal state
data SwitchboardInternal = SwitchboardInternal
    {sbQueue :: TBQ.TBQueue (Maybe NamedLogItem)
    ,sbDispatch :: Async.Async ()
    ,sbBackends :: [Backend]
    }
```

Starting the switchboard from configuration

The queue is initialized and the message dispatcher launched. TODO: the backends should be connected according to configuration.

```
setup :: Configuration → IO Switchboard
setup cfg = do
    ekgv ← Cardano.BM.Output ∘ EKGView.setup cfg
    aggr ← Cardano.BM.Output ∘ Aggregation.setup cfg
    logs ← Cardano.BM.Output ∘ Log.setup cfg
    -- TODO connect backends according to configuration
    let bs = [MkBackend {pass' = Cardano.BM.Output ∘ Log.passN "StdoutSK" logs}
            ,MkBackend {pass' = Cardano.BM.Output ∘ EKGView.pass ekgv}
            ,MkBackend {pass' = Cardano.BM.Output ∘ Aggregation.pass aggr}]
    sbref ← newEmptyMVar
    q ← atomically $ TBQ.newTBQueue 2048
    d ← spawnDispatcher sbref q
    putMVar sbref $ SwitchboardInternal q d bs
    return $ Switchboard sbref
where
    spawnDispatcher :: SwitchboardMVar → TBQ.TBQueue (Maybe NamedLogItem) → IO (Async.Async ())
    spawnDispatcher switchboard queue = Async.async qProc
    where
        qProc = do
            nli' ← atomically $ TBQ.readTBQueue queue
            case nli' of
                Just nli → do
                    putStrLn $ "dispatcher read: " ++ (show nli)
                    withMVar switchboard $ \sb →
                        forM_ (sbBackends sb) (dispatch nli)
                Nothing → return () -- end dispatcher
```



```
dispatch :: NamedLogItem → Backend → IO ()
dispatch nli backend = (pass' backend) nli
```

Process incoming messages

Incoming messages are put into the queue, and then processed by the dispatcher.

```
instance HasPass Switchboard where
  pass switchboard item = do
    let writequeue :: TBQ.TBQueue (Maybe NamedLogItem) → NamedLogItem → STM ()
    writequeue q i = do
      nocapacity ← TBQ.isFullTBQueue q
      if ¬ nocapacity
      then TBQ.writeTBQueue q (Just i)
      else return ()
    putStrLn $ "Cardano.BM.Output.Switchboard.pass " ++ (show item)
    withMVar (getSB switchboard) $ λsb →
      atomically $ writequeue (sbQueue sb) item
```

Halting the switchboard

The queue is flushed before the dispatcher terminates.

```
takedown :: Switchboard → IO ()
takedown switchboard = do
  (q,d) ← withMVar (getSB switchboard) $ λsb →
    return (sbQueue sb, sbDispatch sb)
  -- send terminating item to the queue
  atomically $ TBQ.writeTBQueue q Nothing
  -- wait for the dispatcher to exit
  _ ← Async.waitCatch d
  return ()
```

1.4.23 Cardano.BM.Output.Log

Log is a singleton.

```
type KatipMVar = MVar KatipInternal
newtype Log = Log
  {getK :: KatipMVar}
-- Our internal state
data KatipInternal = KatipInternal
  {kLogEnv :: K.LogEnv}

instance HasPass Log where
  pass _ = pure () -- error "use passN"
```

Setup *katip* and its scribes according to the configuration

```

setup :: Config.Configuration → IO Log
setup config = do
  cfoKey ← Config.getOptionOrDefault config (pack "cfokey") (pack "<unknown>")
  -- TODO setup katip
  le0 ← K.initLogEnv
    (K.Namespace [ "ouroboros-bm" ])
    (fromString $ (unpack cfoKey) <> ":" <> showVersion mockVersion)
  -- request a new time 'getCurrentTime' at most 100 times a second
  timer ← mkAutoUpdate defaultUpdateSettings {updateAction = getCurrentTime, updateFreq = 10000}
  let le1 = updateEnv le0 timer
  stdoutScribe ← mkStdoutScribeJson K.V0
  le ← register [(StdoutSK, "stdout", stdoutScribe)] le1
  kref ← newEmptyMVar
  putMVar kref $ KatipInternal le
  let katipref = Log kref
  setDefaultBackends config
    [ MkBackend {pass' = Cardano.BM.Output ∘ Log.passN (pack (show StdoutSK)) katipref}
    , MkBackend {pass' = Cardano.BM.Output ∘ Log.passN (pack (show FileTextSK)) katipref}
    , MkBackend {pass' = Cardano.BM.Output ∘ Log.passN (pack (show FileJsonSK)) katipref}
    ]
  return katipref
where
  updateEnv :: K.LogEnv → IO UTCTime → K.LogEnv
  updateEnv le timer =
    le {K._logEnvTimer = timer, K._logEnvHost = "hostname"}
  register :: [(ScribeKind, Text, K.Scribe)] → K.LogEnv → IO K.LogEnv
  register [] le = return le
  register ((kind, name, scribe) : scs) le =
    let name' = pack (show kind) <> ":" <> name in
    register scs ≡ K.registerScribe name' scribe scribeSettings le
  mockVersion :: Version
  mockVersion = Version [0, 1, 0, 0] []
  scribeSettings :: KC.ScribeSettings
  scribeSettings = KC.ScribeSettings bufferSize
  where
    bufferSize = 5000 -- size of the queue (in log items)

example :: IO ()
example = do
  config ← Config.setup "from_some_path.yaml"
  k ← setup config
  passN (pack (show StdoutSK)) k $ LogNamed
    {lnName = "test"
    , lnItem = LP $ LogMessage $ LogItem
    {liSelection = Both

```

```

        ,liSeverity = Info
        ,liPayload = "Hello!"
    }
}
passN (pack (show StdoutSK)) k $ LogNamed
{lnName = "test"
 ,lnItem = LP $ LogValue "cpu-no" 1
}

-- useful instances for katip
deriving instance K.ToObject LogObject
deriving instance K.ToObject LogItem
deriving instance K.ToObject (Maybe LogObject)
instance KC.LogItem LogObject where
    payloadKeys _ = KC.AllKeys
instance KC.LogItem LogItem where
    payloadKeys _ = KC.AllKeys
instance KC.LogItem (Maybe LogObject) where
    payloadKeys _ = KC.AllKeys

passN :: Text → Log → NamedLogItem → IO ()
passN backend katip namedLogItem = withMVar (getK katip) $ \k → do
    -- TODO go through list of registered scribes
    -- and put into queue of scribe if backend kind matches
    -- compare start of name of scribe to (show backend <> "::")
    let env = kLogEnv k
    forM_ (Map.toList $ K._logEnvScribes env) $
        \ (scName, (KC.ScribeHandle _ shChan)) →
            -- check start of name to match ScribeKind
            if backend 'isPrefixOf' scName
            then do
                let item = lnItem namedLogItem
                let (sev, msg, payload) = case item of
                    (LP (LogMessage logItem)) →
                        (liSeverity logItem, liPayload logItem, Nothing)
                    _ → (Info, "", Just item)
                threadIdText ← KC.mkThreadIdText < $ > myThreadId
                let ns = lnName namedLogItem
                itemTime ← env ^. KC.logEnvTimer
                let itemKatip = K.Item {
                    _itemApp      = env ^. KC.logEnvApp
                    , _itemEnv     = env ^. KC.logEnvEnv
                    , _itemSeverity = sev2klog sev
                    , _itemThread  = threadIdText
                    , _itemHost    = env ^. KC.logEnvHost
                    , _itemProcess = env ^. KC.logEnvPid
                    , _itemPayload = payload

```

```

    ,_itemMessage = K.logStr msg
    ,_itemTime    = itemTime
    ,_itemNamespace = (env ^. KC.logEnvApp) <> (K.Namespace [ns])
    ,_itemLoc      = Nothing
  }
  atomically $ KC.tryWriteTBQueue shChan (KC.NewItem itemKatip)
else return False

```

Scribes

```

mkStdoutScribe :: K.Verbosity → IO K.Scribe
mkStdoutScribe = mkTextFileScribeH stdout True

mkStdoutScribeJson :: K.Verbosity → IO K.Scribe
mkStdoutScribeJson = mkJsonFileScribeH stdout True

mkStderrScribe :: K.Verbosity → IO K.Scribe
mkStderrScribe = mkTextFileScribeH stderr True

mkJsonFileScribeH :: Handle → Bool → K.Verbosity → IO K.Scribe
mkJsonFileScribeH handler color verb = do
  mkFileScribeH handler formatter color verb
where
  formatter :: (K.LogItem a) ⇒ Handle → Bool → K.Verbosity → K.Item a → IO ()
  formatter h _ verbosity item = do
    let tmsg = case KC._itemMessage item of
      K.LogStr " " → K.itemJson verbosity item
      K.LogStr msg → K.itemJson verbosity $
        item { KC._itemMessage = K.logStr (" " :: Text)
              , KC._itemPayload = LogItem Both Info $ toStrict $ toLazyText msg
              }
    TIO.hPutStrLn h (encodeToLazyText tmsg)

mkTextFileScribeH :: Handle → Bool → K.Verbosity → IO K.Scribe
mkTextFileScribeH handler color verb = do
  mkFileScribeH handler formatter color verb
where
  formatter h colorize verbosity item =
    TIO.hPutStrLn h $! toLazyText $ formatItem colorize verbosity item

mkFileScribeH
  :: Handle
  → (forall a ◦ K.LogItem a ⇒ Handle → Bool → K.Verbosity → K.Item a → IO ()) -- format and output f
  → Bool -- whether the output is colourized
  → K.Verbosity
  → IO K.Scribe
mkFileScribeH h formatter colorize verbosity = do
  hSetBuffering h LineBuffering
  locklocal ← newMVar ()
  let logger :: forall a ◦ K.LogItem a ⇒ K.Item a → IO ()
      logger item = withMVar locklocal $ \_ →

```

```

    formatter h colorize verbosity item
  pure $ K.Scribe logger (hClose h)
mkTextFileScribe :: FileDescription → Bool → Severity → K.Verbosity → IO K.Scribe
mkTextFileScribe fdesc colorize s v = do
  mkFileScribe fdesc formatter colorize s v
where
  formatter :: Handle → Bool → K.Verbosity → K.Item a → IO ()
  formatter hdl colorize' v' item = do
    let tmsg = toLazyText $ formatItem colorize' v' item
    TIO.hPutStrLn hdl tmsg
mkFileScribe
  :: FileDescription
  → (forall a ◦ K.LogItem a ⇒ Handle → Bool → K.Verbosity → K.Item a → IO ()) -- format and output f
  → Bool -- whether the output is colourized
  → Severity
  → K.Verbosity
  → IO K.Scribe
mkFileScribe fdesc formatter colorize _ v = do
  let prefixDir = prefixPath fdesc
  (createDirectoryIfMissing True prefixDir)
  'catchIO' (prtoutException ("cannot log prefix directory: " ++ prefixDir))
  let fpath = filePath fdesc
  h ← catchIO (openFile fpath WriteMode) $
    λe → do
      prtoutException ("error while opening log: " ++ fpath) e
      -- fallback to standard output in case of exception
      return stdout
  hSetBuffering h LineBuffering
  scribestate ← newMVar h
  let finalizer :: IO ()
      finalizer = withMVar scribestate hClose
  let logger :: forall a ◦ K.LogItem a ⇒ K.Item a → IO ()
      logger item =
        withMVar scribestate $ λhandler →
          formatter handler colorize v item
  return $ K.Scribe logger finalizer

formatItem :: Bool → K.Verbosity → K.Item a → Builder
formatItem withColor _verb K.Item {..} =
  fromText header <>
  fromText " " <>
  brackets (fromText timestamp) <>
  fromText " " <>
  KC.unLogStr _itemMessage
where
  header = colorBySeverity _itemSeverity $
    "[ " <> mconcat namedcontext <> ": " <> severity <> ": " <> threadid <> "]"

```

```

namedcontext = KC.intercalateNs _itemNamespace
severity = KC.renderSeverity _itemSeverity
threadid = KC.getThreadIdText _itemThread
timestamp = pack $ formatTime defaultTimeLocale tsformat _itemTime
tsformat :: String
tsformat = "%F %T%2Q %Z"
colorBySeverity s m = case s of
  K.EmergencyS → red m
  K.AlertS     → red m
  K.CriticalS  → red m
  K.ErrorS     → red m
  K.NoticeS    → magenta m
  K.WarningS   → yellow m
  K.InfoS      → blue m
  _           → m
red = colorize "31"
yellow = colorize "33"
magenta = colorize "35"
blue = colorize "34"
colorize c m
  | withColor = "\ESC[" <> c <> "m" <> m <> "\ESC[0m"
  | otherwise = m
-- translate Severity to Log.Severity
sev2klog :: Severity → K.Severity
sev2klog = λcase
  Debug → K.DebugS
  Info   → K.InfoS
  Notice → K.NoticeS
  Warning → K.WarningS
  Error  → K.ErrorS

data FileDescription = FileDescription {
  filePath :: !FilePath
  deriving (Show)
  prefixPath :: FileDescription → FilePath
  prefixPath = takeDirectory ∘ filePath
  -- display message and stack trace of exception on stdout
  prtoutException :: Exception e ⇒ String → e → IO ()
  prtoutException msg e = do
    putStrLn msg
    putStrLn ("exception: " ++ displayException e)

```

1.4.24 Cardano.BM.Output.EKGView

The ekview is a singleton.

```

type EKGViewMVar = MVar EKGViewInternal
newtype EKGView = EKGView

```

```

    {getEV :: EKGViewMVar}
-- Our internal state
data EKGViewInternal = EKGViewInternal
    { evGauges :: HM.HashMap Text Gauge.Gauge
    , evLabels  :: HM.HashMap Text Label.Label
    , _ekgServer :: Server
    }

setup :: Configuration → IO EKGView
setup _ = do
    evref ← newEmptyMVar
    ehdl ← forkServer "127.0.0.1" 16543
    putMVar evref $ EKGViewInternal HM.empty HM.empty ehdl
    return $ EKGView evref

instance HasPass EKGView where
    pass ekgtview item =
        let update :: LogObject → LoggerName → EKGViewInternal → IO (Maybe EKGViewInternal)
            update (LP (LogMessage logitem)) logname ekg@(EKGViewInternal _ labels server) =
                case HM.lookup logname labels of
                    Nothing → do
                        ekghdl ← getLabel logname server
                        Label.set ekghdl (liPayload logitem)
                        return $ Just $ ekg {evLabels = HM.insert logname ekghdl labels}
                    Just ekghdl → do
                        Label.set ekghdl (liPayload logitem)
                        return Nothing
            update (LP (LogValue iname value)) logname ekg@(EKGViewInternal gauges _ server) =
                let name = logname <> "." <> iname
                in
                case HM.lookup name gauges of
                    Nothing → do
                        ekghdl ← getGauge name server
                        Gauge.set ekghdl (fromInteger value)
                        return $ Just $ ekg {evGauges = HM.insert name ekghdl gauges}
                    Just ekghdl → do
                        Gauge.set ekghdl (fromInteger value)
                        return Nothing
            update _ _ _ = return Nothing
        in do
            ekg ← takeMVar (getEV ekgtview)
            upd ← update (lnItem item) (lnName item) ekg
            case upd of
                Nothing → putMVar (getEV ekgtview) ekg
                Just ekg' → putMVar (getEV ekgtview) ekg'

```

1.4.25 Cardano.BM.Output.Aggregation

The aggregation is a singleton.

```

type AggregationMVar = MVar AggregationInternal
newtype Aggregation = Aggregation
    {getAg :: AggregationMVar}
-- Our internal state
data AggregationInternal = AggregationInternal
    {agMap :: HM.HashMap Text Aggregated
    ,agSome :: [Int]-- TODO
    }

inspect :: Aggregation → Text → IO (Maybe Aggregated)
inspect agg name =
    withMVar (getAg agg) $ \ag →
        return $ HM.lookup name (agMap ag)

setup :: Configuration → IO Aggregation
setup _ = do
    aggref ← newEmptyMVar
    -- TODO create thread which will periodically output
    -- aggregated values to the switchboard
    putMVar aggref $ AggregationInternal HM.empty []
    return $ Aggregation aggref

pass :: Aggregation → NamedLogItem → IO ()
pass agg item = do
    ag ← takeMVar (getAg agg)
    putMVar (getAg agg) $ AggregationInternal (updated $ agMap ag) (agSome ag)
where
    updated agmap = pass' (lnItem item) (lnName item) agmap
    pass' :: LogObject → LoggerName → HM.HashMap Text Aggregated → HM.HashMap Text Aggregated
    pass' (LP (LogValue iname value)) logname agmap =
        let name = logname <> "." <> iname
        in
            HM.alter (λm → updateAggregation value m) name agmap
    -- TODO for text messages aggregate on delta of timestamps
    pass' _ _ agmap = agmap

```