

# Testing benchmarking and logging

Alexander Diemand

Andreas Triantafyllos

November 2018

# Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Test coverage</b>                    | <b>2</b> |
| 1.1      | Coverage . . . . .                      | 2        |
| <b>2</b> | <b>Testing</b>                          | <b>4</b> |
| 2.1      | Test main entry point . . . . .         | 4        |
| 2.1.1    | instance Arbitrary Aggregated . . . . . | 4        |
| 2.1.2    | Testing aggregation . . . . .           | 5        |
| 2.1.3    | STM . . . . .                           | 6        |
| 2.1.4    | Trace . . . . .                         | 6        |
| 2.1.5    | Testing configuration . . . . .         | 15       |

## **Abstract**

abstract ...

# Chapter 1

## Test coverage

### 1.1 Coverage

Test coverage is calculated as the fraction of functions which are called from test routines. This percentage is calculated by the tool *hpc* with a call to

```
cabal new-test
```

Add to a local `cabal.project.local` file these lines:

```
tests:           True
coverage:        True
library-coverage: True
```

|                                 |      |
|---------------------------------|------|
| Cardano.BM.Counters.Dummy       | 100% |
| Cardano.BM.Counters             | 100% |
| Cardano.BM.Configuration        | 100% |
| Cardano.BM.Data.Configuration   | 83%  |
| Cardano.BM.Data.Trace           | 80%  |
| Cardano.BM.BaseTrace            | 80%  |
| Cardano.BM.Setup                | 75%  |
| Cardano.BM.Observer.Monadic     | 75%  |
| Cardano.BM.Configuration.Model  | 72%  |
| Cardano.BM.Output.Switchboard   | 66%  |
| Cardano.BM.Counters.Common      | 66%  |
| Cardano.BM.Data.Aggregated      | 64%  |
| Cardano.BM.Data.Counter         | 56%  |
| Cardano.BM.Data.Severity        | 54%  |
| Cardano.BM.Data.Output          | 50%  |
| Cardano.BM.Data.BackendKind     | 50%  |
| Cardano.BM.Configuration.Static | 50%  |
| Cardano.BM.Output.Log           | 45%  |
| Cardano.BM.Output.Aggregation   | 42%  |
| Cardano.BM.Data.SubTrace        | 40%  |
| Cardano.BM.Data.LogItem         | 40%  |
| Cardano.BM.Observer.STM         | 33%  |
| Cardano.BM.Data.AggregatedKind  | 33%  |
| Cardano.BM.Trace                | 29%  |
| Cardano.BM.Data.Backend         | 25%  |
| Cardano.BM.Data.Observable      | 20%  |
| Cardano.BM.Data.Rotation        | 10%  |
| Cardano.BM.Output.EKGView       | 0%   |
| Paths_iohk_monitoring           | 0%   |
|                                 | 48%  |

Figure 1.1: Test coverage of modules in percent as computed by the tool 'hpc'

# Chapter 2

## Testing

### 2.1 Test main entry point

```
module Main
(
    main
) where
import Test.Tasty
import qualified Cardano.BM.Test.Agregated (tests)
import qualified Cardano.BM.Test.STM (tests)
import qualified Cardano.BM.Test.Trace (tests)
import qualified Cardano.BM.Test.Configuration (tests)
main :: IO ()
main = defaultMain tests
tests :: TestTree
tests =
    testGroup "iohk-monitoring"
    [ Cardano.BM.Test ◦ Aggregated.tests
    , Cardano.BM.Test ◦ STM.tests
    , Cardano.BM.Test ◦ Trace.tests
    , Cardano.BM.Test ◦ Configuration.tests
    ]
```

#### 2.1.1 instance Arbitrary Aggregated

We define an instance of *Arbitrary* for an *Aggregated* which lets *QuickCheck* generate arbitrary instances of *Aggregated*. For this an arbitrary list of *Integer* is generated and this list is aggregated into a structure of *Aggregated*.

```
instance Arbitrary Aggregated where
    arbitrary = do
        vs' ← arbitrary :: Gen [Integer]
        let vs = 42 : 17 : vs'
        (m,s) = updateMeanVar $ map fromInteger vs
```

```

return $ AggregatedStats (Stats
  (PureI (last vs))
  (PureI (minimum vs))
  (PureI (maximum vs))
  (toInteger $ length vs)
  (m)
  (s)
)

```

Estimators for mean and variance must be updated the same way as in the code.

```

updateMeanVar :: [Double] → (Double, Double)
updateMeanVar [] = (0, 0)
updateMeanVar (val : vals) = updateMeanVar' (val, 0) 1 vals
where
  updateMeanVar' (m, s) _ [] = (m, s)
  updateMeanVar' (m, s) cnt (a : r) =
    let delta = a - m
        newcount = cnt + 1
        m' = m + (delta / newcount)
        s' = s + (delta * (a - m'))
    in
      updateMeanVar' (m', s') newcount r

```

### 2.1.2 Testing aggregation

```

tests :: TestTree
tests = testGroup "aggregation measurements" [
  property_tests
, unit_tests
]
property_tests :: TestTree
property_tests = testGroup "Properties" [
  testProperty "minimal" prop_Aggregation_minimal
, testProperty "commutative" prop_Aggregation_comm
]
unit_tests :: TestTree
unit_tests = testGroup "Unit tests" [
  testCase "initial_minus_1" unit_Aggregation_initial_minus_1
, testCase "initial_plus_1" unit_Aggregation_initial_plus_1
, testCase "initial_0" unit_Aggregation_initial_zero
]
prop_Aggregation_minimal :: Bool
prop_Aggregation_minimal = True
prop_Aggregation_comm :: Integer → Integer → Aggregated → Bool
prop_Aggregation_comm v1 v2 ag =

```

```

let AggregatedStats stats1 = updateAggregation (PureI v1) (updateAggregation (PureI v2) ag Nothing) Nothing
    AggregatedStats stats2 = updateAggregation (PureI v2) (updateAggregation (PureI v1) ag Nothing) Nothing
in
  fmin stats1  $\equiv$  fmin stats2  $\wedge$ 
  fmax stats1  $\equiv$  fmax stats2  $\wedge$ 
  fcount stats1  $\equiv$  fcount stats2  $\wedge$ 
  abs (fsum_A stats1 - fsum_A stats2) < 1.0e-4  $\wedge$ 
  abs (fsum_B stats1 - fsum_B stats2) < 1.0e-4  $\wedge$ 
  (v1  $\equiv$  v2) 'implies' (flast stats1  $\equiv$  flast stats2)

-- implication: if p1 is true, then return p2; otherwise true
implies :: Bool  $\rightarrow$  Bool  $\rightarrow$  Bool
implies p1 p2 = ( $\neg$  p1)  $\vee$  p2

unit Aggregation_initial_minus_1 :: Assertion
unit Aggregation_initial_minus_1 =
  updateAggregation (-1) firstStateAggregatedStats Nothing @? =
    AggregatedStats (Stats (-1) (-1) 0 2 (-0.5) 0.5)
unit Aggregation_initial_plus_1 :: Assertion
unit Aggregation_initial_plus_1 =
  updateAggregation 1 firstStateAggregatedStats Nothing @? = AggregatedStats (Stats 1 0 1 2 0.5 0.5)
unit Aggregation_initial_zero :: Assertion
unit Aggregation_initial_zero =
  updateAggregation 0 firstStateAggregatedStats Nothing @? = AggregatedStats (Stats 0 0 0 2 0 0)
firstStateAggregatedStats :: Aggregated
firstStateAggregatedStats = AggregatedStats (Stats 0 0 0 1 0 0)

```

### 2.1.3 STM

```

module Cardano.BM.Test.STM (
  tests
) where
import Test.Tasty
import Test.Tasty.QuickCheck

tests :: TestTree
tests = testGroup "observing STM actions" [
  testProperty "minimal" prop_STM_observer
]

prop_STM_observer :: Bool
prop_STM_observer = True

```

### 2.1.4 Trace

```

tests :: TestTree
tests = testGroup "testing Trace" [
  unit_tests
]

```



```

,testCase "forked traces stress testing" stress_trace_in_fork
,testCase "stress testing: ObservableTrace vs. NoTrace" timing_Observable_vs_Untimed
,testCaseInfo "demonstrating nested named context logging" example_with_named_contexts
]
unit_tests :: TestTree
unit_tests = testGroup "Unit tests" [
  testCase "opening messages should not be traced" unit_noOpening_Trace
, testCase "hierarchy of traces" unit_hierarchy
, testCase "forked traces" unit_trace_in_fork
, testCase "hierarchy of traces with NoTrace" $
  unit_hierarchy' [Neutral, NoTrace, (ObservableTrace observablesSet)]
  onlyLevelOneMessage
, testCase "hierarchy of traces with DropOpening" $
  unit_hierarchy' [Neutral, DropOpening, (ObservableTrace observablesSet)]
  notObserveOpen
, testCase "hierarchy of traces with UntimedTrace" $
  unit_hierarchy' [Neutral, UntimedTrace, UntimedTrace]
  observeOpenWithoutMeasures
, testCase "changing the minimum severity of a trace at runtime"
  unit_trace_min_severity
, testCase "changing the minimum severity of a named context at runtime"
  unit_named_min_severity
, testCase "appending names should not exceed 80 chars" unit_append_name
, testCase "creat subtrace which duplicates messages" unit_trace_duplicate
]
where
  observablesSet = [ MonotonicClock, MemoryStats ]
  notObserveOpen :: [LogObject] → Bool
  notObserveOpen = all (λcase { ObserveOpen _ → False; _ → True })
  onlyLevelOneMessage :: [LogObject] → Bool
  onlyLevelOneMessage = λcase
    [ LP (LogMessage (LogItem _ _ "Message from level 1. ")) ] → True
    _ → False
  observeOpenWithoutMeasures :: [LogObject] → Bool
  observeOpenWithoutMeasures = any $ λcase
    ObserveOpen (CounterState _ counters) → null counters
    _ → False

```

## Helper routines

```

data TraceConfiguration = TraceConfiguration
  { tcOutputKind :: OutputKind
  , tcName       :: LoggerName
  , tcSubTrace   :: SubTrace
  , tcSeverity   :: Severity
  }

```

```

setupTrace :: TraceConfiguration → IO (Trace IO)
setupTrace (TraceConfiguration outk name subTr sev) = do
  c ← liftIO $ Cardano.BM.Configuration o Model.empty
  mockSwitchboard ← newMVar $ error "Switchboard uninitialized."
  ctx ← liftIO $ newContext name c sev $ Switchboard mockSwitchboard
  let logTrace0 = case outk of
    TVarList tvar → BaseTrace.natTrace liftIO $ traceInTVarIO tvar
    TVarListNamed tvar → BaseTrace.natTrace liftIO $ traceNamedInTVarIO tvar
  setSubTrace (configuration ctx) name (Just subTr)
  logTrace' ← subTrace "" (ctx, logTrace0)
  return logTrace'

setTransformer_ :: Trace IO → LoggerName → Maybe SubTrace → IO ()
setTransformer_ (ctx, _) name subtr = do
  let c = configuration ctx
  n = (loggerName ctx) <> "." <> name
  setSubTrace c n subtr

```

### Example of using named contexts with Trace

```

example_with_named_contexts :: IO String
example_with_named_contexts = do
  cfg ← defaultConfigTesting
  logTrace ← Setup.setupTrace (Right cfg) "test"
  putStrLn "\n"
  logInfo logTrace "entering"
  logTrace0 ← appendName "simple-work-0" logTrace
  work0 ← complexWork0 logTrace0 "0"
  logTrace1 ← appendName "complex-work-1" logTrace
  work1 ← complexWork1 logTrace1 "42"
  Async.wait work0
  Async.wait work1
  -- the named context will include "complex" in the logged message
  logInfo logTrace "done."
  threadDelay 1000
  return ""

where
  complexWork0 tr msg = Async.async $ logInfo tr ("let's see (0): " 'append' msg)
  complexWork1 tr msg = Async.async $ do
    logInfo tr ("let's see (1): " 'append' msg)
    trInner@(ctx, _) ← appendName "inner-work-1" tr
    let observablesSet = [MonotonicClock]
    setSubTrace (configuration ctx) "test.complex-work-1.inner-work-1.STM-action" $
      Just $ ObservableTrace observablesSet
    _ ← STMObserver.bracketObserveIO trInner "STM-action" setVar_
    logInfo trInner "let's see: done."
    -- logInfo logTrace' "let's see: done."

```

**Show effect of turning off observables**

```

run_timed_action :: Trace IO → IO Microsecond
run_timed_action logTrace = do
  runid ← newUnique
  t0 ← getMonoClock
  forM_ [1 :: Int..10] $ const $ observeAction logTrace
  t1 ← getMonoClock
  return $ diffTimeObserved (CounterState runid t0) (CounterState runid t1)
where
  observeAction trace = do
    _ ← MonadicObserver.bracketObserveIO trace "" action
    return ()
  action = return $ forM [1 :: Int..100] $ \_ → reverse [1 :: Int..1000]

timing_Observable_vs_Untimed :: Assertion
timing_Observable_vs_Untimed = do
  msgs1 ← STM.newTVarIO []
  traceObservable ← setupTrace $ TraceConfiguration
    (TVarList msgs1)
    "observables"
    (ObservableTrace observablesSet)
    Debug
  msgs2 ← STM.newTVarIO []
  traceUntimed ← setupTrace $ TraceConfiguration
    (TVarList msgs2)
    "no timing"
    UntimedTrace
    Debug
  msgs3 ← STM.newTVarIO []
  traceNoTrace ← setupTrace $ TraceConfiguration
    (TVarList msgs3)
    "no trace"
    NoTrace
    Debug
  t_observable ← run_timed_action traceObservable
  t_untimed ← run_timed_action traceUntimed
  t_notrace ← run_timed_action traceNoTrace
  assertBool
    ("Untimed consumed more time than ObservableTrace " ++ (show [t_untimed,t_observable]))
    (t_untimed < t_observable)
  assertBool
    ("NoTrace consumed more time than ObservableTrace" ++ (show [t_notrace,t_observable]))
    (t_notrace < t_observable)
  assertBool
    ("NoTrace consumed more time than Untimed" ++ (show [t_notrace,t_untimed]))
    True

```

where

```
observablesSet = [MonotonicClock, MemoryStats]
```

### Control tracing in a hierarchy of *Traces*

We can lay out traces in a hierarchical manner, that the children forward traced items to the parent *Trace*. A *NoTrace* introduced in this hierarchy will cut off a branch from messaging to the root.

```
unit_hierarchy :: Assertion
unit_hierarchy = do
  msgs ← STM.newTVarIO []
  trace0 ← setupTrace $ TraceConfiguration (TVarList msgs) "test" Neutral Debug
  logInfo trace0 "This should have been displayed!"
  -- subtrace of trace which traces nothing
  setTransformer_trace0 "inner" (Just NoTrace)
  trace1 ← subTrace "inner" trace0
  logInfo trace1 "This should NOT have been displayed!"
  setTransformer_trace1 "innermost" (Just Neutral)
  trace2 ← subTrace "innermost" trace1
  logInfo trace2 "This should NOT have been displayed also due to the trace one level above!"
  -- acquire the traced objects
  res ← STM.readTVarIO msgs
  -- only the first message should have been traced
  assertBool
    ("Found more or less messages than expected: " ++ show res)
    (length res == 1)
```

### Change a trace's minimum severity

A trace is configured with a minimum severity and filters out messages that are labelled with a lower severity. This minimum severity of the current trace can be changed.

```
unit_trace_min_severity :: Assertion
unit_trace_min_severity = do
  msgs ← STM.newTVarIO []
  trace@(ctx, _) ← setupTrace $ TraceConfiguration (TVarList msgs) "test min severity" Neutral Debug
  logInfo trace "Message #1"
  -- raise the minimum severity to Warning
  setMinSeverity (configuration ctx) Warning
  msev ← Cardano.BM.Configuration.minSeverity (configuration ctx)
  assertBool ("min severity should be Warning, but is " ++ (show msev))
    (msev == Warning)
  -- this message will not be traced
  logInfo trace "Message #2"
  -- lower the minimum severity to Info
```

```

setMinSeverity (configuration ctx) Info
-- this message is traced
logInfo trace "Message #3"
-- acquire the traced objects
res ← STM.readTVarIO msgs
-- only the first and last messages should have been traced
assertBool
  ("Found more or less messages than expected: " ++ show res)
  (length res ≡ 2)
assertBool
  ("Found Info message when Warning was minimum severity: " ++ show res)
  (all (λcase {(LP (LogMessage (LogItem _ Info "Message #2")) → False; _ → True}) res)

```

### Define a subtrace's behaviour to duplicate all messages

The *SubTrace* will duplicate all messages that pass through it. Each message will be in its own named context.

```

unit_trace_duplicate :: Assertion
unit_trace_duplicate = do
  msgs ← STM.newTVarIO []
  trace0@(ctx, _) ← setupTrace $ TraceConfiguration (TVarList msgs) "test duplicate" Neutral Debug
  logInfo trace0 "Message #1"
  -- create a subtrace which duplicates all messages
  setSubTrace (configuration ctx) "test duplicate.orig" $ Just (TeeTrace "dup")
  trace ← subTrace "orig" trace0
  -- this message will be duplicated
  logInfo trace "You will see me twice!"
  -- acquire the traced objects
  res ← STM.readTVarIO msgs
  -- only the first and last messages should have been traced
  assertBool
    ("Found more or less messages than expected: " ++ show res)
    (length res ≡ 3)

```

### Change the minimum severity of a named context

A trace of a named context can be configured with a minimum severity, such that the trace will filter out messages that are labelled with a lower severity.

```

unit_named_min_severity :: Assertion
unit_named_min_severity = do
  msgs ← STM.newTVarIO []
  trace0 ← setupTrace $ TraceConfiguration (TVarList msgs) "test named severity" Neutral Debug
  trace@(ctx, _) ← appendName "sev-change" trace0
  logInfo trace "Message #1"

```

```

-- raise the minimum severity to Warning
setSeverity (configuration ctx) (loggerName ctx) (Just Warning)
msev ← Cardano.BM.Configuration.inspectSeverity (configuration ctx) (loggerName ctx)
assertBool ("min severity should be Warning, but is " ++ (show msev))
  (msev ≡ Just Warning)
-- this message will not be traced
logInfo trace "Message #2"
-- lower the minimum severity to Info
setSeverity (configuration ctx) (loggerName ctx) (Just Info)
-- this message is traced
logInfo trace "Message #3"
-- acquire the traced objects
res ← STM.readTVarIO msgs
-- only the first and last messages should have been traced
assertBool
  ("Found more or less messages than expected: " ++ show res)
  (length res ≡ 2)
assertBool
  ("Found Info message when Warning was minimum severity: " ++ show res)
  (all (λcase {(LP (LogMessage (LogItem _ Info "Message #2")) → False; _ → True}) res)

```

```

unit_hierarchy' :: [SubTrace] → ([LogObject] → Bool) → Assertion
unit_hierarchy' subtraces f = do
  let (t1 : t2 : t3 : _) = cycle subtraces
  msgs ← STM.newTVarIO []
  -- create trace of type 1
  trace1 ← setupTrace $ TraceConfiguration (TVarList msgs) "test" t1 Debug
  logInfo trace1 "Message from level 1."
  -- subtrace of type 2
  setTransformer_trace1 "inner" (Just t2)
  trace2 ← subTrace "inner" trace1
  logInfo trace2 "Message from level 2."
  -- subsubtrace of type 3
  setTransformer_trace2 "innermost" (Just t3)
  _ ← STMObserver.bracketObserveIO trace2 "innermost" setVar_
  logInfo trace2 "Message from level 3."
  -- acquire the traced objects
  res ← STM.readTVarIO msgs
  -- only the first message should have been traced
  assertBool
    ("Found more or less messages than expected: " ++ show res)
    (f res)

```

**Logging in parallel**

```

unit_trace_in_fork :: Assertion
unit_trace_in_fork = do
  msgs ← STM.newTVarIO [ ]
  trace ← setupTrace $ TraceConfiguration (TVarListNamed msgs) "test" Neutral Debug
  trace0 ← appendName "work0" trace
  trace1 ← appendName "work1" trace
  work0 ← work trace0
  threadDelay 5000
  work1 ← work trace1
  Async.wait $ work0
  Async.wait $ work1
  res ← STM.readTVarIO msgs
  let names@(_ : namesTail) = map lnName res
  -- each trace should have its own name and log right after the other
  assertBool
    ("Consecutive loggernames are not different: " ++ show names)
    (and $ zipWith (≠) names namesTail)
where
  work :: Trace IO → IO (Async.Async ())
  work trace = Async.async $ do
    logInfoDelay trace "1"
    logInfoDelay trace "2"
    logInfoDelay trace "3"
  logInfoDelay :: Trace IO → Text → IO ()
  logInfoDelay trace msg =
    logInfo trace msg >>
    threadDelay 10000

```

**Stress testing parallel logging**

```

stress_trace_in_fork :: Assertion
stress_trace_in_fork = do
  msgs ← STM.newTVarIO [ ]
  trace ← setupTrace $ TraceConfiguration (TVarListNamed msgs) "test" Neutral Debug
  let names = map (λa → ("work-" <> pack (show a))) [1..(10 :: Int)]
  ts ← forM names $ λname → do
    trace' ← appendName name trace
    work trace'
  forM_ ts Async.wait
  res ← STM.readTVarIO msgs
  let resNames = map lnName res
  let frequencyMap = fromListWith (+) [(x, 1) | x ← resNames]
  -- each trace should have traced 'totalMessages' messages
  assertBool

```

```

    ("Frequencies of logged messages according to loggername: " ++ show frequencyMap)
    (all ( $\lambda$ name  $\rightarrow$  (lookup ("test." <> name) frequencyMap)  $\equiv$  Just totalMessages) names)
  where
    work :: Trace IO  $\rightarrow$  IO (Async.Async ())
    work trace = Async.async $ forM_ [1..totalMessages] $ (logInfo trace)  $\circ$  pack  $\circ$  show
    totalMessages :: Int
    totalMessages = 10

```

### Dropping ObserveOpen messages in a subtrace

```

unit_noOpening_Trace :: Assertion
unit_noOpening_Trace = do
  msgs  $\leftarrow$  STM.newTVarIO []
  logTrace  $\leftarrow$  setupTrace $ TraceConfiguration (TVarList msgs) "test" DropOpening Debug
  _  $\leftarrow$  STMObserver.bracketObserveIO logTrace "setTVar" setVar_
  res  $\leftarrow$  STM.readTVarIO msgs
  assertBool
    ("Found non-expected ObserveOpen message: " ++ show res)
    (all ( $\lambda$ case { ObserveOpen _  $\rightarrow$  False; _  $\rightarrow$  True }) res)

```

### Assert maximum length of log context name

The name of the log context cannot grow beyond a maximum number of characters, currently the limit is set to 80.

```

unit_append_name :: Assertion
unit_append_name = do
  cfg  $\leftarrow$  defaultConfigTesting
  trace0  $\leftarrow$  Setup.setupTrace (Right cfg) "test"
  trace1  $\leftarrow$  appendName bigName trace0
  (ctx2, _)  $\leftarrow$  appendName bigName trace1
  assertBool
    ("Found logger name with more than 80 chars: " ++ show (loggerName ctx2))
    (T.length (loggerName ctx2)  $\leq$  80)
  where
    bigName = T.replicate 30 "abcdefghijklmnopqrstuvwxy"

```

```

setVar_ :: STM.STM Integer
setVar_ = do
  t  $\leftarrow$  STM.newTVar 0
  STM.writeTVar t 42
  res  $\leftarrow$  STM.readTVar t
  return res

```



### 2.1.5 Testing configuration

#### Test declarations

```

tests :: TestTree
tests = testGroup "config tests" [
    property_tests
    , unit_tests
]

property_tests :: TestTree
property_tests = testGroup "Properties" [
    testProperty "minimal" prop_Configuration_minimal
]

unit_tests :: TestTree
unit_tests = testGroup "Unit tests" [
    testCase "static_representation" unit_Configuration_static_representation
    , testCase "parsed_representation" unit_Configuration_parsed_representation
    , testCase "parsed_configuration" unit_Configuration_parsed
    , testCase "include_EKG_if_defined" unit_Configuration_check_EKG_positive
    , testCase "not_include_EKG_if_ndef" unit_Configuration_check_EKG_negative
]

```

#### Property tests

```

prop_Configuration_minimal :: Bool
prop_Configuration_minimal = True

```

#### Unit tests

The configuration file only indicates that EKG is listening on port nnnnn. Infer that *EKGViewBK* needs to be started as a backend.

```

unit_Configuration_check_EKG_positive :: Assertion
unit_Configuration_check_EKG_positive = do
    let c = [ "rotation:"
        , "  rpLogLimitBytes: 5000000"
        , "  rpKeepFilesNum: 10"
        , "  rpMaxAgeHours: 24"
        , "minSeverity: Info"
        , "defaultBackends:"
        , "  - KatipBK"
        , "setupBackends:"
        , "  - KatipBK"
        , "defaultScribes:"
        , "  - - StdoutSK"
        , "  - stdout"
    ]

```

```

    , "setupScribes:"
    , "- scName: stdout"
    , "  scRotation: null"
    , "  scKind: StdoutSK"
    , "hasEKG: 18321"
    , "options:"
    , "  test:"
    , "    value: nothing"
  ]
  fp = "/tmp/test_ekgv_config.yaml"
  writeFile fp $unlines c
  repr ← parseRepresentation fp
  assertBool "expecting EKGViewBK to be setup" $
    EKGViewBK ∈ (setupBackends repr)

```

If there is no port defined for EKG, then do not start it even if present in the config.

```

unit.Configuration.check_EKG_negative :: Assertion
unit.Configuration.check_EKG_negative = do
  let c = [ "rotation:"
    , "  rpLogLimitBytes: 5000000"
    , "  rpKeepFilesNum: 10"
    , "  rpMaxAgeHours: 24"
    , "minSeverity: Info"
    , "defaultBackends:"
    , "  - KatipBK"
    , "  - EKGViewBK"
    , "setupBackends:"
    , "  - KatipBK"
    , "  - EKGViewBK"
    , "defaultScribes:"
    , "- - StdoutSK"
    , "  - stdout"
    , "setupScribes:"
    , "- scName: stdout"
    , "  scRotation: null"
    , "  scKind: StdoutSK"
    , "###hasEKG: 18321"
    , "options:"
    , "  test:"
    , "    value: nothing"
  ]
  fp = "/tmp/test_ekgv_config.yaml"
  writeFile fp $unlines c
  repr ← parseRepresentation fp
  assertBool "EKGViewBK shall not be setup" $
    ¬ $ EKGViewBK ∈ (setupBackends repr)

```

```

    assertBool "EKGViewBK shall not receive messages" $
        ¬$ EKGViewBK ∈ (defaultBackends repr)

unit_Configuration_static_representation :: Assertion
unit_Configuration_static_representation =
    let r = Representation
        { minSeverity = Info
        , rotation = RotationParameters 5000000 24 10
        , setupScribes =
            [ ScribeDefinition { scName = "stdout"
                               , scKind = StdoutSK
                               , scRotation = Nothing }
            ]
        , defaultScribes = [(StdoutSK, "stdout")]
        , setupBackends = [EKGViewBK, KatipBK]
        , defaultBackends = [KatipBK]
        , hasGUI = Just 12789
        , hasEKG = Just 18321
        , options =
            HM.fromList [("test1", (HM.singleton "value" "object1"))
                        , ("test2", (HM.singleton "value" "object2"))]
        }
    in
        encode r @? = ""
"rotation:\n"
"  rpLogLimitBytes: 5000000\n"
"  rpKeepFilesNum: 10\n"
"  rpMaxAgeHours: 24\n"
"defaultBackends:\n"
"- KatipBK\n"
"setupBackends:\n"
"- EKGViewBK\n"
"- KatipBK\n"
"hasGUI: 12789\n"
"defaultScribes:\n"
"- - StdoutSK\n"
"  - stdout\n"
"options:\n"
"  test2:\n"
"    value: object2\n"
"  test1:\n"
"    value: object1\n"
"setupScribes:\n"
"- scName: stdout\n"
"  scRotation: null\n"
"  scKind: StdoutSK\n"
"hasEKG: 18321\n"
"minSeverity: Info\n"

```

```

unit_Configuration_parsed_representation :: Assertion
unit_Configuration_parsed_representation = do
  repr ← parseRepresentation "test/config.yaml"
  encode repr @? = ""
  "rotation:\n"
  "  rpLogLimitBytes: 5000000\n"
  "  rpKeepFilesNum: 10\n"
  "  rpMaxAgeHours: 24\n"
  "defaultBackends:\n"
  "- KatipBK\n"
  "setupBackends:\n"
  "- AggregationBK\n"
  "- EKGViewBK\n"
  "- KatipBK\n"
  "hasGUI: null\n"
  "defaultScribes:\n"
  "- - StdoutSK\n"
  "  - stdout\n"
  "options:\n"
  "  mapSubtrace:\n"
  "    iohk.benchmarking:\n"
  "      tag: ObservableTrace\n"
  "      contents:\n"
  "        - GhcRtsStats\n"
  "        - MonotonicClock\n"
  "    iohk.deadend: NoTrace\n"
  "  mapSeverity:\n"
  "    iohk.startup: Debug\n"
  "    iohk.background.process: Error\n"
  "    iohk.testing.uncritical: Warning\n"
  "  mapAggregatedkinds:\n"
  "    iohk.interesting.value: EwmaAK {alpha = 0.75}\n"
  "    iohk.background.process: StatsAK\n"
  "  cfokey:\n"
  "    value: Release-1.0.0\n"
  "  mapScribes:\n"
  "    iohk.interesting.value:\n"
  "      - StdoutSK::stdout\n"
  "      - FileTextSK::testlog\n"
  "    iohk.background.process: FileTextSK::testlog\n"
  "  mapBackends:\n"
  "    iohk.interesting.value:\n"
  "      - EKGViewBK\n"
  "      - AggregationBK\n"
  "setupScribes:\n"
  "- scName: testlog\n"
  "  scRotation:\n"
  "    rpLogLimitBytes: 25000000\n"

```

```

"    rpKeepFilesNum: 3\n"
"    rpMaxAgeHours: 24\n"
"    scKind: FileTextSK\n"
"- scName: stdout\n"
"    scRotation: null\n"
"    scKind: StdoutSK\n"
"hasEKG: 12789\n"
"minSeverity: Info\n"
unit_Configuration_parsed :: Assertion
unit_Configuration_parsed = do
  cfg ← setup "test/config.yaml"
  cfgInternal ← readMVar $ getCG cfg
  cfgInternal @? = ConfigurationInternal
    {cgMinSeverity    = Info
    ,cgMapSeverity    = HM.fromList [("iohk.startup", Debug)
                                     ,("iohk.background.process", Error)
                                     ,("iohk.testing.uncritical", Warning)
                                    ]
    ,cgMapSubtrace    = HM.fromList [("iohk.benchmarking",
                                     ObservableTrace [GhcRtsStats, MonotonicClock])
                                     ,("iohk.deadend", NoTrace)
                                    ]
    ,cgOptions        = HM.fromList
      [("mapSubtrace",
        HM.fromList [("iohk.benchmarking",
                      Object (HM.fromList [("tag", String "ObservableTrace")
                                             ,("contents", Array $ V.fromList
                                               [String "GhcRtsStats"
                                                ,String "MonotonicClock" ] ])))
        ,("iohk.deadend", String "NoTrace")])
      ,("mapSeverity", HM.fromList [("iohk.startup", String "Debug")
                                     ,("iohk.background.process", String "Error")
                                     ,("iohk.testing.uncritical", String "Warning")])
      ,("mapAggregatedkinds", HM.fromList [("iohk.interesting.value",
                                             String "EwmaAK {alpha = 0.75}")
                                             ,("iohk.background.process",
                                             String "StatsAK")])
      ,("cfokey", HM.fromList [("value", String "Release-1.0.0")])
      ,("mapScribes", HM.fromList [("iohk.interesting.value",
                                     Array $ V.fromList [String "StdoutSK::stdout"
                                                           ,String "FileTextSK::testlog" ]
                                    )
                                     ,("iohk.background.process", String "FileTextSK::testlog")])
      ,("mapBackends", HM.fromList [("iohk.interesting.value",
                                     Array $ V.fromList [String "EKGViewBK"
                                                           ,String "AggregationBK" ]
                                    )])
    ]
  ,cgMapBackend      = HM.fromList [("iohk.interesting.value", [EKGViewBK, AggregationBK])]
```

```

, cgDefBackendKs = [KatipBK]
, cgSetupBackends = [AggregationBK, EKGViewBK, KatipBK]
, cgMapScribe     = HM.fromList [("iohk.interesting.value",
                                ["StdoutSK::stdout", "FileTextSK::testlog"])
                                , ("iohk.background.process", ["FileTextSK::testlog"])
                                ]
, cgDefScribes    = ["StdoutSK::stdout"]
, cgSetupScribes  = [ScribeDefinition
                     { scKind = FileTextSK
                     , scName = "testlog"
                     , scRotation = Just $ RotationParameters
                       { rpLogLimitBytes = 25000000
                       , rpMaxAgeHours = 24
                       , rpKeepFilesNum = 3
                       }
                     }
                     , ScribeDefinition
                     { scKind = StdoutSK
                     , scName = "stdout"
                     , scRotation = Nothing
                     }
                     ]
, cgMapAggregatedKind = HM.fromList [("iohk.interesting.value", EwmaAK {alpha = 0.75})
                                     , ("iohk.background.process", StatsAK)
                                     ]
, cgDefAggregatedKind = StatsAK
, cgPortEKG           = 12789
, cgPortGUI           = 0
}

```