



VOLUME 06

SHADERS, MATERIALS, ASSETS AND CONTENT PIPELINE

Shader toolchain, material system, asset registry, importers, derived data, cooking, packaging and editor asset workflows.

DOCUMENT CODE	SKEIN-IMP-002-V06
VERSION	0.1
STATUS	DRAFT CONSTRUCTION REFERENCE
PLANNED PAGES	175
CHAPTERS	15
DATE	30 July 2026

IMPLEMENTATION MANUAL / PRINT SET

Current architecture source: SKEIN-SPEC-001 v0.4 and SKEIN-IMP-002-MASTER v0.1

06.01 Shader source policy and compiler pipeline

Purpose and boundary: HLSL

This page defines the purpose and boundary for Shader source policy and compiler pipeline, with particular attention to HLSL. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

HLSL is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with DXC is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for HLSL; distinguish required behavior from illustrative implementation detail.
- Keep DXC behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and HLSL.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Architecture: DXC

This page defines the architecture for Shader source policy and compiler pipeline, with particular attention to DXC. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Dxc is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with DXIL is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for DXC; distinguish required behavior from illustrative implementation detail.
- Keep DXIL behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and DXC.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Data model: DXIL

This page defines the data model for Shader source policy and compiler pipeline, with particular attention to DXIL. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Dxil is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with SPIR-V is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for DXIL; distinguish required behavior from illustrative implementation detail.
- Keep SPIR-V behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and DXIL.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Public API: SPIR-V

This page defines the public api for Shader source policy and compiler pipeline, with particular attention to SPIR-V. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Spir-v is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with include graph is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for SPIR-V; distinguish required behavior from illustrative implementation detail.
- Keep include graph behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and SPIR-V.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Ownership and lifetime: include graph

This page defines the ownership and lifetime for Shader source policy and compiler pipeline, with particular attention to include graph. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Include graph is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with diagnostics is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for include graph; distinguish required behavior from illustrative implementation detail.
- Keep diagnostics behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and include graph.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Threading model: diagnostics

This page defines the threading model for Shader source policy and compiler pipeline, with particular attention to diagnostics. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Diagnostics is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with HLSL is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for diagnostics; distinguish required behavior from illustrative implementation detail.
- Keep HLSL behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and diagnostics.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Memory strategy: HLSL

This page defines the memory strategy for Shader source policy and compiler pipeline, with particular attention to HLSL. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

HLSL is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with DXC is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for HLSL; distinguish required behavior from illustrative implementation detail.
- Keep DXC behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and HLSL.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Failure handling: DXC

This page defines the failure handling for Shader source policy and compiler pipeline, with particular attention to DXC. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Dxc is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with DXIL is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for DXC; distinguish required behavior from illustrative implementation detail.
- Keep DXIL behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and DXC.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Diagnostics: DXIL

This page defines the diagnostics for Shader source policy and compiler pipeline, with particular attention to DXIL. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Dxil is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with SPIR-V is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for DXIL; distinguish required behavior from illustrative implementation detail.
- Keep SPIR-V behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and DXIL.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Implementation sequence: SPIR-V

This page defines the implementation sequence for Shader source policy and compiler pipeline, with particular attention to SPIR-V. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Spir-v is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with include graph is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for SPIR-V; distinguish required behavior from illustrative implementation detail.
- Keep include graph behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and SPIR-V.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Verification: include graph

This page defines the verification for Shader source policy and compiler pipeline, with particular attention to include graph. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Include graph is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with diagnostics is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for include graph; distinguish required behavior from illustrative implementation detail.
- Keep diagnostics behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and include graph.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Completion gate: diagnostics

This page defines the completion gate for Shader source policy and compiler pipeline, with particular attention to diagnostics. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Diagnostics is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with HLSL is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for diagnostics; distinguish required behavior from illustrative implementation detail.
- Keep HLSL behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and diagnostics.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Purpose and boundary: HLSL

This page defines the purpose and boundary for Shader source policy and compiler pipeline, with particular attention to HLSL. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

HLSL is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with DXC is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for HLSL; distinguish required behavior from illustrative implementation detail.
- Keep DXC behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and HLSL.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Architecture: DXC

This page defines the architecture for Shader source policy and compiler pipeline, with particular attention to DXC. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Dxc is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with DXIL is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for DXC; distinguish required behavior from illustrative implementation detail.
- Keep DXIL behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderSourcePolicy");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and DXC.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.01 Shader source policy and compiler pipeline

Data model: DXIL

This page defines the data model for Shader source policy and compiler pipeline, with particular attention to DXIL. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Dxil is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with SPIR-V is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for DXIL; distinguish required behavior from illustrative implementation detail.
- Keep SPIR-V behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderSourcePolicyService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderSourcePolicyConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderSourcePolicyState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.01 and DXIL.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Purpose and boundary: resources

This page defines the purpose and boundary for Shader reflection and binding metadata, with particular attention to resources. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Resources is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with constants is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for resources; distinguish required behavior from illustrative implementation detail.
- Keep constants behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderReflectionAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderReflectionAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderReflectionAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and resources.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Architecture: constants

This page defines the architecture for Shader reflection and binding metadata, with particular attention to constants. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Constants is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with vertex layouts is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for constants; distinguish required behavior from illustrative implementation detail.
- Keep vertex layouts behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderReflectionAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and constants.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Data model: vertex layouts

This page defines the data model for Shader reflection and binding metadata, with particular attention to vertex layouts. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Vertex layouts is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with validation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for vertex layouts; distinguish required behavior from illustrative implementation detail.
- Keep validation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderReflectionAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderReflectionAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderReflectionAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and vertex layouts.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Public API: validation

This page defines the public api for Shader reflection and binding metadata, with particular attention to validation. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Validation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with resources is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for validation; distinguish required behavior from illustrative implementation detail.
- Keep resources behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderReflectionAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and validation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Ownership and lifetime: resources

This page defines the ownership and lifetime for Shader reflection and binding metadata, with particular attention to resources. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Resources is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with constants is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for resources; distinguish required behavior from illustrative implementation detail.
- Keep constants behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderReflectionAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderReflectionAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderReflectionAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and resources.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Threading model: constants

This page defines the threading model for Shader reflection and binding metadata, with particular attention to constants. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Constants is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with vertex layouts is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for constants; distinguish required behavior from illustrative implementation detail.
- Keep vertex layouts behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderReflectionAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and constants.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Memory strategy: vertex layouts

This page defines the memory strategy for Shader reflection and binding metadata, with particular attention to vertex layouts. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Vertex layouts is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with validation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for vertex layouts; distinguish required behavior from illustrative implementation detail.
- Keep validation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderReflectionAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderReflectionAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderReflectionAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and vertex layouts.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Failure handling: validation

This page defines the failure handling for Shader reflection and binding metadata, with particular attention to validation. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Validation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with resources is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for validation; distinguish required behavior from illustrative implementation detail.
- Keep resources behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderReflectionAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and validation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Diagnostics: resources

This page defines the diagnostics for Shader reflection and binding metadata, with particular attention to resources. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Resources is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with constants is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for resources; distinguish required behavior from illustrative implementation detail.
- Keep constants behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderReflectionAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderReflectionAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderReflectionAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and resources.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Implementation sequence: constants

This page defines the implementation sequence for Shader reflection and binding metadata, with particular attention to constants. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Constants is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with vertex layouts is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for constants; distinguish required behavior from illustrative implementation detail.
- Keep vertex layouts behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Shader", "ShaderReflectionAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and constants.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.02 Shader reflection and binding metadata

Verification: vertex layouts

This page defines the verification for Shader reflection and binding metadata, with particular attention to vertex layouts. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Vertex layouts is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with validation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for vertex layouts; distinguish required behavior from illustrative implementation detail.
- Keep validation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ShaderReflectionAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ShaderReflectionAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ShaderReflectionAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.02 and vertex layouts.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Purpose and boundary: feature keys

This page defines the purpose and boundary for Permutation and pipeline cache strategy, with particular attention to feature keys. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Feature keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with variant pruning is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for feature keys; distinguish required behavior from illustrative implementation detail.
- Keep variant pruning behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and feature keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Architecture: variant pruning

This page defines the architecture for Permutation and pipeline cache strategy, with particular attention to variant pruning. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Variant pruning is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with warmup is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for variant pruning; distinguish required behavior from illustrative implementation detail.
- Keep warmup behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Permutation", "PermutationAndPipeline");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and variant pruning.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Data model: warmup

This page defines the data model for Permutation and pipeline cache strategy, with particular attention to warmup. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Warmup is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with disk cache is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for warmup; distinguish required behavior from illustrative implementation detail.
- Keep disk cache behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and warmup.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Public API: disk cache

This page defines the public api for Permutation and pipeline cache strategy, with particular attention to disk cache. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Disk cache is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with feature keys is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for disk cache; distinguish required behavior from illustrative implementation detail.
- Keep feature keys behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Permutation", "PermutationAndPipeline");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and disk cache.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Ownership and lifetime: feature keys

This page defines the ownership and lifetime for Permutation and pipeline cache strategy, with particular attention to feature keys. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Feature keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with variant pruning is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for feature keys; distinguish required behavior from illustrative implementation detail.
- Keep variant pruning behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and feature keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Threading model: variant pruning

This page defines the threading model for Permutation and pipeline cache strategy, with particular attention to variant pruning. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Variant pruning is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with warmup is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for variant pruning; distinguish required behavior from illustrative implementation detail.
- Keep warmup behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Permutation", "PermutationAndPipeline");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and variant pruning.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Memory strategy: warmup

This page defines the memory strategy for Permutation and pipeline cache strategy, with particular attention to warmup. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Warmup is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with disk cache is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for warmup; distinguish required behavior from illustrative implementation detail.
- Keep disk cache behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and warmup.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Failure handling: disk cache

This page defines the failure handling for Permutation and pipeline cache strategy, with particular attention to disk cache. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Disk cache is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with feature keys is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for disk cache; distinguish required behavior from illustrative implementation detail.
- Keep feature keys behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Permutation", "PermutationAndPipeline");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and disk cache.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Diagnostics: feature keys

This page defines the diagnostics for Permutation and pipeline cache strategy, with particular attention to feature keys. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Feature keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with variant pruning is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for feature keys; distinguish required behavior from illustrative implementation detail.
- Keep variant pruning behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and feature keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Implementation sequence: variant pruning

This page defines the implementation sequence for Permutation and pipeline cache strategy, with particular attention to variant pruning. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Variant pruning is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with warmup is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for variant pruning; distinguish required behavior from illustrative implementation detail.
- Keep warmup behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Permutation", "PermutationAndPipeline");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and variant pruning.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Verification: warmup

This page defines the verification for Permutation and pipeline cache strategy, with particular attention to warmup. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Warmup is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with disk cache is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for warmup; distinguish required behavior from illustrative implementation detail.
- Keep disk cache behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and warmup.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Completion gate: disk cache

This page defines the completion gate for Permutation and pipeline cache strategy, with particular attention to disk cache. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Disk cache is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with feature keys is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for disk cache; distinguish required behavior from illustrative implementation detail.
- Keep feature keys behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Permutation", "PermutationAndPipeline");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and disk cache.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.03 Permutation and pipeline cache strategy

Purpose and boundary: feature keys

This page defines the purpose and boundary for Permutation and pipeline cache strategy, with particular attention to feature keys. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Feature keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with variant pruning is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for feature keys; distinguish required behavior from illustrative implementation detail.
- Keep variant pruning behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PermutationAndPipelineService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PermutationAndPipelineConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PermutationAndPipelineState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.03 and feature keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Purpose and boundary: surface domains

This page defines the purpose and boundary for Material domain model, with particular attention to surface domains. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Surface domains is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with blend modes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for surface domains; distinguish required behavior from illustrative implementation detail.
- Keep blend modes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and surface domains.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Architecture: blend modes

This page defines the architecture for Material domain model, with particular attention to blend modes. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Blend modes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shading models is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for blend modes; distinguish required behavior from illustrative implementation detail.
- Keep shading models behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Material", "MaterialDomainModel");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and blend modes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Data model: shading models

This page defines the data model for Material domain model, with particular attention to shading models. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Shading models is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with two-sided is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shading models; distinguish required behavior from illustrative implementation detail.
- Keep two-sided behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and shading models.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Public API: two-sided

This page defines the public api for Material domain model, with particular attention to two-sided. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Two-sided is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with surface domains is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for two-sided; distinguish required behavior from illustrative implementation detail.
- Keep surface domains behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Material", "MaterialDomainModel");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and two-sided.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Ownership and lifetime: surface domains

This page defines the ownership and lifetime for Material domain model, with particular attention to surface domains. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Surface domains is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with blend modes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for surface domains; distinguish required behavior from illustrative implementation detail.
- Keep blend modes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and surface domains.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Threading model: blend modes

This page defines the threading model for Material domain model, with particular attention to blend modes. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Blend modes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shading models is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for blend modes; distinguish required behavior from illustrative implementation detail.
- Keep shading models behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Material", "MaterialDomainModel");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and blend modes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Memory strategy: shading models

This page defines the memory strategy for Material domain model, with particular attention to shading models. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Shading models is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with two-sided is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shading models; distinguish required behavior from illustrative implementation detail.
- Keep two-sided behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and shading models.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Failure handling: two-sided

This page defines the failure handling for Material domain model, with particular attention to two-sided. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Two-sided is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with surface domains is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for two-sided; distinguish required behavior from illustrative implementation detail.
- Keep surface domains behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Material", "MaterialDomainModel");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and two-sided.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Diagnostics: surface domains

This page defines the diagnostics for Material domain model, with particular attention to surface domains. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Surface domains is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with blend modes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for surface domains; distinguish required behavior from illustrative implementation detail.
- Keep blend modes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and surface domains.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Implementation sequence: blend modes

This page defines the implementation sequence for Material domain model, with particular attention to blend modes. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Blend modes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shading models is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for blend modes; distinguish required behavior from illustrative implementation detail.
- Keep shading models behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Material", "MaterialDomainModel");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and blend modes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Verification: shading models

This page defines the verification for Material domain model, with particular attention to shading models. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Shading models is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with two-sided is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shading models; distinguish required behavior from illustrative implementation detail.
- Keep two-sided behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and shading models.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Completion gate: two-sided

This page defines the completion gate for Material domain model, with particular attention to two-sided. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Two-sided is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with surface domains is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for two-sided; distinguish required behavior from illustrative implementation detail.
- Keep surface domains behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Material", "MaterialDomainModel");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and two-sided.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.04 Material domain model

Purpose and boundary: surface domains

This page defines the purpose and boundary for Material domain model, with particular attention to surface domains. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Surface domains is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with blend modes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for surface domains; distinguish required behavior from illustrative implementation detail.
- Keep blend modes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MaterialDomainModelService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MaterialDomainModelConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MaterialDomainModelState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.04 and surface domains.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Purpose and boundary: parameters

This page defines the purpose and boundary for Standard PBR material, with particular attention to parameters. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Parameters is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with textures is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for parameters; distinguish required behavior from illustrative implementation detail.
- Keep textures behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class StandardPbrMaterialService final
{
public:
    [[nodiscard]] Result<void> Initialise(const StandardPbrMaterialConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    StandardPbrMaterialState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and parameters.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Architecture: textures

This page defines the architecture for Standard PBR material, with particular attention to textures. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Textures is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with defaults is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for textures; distinguish required behavior from illustrative implementation detail.
- Keep defaults behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Standard", "StandardPbrMaterial");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and textures.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Data model: defaults

This page defines the data model for Standard PBR material, with particular attention to defaults. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Defaults is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with packing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for defaults; distinguish required behavior from illustrative implementation detail.
- Keep packing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class StandardPbrMaterialService final
{
public:
    [[nodiscard]] Result<void> Initialise(const StandardPbrMaterialConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    StandardPbrMaterialState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and defaults.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Public API: packing

This page defines the public api for Standard PBR material, with particular attention to packing. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Packing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with instances is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for packing; distinguish required behavior from illustrative implementation detail.
- Keep instances behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Standard", "StandardPbrMaterial");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and packing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Ownership and lifetime: instances

This page defines the ownership and lifetime for Standard PBR material, with particular attention to instances. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Instances is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with parameters is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for instances; distinguish required behavior from illustrative implementation detail.
- Keep parameters behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class StandardPbrMaterialService final
{
public:
    [[nodiscard]] Result<void> Initialise(const StandardPbrMaterialConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    StandardPbrMaterialState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and instances.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Threading model: parameters

This page defines the threading model for Standard PBR material, with particular attention to parameters. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Parameters is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with textures is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for parameters; distinguish required behavior from illustrative implementation detail.
- Keep textures behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Standard", "StandardPbrMaterial");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and parameters.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Memory strategy: textures

This page defines the memory strategy for Standard PBR material, with particular attention to textures. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Textures is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with defaults is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for textures; distinguish required behavior from illustrative implementation detail.
- Keep defaults behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class StandardPbrMaterialService final
{
public:
    [[nodiscard]] Result<void> Initialise(const StandardPbrMaterialConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    StandardPbrMaterialState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and textures.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Failure handling: defaults

This page defines the failure handling for Standard PBR material, with particular attention to defaults. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Defaults is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with packing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for defaults; distinguish required behavior from illustrative implementation detail.
- Keep packing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Standard", "StandardPbrMaterial");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and defaults.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Diagnostics: packing

This page defines the diagnostics for Standard PBR material, with particular attention to packing. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Packing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with instances is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for packing; distinguish required behavior from illustrative implementation detail.
- Keep instances behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class StandardPbrMaterialService final
{
public:
    [[nodiscard]] Result<void> Initialise(const StandardPbrMaterialConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    StandardPbrMaterialState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and packing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Implementation sequence: instances

This page defines the implementation sequence for Standard PBR material, with particular attention to instances. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Instances is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with parameters is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for instances; distinguish required behavior from illustrative implementation detail.
- Keep parameters behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Standard", "StandardPbrMaterial");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and instances.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.05 Standard PBR material

Verification: parameters

This page defines the verification for Standard PBR material, with particular attention to parameters. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Parameters is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with textures is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for parameters; distinguish required behavior from illustrative implementation detail.
- Keep textures behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class StandardPbrMaterialService final
{
public:
    [[nodiscard]] Result<void> Initialise(const StandardPbrMaterialConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    StandardPbrMaterialState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.05 and parameters.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Purpose and boundary: custom shaders

This page defines the purpose and boundary for Advanced shader-backed materials, with particular attention to custom shaders. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Custom shaders is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with safe extension is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for custom shaders; distinguish required behavior from illustrative implementation detail.
- Keep safe extension behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AdvancedShaderBackedService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AdvancedShaderBackedConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AdvancedShaderBackedState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and custom shaders.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Architecture: safe extension

This page defines the architecture for Advanced shader-backed materials, with particular attention to safe extension. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Safe extension is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fallbacks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for safe extension; distinguish required behavior from illustrative implementation detail.
- Keep fallbacks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Advanced", "AdvancedShaderBacked");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and safe extension.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Data model: fallbacks

This page defines the data model for Advanced shader-backed materials, with particular attention to fallbacks. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Fallbacks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with editor metadata is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for fallbacks; distinguish required behavior from illustrative implementation detail.
- Keep editor metadata behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AdvancedShaderBackedService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AdvancedShaderBackedConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AdvancedShaderBackedState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and fallbacks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Public API: editor metadata

This page defines the public api for Advanced shader-backed materials, with particular attention to editor metadata. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Editor metadata is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with custom shaders is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for editor metadata; distinguish required behavior from illustrative implementation detail.
- Keep custom shaders behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Advanced", "AdvancedShaderBacked");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and editor metadata.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Ownership and lifetime: custom shaders

This page defines the ownership and lifetime for Advanced shader-backed materials, with particular attention to custom shaders. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Custom shaders is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with safe extension is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for custom shaders; distinguish required behavior from illustrative implementation detail.
- Keep safe extension behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AdvancedShaderBackedService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AdvancedShaderBackedConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AdvancedShaderBackedState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and custom shaders.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Threading model: safe extension

This page defines the threading model for Advanced shader-backed materials, with particular attention to safe extension. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Safe extension is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fallbacks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for safe extension; distinguish required behavior from illustrative implementation detail.
- Keep fallbacks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Advanced", "AdvancedShaderBacked");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and safe extension.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Memory strategy: fallbacks

This page defines the memory strategy for Advanced shader-backed materials, with particular attention to fallbacks. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Fallbacks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with editor metadata is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for fallbacks; distinguish required behavior from illustrative implementation detail.
- Keep editor metadata behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AdvancedShaderBackedService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AdvancedShaderBackedConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AdvancedShaderBackedState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and fallbacks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Failure handling: editor metadata

This page defines the failure handling for Advanced shader-backed materials, with particular attention to editor metadata. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Editor metadata is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with custom shaders is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for editor metadata; distinguish required behavior from illustrative implementation detail.
- Keep custom shaders behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Advanced", "AdvancedShaderBacked");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and editor metadata.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Diagnostics: custom shaders

This page defines the diagnostics for Advanced shader-backed materials, with particular attention to custom shaders. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Custom shaders is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with safe extension is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for custom shaders; distinguish required behavior from illustrative implementation detail.
- Keep safe extension behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AdvancedShaderBackedService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AdvancedShaderBackedConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AdvancedShaderBackedState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and custom shaders.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.06 Advanced shader-backed materials

Implementation sequence: safe extension

This page defines the implementation sequence for Advanced shader-backed materials, with particular attention to safe extension. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Safe extension is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fallbacks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for safe extension; distinguish required behavior from illustrative implementation detail.
- Keep fallbacks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Advanced", "AdvancedShaderBacked");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.06 and safe extension.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Purpose and boundary: UUIDs

This page defines the purpose and boundary for Asset identity and registry, with particular attention to UUIDs. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Uuids is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with paths is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for UUIDs; distinguish required behavior from illustrative implementation detail.
- Keep paths behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and UUIDs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Architecture: paths

This page defines the architecture for Asset identity and registry, with particular attention to paths. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Paths is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with redirectors is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for paths; distinguish required behavior from illustrative implementation detail.
- Keep redirectors behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetIdentityAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and paths.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Data model: redirectors

This page defines the data model for Asset identity and registry, with particular attention to redirectors. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Redirectors is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with dependencies is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for redirectors; distinguish required behavior from illustrative implementation detail.
- Keep dependencies behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and redirectors.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Public API: dependencies

This page defines the public api for Asset identity and registry, with particular attention to dependencies. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Dependencies is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with tags is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for dependencies; distinguish required behavior from illustrative implementation detail.
- Keep tags behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetIdentityAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and dependencies.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Ownership and lifetime: tags

This page defines the ownership and lifetime for Asset identity and registry, with particular attention to tags. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Tags is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with UUIDs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for tags; distinguish required behavior from illustrative implementation detail.
- Keep UUIDs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and tags.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Threading model: UUIDs

This page defines the threading model for Asset identity and registry, with particular attention to UUIDs. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Uuids is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with paths is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for UUIDs; distinguish required behavior from illustrative implementation detail.
- Keep paths behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetIdentityAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and UUIDs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Memory strategy: paths

This page defines the memory strategy for Asset identity and registry, with particular attention to paths. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Paths is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with redirectors is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for paths; distinguish required behavior from illustrative implementation detail.
- Keep redirectors behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and paths.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Failure handling: redirectors

This page defines the failure handling for Asset identity and registry, with particular attention to redirectors. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Redirectors is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with dependencies is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for redirectors; distinguish required behavior from illustrative implementation detail.
- Keep dependencies behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetIdentityAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and redirectors.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Diagnostics: dependencies

This page defines the diagnostics for Asset identity and registry, with particular attention to dependencies. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Dependencies is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with tags is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for dependencies; distinguish required behavior from illustrative implementation detail.
- Keep tags behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and dependencies.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Implementation sequence: tags

This page defines the implementation sequence for Asset identity and registry, with particular attention to tags. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Tags is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with UUIDs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for tags; distinguish required behavior from illustrative implementation detail.
- Keep UUIDs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetIdentityAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and tags.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Verification: UUIDs

This page defines the verification for Asset identity and registry, with particular attention to UUIDs. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Uuids is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with paths is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for UUIDs; distinguish required behavior from illustrative implementation detail.
- Keep paths behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and UUIDs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Completion gate: paths

This page defines the completion gate for Asset identity and registry, with particular attention to paths. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Paths is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with redirectors is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for paths; distinguish required behavior from illustrative implementation detail.
- Keep redirectors behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetIdentityAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and paths.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.07 Asset identity and registry

Purpose and boundary: redirectors

This page defines the purpose and boundary for Asset identity and registry, with particular attention to redirectors. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Redirectors is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with dependencies is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for redirectors; distinguish required behavior from illustrative implementation detail.
- Keep dependencies behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetIdentityAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetIdentityAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetIdentityAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.07 and redirectors.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Purpose and boundary: source files

This page defines the purpose and boundary for Import pipeline architecture, with particular attention to source files. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Source files is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with import settings is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for source files; distinguish required behavior from illustrative implementation detail.
- Keep import settings behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and source files.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Architecture: import settings

This page defines the architecture for Import pipeline architecture, with particular attention to import settings. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Import settings is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with workers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for import settings; distinguish required behavior from illustrative implementation detail.
- Keep workers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and import settings.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Data model: workers

This page defines the data model for Import pipeline architecture, with particular attention to workers. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Workers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with cancellation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for workers; distinguish required behavior from illustrative implementation detail.
- Keep cancellation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and workers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Public API: cancellation

This page defines the public api for Import pipeline architecture, with particular attention to cancellation. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Cancellation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with reimport is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cancellation; distinguish required behavior from illustrative implementation detail.
- Keep reimport behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and cancellation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Ownership and lifetime: reimport

This page defines the ownership and lifetime for Import pipeline architecture, with particular attention to reimport. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Reimport is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with source files is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for reimport; distinguish required behavior from illustrative implementation detail.
- Keep source files behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and reimport.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Threading model: source files

This page defines the threading model for Import pipeline architecture, with particular attention to source files. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Source files is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with import settings is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for source files; distinguish required behavior from illustrative implementation detail.
- Keep import settings behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and source files.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Memory strategy: import settings

This page defines the memory strategy for Import pipeline architecture, with particular attention to import settings. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Import settings is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with workers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for import settings; distinguish required behavior from illustrative implementation detail.
- Keep workers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and import settings.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Failure handling: workers

This page defines the failure handling for Import pipeline architecture, with particular attention to workers. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Workers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with cancellation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for workers; distinguish required behavior from illustrative implementation detail.
- Keep cancellation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and workers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Diagnostics: cancellation

This page defines the diagnostics for Import pipeline architecture, with particular attention to cancellation. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Cancellation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with reimport is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cancellation; distinguish required behavior from illustrative implementation detail.
- Keep reimport behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and cancellation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Implementation sequence: reimport

This page defines the implementation sequence for Import pipeline architecture, with particular attention to reimport. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Reimport is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with source files is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for reimport; distinguish required behavior from illustrative implementation detail.
- Keep source files behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and reimport.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Verification: source files

This page defines the verification for Import pipeline architecture, with particular attention to source files. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Source files is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with import settings is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for source files; distinguish required behavior from illustrative implementation detail.
- Keep import settings behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and source files.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Completion gate: import settings

This page defines the completion gate for Import pipeline architecture, with particular attention to import settings. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Import settings is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with workers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for import settings; distinguish required behavior from illustrative implementation detail.
- Keep workers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and import settings.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Purpose and boundary: workers

This page defines the purpose and boundary for Import pipeline architecture, with particular attention to workers. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Workers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with cancellation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for workers; distinguish required behavior from illustrative implementation detail.
- Keep cancellation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and workers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Architecture: cancellation

This page defines the architecture for Import pipeline architecture, with particular attention to cancellation. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Cancellation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with reimport is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cancellation; distinguish required behavior from illustrative implementation detail.
- Keep reimport behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Import", "ImportPipelineArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and cancellation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.08 Import pipeline architecture

Data model: reimport

This page defines the data model for Import pipeline architecture, with particular attention to reimport. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Reimport is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with source files is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for reimport; distinguish required behavior from illustrative implementation detail.
- Keep source files behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ImportPipelineArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ImportPipelineArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ImportPipelineArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.08 and reimport.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Purpose and boundary: formats

This page defines the purpose and boundary for Texture import and processing, with particular attention to formats. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Formats is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with mips is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for formats; distinguish required behavior from illustrative implementation detail.
- Keep mips behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TextureImportAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TextureImportAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TextureImportAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and formats.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Architecture: mips

This page defines the architecture for Texture import and processing, with particular attention to mips. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Mips is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with compression is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for mips; distinguish required behavior from illustrative implementation detail.
- Keep compression behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Texture", "TextureImportAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and mips.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Data model: compression

This page defines the data model for Texture import and processing, with particular attention to compression. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Compression is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with colour space is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for compression; distinguish required behavior from illustrative implementation detail.
- Keep colour space behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TextureImportAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TextureImportAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TextureImportAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and compression.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Public API: colour space

This page defines the public api for Texture import and processing, with particular attention to colour space. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Colour space is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with virtual textures deferred is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for colour space; distinguish required behavior from illustrative implementation detail.
- Keep virtual textures deferred behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Texture", "TextureImportAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and colour space.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Ownership and lifetime: virtual textures deferred

This page defines the ownership and lifetime for Texture import and processing, with particular attention to virtual textures deferred. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Virtual textures deferred is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with formats is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for virtual textures deferred; distinguish required behavior from illustrative implementation detail.
- Keep formats behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TextureImportAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TextureImportAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TextureImportAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and virtual textures deferred.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Threading model: formats

This page defines the threading model for Texture import and processing, with particular attention to formats. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Formats is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with mips is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for formats; distinguish required behavior from illustrative implementation detail.
- Keep mips behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Texture", "TextureImportAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and formats.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Memory strategy: mips

This page defines the memory strategy for Texture import and processing, with particular attention to mips. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Mips is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with compression is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for mips; distinguish required behavior from illustrative implementation detail.
- Keep compression behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TextureImportAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TextureImportAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TextureImportAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and mips.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Failure handling: compression

This page defines the failure handling for Texture import and processing, with particular attention to compression. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Compression is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with colour space is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for compression; distinguish required behavior from illustrative implementation detail.
- Keep colour space behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Texture", "TextureImportAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and compression.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Diagnostics: colour space

This page defines the diagnostics for Texture import and processing, with particular attention to colour space. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Colour space is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with virtual textures deferred is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for colour space; distinguish required behavior from illustrative implementation detail.
- Keep virtual textures deferred behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TextureImportAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TextureImportAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TextureImportAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and colour space.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Implementation sequence: virtual textures deferred

This page defines the implementation sequence for Texture import and processing, with particular attention to virtual textures deferred. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Virtual textures deferred is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with formats is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for virtual textures deferred; distinguish required behavior from illustrative implementation detail.
- Keep formats behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Texture", "TextureImportAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and virtual textures deferred.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.09 Texture import and processing

Verification: formats

This page defines the verification for Texture import and processing, with particular attention to formats. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Formats is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with mips is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for formats; distinguish required behavior from illustrative implementation detail.
- Keep mips behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TextureImportAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TextureImportAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TextureImportAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.09 and formats.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Purpose and boundary: glTF

This page defines the purpose and boundary for Mesh and skeleton import, with particular attention to glTF. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

GlTF is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with coordinate conversion is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for glTF; distinguish required behavior from illustrative implementation detail.
- Keep coordinate conversion behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and glTF.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Architecture: coordinate conversion

This page defines the architecture for Mesh and skeleton import, with particular attention to coordinate conversion. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Coordinate conversion is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with LODs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for coordinate conversion; distinguish required behavior from illustrative implementation detail.
- Keep LODs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and coordinate conversion.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Data model: LODs

This page defines the data model for Mesh and skeleton import, with particular attention to LODs. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Lods is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with skin is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for LODs; distinguish required behavior from illustrative implementation detail.
- Keep skin behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and LODs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Public API: skin

This page defines the public api for Mesh and skeleton import, with particular attention to skin. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Skin is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with collision is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for skin; distinguish required behavior from illustrative implementation detail.
- Keep collision behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and skin.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Ownership and lifetime: collision

This page defines the ownership and lifetime for Mesh and skeleton import, with particular attention to collision. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Collision is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with glTF is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for collision; distinguish required behavior from illustrative implementation detail.
- Keep glTF behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and collision.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Threading model: glTF

This page defines the threading model for Mesh and skeleton import, with particular attention to glTF. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

GlTF is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with coordinate conversion is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for glTF; distinguish required behavior from illustrative implementation detail.
- Keep coordinate conversion behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and glTF.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Memory strategy: coordinate conversion

This page defines the memory strategy for Mesh and skeleton import, with particular attention to coordinate conversion. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Coordinate conversion is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with LODs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for coordinate conversion; distinguish required behavior from illustrative implementation detail.
- Keep LODs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and coordinate conversion.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Failure handling: LODs

This page defines the failure handling for Mesh and skeleton import, with particular attention to LODs. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Lods is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with skin is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for LODs; distinguish required behavior from illustrative implementation detail.
- Keep skin behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and LODs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Diagnostics: skin

This page defines the diagnostics for Mesh and skeleton import, with particular attention to skin. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Skin is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with collision is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for skin; distinguish required behavior from illustrative implementation detail.
- Keep collision behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and skin.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Implementation sequence: collision

This page defines the implementation sequence for Mesh and skeleton import, with particular attention to collision. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Collision is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with glTF is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for collision; distinguish required behavior from illustrative implementation detail.
- Keep glTF behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and collision.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Verification: glTF

This page defines the verification for Mesh and skeleton import, with particular attention to glTF. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

GlTF is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with coordinate conversion is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for glTF; distinguish required behavior from illustrative implementation detail.
- Keep coordinate conversion behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and glTF.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Completion gate: coordinate conversion

This page defines the completion gate for Mesh and skeleton import, with particular attention to coordinate conversion. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Coordinate conversion is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with LODs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for coordinate conversion; distinguish required behavior from illustrative implementation detail.
- Keep LODs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and coordinate conversion.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Purpose and boundary: LODs

This page defines the purpose and boundary for Mesh and skeleton import, with particular attention to LODs. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Lods is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with skin is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for LODs; distinguish required behavior from illustrative implementation detail.
- Keep skin behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and LODs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Architecture: skin

This page defines the architecture for Mesh and skeleton import, with particular attention to skin. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Skin is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with collision is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for skin; distinguish required behavior from illustrative implementation detail.
- Keep collision behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Mesh", "MeshAndSkeleton");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and skin.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.10 Mesh and skeleton import

Data model: collision

This page defines the data model for Mesh and skeleton import, with particular attention to collision. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Collision is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with glTF is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for collision; distinguish required behavior from illustrative implementation detail.
- Keep glTF behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MeshAndSkeletonService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MeshAndSkeletonConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MeshAndSkeletonState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.10 and collision.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Purpose and boundary: WAV

This page defines the purpose and boundary for Audio and miscellaneous importers, with particular attention to WAV. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Wav is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fonts is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for WAV; distinguish required behavior from illustrative implementation detail.
- Keep fonts behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AudioAndMiscellaneousService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AudioAndMiscellaneousConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AudioAndMiscellaneousState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and WAV.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Architecture: fonts

This page defines the architecture for Audio and miscellaneous importers, with particular attention to fonts. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Fonts is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with localization tables is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for fonts; distinguish required behavior from illustrative implementation detail.
- Keep localization tables behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Audio", "AudioAndMiscellaneous");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and fonts.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Data model: localization tables

This page defines the data model for Audio and miscellaneous importers, with particular attention to localization tables. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Localization tables is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with plugin importers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for localization tables; distinguish required behavior from illustrative implementation detail.
- Keep plugin importers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AudioAndMiscellaneousService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AudioAndMiscellaneousConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AudioAndMiscellaneousState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and localization tables.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Public API: plugin importers

This page defines the public api for Audio and miscellaneous importers, with particular attention to plugin importers. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Plugin importers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with WAV is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for plugin importers; distinguish required behavior from illustrative implementation detail.
- Keep WAV behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Audio", "AudioAndMiscellaneous");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and plugin importers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Ownership and lifetime: WAV

This page defines the ownership and lifetime for Audio and miscellaneous importers, with particular attention to WAV. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Wav is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fonts is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for WAV; distinguish required behavior from illustrative implementation detail.
- Keep fonts behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AudioAndMiscellaneousService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AudioAndMiscellaneousConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AudioAndMiscellaneousState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and WAV.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Threading model: fonts

This page defines the threading model for Audio and miscellaneous importers, with particular attention to fonts. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Fonts is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with localization tables is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for fonts; distinguish required behavior from illustrative implementation detail.
- Keep localization tables behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Audio", "AudioAndMiscellaneous");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and fonts.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Memory strategy: localization tables

This page defines the memory strategy for Audio and miscellaneous importers, with particular attention to localization tables. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Localization tables is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with plugin importers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for localization tables; distinguish required behavior from illustrative implementation detail.
- Keep plugin importers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AudioAndMiscellaneousService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AudioAndMiscellaneousConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AudioAndMiscellaneousState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and localization tables.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.11 Audio and miscellaneous importers

Failure handling: plugin importers

This page defines the failure handling for Audio and miscellaneous importers, with particular attention to plugin importers. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Plugin importers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with WAV is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for plugin importers; distinguish required behavior from illustrative implementation detail.
- Keep WAV behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Audio", "AudioAndMiscellaneous");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.11 and plugin importers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Purpose and boundary: keys

This page defines the purpose and boundary for Derived Data Cache, with particular attention to keys. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with local cache is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for keys; distinguish required behavior from illustrative implementation detail.
- Keep local cache behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class DerivedDataCacheService final
{
public:
    [[nodiscard]] Result<void> Initialise(const DerivedDataCacheConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    DerivedDataCacheState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Architecture: local cache

This page defines the architecture for Derived Data Cache, with particular attention to local cache. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Local cache is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with invalidation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for local cache; distinguish required behavior from illustrative implementation detail.
- Keep invalidation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Derived", "DerivedDataCache");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and local cache.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Data model: invalidation

This page defines the data model for Derived Data Cache, with particular attention to invalidation. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Invalidation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with cleanup is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for invalidation; distinguish required behavior from illustrative implementation detail.
- Keep cleanup behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class DerivedDataCacheService final
{
public:
    [[nodiscard]] Result<void> Initialise(const DerivedDataCacheConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    DerivedDataCacheState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and invalidation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Public API: cleanup

This page defines the public api for Derived Data Cache, with particular attention to cleanup. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Cleanup is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shared cache future is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cleanup; distinguish required behavior from illustrative implementation detail.
- Keep shared cache future behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Derived", "DerivedDataCache");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and cleanup.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Ownership and lifetime: shared cache future

This page defines the ownership and lifetime for Derived Data Cache, with particular attention to shared cache future. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Shared cache future is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with keys is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shared cache future; distinguish required behavior from illustrative implementation detail.
- Keep keys behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class DerivedDataCacheService final
{
public:
    [[nodiscard]] Result<void> Initialise(const DerivedDataCacheConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    DerivedDataCacheState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and shared cache future.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Threading model: keys

This page defines the threading model for Derived Data Cache, with particular attention to keys. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with local cache is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for keys; distinguish required behavior from illustrative implementation detail.
- Keep local cache behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Derived", "DerivedDataCache");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Memory strategy: local cache

This page defines the memory strategy for Derived Data Cache, with particular attention to local cache. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Local cache is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with invalidation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for local cache; distinguish required behavior from illustrative implementation detail.
- Keep invalidation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class DerivedDataCacheService final
{
public:
    [[nodiscard]] Result<void> Initialise(const DerivedDataCacheConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    DerivedDataCacheState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and local cache.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Failure handling: invalidation

This page defines the failure handling for Derived Data Cache, with particular attention to invalidation. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Invalidation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with cleanup is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for invalidation; distinguish required behavior from illustrative implementation detail.
- Keep cleanup behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Derived", "DerivedDataCache");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and invalidation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Diagnostics: cleanup

This page defines the diagnostics for Derived Data Cache, with particular attention to cleanup. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Cleanup is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shared cache future is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cleanup; distinguish required behavior from illustrative implementation detail.
- Keep shared cache future behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class DerivedDataCacheService final
{
public:
    [[nodiscard]] Result<void> Initialise(const DerivedDataCacheConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    DerivedDataCacheState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and cleanup.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Implementation sequence: shared cache future

This page defines the implementation sequence for Derived Data Cache, with particular attention to shared cache future. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Shared cache future is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with keys is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shared cache future; distinguish required behavior from illustrative implementation detail.
- Keep keys behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Derived", "DerivedDataCache");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and shared cache future.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.12 Derived Data Cache

Verification: keys

This page defines the verification for Derived Data Cache, with particular attention to keys. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Keys is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with local cache is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for keys; distinguish required behavior from illustrative implementation detail.
- Keep local cache behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class DerivedDataCacheService final
{
public:
    [[nodiscard]] Result<void> Initialise(const DerivedDataCacheConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    DerivedDataCacheState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.12 and keys.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Purpose and boundary: target data

This page defines the purpose and boundary for Cooking and packaging, with particular attention to target data. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Target data is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with archives is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for target data; distinguish required behavior from illustrative implementation detail.
- Keep archives behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and target data.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Architecture: archives

This page defines the architecture for Cooking and packaging, with particular attention to archives. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Archives is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with incremental cook is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for archives; distinguish required behavior from illustrative implementation detail.
- Keep incremental cook behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Cooking", "CookingAndPackaging");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and archives.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Data model: incremental cook

This page defines the data model for Cooking and packaging, with particular attention to incremental cook. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Incremental cook is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with integrity is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for incremental cook; distinguish required behavior from illustrative implementation detail.
- Keep integrity behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and incremental cook.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Public API: integrity

This page defines the public api for Cooking and packaging, with particular attention to integrity. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Integrity is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shipping layout is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for integrity; distinguish required behavior from illustrative implementation detail.
- Keep shipping layout behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Cooking", "CookingAndPackaging");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and integrity.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Ownership and lifetime: shipping layout

This page defines the ownership and lifetime for Cooking and packaging, with particular attention to shipping layout. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Shipping layout is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with target data is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shipping layout; distinguish required behavior from illustrative implementation detail.
- Keep target data behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and shipping layout.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Threading model: target data

This page defines the threading model for Cooking and packaging, with particular attention to target data. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Target data is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with archives is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for target data; distinguish required behavior from illustrative implementation detail.
- Keep archives behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Cooking", "CookingAndPackaging");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and target data.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Memory strategy: archives

This page defines the memory strategy for Cooking and packaging, with particular attention to archives. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Archives is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with incremental cook is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for archives; distinguish required behavior from illustrative implementation detail.
- Keep incremental cook behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and archives.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Failure handling: incremental cook

This page defines the failure handling for Cooking and packaging, with particular attention to incremental cook. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Incremental cook is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with integrity is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for incremental cook; distinguish required behavior from illustrative implementation detail.
- Keep integrity behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Cooking", "CookingAndPackaging");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and incremental cook.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Diagnostics: integrity

This page defines the diagnostics for Cooking and packaging, with particular attention to integrity. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Integrity is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shipping layout is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for integrity; distinguish required behavior from illustrative implementation detail.
- Keep shipping layout behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and integrity.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Implementation sequence: shipping layout

This page defines the implementation sequence for Cooking and packaging, with particular attention to shipping layout. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Shipping layout is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with target data is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shipping layout; distinguish required behavior from illustrative implementation detail.
- Keep target data behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Cooking", "CookingAndPackaging");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and shipping layout.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Verification: target data

This page defines the verification for Cooking and packaging, with particular attention to target data. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Target data is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with archives is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for target data; distinguish required behavior from illustrative implementation detail.
- Keep archives behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and target data.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Completion gate: archives

This page defines the completion gate for Cooking and packaging, with particular attention to archives. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Archives is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with incremental cook is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for archives; distinguish required behavior from illustrative implementation detail.
- Keep incremental cook behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Cooking", "CookingAndPackaging");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and archives.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.13 Cooking and packaging

Purpose and boundary: incremental cook

This page defines the purpose and boundary for Cooking and packaging, with particular attention to incremental cook. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Incremental cook is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with integrity is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for incremental cook; distinguish required behavior from illustrative implementation detail.
- Keep integrity behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class CookingAndPackagingService final
{
public:
    [[nodiscard]] Result<void> Initialise(const CookingAndPackagingConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    CookingAndPackagingState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.13 and incremental cook.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Purpose and boundary: thumbnails

This page defines the purpose and boundary for Asset browser and diagnostics, with particular attention to thumbnails. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Thumbnails is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with reference viewer is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for thumbnails; distinguish required behavior from illustrative implementation detail.
- Keep reference viewer behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetBrowserAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetBrowserAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetBrowserAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and thumbnails.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Architecture: reference viewer

This page defines the architecture for Asset browser and diagnostics, with particular attention to reference viewer. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Reference viewer is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with missing assets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for reference viewer; distinguish required behavior from illustrative implementation detail.
- Keep missing assets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetBrowserAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and reference viewer.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Data model: missing assets

This page defines the data model for Asset browser and diagnostics, with particular attention to missing assets. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Missing assets is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with audit is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for missing assets; distinguish required behavior from illustrative implementation detail.
- Keep audit behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetBrowserAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetBrowserAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetBrowserAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and missing assets.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Public API: audit

This page defines the public api for Asset browser and diagnostics, with particular attention to audit. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Audit is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with thumbnails is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for audit; distinguish required behavior from illustrative implementation detail.
- Keep thumbnails behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetBrowserAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and audit.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Ownership and lifetime: thumbnails

This page defines the ownership and lifetime for Asset browser and diagnostics, with particular attention to thumbnails. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Thumbnails is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with reference viewer is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for thumbnails; distinguish required behavior from illustrative implementation detail.
- Keep reference viewer behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetBrowserAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetBrowserAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetBrowserAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and thumbnails.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Threading model: reference viewer

This page defines the threading model for Asset browser and diagnostics, with particular attention to reference viewer. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Reference viewer is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with missing assets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for reference viewer; distinguish required behavior from illustrative implementation detail.
- Keep missing assets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetBrowserAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and reference viewer.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Memory strategy: missing assets

This page defines the memory strategy for Asset browser and diagnostics, with particular attention to missing assets. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Missing assets is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with audit is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for missing assets; distinguish required behavior from illustrative implementation detail.
- Keep audit behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AssetBrowserAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AssetBrowserAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AssetBrowserAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and missing assets.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.14 Asset browser and diagnostics

Failure handling: audit

This page defines the failure handling for Asset browser and diagnostics, with particular attention to audit. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Audit is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with thumbnails is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for audit; distinguish required behavior from illustrative implementation detail.
- Keep thumbnails behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Asset", "AssetBrowserAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.14 and audit.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Purpose and boundary: round trips

This page defines the purpose and boundary for Pipeline tests and acceptance, with particular attention to round trips. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Round trips is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with determinism is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for round trips; distinguish required behavior from illustrative implementation detail.
- Keep determinism behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PipelineTestsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PipelineTestsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PipelineTestsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and round trips.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Architecture: determinism

This page defines the architecture for Pipeline tests and acceptance, with particular attention to determinism. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Determinism is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with corruption is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for determinism; distinguish required behavior from illustrative implementation detail.
- Keep corruption behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Pipeline", "PipelineTestsAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and determinism.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Data model: corruption

This page defines the data model for Pipeline tests and acceptance, with particular attention to corruption. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Corruption is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with performance is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for corruption; distinguish required behavior from illustrative implementation detail.
- Keep performance behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PipelineTestsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PipelineTestsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PipelineTestsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and corruption.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Public API: performance

This page defines the public api for Pipeline tests and acceptance, with particular attention to performance. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Performance is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with licensing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for performance; distinguish required behavior from illustrative implementation detail.
- Keep licensing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Pipeline", "PipelineTestsAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and performance.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Ownership and lifetime: licensing

This page defines the ownership and lifetime for Pipeline tests and acceptance, with particular attention to licensing. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Licensing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with round trips is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for licensing; distinguish required behavior from illustrative implementation detail.
- Keep round trips behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PipelineTestsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PipelineTestsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PipelineTestsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and licensing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Threading model: round trips

This page defines the threading model for Pipeline tests and acceptance, with particular attention to round trips. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Round trips is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with determinism is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for round trips; distinguish required behavior from illustrative implementation detail.
- Keep determinism behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Pipeline", "PipelineTestsAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and round trips.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

06.15 Pipeline tests and acceptance

Memory strategy: determinism

This page defines the memory strategy for Pipeline tests and acceptance, with particular attention to determinism. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Determinism is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with corruption is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for determinism; distinguish required behavior from illustrative implementation detail.
- Keep corruption behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PipelineTestsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PipelineTestsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PipelineTestsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 06.15 and determinism.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.