



VOLUME 11

SKEININSIGHTS, DIAGNOSTICS AND PROFILING

SkeinTrace, trace transport and storage, analysis providers, timing views, memory, jobs, rendering, world streaming and network analysis.

DOCUMENT CODE	SKEIN-IMP-002-V11
VERSION	0.1
STATUS	DRAFT CONSTRUCTION REFERENCE
PLANNED PAGES	135
CHAPTERS	15
DATE	30 July 2026

IMPLEMENTATION MANUAL / PRINT SET

Current architecture source: SKEIN-SPEC-001 v0.4 and SKEIN-IMP-002-MASTER v0.1

11.01 Observability architecture

Purpose and boundary: trace/analysis/UI separation

This page defines the purpose and boundary for Observability architecture, with particular attention to trace/analysis/UI separation. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Trace/analysis/ui separation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with overhead budgets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for trace/analysis/UI separation; distinguish required behavior from illustrative implementation detail.
- Keep overhead budgets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ObservabilityArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ObservabilityArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ObservabilityArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and trace/analysis/UI separation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Architecture: overhead budgets

This page defines the architecture for Observability architecture, with particular attention to overhead budgets. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Overhead budgets is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shipping policy is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for overhead budgets; distinguish required behavior from illustrative implementation detail.
- Keep shipping policy behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Observability", "ObservabilityArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and overhead budgets.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Data model: shipping policy

This page defines the data model for Observability architecture, with particular attention to shipping policy. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Shipping policy is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with trace/analysis/UI separation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shipping policy; distinguish required behavior from illustrative implementation detail.
- Keep trace/analysis/UI separation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ObservabilityArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ObservabilityArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ObservabilityArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and shipping policy.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Public API: trace/analysis/UI separation

This page defines the public api for Observability architecture, with particular attention to trace/analysis/UI separation. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Trace/analysis/ui separation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with overhead budgets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for trace/analysis/UI separation; distinguish required behavior from illustrative implementation detail.
- Keep overhead budgets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Observability", "ObservabilityArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and trace/analysis/UI separation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Ownership and lifetime: overhead budgets

This page defines the ownership and lifetime for Observability architecture, with particular attention to overhead budgets. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Overhead budgets is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shipping policy is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for overhead budgets; distinguish required behavior from illustrative implementation detail.
- Keep shipping policy behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ObservabilityArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ObservabilityArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ObservabilityArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and overhead budgets.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Threading model: shipping policy

This page defines the threading model for Observability architecture, with particular attention to shipping policy. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Shipping policy is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with trace/analysis/UI separation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for shipping policy; distinguish required behavior from illustrative implementation detail.
- Keep trace/analysis/UI separation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Observability", "ObservabilityArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and shipping policy.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Memory strategy: trace/analysis/UI separation

This page defines the memory strategy for Observability architecture, with particular attention to trace/analysis/UI separation. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Trace/analysis/ui separation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with overhead budgets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for trace/analysis/UI separation; distinguish required behavior from illustrative implementation detail.
- Keep overhead budgets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class ObservabilityArchitectureService final
{
public:
    [[nodiscard]] Result<void> Initialise(const ObservabilityArchitectureConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    ObservabilityArchitectureState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and trace/analysis/UI separation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.01 Observability architecture

Failure handling: overhead budgets

This page defines the failure handling for Observability architecture, with particular attention to overhead budgets. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Overhead budgets is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with shipping policy is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for overhead budgets; distinguish required behavior from illustrative implementation detail.
- Keep shipping policy behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Observability", "ObservabilityArchitecture");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.01 and overhead budgets.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Purpose and boundary: event IDs

This page defines the purpose and boundary for Trace event schema, with particular attention to event IDs. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Event ids is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fields is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for event IDs; distinguish required behavior from illustrative implementation detail.
- Keep fields behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceEventSchemaService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceEventSchemaConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceEventSchemaState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and event IDs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Architecture: fields

This page defines the architecture for Trace event schema, with particular attention to fields. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Fields is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with metadata is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for fields; distinguish required behavior from illustrative implementation detail.
- Keep metadata behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceEventSchema");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and fields.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Data model: metadata

This page defines the data model for Trace event schema, with particular attention to metadata. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Metadata is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with self-description is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for metadata; distinguish required behavior from illustrative implementation detail.
- Keep self-description behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceEventSchemaService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceEventSchemaConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceEventSchemaState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and metadata.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Public API: self-description

This page defines the public api for Trace event schema, with particular attention to self-description. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Self-description is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with versions is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for self-description; distinguish required behavior from illustrative implementation detail.
- Keep versions behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceEventSchema");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and self-description.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Ownership and lifetime: versions

This page defines the ownership and lifetime for Trace event schema, with particular attention to versions. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Versions is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with event IDs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for versions; distinguish required behavior from illustrative implementation detail.
- Keep event IDs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceEventSchemaService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceEventSchemaConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceEventSchemaState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and versions.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Threading model: event IDs

This page defines the threading model for Trace event schema, with particular attention to event IDs. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Event ids is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with fields is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for event IDs; distinguish required behavior from illustrative implementation detail.
- Keep fields behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceEventSchema");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and event IDs.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Memory strategy: fields

This page defines the memory strategy for Trace event schema, with particular attention to fields. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Fields is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with metadata is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for fields; distinguish required behavior from illustrative implementation detail.
- Keep metadata behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceEventSchemaService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceEventSchemaConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceEventSchemaState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and fields.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Failure handling: metadata

This page defines the failure handling for Trace event schema, with particular attention to metadata. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Metadata is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with self-description is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for metadata; distinguish required behavior from illustrative implementation detail.
- Keep self-description behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceEventSchema");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and metadata.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Diagnostics: self-description

This page defines the diagnostics for Trace event schema, with particular attention to self-description. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Self-description is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with versions is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for self-description; distinguish required behavior from illustrative implementation detail.
- Keep versions behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceEventSchemaService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceEventSchemaConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceEventSchemaState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and self-description.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.02 Trace event schema

Implementation sequence: versions

This page defines the implementation sequence for Trace event schema, with particular attention to versions. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Versions is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with event IDs is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for versions; distinguish required behavior from illustrative implementation detail.
- Keep event IDs behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceEventSchema");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.02 and versions.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Purpose and boundary: lock avoidance

This page defines the purpose and boundary for Per-thread trace buffers, with particular attention to lock avoidance. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Lock avoidance is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with buffering is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for lock avoidance; distinguish required behavior from illustrative implementation detail.
- Keep buffering behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PerThreadTraceService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PerThreadTraceConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PerThreadTraceState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and lock avoidance.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Architecture: buffering

This page defines the architecture for Per-thread trace buffers, with particular attention to buffering. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Buffering is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with timestamps is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for buffering; distinguish required behavior from illustrative implementation detail.
- Keep timestamps behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Per", "PerThreadTrace");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and buffering.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Data model: timestamps

This page defines the data model for Per-thread trace buffers, with particular attention to timestamps. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Timestamps is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with loss accounting is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for timestamps; distinguish required behavior from illustrative implementation detail.
- Keep loss accounting behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PerThreadTraceService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PerThreadTraceConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PerThreadTraceState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and timestamps.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Public API: loss accounting

This page defines the public api for Per-thread trace buffers, with particular attention to loss accounting. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Loss accounting is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with flush is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for loss accounting; distinguish required behavior from illustrative implementation detail.
- Keep flush behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Per", "PerThreadTrace");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and loss accounting.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Ownership and lifetime: flush

This page defines the ownership and lifetime for Per-thread trace buffers, with particular attention to flush. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Flush is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with lock avoidance is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for flush; distinguish required behavior from illustrative implementation detail.
- Keep lock avoidance behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PerThreadTraceService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PerThreadTraceConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PerThreadTraceState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and flush.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Threading model: lock avoidance

This page defines the threading model for Per-thread trace buffers, with particular attention to lock avoidance. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Lock avoidance is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with buffering is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for lock avoidance; distinguish required behavior from illustrative implementation detail.
- Keep buffering behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Per", "PerThreadTrace");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and lock avoidance.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Memory strategy: buffering

This page defines the memory strategy for Per-thread trace buffers, with particular attention to buffering. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Buffering is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with timestamps is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for buffering; distinguish required behavior from illustrative implementation detail.
- Keep timestamps behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PerThreadTraceService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PerThreadTraceConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PerThreadTraceState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and buffering.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Failure handling: timestamps

This page defines the failure handling for Per-thread trace buffers, with particular attention to timestamps. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Timestamps is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with loss accounting is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for timestamps; distinguish required behavior from illustrative implementation detail.
- Keep loss accounting behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Per", "PerThreadTrace");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and timestamps.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Diagnostics: loss accounting

This page defines the diagnostics for Per-thread trace buffers, with particular attention to loss accounting. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Loss accounting is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with flush is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for loss accounting; distinguish required behavior from illustrative implementation detail.
- Keep flush behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PerThreadTraceService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PerThreadTraceConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PerThreadTraceState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and loss accounting.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Implementation sequence: flush

This page defines the implementation sequence for Per-thread trace buffers, with particular attention to flush. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Flush is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with lock avoidance is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for flush; distinguish required behavior from illustrative implementation detail.
- Keep lock avoidance behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Per", "PerThreadTrace");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and flush.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Verification: lock avoidance

This page defines the verification for Per-thread trace buffers, with particular attention to lock avoidance. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Lock avoidance is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with buffering is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for lock avoidance; distinguish required behavior from illustrative implementation detail.
- Keep buffering behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class PerThreadTraceService final
{
public:
    [[nodiscard]] Result<void> Initialise(const PerThreadTraceConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    PerThreadTraceState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and lock avoidance.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.03 Per-thread trace buffers

Completion gate: buffering

This page defines the completion gate for Per-thread trace buffers, with particular attention to buffering. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Buffering is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with timestamps is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for buffering; distinguish required behavior from illustrative implementation detail.
- Keep timestamps behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Per", "PerThreadTrace");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.03 and buffering.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Purpose and boundary: channels

This page defines the purpose and boundary for Trace channels and presets, with particular attention to channels. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Channels is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with runtime toggles is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for channels; distinguish required behavior from illustrative implementation detail.
- Keep runtime toggles behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceChannelsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceChannelsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceChannelsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and channels.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Architecture: runtime toggles

This page defines the architecture for Trace channels and presets, with particular attention to runtime toggles. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Runtime toggles is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with command line is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for runtime toggles; distinguish required behavior from illustrative implementation detail.
- Keep command line behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceChannelsAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and runtime toggles.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Data model: command line

This page defines the data model for Trace channels and presets, with particular attention to command line. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Command line is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with project presets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for command line; distinguish required behavior from illustrative implementation detail.
- Keep project presets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceChannelsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceChannelsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceChannelsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and command line.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Public API: project presets

This page defines the public api for Trace channels and presets, with particular attention to project presets. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Project presets is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with channels is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for project presets; distinguish required behavior from illustrative implementation detail.
- Keep channels behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceChannelsAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and project presets.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Ownership and lifetime: channels

This page defines the ownership and lifetime for Trace channels and presets, with particular attention to channels. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Channels is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with runtime toggles is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for channels; distinguish required behavior from illustrative implementation detail.
- Keep runtime toggles behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceChannelsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceChannelsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceChannelsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and channels.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Threading model: runtime toggles

This page defines the threading model for Trace channels and presets, with particular attention to runtime toggles. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Runtime toggles is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with command line is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for runtime toggles; distinguish required behavior from illustrative implementation detail.
- Keep command line behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Trace", "TraceChannelsAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and runtime toggles.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.04 Trace channels and presets

Memory strategy: command line

This page defines the memory strategy for Trace channels and presets, with particular attention to command line. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Command line is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with project presets is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for command line; distinguish required behavior from illustrative implementation detail.
- Keep project presets behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TraceChannelsAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TraceChannelsAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TraceChannelsAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.04 and command line.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Purpose and boundary: local/remote

This page defines the purpose and boundary for Transport, TraceServer and files, with particular attention to local/remote. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Local/remote is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with framing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for local/remote; distinguish required behavior from illustrative implementation detail.
- Keep framing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TransportTraceserverAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TransportTraceserverAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TransportTraceserverAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and local/remote.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Architecture: framing

This page defines the architecture for Transport, TraceServer and files, with particular attention to framing. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Framing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with storage is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for framing; distinguish required behavior from illustrative implementation detail.
- Keep storage behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Transport", "TransportTraceserverAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and framing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Data model: storage

This page defines the data model for Transport, TraceServer and files, with particular attention to storage. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Storage is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with rotation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for storage; distinguish required behavior from illustrative implementation detail.
- Keep rotation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TransportTraceserverAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TransportTraceserverAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TransportTraceserverAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and storage.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Public API: rotation

This page defines the public api for Transport, TraceServer and files, with particular attention to rotation. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Rotation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with recovery is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for rotation; distinguish required behavior from illustrative implementation detail.
- Keep recovery behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Transport", "TransportTraceserverAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and rotation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Ownership and lifetime: recovery

This page defines the ownership and lifetime for Transport, TraceServer and files, with particular attention to recovery. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Recovery is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with local/remote is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for recovery; distinguish required behavior from illustrative implementation detail.
- Keep local/remote behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TransportTraceserverAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TransportTraceserverAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TransportTraceserverAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and recovery.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Threading model: local/remote

This page defines the threading model for Transport, TraceServer and files, with particular attention to local/remote. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Local/remote is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with framing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for local/remote; distinguish required behavior from illustrative implementation detail.
- Keep framing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Transport", "TransportTraceserverAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and local/remote.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Memory strategy: framing

This page defines the memory strategy for Transport, TraceServer and files, with particular attention to framing. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Framing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with storage is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for framing; distinguish required behavior from illustrative implementation detail.
- Keep storage behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TransportTraceserverAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TransportTraceserverAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TransportTraceserverAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and framing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Failure handling: storage

This page defines the failure handling for Transport, TraceServer and files, with particular attention to storage. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Storage is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with rotation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for storage; distinguish required behavior from illustrative implementation detail.
- Keep rotation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Transport", "TransportTraceserverAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and storage.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Diagnostics: rotation

This page defines the diagnostics for Transport, TraceServer and files, with particular attention to rotation. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Rotation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with recovery is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for rotation; distinguish required behavior from illustrative implementation detail.
- Keep recovery behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TransportTraceserverAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TransportTraceserverAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TransportTraceserverAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and rotation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Implementation sequence: recovery

This page defines the implementation sequence for Transport, TraceServer and files, with particular attention to recovery. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Recovery is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with local/remote is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for recovery; distinguish required behavior from illustrative implementation detail.
- Keep local/remote behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Transport", "TransportTraceserverAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and recovery.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Verification: local/remote

This page defines the verification for Transport, TraceServer and files, with particular attention to local/remote. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Local/remote is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with framing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for local/remote; distinguish required behavior from illustrative implementation detail.
- Keep framing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TransportTraceserverAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TransportTraceserverAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TransportTraceserverAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and local/remote.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.05 Transport, TraceServer and files

Completion gate: framing

This page defines the completion gate for Transport, TraceServer and files, with particular attention to framing. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Framing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with storage is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for framing; distinguish required behavior from illustrative implementation detail.
- Keep storage behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Transport", "TransportTraceserverAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.05 and framing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Purpose and boundary: session model

This page defines the purpose and boundary for Analysis framework and providers, with particular attention to session model. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Session model is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with indexes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for session model; distinguish required behavior from illustrative implementation detail.
- Keep indexes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AnalysisFrameworkAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AnalysisFrameworkAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AnalysisFrameworkAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and session model.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Architecture: indexes

This page defines the architecture for Analysis framework and providers, with particular attention to indexes. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Indexes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with queries is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for indexes; distinguish required behavior from illustrative implementation detail.
- Keep queries behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Analysis", "AnalysisFrameworkAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and indexes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Data model: queries

This page defines the data model for Analysis framework and providers, with particular attention to queries. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Queries is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with extensibility is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for queries; distinguish required behavior from illustrative implementation detail.
- Keep extensibility behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AnalysisFrameworkAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AnalysisFrameworkAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AnalysisFrameworkAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and queries.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Public API: extensibility

This page defines the public api for Analysis framework and providers, with particular attention to extensibility. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Extensibility is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with session model is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for extensibility; distinguish required behavior from illustrative implementation detail.
- Keep session model behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Analysis", "AnalysisFrameworkAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and extensibility.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Ownership and lifetime: session model

This page defines the ownership and lifetime for Analysis framework and providers, with particular attention to session model. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Session model is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with indexes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for session model; distinguish required behavior from illustrative implementation detail.
- Keep indexes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AnalysisFrameworkAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AnalysisFrameworkAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AnalysisFrameworkAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and session model.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Threading model: indexes

This page defines the threading model for Analysis framework and providers, with particular attention to indexes. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Indexes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with queries is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for indexes; distinguish required behavior from illustrative implementation detail.
- Keep queries behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Analysis", "AnalysisFrameworkAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and indexes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Memory strategy: queries

This page defines the memory strategy for Analysis framework and providers, with particular attention to queries. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Queries is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with extensibility is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for queries; distinguish required behavior from illustrative implementation detail.
- Keep extensibility behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AnalysisFrameworkAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AnalysisFrameworkAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AnalysisFrameworkAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and queries.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Failure handling: extensibility

This page defines the failure handling for Analysis framework and providers, with particular attention to extensibility. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Extensibility is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with session model is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for extensibility; distinguish required behavior from illustrative implementation detail.
- Keep session model behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Analysis", "AnalysisFrameworkAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and extensibility.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Diagnostics: session model

This page defines the diagnostics for Analysis framework and providers, with particular attention to session model. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Session model is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with indexes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for session model; distinguish required behavior from illustrative implementation detail.
- Keep indexes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class AnalysisFrameworkAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const AnalysisFrameworkAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    AnalysisFrameworkAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and session model.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.06 Analysis framework and providers

Implementation sequence: indexes

This page defines the implementation sequence for Analysis framework and providers, with particular attention to indexes. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Indexes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with queries is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for indexes; distinguish required behavior from illustrative implementation detail.
- Keep queries behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Analysis", "AnalysisFrameworkAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.06 and indexes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Purpose and boundary: CPU lanes

This page defines the purpose and boundary for Timing and frame analysis, with particular attention to CPU lanes. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Cpu lanes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with frames is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for CPU lanes; distinguish required behavior from illustrative implementation detail.
- Keep frames behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TimingAndFrameService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TimingAndFrameConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TimingAndFrameState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and CPU lanes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Architecture: frames

This page defines the architecture for Timing and frame analysis, with particular attention to frames. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Frames is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with scopes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for frames; distinguish required behavior from illustrative implementation detail.
- Keep scopes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Timing", "TimingAndFrame");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and frames.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Data model: scopes

This page defines the data model for Timing and frame analysis, with particular attention to scopes. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Scopes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with aggregation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for scopes; distinguish required behavior from illustrative implementation detail.
- Keep aggregation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TimingAndFrameService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TimingAndFrameConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TimingAndFrameState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and scopes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Public API: aggregation

This page defines the public api for Timing and frame analysis, with particular attention to aggregation. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Aggregation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with critical path is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for aggregation; distinguish required behavior from illustrative implementation detail.
- Keep critical path behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Timing", "TimingAndFrame");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and aggregation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Ownership and lifetime: critical path

This page defines the ownership and lifetime for Timing and frame analysis, with particular attention to critical path. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Critical path is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with CPU lanes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for critical path; distinguish required behavior from illustrative implementation detail.
- Keep CPU lanes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TimingAndFrameService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TimingAndFrameConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TimingAndFrameState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and critical path.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Threading model: CPU lanes

This page defines the threading model for Timing and frame analysis, with particular attention to CPU lanes. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Cpu lanes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with frames is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for CPU lanes; distinguish required behavior from illustrative implementation detail.
- Keep frames behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Timing", "TimingAndFrame");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and CPU lanes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Memory strategy: frames

This page defines the memory strategy for Timing and frame analysis, with particular attention to frames. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Frames is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with scopes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for frames; distinguish required behavior from illustrative implementation detail.
- Keep scopes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TimingAndFrameService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TimingAndFrameConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TimingAndFrameState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and frames.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Failure handling: scopes

This page defines the failure handling for Timing and frame analysis, with particular attention to scopes. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Scopes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with aggregation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for scopes; distinguish required behavior from illustrative implementation detail.
- Keep aggregation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Timing", "TimingAndFrame");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and scopes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Diagnostics: aggregation

This page defines the diagnostics for Timing and frame analysis, with particular attention to aggregation. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Aggregation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with critical path is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for aggregation; distinguish required behavior from illustrative implementation detail.
- Keep critical path behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TimingAndFrameService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TimingAndFrameConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TimingAndFrameState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and aggregation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Implementation sequence: critical path

This page defines the implementation sequence for Timing and frame analysis, with particular attention to critical path. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Critical path is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with CPU lanes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for critical path; distinguish required behavior from illustrative implementation detail.
- Keep CPU lanes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Timing", "TimingAndFrame");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and critical path.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Verification: CPU lanes

This page defines the verification for Timing and frame analysis, with particular attention to CPU lanes. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Cpu lanes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with frames is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for CPU lanes; distinguish required behavior from illustrative implementation detail.
- Keep frames behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TimingAndFrameService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TimingAndFrameConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TimingAndFrameState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and CPU lanes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.07 Timing and frame analysis

Completion gate: frames

This page defines the completion gate for Timing and frame analysis, with particular attention to frames. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Frames is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with scopes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for frames; distinguish required behavior from illustrative implementation detail.
- Keep scopes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Timing", "TimingAndFrame");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.07 and frames.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Purpose and boundary: queues

This page defines the purpose and boundary for Job-system analysis, with particular attention to queues. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Queues is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with waits is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for queues; distinguish required behavior from illustrative implementation detail.
- Keep waits behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class JobSystemAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const JobSystemAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    JobSystemAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and queues.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Architecture: waits

This page defines the architecture for Job-system analysis, with particular attention to waits. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Waits is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with steals is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for waits; distinguish required behavior from illustrative implementation detail.
- Keep steals behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Job", "JobSystemAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and waits.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Data model: steals

This page defines the data model for Job-system analysis, with particular attention to steals. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Steals is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with utilisation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for steals; distinguish required behavior from illustrative implementation detail.
- Keep utilisation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class JobSystemAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const JobSystemAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    JobSystemAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and steals.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Public API: utilisation

This page defines the public api for Job-system analysis, with particular attention to utilisation. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Utilisation is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with dependency graph is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for utilisation; distinguish required behavior from illustrative implementation detail.
- Keep dependency graph behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Job", "JobSystemAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and utilisation.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Ownership and lifetime: dependency graph

This page defines the ownership and lifetime for Job-system analysis, with particular attention to dependency graph. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Dependency graph is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with queues is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for dependency graph; distinguish required behavior from illustrative implementation detail.
- Keep queues behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class JobSystemAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const JobSystemAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    JobSystemAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and dependency graph.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Threading model: queues

This page defines the threading model for Job-system analysis, with particular attention to queues. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Queues is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with waits is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for queues; distinguish required behavior from illustrative implementation detail.
- Keep waits behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Job", "JobSystemAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and queues.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Memory strategy: waits

This page defines the memory strategy for Job-system analysis, with particular attention to waits. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Waits is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with steals is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for waits; distinguish required behavior from illustrative implementation detail.
- Keep steals behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class JobSystemAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const JobSystemAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    JobSystemAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and waits.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.08 Job-system analysis

Failure handling: steals

This page defines the failure handling for Job-system analysis, with particular attention to steals. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Steals is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with utilisation is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for steals; distinguish required behavior from illustrative implementation detail.
- Keep utilisation behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Job", "JobSystemAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.08 and steals.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Purpose and boundary: alloc/free

This page defines the purpose and boundary for Memory analysis, with particular attention to alloc/free. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Alloc/free is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with tags is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for alloc/free; distinguish required behavior from illustrative implementation detail.
- Keep tags behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MemoryAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MemoryAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MemoryAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and alloc/free.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Architecture: tags

This page defines the architecture for Memory analysis, with particular attention to tags. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Tags is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with call stacks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for tags; distinguish required behavior from illustrative implementation detail.
- Keep call stacks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Memory", "MemoryAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and tags.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Data model: call stacks

This page defines the data model for Memory analysis, with particular attention to call stacks. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Call stacks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with lifetimes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for call stacks; distinguish required behavior from illustrative implementation detail.
- Keep lifetimes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MemoryAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MemoryAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MemoryAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and call stacks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Public API: lifetimes

This page defines the public api for Memory analysis, with particular attention to lifetimes. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Lifetimes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with leaks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for lifetimes; distinguish required behavior from illustrative implementation detail.
- Keep leaks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Memory", "MemoryAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and lifetimes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Ownership and lifetime: leaks

This page defines the ownership and lifetime for Memory analysis, with particular attention to leaks. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Leaks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with comparison is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for leaks; distinguish required behavior from illustrative implementation detail.
- Keep comparison behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MemoryAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MemoryAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MemoryAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and leaks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Threading model: comparison

This page defines the threading model for Memory analysis, with particular attention to comparison. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Comparison is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with alloc/free is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for comparison; distinguish required behavior from illustrative implementation detail.
- Keep alloc/free behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Memory", "MemoryAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and comparison.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Memory strategy: alloc/free

This page defines the memory strategy for Memory analysis, with particular attention to alloc/free. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Alloc/free is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with tags is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for alloc/free; distinguish required behavior from illustrative implementation detail.
- Keep tags behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MemoryAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MemoryAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MemoryAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and alloc/free.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Failure handling: tags

This page defines the failure handling for Memory analysis, with particular attention to tags. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Tags is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with call stacks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for tags; distinguish required behavior from illustrative implementation detail.
- Keep call stacks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Memory", "MemoryAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and tags.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Diagnostics: call stacks

This page defines the diagnostics for Memory analysis, with particular attention to call stacks. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Call stacks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with lifetimes is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for call stacks; distinguish required behavior from illustrative implementation detail.
- Keep lifetimes behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MemoryAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MemoryAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MemoryAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and call stacks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Implementation sequence: lifetimes

This page defines the implementation sequence for Memory analysis, with particular attention to lifetimes. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Lifetimes is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with leaks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for lifetimes; distinguish required behavior from illustrative implementation detail.
- Keep leaks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Memory", "MemoryAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and lifetimes.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Verification: leaks

This page defines the verification for Memory analysis, with particular attention to leaks. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract defines unit, integration, stress, performance, and cross-compiler evidence.

Leaks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to establish its inputs, validate state transitions, and bound failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with comparison is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for leaks; distinguish required behavior from illustrative implementation detail.
- Keep comparison behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class MemoryAnalysisService final
{
public:
    [[nodiscard]] Result<void> Initialise(const MemoryAnalysisConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    MemoryAnalysisState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and leaks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.09 Memory analysis

Completion gate: comparison

This page defines the completion gate for Memory analysis, with particular attention to comparison. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract lists the objective criteria that permit dependent chapters to begin.

Comparison is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to enforce its inputs, isolate state transitions, and expose failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with alloc/free is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for comparison; distinguish required behavior from illustrative implementation detail.
- Keep alloc/free behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Memory", "MemoryAnalysis");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.09 and comparison.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Purpose and boundary: render graph

This page defines the purpose and boundary for Rendering and GPU analysis, with particular attention to render graph. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Render graph is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with queues is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for render graph; distinguish required behavior from illustrative implementation detail.
- Keep queues behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class RenderingAndGpuService final
{
public:
    [[nodiscard]] Result<void> Initialise(const RenderingAndGpuConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    RenderingAndGpuState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and render graph.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Architecture: queues

This page defines the architecture for Rendering and GPU analysis, with particular attention to queues. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Queues is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with draws is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for queues; distinguish required behavior from illustrative implementation detail.
- Keep draws behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Rendering", "RenderingAndGpu");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and queues.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Data model: draws

This page defines the data model for Rendering and GPU analysis, with particular attention to draws. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Draws is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with resources is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for draws; distinguish required behavior from illustrative implementation detail.
- Keep resources behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class RenderingAndGpuService final
{
public:
    [[nodiscard]] Result<void> Initialise(const RenderingAndGpuConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    RenderingAndGpuState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and draws.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Public API: resources

This page defines the public api for Rendering and GPU analysis, with particular attention to resources. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Resources is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with frame pacing is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for resources; distinguish required behavior from illustrative implementation detail.
- Keep frame pacing behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Rendering", "RenderingAndGpu");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and resources.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Ownership and lifetime: frame pacing

This page defines the ownership and lifetime for Rendering and GPU analysis, with particular attention to frame pacing. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Frame pacing is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with render graph is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for frame pacing; distinguish required behavior from illustrative implementation detail.
- Keep render graph behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class RenderingAndGpuService final
{
public:
    [[nodiscard]] Result<void> Initialise(const RenderingAndGpuConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    RenderingAndGpuState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and frame pacing.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Threading model: render graph

This page defines the threading model for Rendering and GPU analysis, with particular attention to render graph. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Render graph is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with queues is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for render graph; distinguish required behavior from illustrative implementation detail.
- Keep queues behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Rendering", "RenderingAndGpu");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and render graph.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Memory strategy: queues

This page defines the memory strategy for Rendering and GPU analysis, with particular attention to queues. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Queues is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with draws is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for queues; distinguish required behavior from illustrative implementation detail.
- Keep draws behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class RenderingAndGpuService final
{
public:
    [[nodiscard]] Result<void> Initialise(const RenderingAndGpuConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    RenderingAndGpuState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and queues.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.10 Rendering and GPU analysis

Failure handling: draws

This page defines the failure handling for Rendering and GPU analysis, with particular attention to draws. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Draws is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with resources is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for draws; distinguish required behavior from illustrative implementation detail.
- Keep resources behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Rendering", "RenderingAndGpu");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.10 and draws.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Purpose and boundary: cells

This page defines the purpose and boundary for World streaming and asset analysis, with particular attention to cells. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Cells is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with I/O is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cells; distinguish required behavior from illustrative implementation detail.
- Keep I/O behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class WorldStreamingAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const WorldStreamingAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    WorldStreamingAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and cells.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Architecture: I/O

This page defines the architecture for World streaming and asset analysis, with particular attention to I/O. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

I/o is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with residency is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for I/O; distinguish required behavior from illustrative implementation detail.
- Keep residency behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("World", "WorldStreamingAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and I/O.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Data model: residency

This page defines the data model for World streaming and asset analysis, with particular attention to residency. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Residency is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with dependencies is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for residency; distinguish required behavior from illustrative implementation detail.
- Keep dependencies behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class WorldStreamingAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const WorldStreamingAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    WorldStreamingAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and residency.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Public API: dependencies

This page defines the public api for World streaming and asset analysis, with particular attention to dependencies. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Dependencies is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with stalls is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for dependencies; distinguish required behavior from illustrative implementation detail.
- Keep stalls behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("World", "WorldStreamingAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and dependencies.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Ownership and lifetime: stalls

This page defines the ownership and lifetime for World streaming and asset analysis, with particular attention to stalls. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Stalls is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with cells is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for stalls; distinguish required behavior from illustrative implementation detail.
- Keep cells behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class WorldStreamingAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const WorldStreamingAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    WorldStreamingAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and stalls.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Threading model: cells

This page defines the threading model for World streaming and asset analysis, with particular attention to cells. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Cells is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with I/O is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for cells; distinguish required behavior from illustrative implementation detail.
- Keep I/O behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("World", "WorldStreamingAnd");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and cells.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.11 World streaming and asset analysis

Memory strategy: I/O

This page defines the memory strategy for World streaming and asset analysis, with particular attention to I/O. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

I/o is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with residency is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for I/O; distinguish required behavior from illustrative implementation detail.
- Keep residency behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class WorldStreamingAndService final
{
public:
    [[nodiscard]] Result<void> Initialise(const WorldStreamingAndConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    WorldStreamingAndState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.11 and I/O.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Purpose and boundary: connections

This page defines the purpose and boundary for Network and Starcore analysis, with particular attention to connections. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Connections is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with messages is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for connections; distinguish required behavior from illustrative implementation detail.
- Keep messages behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class NetworkAndStarcoreService final
{
public:
    [[nodiscard]] Result<void> Initialise(const NetworkAndStarcoreConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    NetworkAndStarcoreState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and connections.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Architecture: messages

This page defines the architecture for Network and Starcore analysis, with particular attention to messages. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Messages is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with bandwidth is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for messages; distinguish required behavior from illustrative implementation detail.
- Keep bandwidth behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Network", "NetworkAndStarcore");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and messages.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Data model: bandwidth

This page defines the data model for Network and Starcore analysis, with particular attention to bandwidth. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Bandwidth is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with RTT is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for bandwidth; distinguish required behavior from illustrative implementation detail.
- Keep RTT behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class NetworkAndStarcoreService final
{
public:
    [[nodiscard]] Result<void> Initialise(const NetworkAndStarcoreConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    NetworkAndStarcoreState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and bandwidth.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Public API: RTT

This page defines the public api for Network and Starcore analysis, with particular attention to RTT. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Rtt is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with server markers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for RTT; distinguish required behavior from illustrative implementation detail.
- Keep server markers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Network", "NetworkAndStarcore");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and RTT.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Ownership and lifetime: server markers

This page defines the ownership and lifetime for Network and Starcore analysis, with particular attention to server markers. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Server markers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with connections is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for server markers; distinguish required behavior from illustrative implementation detail.
- Keep connections behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class NetworkAndStarcoreService final
{
public:
    [[nodiscard]] Result<void> Initialise(const NetworkAndStarcoreConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    NetworkAndStarcoreState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and server markers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Threading model: connections

This page defines the threading model for Network and Starcore analysis, with particular attention to connections. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Connections is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with messages is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for connections; distinguish required behavior from illustrative implementation detail.
- Keep messages behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Network", "NetworkAndStarcore");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and connections.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.12 Network and Starcore analysis

Memory strategy: messages

This page defines the memory strategy for Network and Starcore analysis, with particular attention to messages. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Messages is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with bandwidth is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for messages; distinguish required behavior from illustrative implementation detail.
- Keep bandwidth behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class NetworkAndStarcoreService final
{
public:
    [[nodiscard]] Result<void> Initialise(const NetworkAndStarcoreConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    NetworkAndStarcoreState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.12 and messages.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Purpose and boundary: session browser

This page defines the purpose and boundary for SkeinInsights application UI, with particular attention to session browser. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Session browser is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with live capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for session browser; distinguish required behavior from illustrative implementation detail.
- Keep live capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class SkeininsightsApplicationService final
{
public:
    [[nodiscard]] Result<void> Initialise(const SkeininsightsApplicationConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    SkeininsightsApplicationState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and session browser.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Architecture: live capture

This page defines the architecture for SkeinInsights application UI, with particular attention to live capture. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Live capture is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with views is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for live capture; distinguish required behavior from illustrative implementation detail.
- Keep views behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Skeininsights", "SkeininsightsApplication");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and live capture.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Data model: views

This page defines the data model for SkeinInsights application UI, with particular attention to views. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Views is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with filters is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for views; distinguish required behavior from illustrative implementation detail.
- Keep filters behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class SkeininsightsApplicationService final
{
public:
    [[nodiscard]] Result<void> Initialise(const SkeininsightsApplicationConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    SkeininsightsApplicationState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and views.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Public API: filters

This page defines the public api for SkeinInsights application UI, with particular attention to filters. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Filters is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with exports is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for filters; distinguish required behavior from illustrative implementation detail.
- Keep exports behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Skeininsights", "SkeininsightsApplication");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and filters.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Ownership and lifetime: exports

This page defines the ownership and lifetime for SkeinInsights application UI, with particular attention to exports. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Exports is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with session browser is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for exports; distinguish required behavior from illustrative implementation detail.
- Keep session browser behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class SkeininsightsApplicationService final
{
public:
    [[nodiscard]] Result<void> Initialise(const SkeininsightsApplicationConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    SkeininsightsApplicationState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and exports.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Threading model: session browser

This page defines the threading model for SkeinInsights application UI, with particular attention to session browser. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Session browser is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with live capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for session browser; distinguish required behavior from illustrative implementation detail.
- Keep live capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Skeininsights", "SkeininsightsApplication");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and session browser.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Memory strategy: live capture

This page defines the memory strategy for SkeinInsights application UI, with particular attention to live capture. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Live capture is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with views is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for live capture; distinguish required behavior from illustrative implementation detail.
- Keep views behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class SkeininsightsApplicationService final
{
public:
    [[nodiscard]] Result<void> Initialise(const SkeininsightsApplicationConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    SkeininsightsApplicationState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and live capture.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Failure handling: views

This page defines the failure handling for SkeinInsights application UI, with particular attention to views. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract defines validation, recoverable errors, fatal conditions, rollback, and degraded operation.

Views is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to reject its inputs, establish state transitions, and validate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with filters is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for views; distinguish required behavior from illustrative implementation detail.
- Keep filters behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Skeininsights", "SkeininsightsApplication");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and views.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Diagnostics: filters

This page defines the diagnostics for SkeinInsights application UI, with particular attention to filters. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract identifies logs, counters, trace events, debug views, and evidence needed to understand behavior.

Filters is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to instrument its inputs, enforce state transitions, and isolate failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with exports is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for filters; distinguish required behavior from illustrative implementation detail.
- Keep exports behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class SkeininsightsApplicationService final
{
public:
    [[nodiscard]] Result<void> Initialise(const SkeininsightsApplicationConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    SkeininsightsApplicationState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and filters.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.13 SkeinInsights application UI

Implementation sequence: exports

This page defines the implementation sequence for SkeinInsights application UI, with particular attention to exports. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract orders the work so each step produces a testable vertical slice without premature abstraction.

Exports is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to document its inputs, record state transitions, and measure failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with session browser is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for exports; distinguish required behavior from illustrative implementation detail.
- Keep session browser behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Skeininsights", "SkeininsightsApplication");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.13 and exports.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Purpose and boundary: hitch triggers

This page defines the purpose and boundary for Triggered and circular capture, with particular attention to hitch triggers. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Hitch triggers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with assert/crash capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for hitch triggers; distinguish required behavior from illustrative implementation detail.
- Keep assert/crash capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TriggeredAndCircularService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TriggeredAndCircularConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TriggeredAndCircularState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and hitch triggers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Architecture: assert/crash capture

This page defines the architecture for Triggered and circular capture, with particular attention to assert/crash capture. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Assert/crash capture is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with headless capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for assert/crash capture; distinguish required behavior from illustrative implementation detail.
- Keep headless capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Triggered", "TriggeredAndCircular");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and assert/crash capture.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Data model: headless capture

This page defines the data model for Triggered and circular capture, with particular attention to headless capture. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Headless capture is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with hitch triggers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for headless capture; distinguish required behavior from illustrative implementation detail.
- Keep hitch triggers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TriggeredAndCircularService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TriggeredAndCircularConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TriggeredAndCircularState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and headless capture.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Public API: hitch triggers

This page defines the public api for Triggered and circular capture, with particular attention to hitch triggers. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Hitch triggers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with assert/crash capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for hitch triggers; distinguish required behavior from illustrative implementation detail.
- Keep assert/crash capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Triggered", "TriggeredAndCircular");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and hitch triggers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Ownership and lifetime: assert/crash capture

This page defines the ownership and lifetime for Triggered and circular capture, with particular attention to assert/crash capture. The implementation must be recoverable, deterministic, and independently verifiable under MSVC and clang-cl. The contract assigns creation, retention, transfer, invalidation, and destruction responsibilities.

Assert/crash capture is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to bound its inputs, reject state transitions, and establish failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with headless capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for assert/crash capture; distinguish required behavior from illustrative implementation detail.
- Keep headless capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TriggeredAndCircularService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TriggeredAndCircularConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TriggeredAndCircularState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and assert/crash capture.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Threading model: headless capture

This page defines the threading model for Triggered and circular capture, with particular attention to headless capture. The implementation must be plugin-safe, versioned, and independently verifiable under MSVC and clang-cl. The contract defines thread affinity, parallel work, synchronization points, cancellation, and shutdown behavior.

Headless capture is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to expose its inputs, instrument state transitions, and enforce failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with hitch triggers is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for headless capture; distinguish required behavior from illustrative implementation detail.
- Keep hitch triggers behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Triggered", "TriggeredAndCircular");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and headless capture.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.14 Triggered and circular capture

Memory strategy: hitch triggers

This page defines the memory strategy for Triggered and circular capture, with particular attention to hitch triggers. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract sets allocation domains, budgets, transient storage, pooling, and diagnostic tags.

Hitch triggers is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to preserve its inputs, document state transitions, and record failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with assert/crash capture is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for hitch triggers; distinguish required behavior from illustrative implementation detail.
- Keep assert/crash capture behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class TriggeredAndCircularService final
{
public:
    [[nodiscard]] Result<void> Initialise(const TriggeredAndCircularConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    TriggeredAndCircularState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.14 and hitch triggers.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.15 Overhead and correctness gate

Purpose and boundary: benchmarks

This page defines the purpose and boundary for Overhead and correctness gate, with particular attention to benchmarks. The implementation must be explicit, allocation-aware, and independently verifiable under MSVC and clang-cl. The contract defines what the subsystem owns, what it deliberately excludes, and the observable contract consumed by dependent modules.

Benchmarks is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to record its inputs, measure state transitions, and preserve failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with lost events is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for benchmarks; distinguish required behavior from illustrative implementation detail.
- Keep lost events behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class OverheadAndCorrectnessService final
{
public:
    [[nodiscard]] Result<void> Initialise(const OverheadAndCorrectnessConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    OverheadAndCorrectnessState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.15 and benchmarks.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.15 Overhead and correctness gate

Architecture: lost events

This page defines the architecture for Overhead and correctness gate, with particular attention to lost events. The implementation must be thread-safe, portable, and independently verifiable under MSVC and clang-cl. The contract maps responsibilities into modules, services, data flows, and explicit dependency edges.

Lost events is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to validate its inputs, bound state transitions, and reject failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with clock tests is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for lost events; distinguish required behavior from illustrative implementation detail.
- Keep clock tests behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Overhead", "OverheadAndCorrectness");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.15 and lost events.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.15 Overhead and correctness gate

Data model: clock tests

This page defines the data model for Overhead and correctness gate, with particular attention to clock tests. The implementation must be diagnosable, bounded, and independently verifiable under MSVC and clang-cl. The contract specifies the stable types, identifiers, descriptors, records, and state transitions required by the implementation.

Clock tests is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to isolate its inputs, expose state transitions, and instrument failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with large traces is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for clock tests; distinguish required behavior from illustrative implementation detail.
- Keep large traces behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
class OverheadAndCorrectnessService final
{
public:
    [[nodiscard]] Result<void> Initialise(const OverheadAndCorrectnessConfig& config);
    void Tick(const FrameContext& frame);
    void Shutdown() noexcept;
private:
    OverheadAndCorrectnessState m_state{};
};
```

REQUIRED EVIDENCE

- A focused test named for 11.15 and clock tests.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.

11.15 Overhead and correctness gate

Public API: large traces

This page defines the public api for Overhead and correctness gate, with particular attention to large traces. The implementation must be testable, cache-conscious, and independently verifiable under MSVC and clang-cl. The contract defines caller-visible functions, result semantics, invariants, and versioning expectations.

Large traces is treated as an owned engineering concern rather than an incidental detail. The chapter requires the implementation to measure its inputs, preserve state transitions, and document failure evidence. No caller may depend on private storage layout, backend-specific handles, undocumented thread behavior, or allocator side effects.

The primary interaction with benchmarks is expressed through stable descriptors and handles. Dependent modules consume immutable descriptions or narrow service interfaces; they do not reach into internal containers. All externally visible identifiers remain valid only for their documented generation and lifetime, and stale references must fail predictably in development builds.

Implementation work should begin with the smallest executable path that proves the contract: configuration, construction, one successful operation, one deliberate failure, shutdown, and retained diagnostics. Optimizations follow only after the baseline is covered by tests and SkeinTrace markers. Performance changes must preserve behavior and include before/after evidence.

DESIGN OBLIGATIONS

- Define the normative contract for large traces; distinguish required behavior from illustrative implementation detail.
- Keep benchmarks behind SKEIN-owned interfaces so third-party or platform code cannot leak into callers.
- Assign each mutable field to one owning thread or protect it with a documented synchronization primitive.
- Tag persistent, transient, frame, and scratch allocations separately; expose budgets through diagnostics.

```
SKEIN_TRACE_SCOPE("Overhead", "OverheadAndCorrectness");
SKEIN_ASSERT(IsOnExpectedThread());
auto result = Validate(description);
if (!result)
    return Unexpected(result.Error());
```

REQUIRED EVIDENCE

- A focused test named for 11.15 and large traces.
- SkeinTrace events showing startup, operation, failure, and shutdown.
- Allocation and thread-affinity assertions enabled in Debug.
- Build and test results for msvc-debug, msvc-release, clang-debug, and clang-release.