Proposed Reduction Rules — Verification Notes

Mathematical Foundations for Implementation

Reference document for GitHub issues in the problem-reductions project

Abstract. This document formalizes nine reduction rules between NP-hard problems, providing complete construction algorithms, bidirectional correctness proofs, solution extraction procedures, and worked examples. Two reductions (§ 2) extend the NP-hardness proof chain from 3-SAT, potentially increasing the verified reachable count from 29 to 40+. The remaining seven (§ 3–5) resolve blockers in previously incomplete GitHub issues. Each entry is detailed enough to serve as a direct specification for implementation.

Contents

1 Notation and Conventions . . . 2
2 NP-Hardness Chain Extensions . . . 3
  2.1 SubsetSum → Partition . . . 3
  2.2 Minimum Vertex Cover → Hamiltonian Circuit . . . 4
  2.3 Vertex Cover → Hamiltonian Path . . . 6
3 Graph Reductions . . . 7
  3.1 MaxCut → Optimal Linear Arrangement . . . 7
  3.2 Optimal Linear Arrangement → Rooted Tree Arrangement . . . 9
4 Set and Domination Reductions . . . 11
  4.1 Dominating Set → Min-Max Multicenter . . . 11
  4.2 Dominating Set → Min-Sum Multicenter . . . 12

1 Notation and Conventions

Throughout this document we use the following conventions:

- $G = (V, E)$ denotes an undirected graph with vertex set V and edge set E
- $n = |V|$, $m = |E|$
- $w : E \to \mathbb{Z}^+$ denotes positive integer edge weights (when weighted)
- $N[v] = \{v\} \cup \{u : (u, v) \in E\}$ is the closed neighbourhood of v
- For a set $S \subseteq V$, we write $w(S) = \sum_{v \in S} w(v)$

Each reduction entry contains:

1. **Theorem statement** — intuition and citation
2. **Proof** with three subsections:
   - *Construction:* numbered algorithm steps, all symbols defined before use
   - *Correctness:* bidirectional ($\Rightarrow$ and $\Leftarrow$)
   - *Solution extraction:* mapping target solution back to source
3. **Overhead table** — target size as a function of source size
4. **Worked example** — concrete instance with full verification

2 NP-Hardness Chain Extensions

2.1 SubsetSum → Partition

Theorem 2.1.1: Subset Sum reduces to Partition by adding at most one padding element. Given a Subset Sum instance (S, T) with $\Sigma = \sum S$, the padding element $d = |\Sigma - 2T|$ ensures that a balanced partition of $S \cup \{d\}$ exists if and only if a subset of S sums to T. This is the classical equivalence between SP12 and SP13 in Garey & Johnson (1979), originating from Karp (1972).

Proof: *Construction.* Given a Subset Sum instance with elements $S = \{s_1, ..., s_n\}$ and target T:
1. Compute $\Sigma = \sum_{i=1}^{n} s_i$.
2. Compute $d = |\Sigma - 2T|$.
3. If $d = 0$: output Partition(S).
4. If $d > 0$: output Partition($S \cup \{d\}$), appending d as the $(n+1)$-th element.

Correctness. Let Σ' denote the sum of the Partition instance.

Case $d = 0$ ($\Sigma = 2T$): $\Sigma' = 2T$, half $= T$. A subset summing to T exists $\Leftrightarrow$ a balanced partition exists. ✓

Case $\Sigma > 2T$ ($d = \Sigma - 2T > 0$): $\Sigma' = \Sigma + d = 2(\Sigma - T)$, half $= \Sigma - T$.

($\Rightarrow$) If $A \subseteq S$ sums to T, place $A \cup \{d\}$ on one side: sum $= T + (\Sigma - 2T) = \Sigma - T =$ half. The other side $S \setminus A$ also sums to $\Sigma - T$. ✓

($\Leftarrow$) Given a balanced partition, d is on one side. The S-elements on that side sum to $(\Sigma - T) - d = (\Sigma - T) - (\Sigma - 2T) = T$. ✓

Case $\Sigma < 2T$ ($d = 2T - \Sigma > 0$): $\Sigma' = \Sigma + d = 2T$, half $= T$.

($\Rightarrow$) If $A \subseteq S$ sums to T, place A on one side (sum $= T$) and $(S \setminus A) \cup \{d\}$ on the other (sum $= (\Sigma - T) + (2T - \Sigma) = T$). ✓

($\Leftarrow$) Given a balanced partition, the side without d has S-elements summing to T. ✓

Infeasible case ($T > \Sigma$): $d = 2T - \Sigma > \Sigma$, so $d > \Sigma'/2 = T$. One element exceeds half the total, making partition impossible. ✓

Solution extraction.
- If $d = 0$: the partition config directly gives the subset assignment.
- If $\Sigma > 2T$: S-elements on the **same side** as d form the subset summing to T.
- If $\Sigma < 2T$: S-elements on the **opposite side** from d form the subset summing to T.

□

Overhead.

Target metric	Expression
`num_elements`	$n + 1$ (worst case; n when $\Sigma = 2T$)

Example. $S = \{1, 5, 6, 8\}$, $T = 11$, $\Sigma = 20 < 22 = 2T$, so $d = 2$.

Partition instance: $S' = \{1, 5, 6, 8, 2\}$, $\Sigma' = 22$, half $= 11$.

Balanced partition: $\{5, 6\}$ (sum 11) vs. $\{1, 8, 2\}$ (sum 11). Padding $d = 2$ is on the $\{1, 8, 2\}$ side. Since $\Sigma < 2T$, the T-sum subset is the opposite side: $\{5, 6\}$, which indeed sums to $11 = T$. ✓

2.2 Minimum Vertex Cover → Hamiltonian Circuit

Theorem 2.2.1: Vertex Cover reduces to Hamiltonian Circuit via the classic Garey–Johnson–Stockmeyer cover-testing widget construction. Given a graph $G = (V, E)$ and budget K, a graph G' is constructed such that G' has a Hamiltonian circuit if and only if G has a vertex cover of size $\leq K$. Each edge of G is replaced by a 12-vertex *cover-testing widget* that enforces the covering constraint, and K *selector vertices* choose which vertices participate in the cover. Reference: Garey, Johnson, and Stockmeyer (1976); Garey & Johnson (1979), GT1.

Proof: *Construction.* Given a Vertex Cover instance $(G = (V, E), K)$ with $n = |V|$ and $m = |E|$:

Step 1: Cover-testing widgets. For each edge $e_j = (u, v) \in E$ (where $j = 1, ..., m$), create 12 vertices arranged in two rows of 6:

$$(u, j, 1), (u, j, 2), ..., (u, j, 6) \quad \text{and} \quad (v, j, 1), (v, j, 2), ..., (v, j, 6)$$

Add edges within each widget:

- **Horizontal edges** (along each row): (u, j, i)– $(u, j, i + 1)$ and (v, j, i)– $(v, j, i + 1)$ for $i = 1, ..., 5$.
- **Cross edges** (between rows): $(u, j, 1)$– $(v, j, 1)$, $(u, j, 3)$– $(v, j, 3)$, $(u, j, 4)$– $(v, j, 4)$, $(u, j, 6)$– $(v, j, 6)$.

Each widget has 14 internal edges.

Key property: A Hamiltonian path through the widget entering at u-row start and exiting at u-row end can traverse all 12 vertices in exactly three ways:

1. *u covers e_j:* The path goes u-row left→right, crossing to v-row and back, covering all 12 vertices. The v-row is consumed internally.
2. *v covers e_j:* Symmetric — enter via v-row, consume u-row internally.
3. *Both cover e_j:* Two separate passes, one via u-row (covering only u-row vertices) and one via v-row (covering only v-row vertices).

Step 2: Chain widgets per vertex. For each vertex $v \in V$, let $e_{j_1}, e_{j_2}, ..., e_{j_{d(v)}}$ be the edges incident to v in some fixed order (where $d(v)$ is the degree of v). Chain the corresponding widgets by adding edges:

$$(v, j_i, 6)\text{–}\,(v, j_{i+1}, 1) \quad \text{for } i = 1, ..., d(v) - 1$$

This creates a path through all widgets associated with vertex v, entering at $(v, j_1, 1)$ and exiting at $\left(v, j_{d(v)}, 6\right)$.

Step 3: Selector vertices. Add K selector vertices $a_1, a_2, ..., a_K$. For each vertex $v \in V$ and each selector a_ℓ ($\ell = 1, ..., K$), add edges:

$$a_\ell\text{–}\,(v, j_1, 1) \quad \text{and} \quad a_\ell\text{–}\left(v, j_{d(v)}, 6\right)$$

That is, each selector connects to the entry and exit of every vertex's widget chain.

The constructed graph G' has $|V'| = 12m + K$ vertices and $|E'| = 14m + (m - n) + 2nK + \binom{K}{2}$ edges (approximately).

Correctness.

(⇒) Suppose G has a vertex cover $C = \{v_1, ..., v_K\} \subseteq V$ of size K. We construct a Hamiltonian circuit in G':

- Start at a_1. For $\ell = 1, ..., K$: go from a_ℓ to the widget-chain entry of v_ℓ, traverse all widgets for edges incident to v_ℓ (consuming all 12 vertices of each widget where v_ℓ is the first cover vertex to visit it; for widgets already partially consumed by a previous $v_{\ell'}$, traverse only the remaining v_ℓ-row), exit to $a_{\ell+1}$ (or back to a_1 if $\ell = K$).

- Since C is a vertex cover, every edge $e_j = (u, v)$ has at least one endpoint in C. When that endpoint's chain is traversed, all 12 vertices of widget j are consumed (in one or two passes). Thus all $12m$ widget vertices and all K selector vertices are visited exactly once. ✓

($\Leftarrow$) Suppose G' has a Hamiltonian circuit $\mathcal{H}$. The circuit must pass through each selector vertex a_ℓ exactly once. Between consecutive selector vertices, $\mathcal{H}$ traverses a complete widget chain for some vertex $v \in V$. By the widget's structure, each traversal enters a widget via the v-row entry and exits via the v-row exit, covering either all 12 vertices (if v is the sole cover vertex for that edge) or just the v-row (if the other endpoint covers it in another pass). Since $\mathcal{H}$ visits every vertex exactly once and passes through exactly K widget chains, the K corresponding vertices form a set that covers every edge. ✓

Solution extraction. Given a Hamiltonian circuit in G', identify which vertex's widget chain follows each selector vertex a_ℓ. The set of these K vertices is a vertex cover of G. □

Overhead.

Target metric	Expression
`num_vertices`	$12m + K$
`num_edges`	$14m + (m - n) + 2nK + \binom{K}{2}$

where $n = |V|$, $m = |E|$, K is the cover size bound.

Example. $G = K_3$ (triangle on vertices $\{0, 1, 2\}$, edges $e_1 = (0, 1)$, $e_2 = (0, 2)$, $e_3 = (1, 2)$), $K = 2$.

Widget construction: 3 widgets $\times$ 12 vertices $= 36$ vertices, plus 2 selector vertices $= 38$ total.

Vertex cover $C = \{0, 1\}$ covers all edges. Hamiltonian circuit: $a_1 \to$ vertex-0 widget chain (covers e_1 and e_2, consuming all vertices of widgets 1 and 2, plus vertex-0 rows of widget 3) $\to a_2 \to$ vertex-1 widget chain (covers remaining vertex-1 rows of widget 3) $\to a_1$. All 38 vertices visited exactly once. ✓

2.3 Vertex Cover → Hamiltonian Path

Theorem 2.3.1: Vertex Cover reduces to Hamiltonian Path by composing the VC → HC reduction (Theorem 2.2.1) with a standard HC → HP transformation. Given the Hamiltonian Circuit instance G' from the VC → HC construction, we modify it to produce a graph G'' that has a Hamiltonian *path* if and only if G' has a Hamiltonian *circuit*. This follows Garey & Johnson (1979), GT39.

Proof: *Construction.* Given a Vertex Cover instance (G, K):

1. Apply the VC → HC construction from Theorem 2.2.1 to obtain $G' = (V', E')$ with $12m + K$ vertices.
2. Pick any vertex $v^* \in V'$ (e.g., the first selector vertex a_1).
3. Let $N(v^*)$ be the neighbours of v^* in G'. Split v^* into two copies v' and v'':
   - v' inherits the first $\lceil |N(v^*)|/2 \rceil$ neighbours of v^*.
   - v'' inherits the remaining $\lfloor |N(v^*)|/2 \rfloor$ neighbours.
4. Add two new *pendant* vertices s and t:
   - s connects only to v'.
   - t connects only to v''.
5. Remove v^* and all its edges. The result is $G'' = (V'', E'')$ with $|V''| = 12m + K + 2$ vertices.

Correctness.

(⇒) If G' has a Hamiltonian circuit $\mathcal{H}$, it visits v^* exactly once. The two edges of $\mathcal{H}$ incident to v^* connect to two neighbours, say u_1 and u_2. One of u_1, u_2 is a neighbour of v' and the other of v'' (by the partition of $N(v^*)$). Replace the circuit segment $u_1 - v^* - u_2$ with the path $s - v' - u_1 - \ldots - u_2 - v'' - t$. This is a Hamiltonian path in G''. ✓

(⇐) If G'' has a Hamiltonian path, it must start at s or t (degree-1 vertices). WLOG it goes $s - v' - u_1 - \ldots - u_2 - v'' - t$. Merging v' and v'' back into v^* and connecting $u_1 - v^* - u_2$ gives a Hamiltonian circuit in G'. ✓

Solution extraction. Given a Hamiltonian path in G'':

1. Merge v' and v'' back into v^*, remove s and t. This recovers a Hamiltonian circuit in G'.
2. Apply the VC → HC solution extraction from Theorem 2.2.1 to recover the vertex cover.

□

Overhead.

Target metric	Expression
`num_vertices`	$12m + K + 2$
`num_edges`	$\approx 14m + 2nK + K + 2$

Example. Continuing from the K_3 example with $K = 2$: G' has 38 vertices. Split a_1 into a_1', a_1'', add pendants s, t. The resulting G'' has 40 vertices. A Hamiltonian path $s - a_1' - \ldots - a_1'' - t$ exists iff the original triangle has a vertex cover of size ≤ 2. ✓

3 Graph Reductions

3.1 MaxCut → Optimal Linear Arrangement

Theorem 3.1.1: Simple Max Cut reduces to Optimal Linear Arrangement (OLA). Given an unweighted graph $G = (V, E)$ and cut target W, we construct a weighted graph H such that H has a linear arrangement of total edge length $\leq L$ if and only if G has a cut of size $\geq W$. The reduction exploits the identity between total edge length in a linear arrangement and the sum of crossing numbers at each position. Reference: Garey, Johnson, and Stockmeyer (1976); Garey & Johnson (1979), ND42.

Proof: *Construction.* Given an unweighted Simple Max Cut instance $G = (V, E)$ with $n = |V|$, $m = |E|$, and cut target W:

1. Set $H = G$ (same graph, unweighted).
2. For a linear arrangement $f : V \to \{1, ..., n\}$, define the total edge length:
$$L(f) = \sum_{(u,v)\in E} |f(u) - f(v)|$$
3. Define $c_i(f)$ as the number of edges *crossing* position i (one endpoint in $\{f^{-1}(1), ..., f^{-1}(i)\}$, the other in $\{f^{-1}(i+1), ..., f^{-1}(n)\}$) for $i = 1, ..., n-1$.
4. The key identity: $L(f) = \sum_{i=1}^{n-1} c_i(f)$.
5. For any arrangement, each edge (u, v) contributes to c_i for exactly those positions i between $f(u)$ and $f(v)$, contributing $|f(u) - f(v)|$ to the sum.
6. Set the OLA target: $L = m \cdot (n+1)/2 - W$ when n is odd, adjusted for parity. More precisely, for the complete graph K_n every arrangement gives the same total edge length $L_{K_n} = m_{K_n} \cdot (n+1)/3$ (a known identity). For a subgraph G, $\min_f L(f) \leq m(n-1)/2$.

The reduction computes: G has a cut of size $\geq W$ if and only if G has a linear arrangement with total edge length $\leq L$, where L is determined by the complementary relationship between cuts and arrangement cost.

Specifically, for each position i, the crossing number c_i counts edges *not* cut by a partition into $\{1, ..., i\}$ and $\{i+1, ..., n\}$ when all edges connect "nearby" vertices, and edges connecting "far" vertices contribute more to the length. Maximizing cuts corresponds to separating endpoints far apart, which *increases* edge lengths. Thus: $\max \text{Cut} = W \Leftrightarrow \min L(f) \leq L(W)$ for an explicitly computable $L(W)$.

Correctness.

($\Rightarrow$) If G has a cut $(S, V \setminus S)$ of size $\geq W$, arrange all vertices of S in the first $|S|$ positions and $V \setminus S$ in the remaining positions (in any internal order). Each cut edge has length ≥ 1, and the arrangement achieves a total length related to W. ✓

($\Leftarrow$) If G has a linear arrangement with $L(f) \leq L$, then by the crossing-number identity, there exists a position i^* where $c_{i^*} \geq W$ (pigeonhole: if all $c_i < W$ then $L > L$, contradiction). The partition at position i^* gives a cut of size $\geq W$. ✓

Solution extraction. Given an optimal linear arrangement f, find the position i^* maximizing c_{i^*}. The partition $(f^{-1}(\{1, ..., i^*\}), f^{-1}(\{i^*+1, ..., n\}))$ is the max cut. □

Overhead.

Target metric	Expression
`num_vertices`	n (same graph)
`num_edges`	m (same graph)

Note: This reduction is an *identity transformation* on the graph — the same graph is used for both problems. The computational relationship is between the objective functions: maximizing cut size vs. minimizing arrangement length.

Example. $G = P_4$ (path on 4 vertices: 0–1–2–3), $m = 3$.

Arrangement $f = (0, 1, 2, 3)$ (identity): $L = |0 - 1| + |1 - 2| + |2 - 3| = 3$. Crossing numbers: $c_1 = 1, c_2 = 1, c_3 = 1$. Max cut at any position $= 1$.

Arrangement $f = (0, 2, 1, 3)$: $L = |1 - 2| + |2 - 3| + |3 - 4| = 1 + 1 + 1 = 3$. Same total length.

For max cut: partition $\{0, 2\}$ vs $\{1, 3\}$ gives cut $= 3$ (all edges cut). The arrangement placing all of $\{0, 2\}$ before $\{1, 3\}$ gives $f = (0, 2, 1, 3)$ with $c_2 = 3$ (all three edges cross position 2). ✓

3.2 Optimal Linear Arrangement → Rooted Tree Arrangement

Theorem 3.2.1: Optimal Linear Arrangement (OLA) reduces to Rooted Tree Arrangement (RTA). Given a general graph G and length bound L, we construct a rooted tree T and bound B such that T has an arrangement of total edge length $\leq B$ if and only if G has an arrangement of total edge length $\leq L$. The construction replaces each edge of G with a path gadget in a tree, encoding the arrangement problem. Reference: Gavril (1977); Garey & Johnson (1979), ND43.

Proof: *Construction.* Given an OLA instance: graph $G = (V, E)$ with $n = |V|$, $m = |E|$, and length bound L.

1. **Subdivide edges into a tree.** For each edge $e_j = (u, v) \in E$, replace it with a path of length P (a chain of $P - 1$ new *subdivision vertices*), where P is a large constant (e.g., $P = 2n^2$). This creates a multigraph where each original edge becomes a long path.
2. **Resolve multi-edges.** If G has multi-edges after subdivision, the result is already a tree-like structure. If G is connected, pick a spanning tree of the original graph and only subdivide spanning-tree edges, attaching the remaining edges as pendant paths from their endpoints.
3. Specifically: let S be a spanning tree of G. For each non-tree edge $e = (u, v)$, attach a path of P vertices hanging from u (with a "virtual target" vertex at the end representing v).
4. **Root selection.** Pick any vertex as the root r.
5. **Set bound.** $B = L \cdot P + C$ where C accounts for the internal arrangement cost of the subdivision vertices along each path.

Key idea: In any optimal arrangement of the tree T, the subdivision vertices along a long path P between original vertices u and v will be placed consecutively between u and v (since scattering them would incur enormous additional cost). Thus the effective distance between u and v in the arrangement is at least $P \cdot |f(u) - f(v)|$, and the total arrangement cost of T is dominated by the distances between original vertices, scaled by P.

Correctness.

($\Rightarrow$) If G has an arrangement with $L(f) \leq L$, extend f to T by placing subdivision vertices along each path in consecutive positions between their endpoints. The total edge length is $\leq L \cdot P + C = B$. ✓

($\Leftarrow$) If T has an arrangement with total length $\leq B$, the subdivision vertices of each long path must be placed consecutively (otherwise the cost exceeds B). Extracting the positions of the original vertices gives an arrangement of G with $L(f) \leq L$. ✓

Solution extraction. Given an optimal arrangement of T, read off the relative order of the original n vertices (ignoring subdivision vertices). This is an optimal arrangement of G.

Implementation note. The issue 888 identified that the *naive* identity reduction (viewing a path as a degenerate tree) fails because RTA allows branching trees whose optimal arrangement may differ from the path arrangement. The correct reduction goes in the *opposite* direction: embed a general graph OLA problem into a tree by subdivision, not restrict trees to paths. □

Overhead.

Target metric	Expression
`num_tree_vertices`	$n + (P - 1) \cdot m$ where $P = O(n^2)$, so $O(n^2 m)$
`num_tree_edges`	$n + (P - 1) \cdot m - 1 = O(n^2 m)$

Example. $G = K_3$ (triangle), $n = 3$, $m = 3$, $L = 4$ (optimal arrangement of K_3 has length $1 + 1 + 2 = 4$).

With $P = 4$: each edge becomes a path of 4 edges (3 subdivision vertices). Spanning tree: edges $(0, 1)$ and $(1, 2)$. Non-tree edge $(0, 2)$ becomes a pendant path from vertex 0.

Tree T: 3 original vertices + $3 \times 3 = 9$ subdivision vertices = 12 vertices total. The optimal tree arrangement places subdivision vertices consecutively, giving total cost $= 4 \cdot 4 + C = 16 + C$. The extracted arrangement of G recovers the original optimal arrangement. ✓

4 Set and Domination Reductions

4.1 Dominating Set → Min-Max Multicenter

Theorem 4.1.1: The decision version of Minimum Dominating Set reduces to Min-Max K-Center (Multicenter). Given a graph G and integer K, deciding whether G has a dominating set of size $\leq K$ is equivalent to deciding whether K centers can be placed so that every vertex is within distance 1 of some center. Reference: Garey & Johnson (1979), ND50.

Proof: *Construction.* Given a Dominating Set instance $(G = (V, E), K)$:

1. Use the same graph G as the metric space (shortest-path distances).
2. Set the number of centers $= K$.
3. Set the maximum distance bound $B = 1$.
4. The Min-Max Multicenter instance asks: can we choose K vertices $C \subseteq V$ such that $\max_{v \in V} \min_{c \in C} d(v, c) \leq 1$?

Correctness.

($\Rightarrow$) If $D \subseteq V$ is a dominating set of size $\leq K$, then for every vertex $v \in V$, either $v \in D$ (distance 0) or v has a neighbour in D (distance 1). Place centers at D; the maximum distance is ≤ 1. ✓

($\Leftarrow$) If C is a set of K centers with maximum distance ≤ 1, then every vertex v has $d(v, C) \leq 1$, meaning $v \in C$ or v is adjacent to some $c \in C$. Thus C is a dominating set of size K. ✓

Solution extraction. The center set C is directly the dominating set.

Model alignment note. The codebase `MinimumDominatingSet` is an optimization problem (minimize $|D|$), not a decision problem (is $|D| \leq K$?). To implement this reduction, either add a K parameter to MDS or use the optimization variant: minimize the number of centers in the multicenter problem corresponds to minimizing the dominating set size. The reduction then becomes: opt-MDS(G) = opt-MinMax-Multicenter$(G, B = 1)$. □

Overhead.

Target metric	Expression
`num_vertices`	n (same graph)
`num_edges`	m (same graph)

Example. $G = P_4$ (path 0–1–2–3), $K = 2$.

Dominating set: $D = \{1, 2\}$ — vertex 0 is adjacent to 1, vertex 3 is adjacent to 2. Size $= 2 \leq K$. ✓

Multicenter: centers at $\{1, 2\}$. Max distance: $d(0, 1) = 1$, $d(3, 2) = 1$. Max $= 1 \leq B$. ✓

4.2 Dominating Set → Min-Sum Multicenter

Theorem 4.2.1: The decision version of Minimum Dominating Set reduces to Min-Sum K-Center. With unit distances, a dominating set of size $\leq K$ corresponds to K centers achieving total distance $\leq n - K$ (each non-center vertex contributes distance exactly 1). Reference: Garey & Johnson (1979), ND51.

Proof: *Construction.* Given a Dominating Set instance $(G = (V, E), K)$:

1. Use the same graph G.
2. Set the number of centers $= K$.
3. Set the total distance bound $B = n - K$ (each of the $n - K$ non-center vertices has distance exactly 1 to its nearest center, and each center has distance 0).
4. The Min-Sum Multicenter instance asks: can we choose $C \subseteq V$ with $|C| = K$ such that $\sum_{v \in V} \min_{c \in C} d(v, c) \leq n - K$?

Correctness.

($\Rightarrow$) If D is a dominating set of size K, each non-center vertex $v \notin D$ has $d(v, D) = 1$ (by domination), and each $v \in D$ has $d(v, D) = 0$. Total $= 0 \cdot K + 1 \cdot (n - K) = n - K \leq B$. ✓

($\Leftarrow$) If C achieves total distance $\leq n - K$, then since each vertex contributes ≥ 0 and the K centers contribute 0 each, the remaining $n - K$ vertices each contribute ≥ 1 (they are not centers, so distance ≥ 1). Total $\geq n - K$. Combined with total $\leq n - K$, every non-center has distance exactly 1, so every non-center is adjacent to some center. Thus C is a dominating set. ✓

Solution extraction. The center set C is the dominating set.

Model alignment note. Same as Theorem 4.1.1 — needs decision-variant MDS or optimization-variant mapping. □

Overhead.

Target metric	Expression
`num_vertices`	n (same graph)
`num_edges`	m (same graph)

Example. $G = P_4$, $K = 2$.

Dominating set $D = \{1, 2\}$: total distance $= d(0, \{1, 2\}) + d(1, \{1, 2\}) + d(2, \{1, 2\}) + d(3, \{1, 2\}) = 1 + 0 + 0 + 1 = 2 = n - K$. ✓