```
function [Ve, newXeSum, Xerr] = FeedbackControl(X, Xd, Xdn, Kp, Ki, dt, XeSum)
% FEEDBACKCONTROL Calculates the task-space feedforward plus feedback control law.
응
% Inputs:
  X: Actual current E-E config of the robot is space frame, a aka
% Tse. Expressed as row in the order r11,r12,r13,r21,r22,r23,r31,r32,r33,
% px, py, pz
  Xd: Desired current E-E config of the robot is space frame.
% aka Tse, d. Expressed in the same order
  Xdn: Reference E-E configuration
% at the next timestep. aka Tse,d,next. Expressed in the same order
% Kp, Ki:PI gain matrices
  dt: timestep delta T between reference trajectory configs
  XeSum: Sum of previous Xe errors, passed in from previous interation,
% initilzed at 0
응
% Outputs:
% Ve: commanded E-E twist expressed in E-E frame
% newXeSum: Sum of previous and current Xe errors, passed on to the next
           iteration
% Xerr: The T matrix that drives X to Xd
%% Feedforward term [AdX-1Xd]Vd(t)
Vd = se3ToVec(MatrixLog6(TransInv(Xd)*Xdn)/dt);
%% Preportional term KpXe(t)
Xerr =se3ToVec(MatrixLog6(TransInv(X)*Xd));
%% Integral Term Ki Sum(Xe(t))
newXeSum = Xerr*dt +XeSum;
%% Total law
Ve = Adjoint(TransInv(X)*Xd) * Vd + Kp*Xerr + Ki*newXeSum;
end
```