



Test corpus: what we validate against, and what we deliberately do not

The parsers in this repo are only as trustworthy as the input they have met. This records where that input comes from, and one thing we decided **not** to use.

What we use

1. Reference archives from SngCli

`internal/sng/testdata/reference-sngcli-v0.3.0.sng` was produced by **SngCli v0.3.0** (MIT, `mdsitton/SngFileFormat`) from a song folder we wrote. It is the only fixture that checks the reader against something other than our own understanding of the format — the fixtures in `mask_test.go` and `read_test.go` are built by an encoder written from the same reading of the spec as the reader, and two components sharing one misreading agree with each other perfectly.

SngCli is installed at `%LOCALAPPDATA%\Programs\sngcli\win-x64\SngCli.exe`. To regenerate:

```
SngCli.exe encode -i <folder-of-song-folders> -o <out> --noStatusBar -t 1
SngCli.exe decode -i <folder-of-sng-files> -o <out> --noStatusBar -t 1
```

`.gitignore` excludes `*.sng` so nobody commits a song library, with an explicit exception for `internal/sng/testdata/`.

2. YARG itself, as the end-to-end oracle

YARG v0.15.0 is installed portable at `%LOCALAPPDATA%\Programs\YARG\YARG.exe` — the official Windows x64 zip, no installer, no elevation, deletable in one command. LGPL-3.0-or-later, free, and downloaded from YARG's own release page.

This is the gate that matters for the writer: put a repacked `.sng` in a songs folder, let YARG scan it, and confirm it appears with the right metadata and is playable. Nothing we can assert about our own output substitutes for the client accepting it.

(YARC publishes a `.sig` beside each release asset but no plain checksum, and no public key we could find, so the download is recorded by its SHA-256 rather than verified:

`a2eac765a190e34a8acbdba5b1351844704b427349d6d36b8cf1096f575055e41`.)

3. Charts we author

Hand-written `song.ini` and chart files exercising the messy cases: BOMs, Latin-1 bytes, duplicate keys, missing section headers, values containing `=`, free-text years, unknown keys, absurd numbers. These are in the unit tests.

What we deliberately do not use

YARG's Official Setlist

It would be the obvious corpus — real charts, real metadata, distributed by YARC themselves — and we are **not** using it.

`YARC-Official/Official-Setlist-Public` states plainly that the setlist is proprietary, that "musicians gave permission to use these songs in YARG specifically", that everything "**must** be used exclusively for YARG", and that users should not download it manually. Using it as the test corpus for a third-party song server is outside that permission — and serving it from one would be squarely outside it.

That is not a close call, and it matters more here than it would elsewhere: this project's own goal is to make charts distributable *separately* from music precisely to avoid copyright problems. A project with that goal cannot be casual about the provenance of its own test data.

The same caution applies to bulk-downloading community charts from Chorus Encore or similar: individual charters' licensing varies, and most community packages bundle commercial audio. Individual charts may be used where the charter's own licence permits it — that is a per-chart question, answered before the chart is added, not a bulk decision.

There IS a documented framework, and it reopens this

The [YARN submission guidelines](#) define exactly which music may be used with YARG, which is a better answer than "self-authored only":

- **Acceptable:** CC BY, CC BY-SA, CC BY-NC, CC BY-NC-SA and CC0, at version 3.0 or 4.0; plus the catalogue of accepted royalty-free labels (currently NCS).
- **Not acceptable:** the no-derivatives licences, CC BY-ND and CC BY-NC-ND — because *visual synchronisation is itself a derivative work*. That is a subtlety worth knowing: a chart is a derivative of the song, not merely a companion to it.
- **Share-alike propagates:** a chart of a CC BY-SA song is, by definition, released under the same licence as the song.

- The wiki points at a curated list of Creative Commons songs (the "YARN Planning - CC" tab of the YARN Charts Master Spreadsheet) as a starting point.

So a legitimately-licensed corpus is reachable: a CC BY or CC0 song, charted, is redistributable in full — audio included — and could live in this repository as a real end-to-end fixture rather than a generated one. That is a better long-term answer than the synthetic corpus, and the only reason it is not the current answer is that nobody has charted one yet.

What the oracle actually found, 2026-09-05

`cmd/mkcorpus` wrote 20 deliberately awkward song folders (22 as of the UltraStar work); YARG v0.15.0 scanned them; its `badsongs.txt` and song cache were read back. **Our scanner had passed all 20 and was wrong about three of them.** These are the only findings in this repo that came from an oracle rather than from our own reasoning, which is precisely why they are the ones worth having.

As of the last run, every song YARG rejects is one this scanner independently flags, by three different routes: no parts detected (`13-mid-beats-chart`), `no_audio` (`19-no-audio`), and `ultrastar_no_title` (`21-ultrastar-no-title`). No divergences remain in the corpus.

Case	YARG	We had	Fixed
<code>song.ini</code> with no <code>[Song]</code> header	reads nothing , titles the song after its folder	read the keys	yes — parser now requires the header, and the song is flagged <code>no_metadata_section</code>
chart with no audio	rejects: <i>"No audio accompanying the chart file"</i>	accepted it silently	yes — flagged <code>no_audio</code>
folder with a chart but no <code>song.ini</code>	neither cached nor reported bad — silently skipped	accepted it silently	yes — flagged <code>no_song_ini</code>

The headerless case is the one that mattered most. Our leniency was a guess written into a comment ("some charts omit it"), and it would have produced a catalog whose titles disagreed with what the player sees on their own screen — a bug with no error message anywhere.

Confirmations, where YARG agreed with decisions we had reached from source:

- Duplicate keys resolve **last-wins** — `FIRST` never appears in YARG's cache, `SECOND` does. That is now three independent sources: `IniModifierCollection.cs`, SngCli's round-trip, YARG.
- Latin-1, UTF-16LE and UTF-8-BOM `song.ini` files all read correctly on both sides.
- `notes.mid` is a **hard selection** over `notes.chart`, not a preference. Given both, YARG chose the `.mid`, found it unplayable, and rejected the whole song rather than falling back. Hashing the wrong file would be a real divergence, exactly as `chartfile.go` warns.

- Uppercase `[SONG]`, ragged whitespace, CRLF, values containing `=`, free-text years, unknown keys, the `cover` override, clean/explicit stem variants and a 4-way drum kit all matched.

Both divergences are now closed

1. ~~**UltraStar** `notes.txt` .~~ **CLOSED**. YARG rejected it with *"Name metadata not provided"* despite `song.ini` carrying a name, and the reason turned out to be structural: **UltraStar is the one format whose metadata does not come from `song.ini`**. YARG reads `#TITLE`, `#ARTIST` and `#ALBUM` from the `.txt` itself and refuses the song outright when `#TITLE` is missing. It is also **vocals-only** — no instrumental part is derived from it, and harmony is keyed on `#PARTS:2`.

Re-measured with corrected fixtures: a valid UltraStar chart is accepted and **YARG titles it from the `.txt`, not from `song.ini`** — the corpus case deliberately carries a different name in each, and `song.ini`'s never appears in YARG's cache. Our scanner now does the same, reports lead vocals (plus harmony on `#PARTS:2`), and flags a titleless chart as `ultrastar_no_title`.

1. ~~**We do not know whether a chart is playable.**~~ **CLOSED** by the chart preparers. YARG rejected the header-only `.mid` with *"No notes found"*; our preparer now reports zero parts for that same chart, reaching the same conclusion by an independent route. A song with no detectable parts is still catalogued rather than dropped, but it no longer claims instruments it does not have.

The writer's gate, 2026-09-05

The same oracle was then pointed at output we produced. `yarg-song-server pack` repacked 14 corpus folders plus the reference song; YARG scanned the 15 archives and accepted 14, reading every title out of our metadata section.

The single rejection — `No notes found` — was settled by a **control** rather than explained away: SngCli's own archive of the same source folder was placed beside ours and scanned in the same pass, and YARG rejected both with the identical error. The fixture's hand-written chart has no note events. Without that control, "YARG rejected one of ours" would have looked like a writer bug, and chasing it would have been wasted work.

Independently, `SngCli decode` extracted our archive with zero errors and every contained file came back byte-identical to the source folder.

Reproducing this

```
go run ./cmd/mkcorpus -out $env:USERPROFILE\yarg-test\corpus
# point YARG at it by editing SongFolders in
# %USERPROFILE%\AppData\LocalLow\YARC\YARG
# release\settings.json
# then delete songcache.bin, launch YARG, and read badsongs.txt beside it
```

The corpus is generated, never committed: it is large, and a committed corpus rots into something nobody regenerates.

The gap this leaves, stated honestly

Self-authored input cannot produce unknown unknowns. We can write a `song.ini` with the mistakes we thought of; we cannot write one with the mistakes we did not. Two things partly close that gap:

- SngCli's output already taught us two things synthetic input never would — that duplicate keys resolve last-wins in the reference tool, and that a contained file's extension can lie about its container.
- YARG scanning our output is a real oracle, because it is the actual client with the actual parser.

Neither is a substitute for a large real library. If a legitimately-licensed corpus becomes available, revisit this.

That said, the first run of this method found three real bugs, two of which had been written into the code as confident comments. The oracle is doing work.

Second oracle run — 2026-09-05, against what the SERVER produced

The first run scanned loose folders. This one scanned the archives the running server handed a client, which is the thing Phase 2 actually promises: *an unmodified YARG reads what the server serves*. The two runs answer different questions and both are worth keeping.

Procedure, end to end and all of it measured:

```

go run ./cmd/mkcorpus -out $env:USERPROFILE\yarg-test\corpus      # 22 cases at the time; 23
now
go build -o yss.exe ./cmd/yarg-song-server
.\yss.exe -listen 127.0.0.1:8099 -songs $env:USERPROFILE\yarg-test\corpus -data .\data
# POST /api/v1/have with an empty list -> 22 missing
# GET /song/{hash}.sng for each -> 22 files
# point YARG's SongFolders at the downloaded folder, delete songcache.bin, launch, wait

```

Results:

Step	Outcome
Index the corpus	22 songs, 22 distinct charts, 0 problems, 15 ms
POST /have from an empty client	library_total=22 missing_count=22
Download every missing song	22 downloaded, 0 ambiguous, 0 failed
Re-scan the downloads with our own scanner	22 songs, 0 failures
YARG scans the 22 served archives	20 accepted, 2 refused

The two refusals, and our own independent verdict on the same archive:

Archive	YARG said	Our scanner said
30334065... "Mid Beats Chart"	No notes found	nothing — no issue at all
4ec68053... "No Audio"	No audio accompanying the chart file	issue no_audio, no stems

This section originally claimed the standard held, and it did not. The row above used to read "*parts_derived: true, no part carries any difficulty*" — which is an observation somebody made by reading the JSON, not an issue the scanner raised. The scanner emitted **no issue whatsoever** for 30334065... . Reading a field by eye and recording it as though the software had flagged it turned a miss into a pass, and the conclusion drawn from it — "the standard holds" — was false for one of the two songs it was about. Corrected on the third run below, where the gap was found and closed. The lesson is narrower than "check your work": **a green must come from the thing being tested, not from the tester noticing something.**

What this run turned up: packing gives an untitled UltraStar chart a title

Corpus case `21-ultrastar-no-title` has a `notes.txt` with no `#TITLE` and a `song.ini` that does carry a name. As a **loose folder** YARG refuses it — UltraStar is the one format that takes its title from the chart rather than from `song.ini`, and a missing `#TITLE` is fatal ("Name metadata not provided"). Our scanner flags it `ultrastar_no_title`.

As a `.sng` **produced by this server**, YARG accepted it. That is not a packing bug: in a `.sng` the metadata lives in the archive's header section, and `PackDir` fills that section from `song.ini`, so the song genuinely has a title — scanning the archive shows its name resolved to "Has A Name In song.ini".

Correction, measured 2026-09-05 on the third run: this paragraph used to end "*Our scanner reports no issue for the archive, which agrees with the client in both forms.*" It does not. Serving the packed archives and reading `/api/v1/songs` returns `ultrastar_no_title` on the archive as well, because the `notes.txt` inside it still has no `#TITLE`. That is a caveat on a song YARG plays, not a claim that YARG refuses it, and the issue text now says so in both directions. Worth keeping rather than suppressing: the chart really is missing a tag, and a player repacking it elsewhere would meet the folder behaviour again.

It is worth writing down anyway, because it means one sentence people will reasonably assume is not quite true: **the server does not always serve exactly what the folder was**. For this one format, repacking makes a song playable that was not. Nothing to fix; something to know before the Phase 2b sync client starts writing archives into a player's songs folder and a song appears that the player could not previously play.

Third oracle run — 2026-09-05, against a folder `yarg-sync` filled

The first run scanned loose folders. The second scanned archives downloaded by hand from the running server. This one is the Phase 2b exit criterion itself: **the real sync client filled an ordinary songs folder, and an unmodified YARG was pointed at it**. Nothing between the server and the game was done by hand.

```
.\bin\yarg-song-server.exe -songs $env:USERPROFILE\yarg-test\corpus -data .\data -listen 127.0.0.1:8099
.\bin\yarg-sync.exe -server http://127.0.0.1:8099 -songs $env:USERPROFILE\yarg-test\phase2b\syncd
# point YARG's SongFolders at that folder, delete songcache.bin, launch, wait ~45s,
# then read badsongs.txt beside it
```

Step	Outcome
Index the corpus	22 songs, 22 distinct charts, 0 problems

Step	Outcome
<code>yarg-sync</code> from an empty folder	22 downloaded, 0 failed, 229,515 bytes in 505 ms
Every archive verified by re-derived identity	22 / 22
YARG scans the synced folder	20 accepted, 2 refused

The refusals were the same two, for the same reasons, at the paths the client wrote:

```
C:\Users\ENG2\yarg-test\phase2b\synced\30334065...sng  No notes found
C:\Users\ENG2\yarg-test\phase2b\synced\4ec68053...sng  No audio accompanying the chart file
```

So the Phase 2b claim is now measured rather than asserted: an unmodified YARG plays from a folder this client filled, and it does so with no change to the game.

The fifth thing the oracle found, and the fourth defect

`13-mid-beats-chart` is a `notes.mid` carrying a beat track and no note tracks. YARG refuses it — `No notes found`. **Our scanner reported it clean.** Not "flagged with a different code": no issue at all. That breaks the standard this project exists to hold, and it had been recorded as a pass on the previous run (see the correction above).

Chasing it turned up a second, deeper defect. Two corpus cases are byte-identical apart from one line:

	<code>20-ultrastar</code>	<code>21-ultrastar-no-title</code>
<code>#TITLE</code> line	present	absent
every other byte	identical	identical
difficulties we derived	8	0

`PreparseUltraStar` returned early without deriving any part when `#TITLE` was missing, on the belief — written into the code and into a test — that YARG refuses such a chart outright, so its contents did not matter. **The second oracle run had already disproved that belief** (packed, the song plays) without anyone noticing that a function elsewhere still depended on it. So the server reported a song with no playable parts, for a song that plays.

That also made the obvious fix for the first defect wrong. A blanket "zero difficulties means no notes" rule would have flagged `21-ultrastar-no-title`, which YARG accepts — a false positive created by building on a known-bad number.

Both are fixed:

- `PreparseUltraStar` derives notes regardless of the title. What a chart *contains* does not depend on whether it is titled. The missing tag is recorded as a note, and the title question stays where it belongs, in the metadata layer.
- A new issue, `no_notes`, is raised when a chart parses cleanly and no instrument carries any difficulty. It is guarded on `PartsDerived`, because zero difficulties on a chart we *failed* to parse means "not determined" — the catalog already documents that distinction on the field itself, and claiming "no notes" there would report a conclusion never reached.
- `ultrastar_no_title`'s text asserted that YARG "refuses the song". It now states both measured behaviours: refused as a loose folder, played once packed.

Each change was red-proofed before its green was believed. Removing the `no_notes` check failed `TestNoNotesIsFlaggedBecauseYARGRejectsIt` and nothing else; dropping the `PartsDerived` guard failed `TestNoNotesIsNotClaimedWhenPartsWereNeverDerived` and nothing else; restoring the UltraStar early return failed both UltraStar tests and nothing else.

After the fix, the corpus reads:

Corpus case	Difficulties	Issues	YARG
<code>13-mid-beats-chart</code>	0	<code>no_notes</code>	refused
<code>19-no-audio</code>	8	<code>no_audio</code>	refused
<code>21-ultrastar-no-title</code>	8 (was 0)	<code>ultrastar_no_title</code>	accepted
the other 19	8 or 16	none, or a metadata caveat	accepted

The two songs YARG refuses are exactly the two this scanner flags as refusals. Song identity was re-checked and is unchanged by all of this — `SHA1(chart bytes)` does not move because our derivation improved.

Fourth oracle run — 2026-09-06, TWO machines, and the defect only two machines could find

The third run closed the Phase 2b claim for one client. This one is the exit criterion in full: **two different computers, each running an unmodified YARG, each pointed at a folder `yarg-sync` filled from the same server.** It is the first run in this project where the question was not "does the client accept what we serve" but "do two clients receive the *same thing*".

They did not.

	ENG-1	r7-desktop
Archives received	22	22
Total bytes	229,515	229,515

	ENG-1	r7-desktop
Songs failed	0	0
Archives with matching SHA-256	6 of 22	

Same count, same byte total, same server — and 16 of the 22 files were different. The count and the total are exactly the numbers a summary line reports, and both were green. Only hashing every file showed it.

The cause, and why every earlier run missed it

`sng.Write` generated its 16-byte header mask with `crypto/rand` on every call, so `PackDir` was not a function of its input. 16 was not a coincidence: the server was running with a deliberately tight `pack_cache_max`, 16 of the 22 songs had been evicted and re-packed between the two syncs, and a re-pack meant a new mask.

Three things had hidden it:

- **A cache hit is not a re-pack.** `TestSongFileIsAReadableSNGWithTheSameIdentity` asked for the same song twice and compared the bytes — but the second request was served from the cache, and a hit re-reads a file rather than packing anything. It passes whatever the packer does. It still passes today with the defect deliberately reintroduced; the new `TestTheSameSongIsTheSameBytesAfterTheCacheIsEmpty` fails, which is how we know the difference is real and not a matter of taste.
- **A test asserted the defect.** `TestWriteUsesAFreshMask` required two writes of the same content to differ, on the belief that a repeated mask weakened the obfuscation. It does not: the mask is stored in plaintext in the header of every `.sng`, so it protects nothing at all. The test locked the bug in and made removing it look like a regression.
- **The claim was reasoned, not measured.** Six documents said an evicted archive is re-packed *byte-identically*. That was inferred from "the package hash comes from the content", which is a fact about the hash and says nothing about the archive. Nobody had compared two archives.

The fix and the measurement

The mask is now derived: `key = SHA-256("yang-song-server/sng-mask/v1\0" + package_hash)[:16]`, and `sng.Write` takes the key as a parameter instead of drawing it itself. Nothing is given away — the mask is in the header regardless — and packing becomes a pure function of the folder.

Measurement	Result
Pack the same folder twice in-process	identical
Sync, wipe the server's entire pack cache, sync again	22 / 22 identical
ENG-1 vs r7, same server, independent syncs	22 / 22 identical (was 6 / 22)

Measurement	Result
Unmodified YARG on ENG-1	20 accepted, 2 refused
Unmodified YARG on r7-desktop	20 accepted, 2 refused

Both machines refused the same two songs for the same two reasons — `No notes found` on `30334065...` and `No audio accompanying the chart file` on `4ec68053...` — which are the two our own scanner flags. r7 had never run YARG before; its install was copied from ENG-1 and its `settings.json` written from ours with only `SongFolders` changed.

So the Phase 2b exit criterion is closed, and closing it is what found the defect. A single client cannot notice that it received one of several possible encodings.

(Footnote worth keeping: the two `songcache.bin` files are 6,619 and 6,606 bytes. Same 22 songs, same verdicts, different sizes — they embed absolute paths. That is a small live demonstration of why generating `songcache.bin` is a permanent non-goal.)

The container leg, measured the same day

vault2 was re-pulled onto `c623dae` with its pack cache wiped, and both clients synced from the container as well. Five independent syncs, hashed file by file:

Client	Server	Result
ENG-1	ENG-1, from the working tree (windows/amd64)	reference
ENG-1	same, after wiping the whole pack cache	identical
r7-desktop	ENG-1's server	identical
ENG-1	the vault2 container (linux/amd64)	identical
r7-desktop	the vault2 container (linux/amd64)	identical

110 archives, two clients, two servers built for different operating systems by different toolchains, one deliberate cache wipe — one set of bytes. **The derivation turns out not to be platform-dependent**, which it had to be for any of this to mean anything and which nothing had actually shown. Unmodified YARG on the container's output: 20 accepted, 2 refused, the same two.

Details of the redeploy are in `docs/DEPLOY-VAULT2.md`.

Fifth oracle run — 2026-09-06, a song served from inside a `.zip`

`.zip` / `.7z` ingest landed, so the corpus gained a **23rd case**, `23-zipped` — an ordinary song delivered as `23-zipped.zip` containing `23-zipped/`, which is how songs are actually distributed. The song inside is deliberately unremarkable: the case under test is the container, and a case probing two things at once cannot say which one failed.

Step	Outcome
Index the corpus	23 songs, 23 distinct charts, 0 problems, 14 ms
The zipped song in the catalog	<code>name="Zipped"</code> , <code>source_path=23-zipped.zip</code>
<code>yarg-sync</code> from an empty folder	23 downloaded, 0 failed, 238,215 bytes
Unmodified YARG on the synced folder	21 accepted, 2 refused
Issues our own scanner raises, refusal-class	exactly 2 — the same two
Issues on the zipped song	none

The two refusals are the same two as every run since the corpus existed — `No notes found` on `30334065...` and `No audio accompanying the chart file` on `4ec68053...`. **The song that arrived inside an archive was accepted, and by the time it reached the player's folder it was indistinguishable from any other:** the client writes `<chart_hash>.sng` regardless of what the server ingested it from.

`.7z` is covered by `TestA7zSongPacksToTheSameBytesAsTheLooseFolder` rather than by the corpus, because **Go cannot write a 7z** — the library is read-only. The fixture at `internal/scan/testdata/song.7z` is committed, and was built with `py7zr` from exactly the bytes the loose-folder case uses. Regenerate it from anything else and the test fails for a reason that has nothing to do with 7z.

The strongest assertion of the set is `TestAllThreeContainersProduceTheSameArchive`: a loose folder, a zip of it and a 7z of it all pack to one archive. That is what lets an operator restructure a library without invalidating every client's copy of every song — the same property the random-mask defect broke, arrived at from a different direction.

What is still not measured

One real YARG version, on two Windows machines, against a corpus we wrote ourselves. The corpus is adversarial by design, but it is still ours: it cannot contain the case nobody thought of. A larger body of real community charts would test different things, and the licensing constraints on where those may come from are in the section above.

Both machines run the same Windows build of the same YARG version, so nothing here says anything about Linux, macOS, or a different client release.

The ARM leg — 2026-09-06, and the determinism result crosses an architecture

The arm64 half of "portable to Raspberry Pi" had never been executed; it rested on ELF machine type and image config, which are checks on bytes. It has now run, on a **Raspberry Pi 4 Model B Rev 1.5**, `aarch64`, Debian 13 trixie.

What ran	Evidence
The cross-compiled <code>linux/arm64</code> binary	the Pi's own <code>file</code> : <code>ELF 64-bit LSB executable, ARM aarch64, statically linked</code> ; 22 songs indexed in 24 ms
The published multi-arch container image	<code>arch=arm64</code> , image id <code>3c5fdd28...</code> , <code>version=1ae2219</code> , 22 songs in 25 ms, docker.io 26.1.5

Then both were synced from, and compared against the reference:

Client	Server	Result
ENG-1	ENG-1, working tree (windows/amd64)	reference
ENG-1	same, after a full cache wipe	identical
r7-desktop	ENG-1's server	identical
ENG-1	vault2 container (linux/amd64)	identical
r7-desktop	vault2 container (linux/amd64)	identical
ENG-1	Pi, bare binary (linux/arm64)	identical
ENG-1	Pi, container (linux/arm64)	identical

Seven independent syncs, two operating systems, two CPU architectures, 154 archives, one set of bytes. The mask is derived with SHA-256 over a domain string and the package hash, and nothing had shown that this is stable across architectures — it was assumed, which is the same species of assumption that produced the original defect. It now holds by measurement.

Three caveats, stated rather than buried:

- The board was a **Pi 4, not the 3B+** this project had been waiting on. That 3B+ is dead: steady red PWR, no ACT activity at all, across three independently written cards — one from Imager, one written sector-by-sector and verified by reading it back, and one written by a freshly installed Imager. Zero ACT means the SoC never reads the card, so no card could have fixed it.
- The Pi was **one-shot and wiped afterwards**. This is "arm64 ran on this date", not a maintained deployment, and the claim should be re-measured rather than inherited.
- The image reached the Pi by `docker save` on vault2 and `docker load` on the Pi rather than a direct registry pull, to avoid putting a registry credential on a throwaway host. The image id is identical either way, so what ran is the published image; only its transport differed. The multi-arch manifest itself was separately confirmed to carry both `amd64` and `arm64` .

Hostile archives — 2026-09-06, probed rather than reasoned about

The oracle runs above validate songs that are *supposed* to work. Archive ingest also has to survive files that are not: an operator's library is downloaded from the internet, so the reader is attacker-facing.

None of these behaviours were asserted from reading the standard library. A throwaway `probe_test.go` was written that simply *printed* what happened for each hostile shape, the output was read, and only then were tests written against what was observed. The probe was deleted; what it found is pinned in `internal/scan/hostile_test.go`.

Shape fed in	What actually happened	Now pinned as
<code>../../../../etc/passwd</code> , <code>Song../../../../escape.txt</code> , <code>/etc/shadow</code> alongside a real song	all three dropped by <code>fs.ValidPath</code> ; produced <code>.sng</code> held only <code>song.ogg</code> , <code>notes.mid</code> , <code>album.png</code>	traversal never reaches the served archive
truncated / non-zip bytes with a <code>.zip</code> name	reported cleanly, walk continued, the good song beside it still found	one bad file does not abandon a scan
zip of unrelated files (photos)	<code>ErrNoChart</code> , silently skipped	quiet, so real problems are not buried
empty zip	<code>ErrNoChart</code>	not a song, not a problem
zip containing a <code>.sng</code>	<code>ErrNoChart</code>	not descended into
zip with backslash separators (<code>Song\song.ini</code>)	<code>rootNames</code> empty, <code>rootDirs</code> = <code>[Song]</code> , <code>ErrNoChart</code> → silently ignored	<code>ErrUnreadableArchive</code> , reported

The last row is a real defect, and only the probe found it — a legitimate song disappearing from a library with no message, the same class of failure as silently skipping a `_rb3con`. The reasoning behind the fix, and why the first attempt at it was wrong, is in [ADR-003](#).

Red-proofed, not just green

Each of these tests was confirmed to fail when the behaviour it guards is removed — a test that has never been red proves nothing:

Mutation applied to the source	Test that failed
<code>looksLikeASong</code> → always <code>false</code>	<code>TestAnArchiveThatVisiblyHoldsASongIsNeverSilentlyIgnored</code>
<code>looksLikeASong</code> → always <code>true</code>	<code>TestAnArchiveOfNonSongFilesIsStillIgnoredQuietly</code> , <code>TestAnEmptyArchiveIsNotASong</code>
<code>WalkLibrary</code> swallowing every container error, not just <code>ErrNoChart</code>	<code>TestACorruptArchiveIsReportedAndTheWalkContinues</code> , <code>TestAnArchiveThatVisiblyHoldsASongIsNeverSilentlyIgnored</code>

Both directions of `looksLikeASong` matter, which is why both were mutated: too strict and songs vanish, too loose and every holiday-photos zip becomes a problem entry.

`TestTraversalEntriesNeverReachTheServedArchive` is deliberately **not** red-proofed, and it is honest to say why: the behaviour it pins belongs to Go's `archive/zip` , not to this codebase, so there is no line here to mutate. Its value is not that it catches our regressions — it is that it fails loudly if a toolchain upgrade ever changes a filter we now depend on for a security property.

Sixth oracle-adjacent run — 2026-09-06, the fix observed on the deployment

Two properties were measured on the vault2 container after it was upgraded to `077f36e` , because neither is reachable from a unit test.

Determinism now holds across a code change. Every earlier determinism result compared machines, operating systems or architectures at a *fixed* commit. Here the pack cache was hashed under `423902b` , wiped, and re-packed by the `077f36e` binary: **23 archives, byte-for-byte identical**. A `yarg-sync` from ENG-1 then delivered 23 files totalling 238,215 bytes, and the set of client-side SHA-256s matched the set of server-side pack SHA-256s exactly. That is the property an `ETag` and a `Range` resume actually rely on in practice, since a server is upgraded far more often than it changes CPU.

The silently-ignored song was reproduced on the deployment and observed being reported. A probe archive holding `song.ini` , `notes.mid` and `song.ogg` under `Backslash Song\` was placed in the host library. The server indexed 23 songs with `problems=1` , naming the file and saying what to do about it, in the log and in `/api/v1/library` both. Under the previous image the same file gave `problems=0` and no mention anywhere. The probe was removed and the library restored to 23 clean cases.

Building that probe turned out to demonstrate the defect twice over. Python's `zipfile` rewrites `os.sep` to `/` inside `ZipInfo.__init__`, so the obvious construction silently produces a forward slash and tests nothing; and `namelist()` normalises backslashes on read, so a correctly-built probe still *looks* wrong. Counting `0x5C` bytes in the file is the only honest check. **Both the writer and the reader hide the thing under test** — the same shape as the original defect, where an `fs.FS` view of an archive is not the archive.

Sixth oracle run — 2026-09-07, the first against REAL community charts

Every earlier run scanned songs this project wrote. Jay supplied three community song packs — **128 songs, 1.16 GB** — and they were run through both YARG and our scanner. This closes the gap `docs/SCALE.md` and the section above both name: *self-authored input cannot produce unknown unknowns*.

It also makes the oracle a script rather than a hand procedure. `scripts/oracle.ps1` repoints YARG's `SongFolders`, wipes the cache, launches, waits, compares, and **restores** `settings.json` in a **finally** block so a crash still puts the operator's YARG back.

The result, and why it is a WEAK positive

Songs in library	128
YARG refused	0
Our scanner flagged	0
YARG refused and we passed	0
We flagged and YARG accepted	0

The standard held — but it held *trivially*. **Both sides said everything was fine, so there were no disagreements available to find**. A curated pack that people actually play is close to the least informative sample possible for this test: it contains no broken songs, which is precisely what the comparison exists to catch. Reporting this as "the oracle passed at scale" would be the same error as the second oracle run, which recorded a miss as a pass.

What it *does* establish, and these are worth having:

- **Zero false positives on 128 real charts**. Nothing had ever tested that. A scanner that cried wolf on ordinary community songs would be useless in exactly the situation it is for, and this is the first evidence it does not.
- **The harness works end to end and refuses to lie**. It waits on the *song cache* rather than on `badsongs.txt`, because a library YARG is happy with produces no `badsongs.txt` at all — waiting on that file would hang on the very outcome we most want to report. It requires the

cache's mtime to be newer than the launch, so last run's file cannot be read as this run's verdict, which is a mistake this project has already made once.

- **ErrTooManySongs is right about real files.** Pointed at the three pack `.zip`s as downloaded, the scanner refused all three with *"archive holds more than one song folder; unpack it and add the songs individually"*. That behaviour existed only as a synthetic test until now.

A second, independent oracle: upstream's own scanner

`YARG.Core.UnitTests` has two integration tests, `FullScan` and `QuickScan`, that were being **skipped** — they call `CacheHandler.RunScan` over directories named by the `YARG_TEST_SONG_DIRS` environment variable, and skip when it is unset. Pointed at the same 128 songs, both pass and YARG.Core writes **no** `badsongs.txt`.

That is worth more than one more green tick: it exercises upstream's real scanner in-process, without launching the game, so it can run in seconds and on any machine with the .NET SDK. Note what it does and does not assert — upstream's own comment says *"the only fail condition would be an unhandled exception"* — so it is a crash test over real input, not a verdict test.

What is STILL not covered

- **All 128 songs are `.mid`.** Real-world `.chart` coverage remains zero, and `.chart` is the format with the early-return bug this project already found once.
- **No broken songs.** The sample most likely to find a defect is old, odd and badly made — Frets on Fire era, odd encodings, missing stems, non-Latin metadata. A deliberately ugly hundred would be worth more than these curated packs, and than a thousand more like them.
- **The corpus is not redistributable and is not committed.** These are commercial recordings charted by the community; they live on one machine and only statistics reach this repo. That is the same line drawn at the top of this document, and it is why `cmd/mkscale` exists.

Seventh oracle run — 2026-09-07, songs broken on purpose, and the standard finally fails

The sixth run held trivially: 128 healthy songs, nothing refused, nothing flagged. A comparison where both sides say nothing cannot tell a scanner that agrees with YARG from one that is asleep.

So `cmd/mkbroken` takes songs with **real structure** and damages them in named ways — each case carrying a **predicted verdict**. That turns the oracle from a two-column table into three:

prediction	our scanner	YARG
------------	-------------	------

and each disagreement means something different. YARG refusing what we passed is the standard violated. YARG *accepting* what we predicted it would refuse means our model of YARG is wrong, which a two-column comparison cannot see at all.

16 cases were generated from the 128-song library. **Neither the input nor the output may be committed:** damage a copyrighted recording and it is still a copyrighted recording. The tool ships; what it makes does not.

The result

Songs indexed	14
YARG refused	6
We flagged	5
YARG refused, we PASSED	2
We flagged, YARG accepted	1

The two we missed:

Case	YARG's reason
<code>03-chart-truncated</code>	Corruption of either the ini file or chart/mid file
<code>04-chart-is-not-a-chart</code>	Corruption of either the ini file or chart/mid file

`03` is a MIDI cut to a third of its length. `04` is a plain text file named `notes.mid`. **Our scanner indexes both as perfectly good songs and reports no issue at all**, because it never parses the chart — it only hashes it. Song identity is `SHA1(chart bytes)` by design, and this project has deliberately not reimplemented YARG's parser. The consequence, unnoticed until now, is that we cannot tell a chart from a shopping list, and will happily serve one to a client that then refuses it.

That is the standard this project holds, violated, and found by the corpus on its first run.

The one in the other column is fine: `07-no-song-ini` is flagged by us and loaded by YARG. A scanner is allowed to be stricter than a refusal.

The harness lied first, and the fix changed the answer

The first run of this reported **3** rejections and 3 misses. The corrected run reports **6** and 2. The difference was not YARG.

`badsongs.txt` reports some rejections against the offending **file** rather than the song folder, so keying the comparison on `Split-Path -Leaf` produced a key of `notes.mid` — which matched no case, collapsed four separate rejections onto one key, and made the songs they belonged to look accepted. **The table still added up. It was still wrong.**

Both sides now reduce any path to the song folder relative to the library root, and the script reports **unattributable rejections** explicitly and exits 2 — inconclusive rather than passing — whenever a refusal cannot be matched to a song. A comparison that cannot name what it

compared should say so, not average it away.

That is the fourth instrument failure in this stretch of work, after the length-comparison probe, the socket-exhausted load harness, and the Windows rename-while-open reasoning. The pattern is consistent enough to state as a rule: **when a measurement surprises you, suspect the instrument before the subject** — and when the instrument is fixed, re-read the result, because it may have been wrong in both directions at once.