



INDIAN INSTITUTE OF TECHNOLOGY ROPAR
Department of Computer Science & Engineering
GE103 Introduction to Computing & Data Structures
MidTerm Exam 05 Oct 2018

105/10/18

Max. Marks: 40

Time Limit: 120 minutes

Name: _____

Roll No: _____

NOTE:

- Read the questions carefully, and write your answers as neatly as possible.
- You need to write your answers in the space provided below each question. No extra sheet should be attached to this paper. Rough work may be done in the space provided or in last empty sheet.
- Best wishes !

1. [2 marks] Consider a two dimensional array : $A[6][8]$ of total 48 integer elements. If the base address (A) is 1600 and the system uses zero-indexing, what is the memory address of element $A[3][4]$? Assume:

(a) Row-major order

$$1600 + (3 \times 8 + 4) \times 4 = 1600 + 112 = 1712$$

(b) Column-major order

$$1600 + (4 \times 6 + 3) \times 4 = 1600 + 108 = 1708$$

2. [18 marks] What will be the output for the following codes. Explanation for the output not necessary.

Answers / OUTPUT

```
#include <stdio.h> /* 2 marks */
int main() {
    float f1; int i=40, j=30, k=20;
    int p=5;
    f1=42/4 + 4.0/3 + 5.24;
    p = i>j>k;
    printf("f1= %.2f p=%d", f1, p);
} /* You may use the space here for rough work/calculations */
```

$$f1 = 17.07$$

$$p = 0$$

Answers / OUTPUT

```
#include<stdio.h> /* 2.5 marks */
void main() {
    char arr[ ] = {'l', 'a', 't', 'e', 's', 't'}; //First element is L lower case
    char *p = (arr+2);
    printf("%c", *p+2);
    printf("\n %d %d", sizeof(arr), sizeof(p));
}/* You may use the space here for rough work/calculations */
```

5
6 4

```
#include <stdio.h> /* 2.5 marks */
void main()
{
    for (int k=1; k<4; )
        printf( "%d \n", ++k );
}/* You may use the space here for rough work/calculations */
```

2, 3 k=1 → 2
k=2 → 3
k=3 → 4

2 3 4

```
# include <stdio.h> /* 3 marks */
int main() {
    int i = 0;
    for (i=1; i<20; i++) {
        switch(i) {
            case 1:
                i += 1;
            case 2:
                i += 3;
            case 4:
                i += 4;
            default:
                i += 8;
                break;
        }
        printf(" %d ", i);
    }
    return 0;
}/* You may use the space here for rough work/calculations */
```

15+8=23
17+8=25
i=2 (1+1) → i=3 9+8=17
i=2+3=5 17+1=18
i=5+4=9 18+3=21

17 26

Handwritten notes on a separate sheet of paper, dated 11-2-29, showing a sequence of operations and calculations:

- $P \rightarrow 9$
- $P \rightarrow 11$
- $P \rightarrow 12$
- $P \rightarrow 13$
- $P \rightarrow 14$
- $P \rightarrow 15$
- $P \rightarrow 16$
- $P \rightarrow 17$
- $P \rightarrow 18$
- $P \rightarrow 19$
- $P \rightarrow 20$
- $P \rightarrow 21$
- $P \rightarrow 22$
- $P \rightarrow 23$
- $P \rightarrow 24$
- $P \rightarrow 25$
- $P \rightarrow 26$
- $P \rightarrow 27$
- $P \rightarrow 28$
- $P \rightarrow 29$
- $P \rightarrow 30$
- $P \rightarrow 31$
- $P \rightarrow 32$
- $P \rightarrow 33$
- $P \rightarrow 34$
- $P \rightarrow 35$
- $P \rightarrow 36$
- $P \rightarrow 37$
- $P \rightarrow 38$
- $P \rightarrow 39$
- $P \rightarrow 40$
- $P \rightarrow 41$
- $P \rightarrow 42$
- $P \rightarrow 43$
- $P \rightarrow 44$
- $P \rightarrow 45$
- $P \rightarrow 46$
- $P \rightarrow 47$
- $P \rightarrow 48$
- $P \rightarrow 49$
- $P \rightarrow 50$
- $P \rightarrow 51$
- $P \rightarrow 52$
- $P \rightarrow 53$
- $P \rightarrow 54$
- $P \rightarrow 55$
- $P \rightarrow 56$
- $P \rightarrow 57$
- $P \rightarrow 58$
- $P \rightarrow 59$
- $P \rightarrow 60$
- $P \rightarrow 61$
- $P \rightarrow 62$
- $P \rightarrow 63$
- $P \rightarrow 64$
- $P \rightarrow 65$
- $P \rightarrow 66$
- $P \rightarrow 67$
- $P \rightarrow 68$
- $P \rightarrow 69$
- $P \rightarrow 70$
- $P \rightarrow 71$
- $P \rightarrow 72$
- $P \rightarrow 73$
- $P \rightarrow 74$
- $P \rightarrow 75$
- $P \rightarrow 76$
- $P \rightarrow 77$
- $P \rightarrow 78$
- $P \rightarrow 79$
- $P \rightarrow 80$
- $P \rightarrow 81$
- $P \rightarrow 82$
- $P \rightarrow 83$
- $P \rightarrow 84$
- $P \rightarrow 85$
- $P \rightarrow 86$
- $P \rightarrow 87$
- $P \rightarrow 88$
- $P \rightarrow 89$
- $P \rightarrow 90$
- $P \rightarrow 91$
- $P \rightarrow 92$
- $P \rightarrow 93$
- $P \rightarrow 94$
- $P \rightarrow 95$
- $P \rightarrow 96$
- $P \rightarrow 97$
- $P \rightarrow 98$
- $P \rightarrow 99$
- $P \rightarrow 100$

3. [2 marks] A student wrote following code for reversing an input integer array A of n elements. But on execution, it is observed that the code is wrong. Student approached the TA Raman who replied that there is/are **small mistake(s)** in this code. Spot the mistake(s) (Encircle that line(s)) & mention what should be the correct statement/expression(s) there.

```
void reverse(int A[], int n) {
    int i, j, temp;
    i=0;
    while (i < n) {
        j = n-1-i;
        temp = A[i];
        A[i] = A[j];
        A[j] = temp;
        i++;
    }
}
```

4. [3 marks] Refer to following partial C code to transpose a square matrix (or say 2D array). Complete the code (.... part) without using any additional array and without declaring any additional variable.

```
#include <stdio.h>
#define N 12 /* this value 12 may vary by program user */
void main() {
    int A[N][N]; int i,j,k,temp1,temp2;
    printf("\n Input the NxN matrix elements where N= %d . \n", N);
    for (i=0;i<N;i++) {
        for (j=0;j<N;j++)
            scanf("%d",&(A[i][j]));
    }
```

.... for (i=0; i<N; i++)
 { for (j=0; j<N; j++)

temp1 = A[i][j];

A[i][j] = A[j][i];
 temp2 = A[i][j];
 printf("%d", temp1);
 printf("\n");

~~for (i=0; i<N; i++)
 { for (j=0; j<N; j++)
 temp1 = A[i][j];
 A[i][j] = A[j][i];
 temp2 = A[i][j];
 printf("%d", temp2);
 printf("\n"); }~~

```
printf("\n Following is the TRANSPOSE matrix \n");
for (i=0;i<N;i++) { printf("\n");
    for (j=0;j<N;j++)
        printf("%d ", (A[i][j]));
    }
```


5. [3 marks] Consider the following C code that aims to print the multiplication table of input value n (assume input n will be positive and less than 100). Will this program give the desired output? If not, Identify and Remove the errors (Mark / Encircle the wrong statements (if any) and write there correct statements.)

```
#include <stdio.h>
void main() {
    int n, factor, k;
    printf("\n Enter the number for which you need to print multiplication table \n");
    scanf("%d ", n);
    printf("\n Multiplication table is as follows \n");
    factor=1;
    while (factor<=10) {
        k=n * factor; k = n * factor++ ;
        printf("%d X %02d = %d", n, factor, k );
    }
}
```

5. [5 marks] Given an input string **inp**, complete the C program below that does the following
- It first computes the total number of those characters that appear twice or more in the input string.
 - Then it removes all digits (if any in the input string) and also changes the input string alphabets to lowercase. Then it prints this modified input string as output string.
- As an example, if input string **inp** is "Animesh181SharmAaa", the output would be

No. of characters that repeat = 5

Output String: animeshsharmaaa

/*Ans above 5 because A, m, h, 1, and a are the characters that appear again */

```
#include<stdio.h>
```

```
/* you are not permitted to use any other library functions */
```

```
#define SZ 1000
```

```
void main() {
```

```
int i,j,k,temp1,temp2; char c1, c2, c3;
```

```
char inp[SZ]; scanf("%s", inp); temp2 = 0;
```

```
// ....
```

```
for (i=0; inp[i] != '\0'; i++)
```

```
{ for (j=i+1; inp[j] != '\0'; j++)
```

```
{ if
```

```
for (i=0; inp[i] != '\0'; i++) { temp1 = 0;
```

```
{ for (j=i+1; inp[j] != '\0'; j++)
```

```
if (inp[i] == inp[j]) temp1++;
```

```
if (temp1 > 1) temp2++;
```

```
printf("%d", temp2); }
```

```
for (i=0; inp[i] != '\0'; i++)
```

```
{ if (inp[i] >= 'a' && inp[i] <= 'z')
```

```
{ printf("%c", inp[i]); }
```

```
else if (inp[i] >= 'A' && inp[i] <= 'Z')
```

```
{ inp[i] = inp[i] + 32;
```

```
printf("%c", inp[i]); }
```

(Note: You may safely assume that size of the input string is less than 1000. You may write the code within the **main** function to achieve the purpose or you may write a separate function e.g. **int fun1(char *arr)** and call that function appropriately within **main** function to achieve the purpose)

else

inp[i] = inp[i] + 1;

printf (" %c", inp[i]); }

}

6. [7 marks] Consider a singly linked list (based on NODE structure as mentioned below) referred using the global node pointer variable **head**. Write the C code for successfully deleting the (first appearing) node having data value **key**. If there is no node in the linked list that has data value **key**, the code brings no change to the linked list. If there are multiple nodes with data value **key**, the code deletes that one which appears first while traversing the linked list using global pointer variable **head**.

```
typedef struct node{
    int data;
    struct node * next;
} NODE;
```

Function prototype is as follows - void find_delete(int key);

```
struct node * head = NULL;

void delete( int key );

struct node * temp;

temp = (struct node*) malloc (sizeof(struct node));
temp->data = key;

if ( temp->data head == NULL )
    head = temp;
while ( temp->next != NULL )
{
    if ( temp->data == key )
    {
        head->next = temp->next;
        temp->next = NULL;
        free( temp );
        temp = NULL;
    }
    else if ( temp->data != key )
        temp = temp->next;
}
```