ONE MODEL. SIMULATE. FIT. OPTIMIZE.

Hands-On with Rumoca

James Goppert · Micah Condie

Purdue University · School of Aeronautics and Astronautics

Georgia Tech · 10:00–13:00

Any modeling domain welcome · no aerospace background needed

MODEL
Declare the physics

FIT
Learn from data

OPTIMIZE
Plan the motion

OPEN THE WORKSHOP

github.com/CogniPilot/rumoca_workshop_amc2026

Run the core. Build something extra.

YOUR PROBLEM. YOUR APP.

Make something you care about.

Build with your agent during downtime.

Core: edit a model, fit data, optimize a trajectory

Optional idea: a Three.js Artemis-style launch

THE PRIZE

FREE

CogniPilot stocking cap

Short demos
Audience hand vote

Enter by 12:40 · up to 5 demos · CHALLENGE.md · APP_PROMPT.md

Why Rumoca? One model, many questions.

A unified, declarative foundation for cyberphysical systems.

Lie group theory

Represent rotations and motion with their geometric structure.

Reachable sets

Bound possible behavior of cyberphysical systems under uncertainty.

Formal software verification

Connect model equations to explicit proof obligations.

System identification + digital twins


Fit physical parameters; compare simulation with experiments.

Research directions: fast Monte Carlo / RL · native AD · heterogeneous compute

Today: one Modelica model → simulation → identification → optimization.

Declare once. Ask different questions.

Quadrotor.mo → JAX + CasADi · the same declared equations




Modelica declares physics · Rumoca compiles · backends compute.

Everyone gets a browser plot

TRY THIS

1. Open the playground
2. Paste the complete browser bundle
3. Gear → BrowserFlight → Play



You should see BrowserFlight Results and a plot.

Choose a full-workshop route

01 Browser: modeling and predictions; no account

02 Codespaces: Python + VS Code; login and allowance

03 Local uv: Python + VS Code; pinned CPU packages


04 Pair or screenshare: keep working if setup fails

Switch route after ten minutes of setup trouble.

Edit with feedback. Check the pipeline.

TRY THIS

1. Open Quadrotor.mo in models/
2. Hover m; try sin completion
3. Run the smoke test; open results/live





```
$ uv run --frozen python scripts/smoke_test.py
```

WORKSHOP PASS · model editor ready

The user guide is a live modeling lab

TRY THIS

1. Edit StopTime: 30 → 2 s
2. Simulate; select the final frame
3. Switch vorticity / pressure




User-guide link and recovery: WORKSHOP.md · no install needed

A planar quadrotor we can inspect

READ THE MODEL

1. World x right; z up
2. Positive pitch tilts thrust toward +x
3. Hover: T = mg = 11.772 N



Find velocities, pitch rate, thrust and torque in the model.

Your first engineering change: drag

Change k_quad = 0.0 to 0.08, save, then simulate.

$$D(v) = -k_{\text{linear}} v - k_{\text{quad}} \sqrt{v^2 + \varepsilon^2}\, v$$

Linear: N s/m Quadratic: N s²/m² ε = 0.01 m/s


Nonnegative coefficients ⇒ drag opposes motion

```
$ uv run --frozen python scripts/simulate.py
```

What changes at high speed? What about negative velocity?

More drag, less distance

Reference at 8 s: 41.60 m → 17.97 m



Compare your current default with the two reference cases.

Back at

11:10

10 MINUTES

Stretch. Ask a question. Keep your editor open.

KEEP YOUR PLACE

Keep your editor and terminal open.


Your simulation plot is the recovery point.

Next: learn drag from noisy data.

Worksheet and commands: WORKSHOP.md · scan the opening QR.

Known experiment. Unknown coefficients.

Three training flights; one held-out flight. 20 Hz, 8 s each.



Speed variation helps separate linear and quadratic drag.

Differentiate the prediction error

Positive parameters; noise-scaled loss; bounded optimization

Generated RHS Modelica → JAX → RK4 rollout positive drag → Data residuals scaled by noise → JAX gradients L-BFGS-B


$$L = \mathrm{mean}\left[\left(\frac{\hat{y} - y}{\sigma}\right)^2\right]$$

$$k_l / k_{l,\mathrm{ref}} = e^a, \quad k_q / k_{q,\mathrm{ref}} = e^b$$

JAX provides gradients. SciPy updates the coefficients.

Run the fit. Test the held-out flight.

Open fit_drag.png and fit_drag.json; compare before and after.




```
$ uv run --frozen python scripts/fit_drag_jax.py
```

Two coefficients · lower loss · improved held-out prediction

Check your result. Keep building.

01 Open your before-and-after prediction plot

02 Compare the held-out flight and fitted values


03 Stretch: rerun from another starting guess


04 App builders: keep your prototype moving

Fit complete? Continue your app or explore the optional checks.

Make a target. Learn a policy.

target.toml → generated Torch → differentiable policy learning






```
$ uv run --frozen --group torch python scripts/learn_hover_torch.py
```

Held-out cost ≈ 0.116 → 0.021 · optional instructions: BACKENDS.md

Back at

12:10

10 MINUTES

Stretch. Ask a question. Keep your editor open.

KEEP YOUR PLACE

Keep your fitted coefficients.

Next: plan a flight using your fit.

Your fit plot is the recovery point.

Same Modelica source; now compile to CasADi.

Move between hovers, respect limits

THE IDEA

1. (0, 1) m → (4, 2) m in 6 s
2. Track target; limit effort and control changes
3. Bound thrust, torque, pitch and altitude



T: 0–20 N τ: ±0.35 N m


z: 0.25–4 m |θ| ≤ 0.55 rad

60 shooting intervals · node pitch margin · independent reintegration

Identified drag is an input to this optimization.

Solve. Inspect. Explain the braking.

Open optimization.png and optimization.json.




```
$ uv run --frozen python scripts/optimize_casadi.py
```

Solve_Succeeded · limits respected · arrive near rest

Next up: pylon racing at PURT


FROM DIGITAL TWIN TO THE RACE COURSE

Build. Fly. Race.

The next competition will leverage Rumoca

Design, simulate, then flight-test your autonomy

Digital twin → real aircraft at PURT



ILLUSTRATIVE COURSE · EVENT DETAILS ON THE SITE


FOLLOW THE
NEXT COMPETITION

pylon-racing.geddes.rcac.purdue.edu

Explore the fixed-wing workbench

TRY THIS

1. Modelica flight simulation + autopilot
2. Try 50 Hz → 20 Hz, restart, then observe
3. Also: slam_web (in development), mocap_sysid



Live links + short experiments: BROWSER_APPS.md

Show your app. Vote for the cap.

5	45 s	1
MAX. PRESENTERS	EACH DEMO	VOTE PER PERSON

Show an interaction + one checked result

Name your agent. Share elapsed build time + your GitHub.

Audience favorite wins a free CogniPilot stocking cap

Random draw if more than 5 ready entries → audience hand vote

Bring your model.
Join the work.

1. Bring a model or a question from your own domain
2. Add a validation case, model library or compiler fix
3. Start a conversation: problem + model + one check


James Goppert · Micah Condie


Scan to join the work · COMMUNITY.md · questions welcome


Exact-real proofs and numerical evidence

THE IDEA

1. Lean: equation equality and invariants
2. Audit: gradients, profiles, integration
3. Papers: model and method choices







None of these certify arbitrary edits or real flight.

Primary papers behind the approach

1. Faessler et al., RA-L 2018: rotor-drag physics and excitation
2. Andersson et al., 2019: CasADi AD and multiple shooting
3. Raue 2009; Wieland 2021: practical identifiability and profiles

World-axis teaching drag differs from body-axis rotor aerodynamics.

Research questions worth exploring

01 Solver specialization across CPU, GPU and embedded hardware

02 Fast batched Monte Carlo and reinforcement learning


03 Native AD and JAX / CasADi / PyTorch integrations

04 Extensible targets for your own numerical tools

Bring a falsifiable question and a measurable benchmark.

Numerical constraints need validation

Reintegrate the inputs independently; inspect errors by physical unit.



Small defects, pitch margin and fine rollout are separate checks.