MigraAI session conversion report

1. Summary

- Package: migraai-teradata-to-snowflake
- Run ID: sample-teradata-snowflake
- Created: 2026-01-01T00:00:00Z
- Total objects: 56
- converted: 56
- expert_review: 0
- failed: 0
- cancelled: 0
- Included in package: 56
- converted: 56
- escalated: 0
- expert review: 0
- failed: 0

2. Source and target

- Source platform: teradata
- Target platform: snowflake
- Confidence threshold: 85%
- KB version: n/a

3. Scope and inventory

Object type	Count
grant	7
hash_index	2
index	2
join_index	1
macro	1
procedure	5
role	3
script	1
synonym	1
table	21
user	2
view	10

Source files:

- indexes.sql
- load_script.sql
- maintenance.sql
- routines.sql
- security.sql
- tables.sql
- views.sql

External references:

- sales.customer_archive

4. Data sent to Devin

- Consent given at: 2026-01-01T00:00:00Z
- Devin host: local mock
- Objects sent: 56
- Batches: 3
- Sessions: 9
- Total ACUs: not reported by the Devin API
- Blocked batches: 0

Role	Batch	State	ACUs	Link
voter_a	0	done	n/a	mock://golden/session-0000
voter_a	1	done	n/a	mock://golden/session-0001
voter_a	2	done	n/a	mock://golden/session-0002
voter_b	0	done	n/a	mock://golden/session-0003
voter_b	1	done	n/a	mock://golden/session-0004
voter_b	2	done	n/a	mock://golden/session-0005
voter_c	0	done	n/a	mock://golden/session-0006
voter_c	1	done	n/a	mock://golden/session-0007
voter_c	2	done	n/a	mock://golden/session-0008

5. Conversion results

Name	Type	Status	Confidence %	Agreement %	Escalated
sales.recovered_after_error	table	converted	98	100	no
reader	role	converted	98	100	no
operator	role	converted	98	100	no
auditor	role	converted	98	100	no
analyst	user	converted	98	100	no
loader	user	converted	98	100	no
ROLE on reader	grant	converted	98	100	no
ROLE on operator	grant	converted	98	100	no
sales.customer	table	converted	98	100	no
sales.account	table	converted	98	100	no
sales.branch	table	converted	98	100	no
sales.employee	table	converted	98	100	no
sales.product	table	converted	98	100	no
sales.order_header	table	converted	98	100	no
sales.order_line	table	converted	98	100	no
sales.payment	table	converted	98	100	no
sales.loan	table	converted	98	100	no
sales.loan_payment	table	converted	98	100	no

Name	Type	Status	Confidence %	Agreement %	Escalated
sales.card	table	converted	98	100	no
sales.card_txn	table	converted	98	100	no
sales.transfer	table	converted	98	100	no
sales.audit_log	table	converted	98	100	no
sales.risk_score	table	converted	98	100	no
sales.account_snapshot	table	converted	98	100	no
sales.customer_segment	table	converted	98	100	no
sales.external_rate	table	converted	98	100	no
sales.daily_balance	table	converted	98	100	no
sales.recovered_table	table	converted	98	100	no
sales.ix_customer_status	index	converted	92	100	no
sales.ix_account_customer	index	converted	92	100	no
sales.hix_account	hash_ index	converted	98	100	no
sales.hix_card	hash_ index	converted	98	100	no
sales.jix_order	join_ index	converted	98	100	no
sales.customer_alias	synonym	converted	98	100	no
load_script.sql	script	converted	92	100	no
sales.add_payment	procedure	converted	87	100	no
sales.update_balance	procedure	converted	87	100	no
sales.post_transfer	procedure	converted	87	100	no
sales.capture_snapshot	procedure	converted	92	100	no
sales.repair_payment	procedure	converted	87	100	no
sales.refresh_daily	macro	converted	92	100	no
SELECT, INSERT on sales.payment	grant	converted	98	100	no
SELECT on sales.audit_log	grant	converted	98	100	no
EXECUTE PROCEDURE on sales.add_payment	grant	converted	98	100	no
sales.customer_accounts	view	converted	98	100	no
sales.account_payments	view	converted	98	100	no
sales.customer_loans	view	converted	98	100	no
sales.order_detail	view	converted	98	100	no
sales.card_activity	view	converted	98	100	no
sales.transfer_activity	view	converted	98	100	no
sales.customer_risk	view	converted	98	100	no
sales.daily_account_balances	view	converted	98	100	no
sales.customer_external_rate	view	converted	98	100	no
sales.unuploaded_reference	view	converted	98	100	no
SELECT on sales.customer_accounts	grant	converted	98	100	no
SELECT on sales.account_payments	grant	converted	98	100	no

6. Validation

Check	Passed	Failed	N/A	Pass rate
syntax	50	6	0	89%
lint	56	0	0	100%
semantic	56	0	0	100%
rule	49	7	0	88%
dependency	31	0	25	100%
object_reference	28	0	28	100%
security	56	0	0	100%

Top findings:

Rule	Check	Severity	Count
syntax. opaque_ statement	syntax	warning	13
syntax.parse_error	syntax	error	6
snowflake. rule. procedure_ execute_ as	rule	error	5
security. masked_ secret_ placeholder	security	warning	3
snowflake. rule. no_ create_ index	rule	error	2

7. Expert review and failed items

None.

8. Assumptions, unsupported constructs and masked secrets

Assumptions

None.

Unsupported constructs

None.

Masked secrets

- WARNING: analyst (security-converted.sql) contains the masked placeholder `***MASKED***`. Replace each one with a secret reference for the target (for example a secret store or environment variable) before running.
- WARNING: loader (security-converted.sql) contains the masked placeholder `***MASKED***`. Replace each one with a secret reference for the target (for example a secret store or environment variable) before running.
- WARNING: load_script.sql (load_script-converted.sql) contains the masked placeholder `***MASKED***`. Replace each one with a secret reference for the target (for example a secret store or environment variable) before running.

9. Execution order and next steps

1. SALES.RECOVERED_AFTER_ERROR (table, converted) -> converted/maintenance-converted.sql
2. reader (role, converted) -> converted/security-converted.sql
3. operator (role, converted) -> converted/security-converted.sql
4. auditor (role, converted) -> converted/security-converted.sql

5. analyst (user, converted) -> converted/security-converted.sql
6. loader (user, converted) -> converted/security-converted.sql
7. ROLE on reader (grant, converted) -> converted/security-converted.sql
8. ROLE on operator (grant, converted) -> converted/security-converted.sql
9. SALES.CUSTOMER (table, converted) -> converted/tables-converted.sql
10. SALES."ACCOUNT" (table, converted) -> converted/tables-converted.sql
11. SALES.BRANCH (table, converted) -> converted/tables-converted.sql
12. SALES.EMPLOYEE (table, converted) -> converted/tables-converted.sql
13. SALES.PRODUCT (table, converted) -> converted/tables-converted.sql
14. SALES.ORDER_HEADER (table, converted) -> converted/tables-converted.sql
15. SALES.ORDER_LINE (table, converted) -> converted/tables-converted.sql
16. SALES.PAYMENT (table, converted) -> converted/tables-converted.sql
17. SALES.LOAN (table, converted) -> converted/tables-converted.sql
18. SALES.LOAN_PAYMENT (table, converted) -> converted/tables-converted.sql
19. SALES.CARD (table, converted) -> converted/tables-converted.sql
20. SALES.CARD_TXN (table, converted) -> converted/tables-converted.sql
21. SALES.TRANSFER (table, converted) -> converted/tables-converted.sql
22. SALES.AUDIT_LOG (table, converted) -> converted/tables-converted.sql
23. SALES.RISK_SCORE (table, converted) -> converted/tables-converted.sql
24. SALES.ACCOUNT_SNAPSHOT (table, converted) -> converted/tables-converted.sql
25. SALES.CUSTOMER_SEGMENT (table, converted) -> converted/tables-converted.sql
26. SALES.EXTERNAL_RATE (table, converted) -> converted/tables-converted.sql
27. SALES.DAILY_BALANCE (table, converted) -> converted/tables-converted.sql
28. SALES.RECOVERED_TABLE (table, converted) -> converted/tables-converted.sql
29. SALES.IX_CUSTOMER_STATUS (index, converted) -> converted/indexes-converted.sql
30. SALES.IX_ACCOUNT_CUSTOMER (index, converted) -> converted/indexes-converted.sql
31. SALES.HIX_ACCOUNT (hash_index, converted) -> converted/indexes-converted.sql
32. SALES.HIX_CARD (hash_index, converted) -> converted/indexes-converted.sql
33. SALES.JIX_ORDER (join_index, converted) -> converted/indexes-converted.sql
34. SALES.CUSTOMER_ALIAS (synonym, converted) -> converted/indexes-converted.sql
35. LOAD_SCRIPT.SQL (script, converted) -> converted/load_script-converted.sql
36. SALES.ADD_PAYMENT (procedure, converted) -> converted/routines-converted.sql
37. SALES.UPDATE_BALANCE (procedure, converted) -> converted/routines-converted.sql
38. SALES.POST_TRANSFER (procedure, converted) -> converted/routines-converted.sql
39. SALES.CAPTURE_SNAPSHOT (procedure, converted) -> converted/routines-converted.sql
40. SALES.REPAIR_PAYMENT (procedure, converted) -> converted/routines-converted.sql
41. SALES.REFRESH_DAILY (macro, converted) -> converted/routines-converted.sql
42. SELECT, INSERT on sales.payment (grant, converted) -> converted/security-converted.sql
43. SELECT on sales.audit_log (grant, converted) -> converted/security-converted.sql
44. EXECUTE PROCEDURE on sales.add_payment (grant, converted) -> converted/security-converted.sql
45. SALES.CUSTOMER_ACCOUNTS (view, converted) -> converted/views-converted.sql
46. SALES.ACCOUNT_PAYMENTS (view, converted) -> converted/views-converted.sql
47. SALES.CUSTOMER_LOANS (view, converted) -> converted/views-converted.sql
48. SALES.ORDER_DETAIL (view, converted) -> converted/views-converted.sql
49. SALES.CARD_ACTIVITY (view, converted) -> converted/views-converted.sql
50. SALES.TRANSFER_ACTIVITY (view, converted) -> converted/views-converted.sql
51. SALES.CUSTOMER_RISK (view, converted) -> converted/views-converted.sql
52. SALES.DAILY_ACCOUNT_BALANCES (view, converted) -> converted/views-converted.sql
53. SALES.CUSTOMER_EXTERNAL_RATE (view, converted) -> converted/views-converted.sql
54. SALES.UNUPLOADED_REFERENCE (view, converted) -> converted/views-converted.sql
55. SELECT on sales.customer_accounts (grant, converted) -> converted/security-converted.sql
56. SELECT on sales.account_payments (grant, converted) -> converted/security-converted.sql

Next steps:

- Review the expert-review items: their converted files carry a `NEEDS-REVIEW` header.
- Replace every masked placeholder (`***MASKED***`) with a secret reference for the target.
- Run the runner in execution/snowflake/ first in its default dry-run mode, which prints the ordered plan without connecting; then rerun with `--execute`.
- Add `--include-review` only after the expert-review files are approved.
- MigraAI never connects to the target; the runner uses the target CLI's own config.