

MigraAI Migration Plan

teradata -> snowflake

Date: 2026-01-01T00:00:00+00:00

KB version: 1

Origin: local_draft

Devin token not configured

Table of Contents

1. A. Architecture Overview
2. B. Major Differences
3. C. Recommended Migration Strategy
4. D. Migration Phases
5. E. Dependencies
6. F. Deliverables
7. G. Object Mapping
8. H. SQL Dialect Differences
9. I. Compatibility Matrix
10. J. Data Movement Plan
11. K. ETL Migration Plan
12. L. Security Migration Plan
13. M. Validation Strategy
14. N. Testing Strategy
15. O. Unsupported Features
16. P. Workarounds
17. Q. Effort Estimation
18. R. Risk Assessment
19. S. Confidence Scoring
20. T. Expert Review Items
21. U. Optimization Hints

A. Architecture Overview

Teradata

- Teradata PE and AMP vprocs share neither memory nor disk, giving a shared-nothing design. (source)
- Teradata hashes each row to an AMP using the row hash of its primary index or primary AMP index. (source)

Snowflake

- Snowflake architecture is a hybrid of shared-disk and shared-nothing database designs. (source)
- Snowflake architecture is organised into key layers including database storage, query processing and cloud services. (source)
- Hybrid tables use index-based random reads and writes, support row locking and enforce unique and referential integrity constraints. (source)

Teradata -> Snowflake differences

- Teradata PE and AMP vprocs share neither memory nor disk, giving a shared-nothing design. (source)
- Snowflake separates centralized storage from virtual warehouse compute in a hybrid shared-disk and shared-nothing design. (source)
- Snowflake stores table data in automatically managed micro-partitions. (source)

1. KB-351 — Platform architecture profile
2. KB-352 — Platform architecture profile
3. KB-266 — Platform architecture profile
4. KB-267 — Platform architecture profile
5. KB-268 — Platform architecture profile
6. KB-3705 — Pair architecture overview
7. KB-3706 — Pair architecture overview
8. KB-3707 — Pair architecture overview

B. Major Differences

Teradata -> Snowflake differences

- Choosing primary indexes so joined rows hash to the same AMP avoids redistributing rows across the BYNET. (source)
- Snowflake separates centralized storage from virtual warehouse compute in a hybrid shared-disk and shared-nothing design. (source)
- Teradata balances work by spreading rows evenly across AMPs, each solely responsible for its own data. (source)
- Snowflake multi-cluster warehouses add clusters automatically to handle query concurrency. (source)
- Teradata row level security controls access per row and per SQL operation by comparing user and row security labels. (source)
- Snowflake access control combines discretionary and role-based models, granting privileges to roles. (source)
- Teradata row partitioning (PPI) enables row partition elimination for large query gains. (source)
- Snowflake stores table data in automatically managed micro-partitions. (source)

1. KB-3736 — Major platform difference
2. KB-3737 — Major platform difference
3. KB-3740 — Major platform difference
4. KB-3741 — Major platform difference

5. KB-3738 — Major platform difference
6. KB-3739 — Major platform difference
7. KB-3734 — Major platform difference
8. KB-3735 — Major platform difference

C. Recommended Migration Strategy

Teradata -> Snowflake differences

- Start with an inventory from the Teradata resource catalog, then convert DDL and SQL with a translation tool where one exists and review the output by hand. Move data in bulk through cloud object storage into Snowflake, then load increments until cut-over. Re-design physical layout (distribution, partitioning, indexing) for Snowflake instead of copying Teradata structures, rewrite procedural code and security rules, and validate row counts and aggregates per table before switching consumers.

D. Migration Phases

Teradata -> Snowflake differences

- Plan discovery, design, build, validation, and cutover phases for Teradata -> Snowflake.

E. Dependencies

Teradata -> Snowflake differences

- Confirm platform access, network connectivity, security, tooling, and operational dependencies for Teradata -> Snowflake.

F. Deliverables

Teradata -> Snowflake differences

- Deliver a migration inventory, converted artifacts, validation evidence, runbooks, and cutover plan for Teradata -> Snowflake.

G. Object Mapping

Teradata -> Snowflake differences

- **TABLE (primary index) -> Table (micro-partitioned):** Snowflake stores table data in automatically managed micro-partitions. (source)
- **MACRO -> Stored procedure (Snowflake Scripting):** Snowflake stored procedures can be written in SQL (Snowflake Scripting), JavaScript, Python, Java or Scala. (source)
- **SQL stored procedure -> Stored procedure (Snowflake Scripting):** Snowflake stored procedures can be written in SQL (Snowflake Scripting), JavaScript, Python, Java or Scala. (source)
- **Row-level security constraint -> Row access policy:** Snowflake row access policies determine which rows a query can return. (source)
- **Foreign table (NOS) -> External stage:** A Snowflake named external stage is a schema object that stores the URL to files in cloud storage. (source)
- **JSON column -> VARIANT / OBJECT / ARRAY column:** Snowflake semi-structured types include VARIANT, OBJECT and ARRAY. (source)

1. KB-3742 — Object mapping evidence
2. KB-3744 — Object mapping evidence
3. KB-3744 — Object mapping evidence
4. KB-3745 — Object mapping evidence
5. KB-3746 — Object mapping evidence
6. KB-3747 — Object mapping evidence

H. SQL Dialect Differences

Teradata -> Snowflake differences

- Teradata ZEROIFNULL converts null to 0. (source)
- Snowflake supports QUALIFY to filter window function results. (source)
- Teradata OREPLACE replaces every occurrence of a search string. (source)
- Snowflake MERGE inserts, updates and deletes target rows based on a source. (source)
- Snowflake Scripting adds procedural blocks, variables, loops and exception handling to SQL. (source)
- A Teradata macro is one or more SQL statements run as a single request. (source)

1. KB-3709 — Knowledge-base claim for SQL Dialect Differences
2. KB-3711 — Knowledge-base claim for SQL Dialect Differences
3. KB-3710 — Knowledge-base claim for SQL Dialect Differences
4. KB-3712 — Knowledge-base claim for SQL Dialect Differences
5. KB-3713 — Knowledge-base claim for SQL Dialect Differences

6. KB-3708 — Knowledge-base claim for SQL Dialect Differences

I. Compatibility Matrix

Teradata -> Snowflake differences

Kind	Canonical	Source native	Target native
type	array	no direct equivalent	ARRAY / ARRAY(type) (https://docs.snowflake.com/en/sql-reference/data-ty
type	binary	BLOB (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals BYTE(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
type	boolean	no direct equivalent	BOOLEAN (https://docs.snowflake.com/en/sql-reference/data-ty
type	char	CHAR(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals GRAPHIC(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	CHAR(n) / VARCHAR(n) / NCHAR (https://docs.snowflake.com/en/sql-reference/data-ty
type	date	DATE (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	DATE (https://docs.snowflake.com/en/sql-reference/data-ty
type	decimal	NUMBER(p,s) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	INT / INTEGER / BIGINT / SMALLINT / TINYINT / BYTEINT (https://docs.snowflake.com/en/sql-reference/data-ty NUMBER(p,s) / DECIMAL / NUMERIC (https://docs.snowflake.com/en/sql-reference/data-ty
type	float64	no direct equivalent	FLOAT / FLOAT4 / FLOAT8 / DOUBLE / REAL (https://docs.snowflake.com/en/sql-reference/data-ty
type	geography	no direct equivalent	GEOGRAPHY (https://docs.snowflake.com/en/sql-reference/data-ty
type	geometry	no direct equivalent	GEOMETRY (https://docs.snowflake.com/en/sql-reference/data-ty
type	int16	SMALLINT (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
type	int32	INTEGER (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
type	int64	BIGINT (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
type	int8	BYTEINT (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
type	interval	INTERVAL DAY(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	INTERVAL YEAR TO MONTH / DAY TO SECOND (https://docs.snowflake.com/en/sql-reference/data-ty
type	json	JSON (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/Database-Design/Database-ty	VARIANT (https://docs.snowflake.com/en/sql-reference/data-ty
type	map	no direct equivalent	MAP(key, value) (https://docs.snowflake.com/en/sql-reference/data-ty
type	other	no direct equivalent	VARCHAR (for uuid / xml / period) (https://docs.snowflake.com/en/sql-reference/data-ty
type	period	PERIOD(DATE	TIMESTAMP) (https://docs.teradata.com/r/Enterprise_IntelliFlex_V
type	string	CLOB (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	STRING / TEXT (https://docs.snowflake.com/en/sql-reference/data-ty

Kind	Canonical	Source native	Target native
type	struct	no direct equivalent	OBJECT / OBJECT(field type, ...) (https://docs.snowflake.com/en/sql-reference/data-ty
type	time	TIME(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	TIME (https://docs.snowflake.com/en/sql-reference/data-ty
type	time_tz	TIME(n) WITH TIME ZONE (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
type	timestamp	TIMESTAMP(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	TIMESTAMP_NTZ / DATETIME (https://docs.snowflake.com/en/sql-reference/data-ty
type	timestamp_tz	TIMESTAMP(n) WITH TIME ZONE (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	TIMESTAMP_LTZ (https://docs.snowflake.com/en/sql-reference/data-ty TIMESTAMP_TZ (https://docs.snowflake.com/en/sql-reference/data-ty
type	varbinary	VARBYTE(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	BINARY / VARBINARY (https://docs.snowflake.com/en/sql-reference/data-ty
type	varchar	VARCHAR(n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	VARCHAR(n) (https://docs.snowflake.com/en/sql-reference/data-ty
function	(no ANSI equivalent)	INITCAP(s) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a LAST_DAY(d) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Date-and-Time-Function LPAD(s, n, fill) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a MONTHS_BETWEEN(a, b) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Date-and-Time-Function NEXT_DAY(d, weekday) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Date-and-Time-Function OREPLACE(s, from, to) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a OTRANSLATE(s, from, to) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a REGEXP_REPLACE(s, re, r) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a REGEXP_SUBSTR(s, re) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a STRTOK(s, delims, n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a TRUNC(x, n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	ARRAY_AGG(x)	no direct equivalent	ARRAY_AGG(x) (https://docs.snowflake.com/en/sql-reference/functio
function	CARDINALITY(a)	no direct equivalent	ARRAY_SIZE(a) (https://docs.snowflake.com/en/sql-reference/functio
function	CASE WHEN a IS NOT NULL THEN b ELSE c END	no direct equivalent	NVL2(a, b, c) (https://docs.snowflake.com/en/sql-reference/functio
function	CASE WHEN b = 0 THEN 0 ELSE a / b END	no direct equivalent	DIV0(a, b) (https://docs.snowflake.com/en/sql-reference/functio
function	CASE WHEN c THEN a ELSE b END	no direct equivalent	IFF(c, a, b) (https://docs.snowflake.com/en/sql-reference/functio
function	CASE WHEN x = s1 THEN r1 ... ELSE d END	no direct equivalent	DECODE(x, s1, r1, ..., d) (https://docs.snowflake.com/en/sql-reference/functio
function	CASE WHEN x IS NOT NULL THEN a ELSE b END	NVL2(x, a, b) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	CASE x WHEN s1 THEN r1 ... ELSE d END	DECODE(x, s1, r1, ..., d) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent

Kind	Canonical	Source native	Target native
function	CAST(s AS DATE)	TO_DATE(s, fmt) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	TO_DATE(s, fmt) (https://docs.snowflake.com/en/sql-reference/functio
function	CAST(s AS DECIMAL(p,s))	TO_NUMBER(s, fmt) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Data-Types-and-Literals	no direct equivalent
function	CAST(s AS TIMESTAMP)	no direct equivalent	TO_TIMESTAMP_NTZ(s) (https://docs.snowflake.com/en/sql-reference/functio
function	CAST(s AS t)	no direct equivalent	TRY_CAST(s AS t) (https://docs.snowflake.com/en/sql-reference/functio
function	CAST(x AS VARCHAR)	no direct equivalent	TO_CHAR(x, fmt) / TO_VARCHAR (https://docs.snowflake.com/en/sql-reference/functio
function	CHAR_LENGTH(s)	CHARACTER_LENGTH(s) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	COALESCE(a, b)	NVL(a, b) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	NVL(a, b) / IFNULL (https://docs.snowflake.com/en/sql-reference/functio
function	COALESCE(x, 0)	ZEROIFNULL(x) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	ZEROIFNULL(x) (https://docs.snowflake.com/en/sql-reference/functio
function	COUNT(DISTINCT x)	no direct equivalent	APPROX_COUNT_DISTINCT(x) (https://docs.snowflake.com/en/sql-reference/functio
function	CURRENT_TIMESTAMP	no direct equivalent	CURRENT_TIMESTAMP / GETDATE / SYSTIMESTAMP (https://docs.snowflake.com/en/sql-reference/functio
function	DATE_TRUNC('MONTH', d) + INTERVAL '1' MONTH - INTERVAL '1' DAY	no direct equivalent	LAST_DAY(d) (https://docs.snowflake.com/en/sql-reference/functio
function	DATE_TRUNC(part, d)	no direct equivalent	DATE_TRUNC(part, d) (https://docs.snowflake.com/en/sql-reference/functio
function	EXTRACT(<part> FROM b - a)	no direct equivalent	DATEDIFF(part, a, b) (https://docs.snowflake.com/en/sql-reference/functio
function	EXTRACT(f FROM x)	EXTRACT(f FROM x) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Date-and-Time-Function	no direct equivalent
function	JSON_QUERY(s, '$')	no direct equivalent	PARSE_JSON(s) (https://docs.snowflake.com/en/sql-reference/functio
function	LISTAGG(x, d) WITHIN GROUP (ORDER BY o)	no direct equivalent	LISTAGG(x, d) WITHIN GROUP (ORDER BY o) (https://docs.snowflake.com/en/sql-reference/functio
function	MOD(a, b)	MOD(a, b) / a MOD b (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	NULLIF(x, 0)	NULLIFZERO(x) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	PERCENTILE_CONT(0.5) WITHIN GROUP (ORDER BY x)	no direct equivalent	MEDIAN(x) (https://docs.snowflake.com/en/sql-reference/functio
function	POSITION(a IN b)	POSITION(a IN b) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	POSITION(b IN a) > 0	no direct equivalent	CONTAINS(a, b) (https://docs.snowflake.com/en/sql-reference/functio
function	POSITION(search IN s)	INSTR(s, search) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	POSITION(sub IN s)	no direct equivalent	CHARINDEX(sub, s[, pos]) (https://docs.snowflake.com/en/sql-reference/functio
function	REGEXP_REPLACE(s, p, r)	no direct equivalent	REGEXP_REPLACE(s, p, r) (https://docs.snowflake.com/en/sql-reference/functio

Kind	Canonical	Source native	Target native
function	ROUND(x, n)	ROUND(x, n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	SPLIT_PART(s, d, n)	no direct equivalent	SPLIT_PART(s, d, n) (https://docs.snowflake.com/en/sql-reference/functio
function	SUBSTRING(s FROM p FOR l)	SUBSTRING(s FROM p FOR l) / SUBSTR (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	SUBSTRING(s SIMILAR p ESCAPE '#')	no direct equivalent	REGEXP_SUBSTR(s, p) (https://docs.snowflake.com/en/sql-reference/functio
function	TRIM(s)	TRIM(s) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Functions-Expressions-a	no direct equivalent
function	UPPER(s) LIKE UPPER(p)	no direct equivalent	s ILIKE p (https://docs.snowflake.com/en/sql-reference/functio
function	a IS NOT DISTINCT FROM b	no direct equivalent	EQUAL_NULL(a, b) (https://docs.snowflake.com/en/sql-reference/functio
function	a LIKE b		'%'
function	d + n * INTERVAL '1' <part>	no direct equivalent	DATEADD(part, n, d) (https://docs.snowflake.com/en/sql-reference/functio
function	d + n * INTERVAL '1' MONTH	ADD_MONTHS(d, n) (https://docs.teradata.com/r/Enterprise_IntelliFlex_VMware/SQL-Date-and-Time-Function	no direct equivalent
function	ts AT TIME ZONE tz	no direct equivalent	CONVERT_TIMEZONE(tz, ts) (https://docs.snowflake.com/en/sql-reference/functio

1. KB-836 — Platform compatibility mapping
2. KB-837 — Platform compatibility mapping
3. KB-838 — Platform compatibility mapping
4. KB-839 — Platform compatibility mapping
5. KB-840 — Platform compatibility mapping
6. KB-841 — Platform compatibility mapping
7. KB-842 — Platform compatibility mapping
8. KB-843 — Platform compatibility mapping
9. KB-844 — Platform compatibility mapping
10. KB-845 — Platform compatibility mapping
11. KB-846 — Platform compatibility mapping
12. KB-847 — Platform compatibility mapping
13. KB-848 — Platform compatibility mapping
14. KB-849 — Platform compatibility mapping
15. KB-850 — Platform compatibility mapping
16. KB-851 — Platform compatibility mapping
17. KB-852 — Platform compatibility mapping
18. KB-853 — Platform compatibility mapping
19. KB-854 — Platform compatibility mapping
20. KB-855 — Platform compatibility mapping
21. KB-856 — Platform compatibility mapping
22. KB-857 — Platform compatibility mapping
23. KB-858 — Platform compatibility mapping
24. KB-859 — Platform compatibility mapping
25. KB-860 — Platform compatibility mapping
26. KB-861 — Platform compatibility mapping
27. KB-862 — Platform compatibility mapping
28. KB-863 — Platform compatibility mapping
29. KB-864 — Platform compatibility mapping
30. KB-865 — Platform compatibility mapping
31. KB-866 — Platform compatibility mapping
32. KB-867 — Platform compatibility mapping
33. KB-868 — Platform compatibility mapping
34. KB-869 — Platform compatibility mapping
35. KB-870 — Platform compatibility mapping
36. KB-871 — Platform compatibility mapping

37. KB-872 — Platform compatibility mapping
38. KB-873 — Platform compatibility mapping
39. KB-874 — Platform compatibility mapping
40. KB-875 — Platform compatibility mapping
41. KB-876 — Platform compatibility mapping
42. KB-877 — Platform compatibility mapping
43. KB-878 — Platform compatibility mapping
44. KB-879 — Platform compatibility mapping
45. KB-880 — Platform compatibility mapping
46. KB-881 — Platform compatibility mapping
47. KB-882 — Platform compatibility mapping
48. KB-883 — Platform compatibility mapping
49. KB-884 — Platform compatibility mapping
50. KB-885 — Platform compatibility mapping
51. KB-886 — Platform compatibility mapping
52. KB-1001 — Platform compatibility mapping
53. KB-1002 — Platform compatibility mapping
54. KB-1003 — Platform compatibility mapping
55. KB-1004 — Platform compatibility mapping
56. KB-1005 — Platform compatibility mapping
57. KB-1006 — Platform compatibility mapping
58. KB-1007 — Platform compatibility mapping
59. KB-1008 — Platform compatibility mapping
60. KB-1009 — Platform compatibility mapping
61. KB-1010 — Platform compatibility mapping
62. KB-1011 — Platform compatibility mapping
63. KB-1012 — Platform compatibility mapping
64. KB-1013 — Platform compatibility mapping
65. KB-1014 — Platform compatibility mapping
66. KB-1015 — Platform compatibility mapping
67. KB-1016 — Platform compatibility mapping
68. KB-1017 — Platform compatibility mapping
69. KB-1018 — Platform compatibility mapping
70. KB-1019 — Platform compatibility mapping
71. KB-1020 — Platform compatibility mapping
72. KB-1021 — Platform compatibility mapping
73. KB-1022 — Platform compatibility mapping
74. KB-1023 — Platform compatibility mapping
75. KB-1024 — Platform compatibility mapping
76. KB-1025 — Platform compatibility mapping
77. KB-1026 — Platform compatibility mapping
78. KB-1027 — Platform compatibility mapping
79. KB-1028 — Platform compatibility mapping
80. KB-1029 — Platform compatibility mapping
81. KB-1030 — Platform compatibility mapping
82. KB-1031 — Platform compatibility mapping
83. KB-1032 — Platform compatibility mapping
84. KB-1033 — Platform compatibility mapping
85. KB-1034 — Platform compatibility mapping
86. KB-1035 — Platform compatibility mapping
87. KB-1036 — Platform compatibility mapping
88. KB-1037 — Platform compatibility mapping
89. KB-1038 — Platform compatibility mapping
90. KB-1039 — Platform compatibility mapping
91. KB-1040 — Platform compatibility mapping
92. KB-1041 — Platform compatibility mapping
93. KB-1042 — Platform compatibility mapping
94. KB-1043 — Platform compatibility mapping
95. KB-1044 — Platform compatibility mapping
96. KB-1045 — Platform compatibility mapping
97. KB-1046 — Platform compatibility mapping
98. KB-1047 — Platform compatibility mapping

J. Data Movement Plan

Teradata

- Teradata NOS can access Google Cloud Storage. (source)
- Teradata foreign tables over Parquet objects use USING STOREDAS ('PARQUET') in CREATE FOREIGN TABLE. (source)

Snowflake

- Snowflake supports bulk unloading of table or query data to files, similar to loading. (source)
- COPY INTO <table> supports bulk and continuous (Snowpipe) loads from internal and external stages. (source)
- Secure Data Sharing shares selected database objects with other Snowflake accounts. (source)

Teradata -> Snowflake differences

- Snowflake loads data from stages with COPY INTO and continuously with Snowpipe. (source)

1. KB-375 — Knowledge-base claim for Data Movement Plan
2. KB-376 — Knowledge-base claim for Data Movement Plan
3. KB-291 — Knowledge-base claim for Data Movement Plan
4. KB-289 — Knowledge-base claim for Data Movement Plan
5. KB-292 — Knowledge-base claim for Data Movement Plan
6. KB-3715 — Knowledge-base claim for Data Movement Plan

K. ETL Migration Plan

Teradata -> Snowflake differences

- Snowflake publishes migration tooling and guides for moving legacy warehouses to Snowflake. (source)
- Teradata Parallel Transporter (TPT) is a client for parallel extraction, loading and updating that builds on FastLoad, MultiLoad, FastExport and TPump. (source)
- SnowConvert is Snowflake's tool for converting source DDL, SQL and procedural code to Snowflake. (source)

1. KB-3719 — Knowledge-base claim for ETL Migration Plan
2. KB-3717 — Knowledge-base claim for ETL Migration Plan
3. KB-3718 — Knowledge-base claim for ETL Migration Plan

L. Security Migration Plan

Teradata -> Snowflake differences

- Teradata directory users inherit privileges of mapped database users and of external roles mapped to their groups. (source)
- Snowflake access control combines discretionary and role-based models, granting privileges to roles. (source)
- Snowflake dynamic data masking applies masking policies to columns at query time. (source)
- Teradata privileges are acquired implicitly through ownership, automatically on creation, by inheritance or by explicit grant. (source)

1. KB-3721 — Knowledge-base claim for Security Migration Plan
2. KB-3722 — Knowledge-base claim for Security Migration Plan
3. KB-3723 — Knowledge-base claim for Security Migration Plan
4. KB-3720 — Knowledge-base claim for Security Migration Plan

M. Validation Strategy

Teradata -> Snowflake differences

- Validate row counts, data distributions, constraints, and business rules between Teradata and Snowflake.

N. Testing Strategy

Teradata -> Snowflake differences

- Test representative workloads, edge cases, performance, recovery, and cutover procedures for Teradata -> Snowflake.

O. Unsupported Features

Teradata

- A Teradata macro is one or more SQL statements run as a single request. (source)
- Teradata row level security controls access per row and per SQL operation by comparing user and row security labels. (source)
- Teradata temporal support adds valid-time and transaction-time dimensions to tables through temporal column attributes. (source)

Snowflake

- On standard tables, PRIMARY KEY, UNIQUE and FOREIGN KEY constraints are optional and not enforced; NOT NULL is enforced. (source)

- Fail-safe adds a non-configurable 7-day period in which Snowflake may recover historical data on a best-effort basis. (source)

Teradata -> Snowflake differences

- Teradata hashes each row to an AMP using the row hash of its primary index or primary AMP index. (source)

1. KB-377 — Knowledge-base claim for Unsupported Features
2. KB-380 — Knowledge-base claim for Unsupported Features
3. KB-379 — Knowledge-base claim for Unsupported Features
4. KB-296 — Knowledge-base claim for Unsupported Features
5. KB-294 — Knowledge-base claim for Unsupported Features
6. KB-3724 — Knowledge-base claim for Unsupported Features

P. Workarounds

Teradata -> Snowflake differences

- Snowflake row access policies determine which rows a query can return. (source)
- Snowflake Scripting adds procedural blocks, variables, loops and exception handling to SQL. (source)
- Snowflake clustering keys co-locate related rows in micro-partitions for very large tables. (source)
- Snowflake Time Travel lets you query and restore data as it was at earlier points in time. (source)

1. KB-3730 — Knowledge-base claim for Workarounds
2. KB-3729 — Knowledge-base claim for Workarounds
3. KB-3728 — Knowledge-base claim for Workarounds
4. KB-3731 — Knowledge-base claim for Workarounds

Q. Effort Estimation

Teradata -> Snowflake differences

- Aggregate inventory estimate: approximately 42.6 person-days across 57 objects (external=1, grant=7, hash_index=2, index=2, join_index=1, macro=1, procedure=5, role=3, script=1, synonym=1, table=21, user=2, view=10). This is a coarse estimate.

R. Risk Assessment

Teradata -> Snowflake differences

- **sql (high):** Teradata extensions and procedural code need rewriting for Snowflake.
- **data (medium):** Type differences (precision, time zones, large objects, semi-structured data) need per-column checks.
- **security (medium):** Grants and row/column rules must be re-implemented with the target security model.
- **governance (low):** Lineage, ownership and audit settings must be re-established on the target.
- **platform (medium):** Unenforced or missing constraints and different transaction semantics can change behaviour.
- **operational (medium):** Load jobs, scheduling and monitoring move to target-native tooling.

S. Confidence Scoring

Teradata -> Snowflake differences

- Aggregate inventory confidence: 98%; unparsed share 0%, partial share 2%.

T. Expert Review Items

Teradata -> Snowflake differences

- Manual review counts: 0 unparsed objects, 1 partial objects, 1 external references; issues by severity: error=1.

U. Optimization Hints

Teradata -> Snowflake differences

- Snowflake search optimization speeds up selective point-lookup queries. (source)
- Snowflake clustering keys co-locate related rows in micro-partitions for very large tables. (source)

1. KB-3733 — Knowledge-base claim for Optimization Hints
2. KB-3732 — Knowledge-base claim for Optimization Hints