



WAYPOINT CONNECT

SETUP, INSTALLATION & DEPLOYMENT GUIDE

# Setup & Deployment Guide

---

Prerequisites, commands, Docker, deployment and troubleshooting

---

**Project** WaypointConnect — delivery planning and tracking for Waypoint Group's Fresh, Style and Tech brands

**Event** Tech-Triathlon 2026 · Team Dark Horse

**Source** Generated 2026-10-04 · repository commit c1e3eb6 + working tree

Accuracy rule: every statement is taken from the project files. Anything that could not be verified is marked "Not verified from the provided project files". No passwords or secrets are included.

# Contents

---

|                                                 |          |
|-------------------------------------------------|----------|
| <b>1. Prerequisites</b>                         | <b>2</b> |
| 1.1 Prerequisites                               | 2        |
| <b>2. Environment configuration</b>             | <b>3</b> |
| 2.1 Environment configuration                   | 3        |
| <b>3. Local installation</b>                    | <b>4</b> |
| 3.1 Repository, install, Prisma, database, seed | 4        |
| 3.2 Running the API and the web app             | 4        |
| 3.3 Tests and checks                            | 4        |
| 3.4 Production build                            | 4        |
| <b>4. Docker Compose</b>                        | <b>5</b> |
| 4.1 Running with Docker Compose                 | 5        |
| <b>5. Deployment</b>                            | <b>6</b> |
| 5.1 Deployment                                  | 6        |
| <b>6. Troubleshooting</b>                       | <b>7</b> |
| 6.1 Troubleshooting and common errors           | 7        |

# 1. Prerequisites

---

## 1.1 Prerequisites

| Item              | Requirement                                                     | Check                                                  |
|-------------------|-----------------------------------------------------------------|--------------------------------------------------------|
| Node.js           | 20 or newer ( <code>engines</code> ); Docker images use Node 20 | <code>node -v</code>                                   |
| pnpm              | 9.12.0 via Corepack ( <code>packageManager</code> )             | <code>corepack enable</code> then <code>pnpm -v</code> |
| Docker            | Docker with Compose v2                                          | <code>docker compose version</code>                    |
| PostgreSQL        | 16 (Docker <code>db</code> service) or a local server           | see Database setup                                     |
| Python 3 + pandas | Only for <code>pnpm check:2b</code>                             |                                                        |
| Git               | To clone the repository                                         |                                                        |

## 2. Environment configuration

### 2.1 Environment configuration

Copy the example and change every `CHANGE_ME` value. Docker Compose reads `.env` in the project folder; `pnpm dev:api` reads it through `--env-file=../../.env`. `.env` is gitignored; never commit it.

```
cp .env.example .env # Windows PowerShell: Copy-Item .env.example .env
```

| Variable                                                                                       | Meaning                                               | Default / note                                                                                   |
|------------------------------------------------------------------------------------------------|-------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <code>DOMAIN</code>                                                                            | Public domain for Caddy (no https://)                 | <code>localhost</code>                                                                           |
| <code>DB_PASSWORD</code>                                                                       | PostgreSQL password                                   | compose default <code>waypoint</code> . Must equal the password inside <code>DATABASE_URL</code> |
| <code>DATABASE_URL</code>                                                                      | Connection string for local (non-Docker) API / Prisma | <code>postgresql://postgres:CHANGE_ME@localhost:15432/waypoint</code>                            |
| <code>JWT_SECRET</code>                                                                        | Signs the 12-hour session tokens                      | compose fallback <code>dev-only-secret-change-me</code> : always change on a server              |
| <code>ACCOUNT_SECRET</code>                                                                    | Derives every account password                        | falls back to <code>JWT_SECRET</code> ; changing it changes all passwords                        |
| <code>API_PORT</code>                                                                          | API port                                              | 3000                                                                                             |
| <code>DEMO_DATE</code>                                                                         | Pin all screens to one day (YYYY-MM-DD)               | empty = real date                                                                                |
| <code>DEMO_MODE</code>                                                                         | Enables the demo-only simulate route                  | compose default 1                                                                                |
| <code>DEMO_CLOCK</code> ,<br><code>DEMO_LOADER_CLOCK</code> ,<br><code>DEMO_STORE_CLOCK</code> | Pin a role's clock (HH:MM)                            | empty = real Colombo time                                                                        |
| <code>DB_HOST_PORT</code>                                                                      | Host port for the database                            | 15432                                                                                            |
| <code>LOG_LEVEL</code>                                                                         | API log level (read by the API)                       | info                                                                                             |

## 3. Local installation

### 3.1 Repository, install, Prisma, database, seed

```
git clone https://github.com/Cognix-0/DarkHorse_WaypointConnect.git
cd DarkHorse_WaypointConnect
corepack enable
pnpm install
cp .env.example .env          # then edit the CHANGE_ME values
docker compose up -d db       # PostgreSQL on 127.0.0.1:15432 (or use any local PostgreSQL and
set DATABASE_URL)
pnpm prisma generate
pnpm prisma db push           # creates the tables from prisma/schema.prisma
pnpm db:seed                  # outlets, vehicles, drivers, 188 accounts, today's orders
```

The scripts are from the root `package.json`: `db:seed = tsx prisma/seed.ts`; `credentials = tsx scripts/credentials.ts`. The seed is safe to run repeatedly. It needs `ACCOUNT_SECRET` or `JWT_SECRET` in the environment (otherwise it stops with "Set ACCOUNT\_SECRET..."). A `db:migrate` script (`prisma migrate dev`) exists, but Docker and the README use `db push`.

### 3.2 Running the API and the web app

```
pnpm dev:api    # http://localhost:3000/api/health
pnpm dev:web    # http://localhost:5173 (proxies /api to localhost:3000)
```

Print the account passwords with `pnpm credentials` (output is CSV: role, depot, vehicle\_or\_store, name, email, password). Keep it private.

### 3.3 Tests and checks

```
pnpm test      # 21 planning-engine tests
pnpm typecheck # all three workspaces (run pnpm prisma generate first)
pnpm check:2b  # engine on the official peak day + check_allocation.py (needs Python 3 + pandas)
```

### 3.4 Production build

```
pnpm --filter @waypoint/web build # tsc + vite build into apps/web/dist
```

The API is run from TypeScript with `tsx` (`pnpm --filter @waypoint/api start`); there is no separate API build step.

## 4. Docker Compose

---

### 4.1 Running with Docker Compose

```
cp .env.example .env
docker compose up --build      # database + API (schema + seed) + web + HTTPS
docker compose up -d --build   # detached; rebuild after code changes
docker compose logs --tail=50 api # wait for the seed and "Server listening"
docker compose down -v && docker compose up -d --build # wipe the database and re-seed
```

Open <https://localhost> and accept the local certificate once. Only Caddy publishes ports 80 and 443. After `git pull`, rebuild with `docker compose up -d --build`; on phones close and reopen the app once.

## 5. Deployment

### 5.1 Deployment

From `docs/deploy.md`. Server: Ubuntu 24.04, 2 vCPU, 2 GB RAM, 20 GB disk, ports 22/80/443 open.

#### One command

```
curl -fsSL https://raw.githubusercontent.com/Cognix-0/DarkHorse_WaypointConnect/main/scripts/server-setup.sh | bash
# with a domain: curl ... | DOMAIN=waypoint.example.com bash
```

It prints `Live: https://...` after 5–10 minutes; without a domain it uses `<ip-with-dashes>.sslip.io`. Run it again to deploy a new commit.

#### By hand

1. Point an A record at the server ( `dig +short your.domain` must print the IP).
2. Install Docker: `curl -fsSL https://get.docker.com | sudo sh`.
3. Clone, `cp .env.example .env`, set `DOMAIN`, `DB_PASSWORD`, `JWT_SECRET`, `ACCOUNT_SECRET` (e.g. `openssl rand -hex 32`).
4. `docker compose up -d --build` then `docker compose logs -f api`.
5. List passwords: `docker compose exec api pnpm -s credentials > credentials.csv` (keep private).

Checklist before submitting: padlock on the HTTPS URL; walkthrough accounts sign in; Order Queue shows 85 orders; driver app loads offline on a phone. Live deployment recorded in this project: <https://3-106-77-179.sslip.io>.

## 6. Troubleshooting

### 6.1 Troubleshooting and common errors

| Symptom                                                                                                                        | Cause and fix                                                                                                                                                       | Source                                      |
|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| TS2339: Property 'driver' does not exist on type PrismaClient (and similar errors for active , lastLoginAt ) in pnpm typecheck | The generated Prisma client is older than the schema. Run <code>pnpm prisma generate</code> , then typecheck again.                                                 | observed 2026-10-04; CI runs generate first |
| pnpm: not found: node                                                                                                          | Node.js is not on the PATH of the shell. Install Node 20+ and reopen the terminal.                                                                                  | pnpm-error.txt                              |
| --progress is a global compose flag                                                                                            | Put the flag before the subcommand: <code>docker compose --progress=plain build web</code> .                                                                        | docker-build.txt                            |
| Seed stops with "Set ACCOUNT_SECRET (or JWT_SECRET)..."                                                                        | Provide the secret in the shell environment or <code>.env</code> .                                                                                                  | prisma/accounts.ts                          |
| Browser shows ERR_TOO_MANY_REDIRECTS                                                                                           | The database container could not bind its host port, so db, api and web did not start. Run <code>docker compose ps</code> ; set <code>DB_HOST_PORT</code> .         | docs/handoff.md                             |
| "Wrong email or password" for a seeded account                                                                                 | Passwords come from <code>ACCOUNT_SECRET</code> ; changing it (or <code>JWT_SECRET</code> when empty) changes all passwords. Re-run <code>pnpm credentials</code> . | docs/deploy.md                              |
| Certificate error / Caddy "challenge failed"                                                                                   | DNS not pointing at the server yet, or ports 80/443 closed. Fix, then <code>docker compose restart caddy</code> .                                                   | deploy.md                                   |
| Build stops with "killed"                                                                                                      | Out of memory: add 2 GB swap.                                                                                                                                       | deploy.md                                   |
| New screens missing after pull                                                                                                 | Rebuild with <code>--build</code> ; close and reopen the phone app (service worker).                                                                                | deploy.md, handoff.md                       |
| /sw.js answers 403                                                                                                             | Fixed in <code>apps/web/Dockerfile</code> (files made world-readable); rebuild the web image.                                                                       | ai-disclosure 2026-10-04                    |
| Store or driver account shows the wrong store/vehicle                                                                          | Database seeded by an older version: <code>docker compose down -v &amp;&amp; docker compose up -d</code> .                                                          | deploy.md                                   |