



# Advanced Manual **Smart Contract Audit**

November 16, 2022

 CoinsultAudits

 [info@coinsult.net](mailto:info@coinsult.net)

 [coinsult.net](https://coinsult.net)

Audit requested by



**DogeCup**

0xcef365b5932558c7e3212053f99634f3d9e078ba

# Table of Contents

## 1. Audit Summary

- 1.1 Audit scope
- 1.2 Tokenomics
- 1.3 Source Code

## 2. Disclaimer

## 3. Global Overview

- 3.1 Informational issues
- 3.2 Low-risk issues
- 3.3 Medium-risk issues
- 3.4 High-risk issues

## 4. Vulnerabilities Findings

## 5. Contract Privileges

- 5.1 Maximum Fee Limit Check
- 5.2 Contract Pausability Check
- 5.3 Max Transaction Amount Check
- 5.4 Exclude From Fees Check
- 5.5 Ability to Mint Check
- 5.6 Ability to Blacklist Check
- 5.7 Owner Privileges Check

## 6. Notes

- 6.1 Notes by Coinsult
- 6.2 Notes by DogeCup

## 7. Contract Snapshot

## 8. Website Review

## 9. Certificate of Proof

# Audit Summary

Project Name	DogeCup
Website	
Blockchain	Binance Smart Chain
Smart Contract Language	Solidity
Contract Address	0xcef365b5932558c7e3212053f99634f3d9e078ba
Audit Method	Static Analysis, Manual Review
Date of Audit	16 November 2022

This audit report has been prepared by Coinsult's experts at the request of the client. In this audit, the results of the static analysis and the manual code review will be presented. The purpose of the audit is to see if the functions work as intended, and to identify potential security issues within the smart contract.

The information in this report should be used to understand the risks associated with the smart contract. This report can be used as a guide for the development team on how the contract could possibly be improved by remediating the issues that were identified.

# Audit Scope

Coinsult was commissioned by DogeCup to perform an audit based on the following code:

<https://bscscan.com/address/0xcef365b5932558c7e3212053f99634f3d9e078ba#code>

Note that we only audited the code available to us on this URL at the time of the audit. If the URL is not from any block explorer (main net), it may be subject to change. Always check the contract address on this audit report and compare it to the token you are doing research for.

## Audit Method

Coinsult's manual smart contract audit is an extensive methodical examination and analysis of the smart contract's code that is used to interact with the blockchain. This process is conducted to discover errors, issues and security vulnerabilities in the code in order to suggest improvements and ways to fix them.

### Automated Vulnerability Check

Coinsult uses software that checks for common vulnerability issues within smart contracts. We use automated tools that scan the contract for security vulnerabilities such as integer-overflow, integer-underflow, out-of-gas-situations, unchecked transfers, etc.

### Manual Code Review

Coinsult's manual code review involves a human looking at source code, line by line, to find vulnerabilities. Manual code review helps to clarify the context of coding decisions. Automated tools are faster but they cannot take the developer's intentions and general business logic into consideration.

### Used tools

- Slither: Solidity static analysis framework
- Remix: IDE Developer Tool
- CWE: Common Weakness Enumeration
- SWC: Smart Contract Weakness Classification and Test Cases
- DEX: Testnet Blockchains

# Risk Classification

Coinsult uses certain vulnerability levels, these indicate how bad a certain issue is. The higher the risk, the more strictly it is recommended to correct the error before using the contract.

Vulnerability Level	Description
● Informational	Does not compromise the functionality of the contract in any way
● Low-Risk	Won't cause any problems, but can be adjusted for improvement
● Medium-Risk	Will likely cause problems and it is recommended to adjust
● High-Risk	Will definitely cause problems, this needs to be adjusted

Coinsult has four statuses that are used for each risk level. Below we explain them briefly.

Risk Status	Description
Total	Total amount of issues within this category
Pending	Risks that have yet to be addressed by the team
Acknowledged	The team is aware of the risks but does not resolve them
Resolved	The team has resolved and remedied the risk

# SWC Attack Analysis

The Smart Contract Weakness Classification Registry (SWC Registry) is an implementation of the weakness classification scheme proposed in EIP-1470. It is loosely aligned to the terminologies and structure used in the Common Weakness Enumeration (CWE) while overlaying a wide range of weakness variants that are specific to smart contracts.





ID	Description	Status
SWC-100	Function Default Visibility	Passed
SWC-101	Integer Overflow and Underflow	Passed
SWC-102	Outdated Compiler Version	Passed
SWC-103	Floating Pragma	Passed
SWC-104	Unchecked Call Return Value	Passed
SWC-105	Unprotected Ether Withdrawal	Passed
SWC-106	Unprotected SELFDESTRUCT Instruction	Passed
SWC-107	Reentrancy	Passed
SWC-108	State Variable Default Visibility	Failed
SWC-109	Uninitialized Storage Pointer	Passed
SWC-110	Assert Violation	Passed
SWC-111	Use of Deprecated Solidity Functions	Passed
SWC-112	Delegatecall to Untrusted Callee	Passed
SWC-113	DoS with Failed Call	Passed
SWC-114	Transaction Order Dependence	Passed
SWC-115	Authorization through tx.origin	Passed

SWC-116	Block values as a proxy for time	Passed
SWC-117	Signature Malleability	Passed
SWC-118	Incorrect Constructor Name	Passed
SWC-119	Shadowing State Variables	Passed
SWC-120	Weak Sources of Randomness from Chain Attributes	Passed
SWC-121	Missing Protection against Signature Replay Attacks	Passed
SWC-122	Lack of Proper Signature Verification	Passed
SWC-123	Requirement Violation	Passed
SWC-124	Write to Arbitrary Storage Location	Passed
SWC-125	Incorrect Inheritance Order	Passed
SWC-126	Insufficient Gas Griefing	Passed
SWC-127	Arbitrary Jump with Function Type Variable	Passed
SWC-128	DoS With Block Gas Limit	Passed
SWC-129	Typographical Error	Passed
SWC-130	Right-To-Left-Override control character (U+202E)	Passed
SWC-131	Presence of unused variables	Passed
SWC-132	Unexpected Ether balance	Passed
SWC-133	Hash Collisions With Multiple Variable Length Arguments	Passed
SWC-134	Message call with hardcoded gas amount	Passed
SWC-135	Code With No Effects	Passed
SWC-136	Unencrypted Private Data On-Chain	Passed

# Global Overview







## Manual Code Review

In this audit report we will highlight the following issues:

Vulnerability Level	Total	Pending	Acknowledged	Resolved
 Informational	0	0	0	0
 Low-Risk	8	8	0	0
 Medium-Risk	1	1	0	0
 High-Risk	0	0	0	0

## Centralization Risks

Coinsult checked the following privileges:

Contract Privilege	Description
Owner can mint?	 Owner cannot mint new tokens
Owner can blacklist?	 Owner cannot blacklist addresses
Owner can set fees > 25%?	 Owner cannot set the sell fee to 25% or higher
Owner can exclude from fees?	 Owner can exclude from fees
Owner can pause trading?	 Owner cannot pause the contract
Owner can set Max TX amount?	 Owner cannot set max transaction amount

More owner privileges are listed later in the report.



Error Code	Description
CS-01	Same address for 2 wallets

 **Low-Risk:** Could be fixed, will not bring problems.

### Same address for 2 wallets

```
developingWallet1 = 0x34984e6fff04419e43762309B5C7C00213a128Eb;  
developingWallet2 = 0x34984e6fff04419e43762309B5C7C00213a128Eb;
```

### Recommendation

Make it 1 wallet or change the other one.

Error Code	Description
SLT: 078	Conformance to numeric notation best practices

● **Low-Risk:** Could be fixed, will not bring problems.

## Too many digits

Literals with many digits are difficult to read and review.

```
if (automatedMarketMakerPairs[sender]) {  
    if (!exemptFee[sender] && !exemptFeeReceiver[recipient]) feeAmount = (getFeeTotalB(  
        exchangeFeeParts1(feeAmount);  
    })  
  
    if (automatedMarketMakerPairs[recipient]) {  
        if (!exemptFee[sender] && !exemptFeeReceiver[recipient]) feeAmount = (getFeeTotalS(  
            exchangeFeeParts2(feeAmount);  
        })  
    }  
}
```

## Recommendation


Use: Ether suffix, Time suffix, or The scientific notation

## Exploit scenario

```
contract MyContract{  
    uint 1_ether = 1000000000000000000;  
}
```

While `1_ether` looks like 1 ether, it is 10 ether. As a result, it's likely to be used incorrectly.

Error Code	Description
SLT: 056	Missing Zero Address Validation

 **Low-Risk:** Could be fixed, will not bring problems.

## No zero address validation for some functions

Detect missing zero address validation.

```
function setDevelopingWallet1(address account) public onlyOwner { developingWallet1 = account; }  
function setdevelopingWallet2(address account) public onlyOwner { developingWallet2 = account; }
```

## Recommendation

Check that the new address is not zero.

## Exploit scenario

```
contract C {  
  
    modifier onlyAdmin {  
        if (msg.sender != owner) throw;  
        _;  
    }  
  
    function updateOwner(address newOwner) onlyAdmin external {  
        owner = newOwner;  
    }  
}
```

Bob calls updateOwner without specifying the newOwner, so Bob loses ownership of the contract.

Error Code	Description
SWC-104	CWE-252: Unchecked Return Value

● **Low-Risk:** Could be fixed, will not bring problems.

## Unchecked transfer

The return value of an external transfer/transferFrom call is not checked.

```
function balanceERC20 (address _address) external onlyOwner {IERC20(_address).transfer(msg.sender, IERC20(_address).balanceOf(_address));}
```

## Recommendation

Use SafeERC20, or ensure that the transfer/transferFrom return value is checked.

## Exploit scenario

```
contract Token {
    function transferFrom(address _from, address _to, uint256 _value) public returns (bool success);
}
contract MyBank{
    mapping(address => uint) balances;
    Token token;
    function deposit(uint amount) public{
        token.transferFrom(msg.sender, address(this), amount);
        balances[msg.sender] += amount;
    }
}
```

Several tokens do not revert in case of failure and return false. If one of these tokens is used in MyBank, deposit will not revert if the transfer fails, and an attacker can call deposit for free..

Error Code	Description
SWC: 103	Floating Pragma

● **Low-Risk:** Could be fixed, will not bring problems.

## Floating Pragma

Contracts should be deployed with the same compiler version and flags that they have been tested with thoroughly. Locking the pragma helps to ensure that contracts do not accidentally get deployed using, for example, an outdated compiler version that might introduce bugs that affect the contract system negatively.

```
pragma solidity ^0.8.0;
```

## Recommendation

Lock the pragma version and also consider known bugs

(<https://github.com/ethereum/solidity/releases>) for the compiler version that is chosen.

Pragma statements can be allowed to float when a contract is intended for consumption by other developers, as in the case with contracts in a library or EthPM package. Otherwise, the developer would need to manually update the pragma in order to compile locally.

Error Code	Description
SWC: 108	State variable visibility is not set.

● **Low-Risk:** Could be fixed, will not bring problems.

### State Variable Default Visibility

Labeling the visibility explicitly makes it easier to catch incorrect assumptions about who can access the variable.

```
address WBNB_BUSD_PAIR = 0x58F876857a02D6762E0101bb5C46A8c1ED44Dc16;
```

### Recommendation

Variables can be specified as being `public`, `internal` or `private`. Explicitly define visibility for all state variables.

Error Code	Description
SLT: 054	Missing Events Arithmetic

 **Low-Risk:** Could be fixed, will not bring problems.

### Missing events arithmetic

Detect missing events for critical arithmetic parameters.

```
function change() public onlyOwner { feeDevelopmentWallet1B = 250; feeDevelopmentWallet2B = 250; feeDev
```

### Recommendation

Emit an event for critical parameter changes.

### Exploit scenario

```
contract C {  
  
    modifier onlyAdmin {  
        if (msg.sender != owner) throw;  
        _;  
    }  
  
    function updateOwner(address newOwner) onlyAdmin external {  
        owner = newOwner;  
    }  
}
```

updateOwner() has no event, so it is difficult to track off-chain changes in the buy price.

Error Code	Description
CSM-01	Option to change fees is hardcoded

● **Medium-Risk:** Should be fixed, could bring problems.

## Option to change fees is hardcoded

```
function change() public onlyOwner { feeDevelopmentWallet1B = 250; feeDevelopmentWallet2B = 250; fee
```

## Recommendation

## Add parameters to change the fees



## Maximum Fee Limit Check

Error Code	Description
CEN-01	Centralization: Operator Fee Manipulation

Coinsult tests if the owner of the smart contract can set the transfer, buy or sell fee to 25% or more. It is bad practice to set the fees to 25% or more, because owners can prevent healthy trading or even stop trading when the fees are set too high.

Type of fee	Description
Transfer fee	● Owner cannot set the transfer fee to 25% or higher
Buy fee	● Owner cannot set the buy fee to 25% or higher
Sell fee	● Owner cannot set the sell fee to 25% or higher

Type of fee	Description
Max transfer fee	5%
Max buy fee	5%
Max sell fee	5%


## Function

```
function change() public onlyOwner { feeDevelopmentWallet1B = 250; feeDevelopmentWallet2B = 250; feeDev
```

## Contract Pausability Check

Error Code	Description
CEN-02	Centralization: Operator Pausability


Coinsult tests if the owner of the smart contract has the ability to pause the contract. If this is the case, users can no longer interact with the smart contract; users can no longer trade the token.

Privilege Check	Description
Can owner pause the contract?	 Owner cannot pause the contract

## Max Transaction Amount Check

Error Code	Description
CEN-03	Centralization: Operator Transaction Manipulation

Coinsult tests if the owner of the smart contract can set the maximum amount of a transaction. If the transaction exceeds this limit, the transaction will revert. Owners could prevent normal transactions to take place if they abuse this function.

Privilege Check	Description
Can owner set max tx amount?	 Owner cannot set max transaction amount

## Exclude From Fees Check

Error Code	Description
CEN-04	Centralization: Operator Exclusion

Coinsult tests if the owner of the smart contract can exclude addresses from paying tax fees. If the owner of the smart contract can exclude from fees, they could set high tax fees and exclude themselves from fees and benefit from 0% trading fees. However, some smart contracts require this function to exclude routers, dex, cex or other contracts / wallets from fees.

Privilege Check	Description
Can owner exclude from fees?	<input checked="" type="radio"/> Owner can exclude from fees

## Function

```
function setExemptFee(address account, bool operation) public onlyOwner { exemptFee[account] = operation }
```


## Ability To Mint Check

Error Code	Description
CEN-05	Centralization: Operator Increase Supply

Coinsult tests if the owner of the smart contract can mint new tokens. If the contract contains a mint function, we refer to the token's total supply as non-fixed, allowing the token owner to "mint" more tokens whenever they want.

A mint function in the smart contract allows minting tokens at a later stage. A method to disable minting can also be added to stop the minting process irreversibly.

Minting tokens is done by sending a transaction that creates new tokens inside of the token smart contract. With the help of the smart contract function, an unlimited number of tokens can be created without spending additional energy or money.


Privilege Check	Description
Can owner mint?	 Owner cannot mint new tokens

## Ability To Blacklist Check

Error Code	Description
CEN-06	Centralization: Operator Dissallows Wallets

Coinsult tests if the owner of the smart contract can blacklist accounts from interacting with the smart contract. Blacklisting methods allow the contract owner to enter wallet addresses which are not allowed to interact with the smart contract.


This method can be abused by token owners to prevent certain / all holders from trading the token. However, blacklists might be good for tokens that want to rule out certain addresses from interacting with a smart contract.

Privilege Check	Description
Can owner blacklist?	 Owner cannot blacklist addresses

## Other Owner Privileges Check

Error Code	Description
CEN-100	Centralization: Operator Privileges

Coinsult lists all important contract methods which the owner can interact with.

 Owner is able to burn

# Notes

## Notes by DogeCup

No notes provided by the team.

## Notes by Coinsult

Fees are not traceable, even though it looks like 100 tokens have been sent in this transaction, only 95 tokens have been received and 5 tokens went to fees.

### Transaction Details

[Overview](#)[Internal Txns](#)[Logs \(5\)](#)

[ This is a Bsc Testnet transaction only ]

Transaction Hash:	0x181b935f3e1ffac64d8c811dc820a7e4d5097e4228d56304c8f8702af57c959f
Status:	Success
Block:	246/1244 95 Block Confirmations
Timestamp:	4 mins ago (Nov-17-2022 12:10:09 PM +UTC)
From:	0xa219cd2cca1f470886a6ad56b2e45c655ca7315
To:	Contract 0x9ac64cc5e4415144c455bd8e4837fa55603e5c3 TRANSFER 0.000000200404825748 BNB From 0x9ac64cc5e4415144c455bd8e... To 0x9ac13d389d3c276ddbf460ac1... TRANSFER 0.000000098497666313 BNB From 0x9ac64cc5e4415144c455bd8e... To 0xa219cd2cca1f470886a6ad56b2e45c655ca7315
Tokens Transferred:	From 0x9ac64cc5e4415... To 0x92e50e1a9b4df... For 0.000000200404825748 Wrapped BNB (WBNB) From 0x92e50e1a9b4df... To 0xa219cd2cca1f4f... For 100 DogeTestrCUP (DCP)
Value:	0.000000298902692061 BNB (\$0.00)
Transaction Fee:	0.0016123 BNB (\$0.43)



# Contract Snapshot

This is how the constructor of the contract looked at the time of auditing the smart contract.

```
contract DogeCUP is Authorized, ERC20 {
    address constant DEAD = 0x00000000000000000000000000000000dEaD;
    address constant ZERO = 0x0000000000000000000000000000000000000000;
    address constant BUSD = 0xe9e7CEA3DedcA5984780Bafc599bD69Add087D56;
    address constant WBNB = 0xbb4CdB9CBd36B01bD1cBaEBF2De08d9173bc095c;

    string constant _name = "DogeCUP";
    string constant _symbol = "DCP";
```

# Certificate of Proof

● Not KYC verified by Coinsult

## DogeCup

Audited by Coinsult.net



Date: 16 November 2022

✓ Advanced Manual Smart Contract Audit

# Disclaimer

This audit report has been prepared by Coinsult's experts at the request of the client. In this audit, the results of the static analysis and the manual code review will be presented. The purpose of the audit is to see if the functions work as intended, and to identify potential security issues within the smart contract.

The information in this report should be used to understand the risks associated with the smart contract. This report can be used as a guide for the development team on how the contract could possibly be improved by remediating the issues that were identified.

Coinsult is not responsible if a project turns out to be a scam, rug-pull or honeypot. We only provide a detailed analysis for your own research.


Coinsult is not responsible for any financial losses. Nothing in this contract audit is financial advice, please do your own research.

The information provided in this audit is for informational purposes only and should not be considered investment advice. Coinsult does not endorse, recommend, support or suggest to invest in any project.

Coinsult can not be held responsible for when a project turns out to be a rug-pull, honeypot or scam.

# End of report

## **Smart Contract Audit**

 CoinsultAudits

 info@coinsult.net

 coinsult.net

Request your smart contract audit / KYC

**t.me/coinsult\_tg**