NAME

ovs-tcpdump - Dump traffic from an Open vSwitch port using **tcpdump**.

SYNOPSIS

ovs-tcpdump -i port tcpdump options...

DESCRIPTION

ovs–tcpdump creates switch mirror ports in the **ovs–vswitchd** daemon and executes **tcpdump** to listen against those ports. When the **tcpdump** instance exits, it then cleans up the mirror port it created.

ovs–tcpdump will not allow multiple mirrors for the same port. It has some logic to parse the current configuration and prevent duplicate mirrors.

The -i option may not appear multiple times.

It is important to note that under **Linux** based kernels, tap devices do not receive packets unless the specific tuntap device has been opened by an application. This requires **CAP_NET_ADMIN** privileges, so the **ovs-tcpdump** command must be run as a user with such permissions (this is usually a super-user).

OPTIONS

-h

--help Prints a brief help message to the console.

 $-\mathbf{V}$

--version

Prints version information to the console.

--db-sock

The Open vSwitch database socket connection string. The default is unix:/usr/local/var/run/open-vswitch/db.sock

--dump-cmd

The command to run instead of **tcpdump**.

−i

--interface

The interface for which a mirror port should be created, and packets should be dumped.

__mirror_to

The name of the interface which should be the destination of the mirrored packets. The default is miINTERFACE

SEE ALSO

ovs-appctl(8), ovs-vswitchd(8), ovs-pcap(1), ovs-tcpundump(1), tcpdump(8), wireshark(8).