

```
In [1]: import pandas as pd
```

```
In [2]: #연습문제 가져오기
```

```
In [2]: df = pd.read_csv("연습데이터셋1.csv", encoding = 'cp949')
df.head()
```

```
Out[2]:
```

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	서울	2023-01-15
1	S002	박서연	25.0	92.0	A	부산	2023-02-20
2	S003	김지훈	NaN	78.0	C	서울	2023-03-10
3	S004	최예은	22.0	NaN	B	인천	2024-04-05
4	S005	정하준	28.0	95.5	A	미상	2024-05-12

```
In [3]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8 entries, 0 to 7
Data columns (total 7 columns):
#   Column                Non-Null Count  Dtype
---  -
0   student_id            8 non-null     object
1   name                  8 non-null     object
2   age                   7 non-null     float64
3   score                 7 non-null     float64
4   grade                 7 non-null     object
5   city                  8 non-null     object
6   registration_date     7 non-null     object
dtypes: float64(2), object(5)
memory usage: 576.0+ bytes
```

## df.isnull(), df.dropna(), df.fillna ()

```
In [4]: #null값 총합
df.isnull().sum()
```

```
Out[4]: student_id      0
name              0
age               1
score             1
grade             1
city              0
registration_date 1
dtype: int64
```

```
In [ ]:
```

```
In [5]: #행 전체 삭제 (dropna)
drop = df.dropna()
drop.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Index: 5 entries, 0 to 7
Data columns (total 7 columns):
#   Column                Non-Null Count  Dtype
---  -
0   student_id            5 non-null     object
1   name                  5 non-null     object
2   age                   5 non-null     float64
3   score                 5 non-null     float64
4   grade                 5 non-null     object
5   city                  5 non-null     object
6   registration_date     5 non-null     object
dtypes: float64(2), object(5)
memory usage: 320.0+ bytes
```

```
In [6]: # 전체 열 삭제 (dropna)
co_drop = df.dropna(axis=1)
co_drop.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8 entries, 0 to 7
Data columns (total 3 columns):
#   Column                Non-Null Count  Dtype
---  -
0   student_id            8 non-null     object
1   name                  8 non-null     object
2   city                  8 non-null     object
dtypes: object(3)
memory usage: 320.0+ bytes
```

```
In [ ]:
```

```
In [7]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8 entries, 0 to 7
Data columns (total 7 columns):
#   Column                Non-Null Count  Dtype
---  -
0   student_id            8 non-null     object
1   name                  8 non-null     object
2   age                   7 non-null     float64
3   score                 7 non-null     float64
4   grade                 7 non-null     object
5   city                  8 non-null     object
6   registration_date     7 non-null     object
dtypes: float64(2), object(5)
memory usage: 576.0+ bytes
```

```
In [8]: df.head()
```

Out[8]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	서울	2023-01-15
1	S002	박서연	25.0	92.0	A	부산	2023-02-20
2	S003	김지훈	NaN	78.0	C	서울	2023-03-10
3	S004	최예은	22.0	NaN	B	인천	2024-04-05
4	S005	정하준	28.0	95.5	A	미상	2024-05-12

## Fillna 예제

예제 1: 전체 컬럼

- `df2=df.fillna('None')`

예제 2: 컬럼 하나

- `df2['Discount'] = df['Discount'].fillna(0)`

예제 3: 그룹 컬럼

- `df2[['Discount','Fee']] = df[['Discount','Fee']].fillna(0)`

예제 4: 그룹 컬럼인데 다른 값

- `df2 = df.fillna(value={'Discount':0,'Fee':10000})`

예제 5: 제한(limit)

- `df2=df.fillna(value={'Discount':0,'Fee':0},limit=1)`

```
In [9]: df_fill = df.fillna(value = {'age':30, 'score':80.0, 'grade': 'None', 'registration_date' : '2023-06-30' })
df_fill.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8 entries, 0 to 7
Data columns (total 7 columns):
#   Column                Non-Null Count  Dtype
---  -
0   student_id            8 non-null     object
1   name                  8 non-null     object
2   age                   8 non-null     float64
3   score                 8 non-null     float64
4   grade                 8 non-null     object
5   city                  8 non-null     object
6   registration_date     8 non-null     object
dtypes: float64(2), object(5)
memory usage: 576.0+ bytes
```

## Astype

```
In [10]: df_fill.dtypes
```

```
Out[10]: student_id      object
        name          object
        age          float64
        score        float64
        grade        object
        city          object
        registration_date object
dtype: object
```

- object ('Kelly','James')
- float64 (3.14,2.5)
- int(4,5,6,7,8,9)

```
In [11]: da = df_fill.astype({'score':'object','age':'object'})
da.dtypes
```

```
Out[11]: student_id      object
        name          object
        age          object
        score        object
        grade        object
        city          object
        registration_date object
dtype: object
```

## df.replace

```
In [12]: df.head()
```

Out[12]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	서울	2023-01-15
1	S002	박서연	25.0	92.0	A	부산	2023-02-20
2	S003	김지훈	NaN	78.0	C	서울	2023-03-10
3	S004	최예은	22.0	NaN	B	인천	2024-04-05
4	S005	정하준	28.0	95.5	A	미상	2024-05-12

```
In [13]: df['city'].value_counts()
```

```
Out[13]: city
서울      3
부산      2
인천      1
미상      1
광주      1
Name: count, dtype: int64
```

```
In [14]: df['city'] = df['city'].replace({'서울':'Seoul', '부산': 'Busan', '인천':'Incheon','미상':'None','광주':'Gwangju'})
df.head()
```

Out[14]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	Seoul	2023-01-15
1	S002	박서연	25.0	92.0	A	Busan	2023-02-20
2	S003	김지훈	NaN	78.0	C	Seoul	2023-03-10
3	S004	최예은	22.0	NaN	B	Incheon	2024-04-05
4	S005	정하준	28.0	95.5	A	None	2024-05-12

## 필터링

```
In [15]: df_fill[df_fill['score']>80]
```

Out[15]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	서울	2023-01-15
1	S002	박서연	25.0	92.0	A	부산	2023-02-20
4	S005	정하준	28.0	95.5	A	미상	2024-05-12
6	S007	한도윤	29.0	88.0	B	광주	2024-07-21

```
In [16]: #And
df_fill[(df_fill['score'] > 80) & (df_fill['age'] >= 25)]
```

Out[16]:

	student_id	name	age	score	grade	city	registration_date
1	S002	박서연	25.0	92.0	A	부산	2023-02-20
4	S005	정하준	28.0	95.5	A	미상	2024-05-12
6	S007	한도윤	29.0	88.0	B	광주	2024-07-21

In [17]:

```
#Or
df_fill[(df_fill['score'] > 80) | (df_fill['age'] >= 25)]
```

Out[17]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	서울	2023-01-15
1	S002	박서연	25.0	92.0	A	부산	2023-02-20
2	S003	김지훈	30.0	78.0	C	서울	2023-03-10
4	S005	정하준	28.0	95.5	A	미상	2024-05-12
5	S006	윤채원	25.0	-1.0	None	부산	2023-06-30
6	S007	한도윤	29.0	88.0	B	광주	2024-07-21

# 인덱스 설정 및 초기화

In [16]:

```
df.head()
```

Out[16]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	Seoul	2023-01-15
1	S002	박서연	25.0	92.0	A	Busan	2023-02-20
2	S003	김지훈	NaN	78.0	C	Seoul	2023-03-10
3	S004	최예은	22.0	NaN	B	Incheon	2024-04-05
4	S005	정하준	28.0	95.5	A	None	2024-05-12

In [18]:

```
ds = df.set_index('student_id')
ds
```

Out[18]:

	name	age	score	grade	city	registration_date
student_id						
S001	이민준	23.0	85.5	B	Seoul	2023-01-15
S002	박서연	25.0	92.0	A	Busan	2023-02-20
S003	김지훈	NaN	78.0	C	Seoul	2023-03-10
S004	최예은	22.0	NaN	B	Incheon	2024-04-05
S005	정하준	28.0	95.5	A	None	2024-05-12
S006	윤채원	25.0	-1.0	NaN	Busan	NaN
S007	한도윤	29.0	88.0	B	Gwangju	2024-07-21
S008	신유나	21.0	76.5	C	Seoul	2024-08-30

In [19]:

```
dr = df.reset_index(drop = True)
dr
```

Out[19]:

	student_id	name	age	score	grade	city	registration_date
0	S001	이민준	23.0	85.5	B	Seoul	2023-01-15
1	S002	박서연	25.0	92.0	A	Busan	2023-02-20
2	S003	김지훈	NaN	78.0	C	Seoul	2023-03-10
3	S004	최예은	22.0	NaN	B	Incheon	2024-04-05
4	S005	정하준	28.0	95.5	A	None	2024-05-12
5	S006	윤채원	25.0	-1.0	NaN	Busan	NaN
6	S007	한도윤	29.0	88.0	B	Gwangju	2024-07-21
7	S008	신유나	21.0	76.5	C	Seoul	2024-08-30

# 시계열 데이터 처리

In [20]:

```
df_fill.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8 entries, 0 to 7
Data columns (total 7 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   student_id            8 non-null     object
1   name                  8 non-null     object
2   age                   8 non-null     float64
3   score                 8 non-null     float64
4   grade                 8 non-null     object
5   city                  8 non-null     object
6   registration_date     8 non-null     object
dtypes: float64(2), object(5)
memory usage: 576.0+ bytes
```

```
In [21]: df_fill['registration_date'] = pd.to_datetime(df_fill['registration_date'])
df_fill.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8 entries, 0 to 7
Data columns (total 7 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   student_id            8 non-null     object
1   name                  8 non-null     object
2   age                   8 non-null     float64
3   score                 8 non-null     float64
4   grade                 8 non-null     object
5   city                  8 non-null     object
6   registration_date     8 non-null     datetime64[ns]
dtypes: datetime64[ns](1), float64(2), object(4)
memory usage: 576.0+ bytes
```

```
In [ ]:
```

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js